


LCPI

Toroid power inductors



Applications

- Filters
- Buck and boost switches
- Chokes

Product features

- Low loss, iron powder cores with stable electrical operating characteristics maximize inductor efficiency by minimizing copper losses
- Available in vertical and horizontal self leaded and header mounted configurations
- Inductance values range from 10 μH to 1000 μH
- Current values range from 1.5 A to 29.5 A
- Meets UL 94V-0 flammability standard
- Iron powder core material

Environmental Data

- Storage temperature range (Component): -40 °C to +105 °C
- Operating temperature range: -40 °C to +105 °C (ambient plus self-temperature rise)



Product Specifications

| Vertical Part Number | Horizontal Part Number | Header Mounted Part Number | OCL ⁽¹⁾ µH +/- 20% | I _{DC} ⁽²⁾ (A) | I _{SAT} ⁽³⁾ (A) | Volt-µsec ⁽⁴⁾ Vµs | Energy ⁽⁵⁾ µJ | DCR (Ω) ⁽⁶⁾ max |
|----------------------|------------------------|----------------------------|----------------------------------|---------------------------------------|--|---------------------------------|-----------------------------|-------------------------------|
| CTX10-1-52-R | CTX10-1-52LP-R | CTX10-1-52M-R | 10.14 | 2.4 | 2.1 | 5.4 | 15 | 0.0481 |
| CTX20-1-52-R | CTX20-1-52LP-R | CTX20-1-52M-R | 20.22 | 1.8 | 2.2 | 7.8 | 36 | 0.0829 |
| CTX50-1-52-R | CTX50-1-52LP-R | CTX50-1-52M-R | 50.29 | 2.6 | 2.7 | 16.3 | 130 | 0.0715 |
| CTX100-1-52-R | CTX100-1-52LP-R | CTX100-1-52M-R | 100.40 | 2.5 | 2.4 | 27.5 | 197 | 0.1060 |
| CTX150-1-52-R | CTX150-1-52LP-R | CTX150-1-52M-R | 151.70 | 2.1 | 2.3 | 35.7 | 283 | 0.1620 |
| CTX250-1-52-R | CTX250-1-52LP-R | CTX250-1-52M-R | 250.90 | 1.9 | 2.2 | 47.8 | 421 | 0.2210 |
| CTX500-1-52-R | CTX500-1-52LP-R | CTX500-1-52M-R | 505.00 | 1.7 | 1.9 | 77.9 | 645 | 0.3610 |
| CTX750-1-52-R | CTX750-1-52LP-R | CTX750-1-52M-R | 754.40 | 1.8 | 2.4 | 114.3 | 1530 | 0.4340 |
| CTX1000-1-52-R | CTX1000-1-52LPR | CTX1000-1-52M-R | 1004.00 | 1.5 | 2.1 | 131.9 | 1530 | 0.6380 |
| CTX10-2-52-R | CTX10-2-52LP-R | CTX10-2-52M-R | 9.60 | 4.7 | 4.5 | 6.6 | 68 | 0.0183 |
| CTX20-2-52-R | CTX20-2-52LP-R | CTX20-2-52M-R | 19.60 | 3.2 | 3.2 | 9.4 | 69 | 0.0392 |
| CTX50-2-52-R | CTX50-2-52LP-R | CTX50-2-52M-R | 50.00 | 4.9 | 4.9 | 21.3 | 420 | 0.0326 |
| CTX100-2-52-R | CTX100-2-52LP-R | CTX100-2-52M-R | 101.70 | 4.4 | 4.3 | 35.0 | 643 | 0.0534 |
| CTX150-2-52-R | CTX150-2-52LP-R | CTX150-2-52M-R | 148.00 | 4.3 | 4.0 | 47.6 | 829 | 0.0719 |
| CTX250-2-52-R | CTX250-2-52LP-R | CTX250-2-52M-R | 251.10 | 4.2 | 4.2 | 66.0 | 1540 | 0.0833 |
| CTX500-2-52-R | CTX500-2-52LP-R | CTX500-2-52M-R | 499.40 | 3.1 | 3.3 | 104.0 | 1890 | 0.1830 |
| CTX750-2-52-R | CTX750-2-52LP-R | CTX750-2-52M-R | 749.30 | 3.4 | 3.4 | 147.3 | 2960 | 0.2080 |
| CTX10-5-52-R | CTX10-5-52LP-R | CTX10-5-52M-R | 9.68 | 8.7 | 11.1 | 9.4 | 417 | 0.0104 |
| CTX20-5-52-R | CTX20-5-52LP-R | CTX20-5-52M-R | 21.25 | 7.8 | 9.3 | 16.0 | 643 | 0.0260 |
| CTX50-5-52-R | CTX50-5-52LP-R | CTX50-5-52M-R | 49.60 | 7.6 | 9.4 | 29.3 | 1530 | 0.0248 |
| CTX100-5-52-R | CTX100-5-52LP-R | CTX100-5-52M-R | 97.20 | 8.2 | 7.5 | 45.7 | 1890 | 0.0267 |
| CTX150-5-52-R | CTX150-5-52LP-R | CTX150-5-52M-R | 150.60 | 7.7 | 7.5 | 66.0 | 2960 | 0.0401 |
| CTX250-5-52-R | CTX250-5-52LP-R | | 254.40 | 9.2 | 8.1 | 102.4 | 5860 | 0.0400 |
| CTX10-7-52-R | CTX10-7-52LP-R | CTX10-7-52M-R | 10.04 | 11.4 | 13.5 | 11.0 | 640 | 0.0080 |
| CTX20-7-52-R | CTX20-7-52LP-R | CTX20-7-52M-R | 20.96 | 11.4 | 14.5 | 19.1 | 1540 | 0.0110 |
| CTX50-7-52-R | CTX50-7-52LP-R | CTX50-7-52M-R | 52.27 | 10.5 | 10.2 | 33.5 | 1900 | 0.0163 |
| CTX100-7-52-R | CTX100-7-52LP-R | | 101.40 | 12.0 | 9.1 | 54.2 | 2960 | 0.0167 |
| CTX150-7-52-R | CTX150-7-52LP-R | | 152.80 | 12.8 | 10.5 | 79.3 | 5900 | 0.0204 |
| CTX10-10-52-R | CTX10-10-52LP-R | | 10.04 | 16.9 | 20.9 | 13.2 | 1530 | 0.0051 |
| CTX20-10-52-R | CTX20-10-52LP-R | | 21.17 | 16.0 | 16.0 | 21.3 | 1900 | 0.0070 |
| CTX50-10-52-R | CTX50-10-52LP-R | | 52.37 | 13.9 | 12.7 | 38.9 | 2960 | 0.0124 |
| CTX100-10-52-R | CTX100-10-52LPR | | 99.38 | 17.6 | 13.0 | 64.0 | 5880 | 0.0109 |
| CTX10-16-52-R | CTX10-16-52LP-R | | 9.90 | 27.3 | 29.3 | 16.9 | 2970 | 0.0032 |
| CTX20-16-52-R | CTX20-16-52LP-R | | 19.24 | 31.5 | 29.5 | 28.1 | 5860 | 0.0034 |

Notes:

- (1) Open circuit inductance test parameters: 100 kHz, 0.250 Vrms, 0 Adc.
- (2) DC current for an approximate ΔT of 30 °C at +75 °C Ambient with no core loss. See Chart 2 for derating of I_{DC} with core loss.
- (3) Peak current for an approximate 30% roll-off in OCL. For other current levels see Chart 1.
- (4) Applied Volt-Time product (Vµs) across the inductor. This value represents the Vµs at 100 kHz necessary to generate a core loss equal to 10% of the total losses for 30°C rise. For other frequencies and operating levels see Chart 2. (Note: skin effect losses not included.)
- (5) Energy storage (µJ) at I_{SAT}. For other current levels see Chart 1.
- (6) Maximum D.C. resistance at +20 °C.

Dimensions- mm

| Vertical and Horizontal Self Leaded Mounting Options | | | | | | | | |
|---|--|---------------------|---------------------|---------------------|--------------------|--------------------|--------------------|--------------------|
| Vertical P/N See Figure 1 | Horizontal P/N See Figure 2 | OD (max) | ID (typ) | Ht (max) | X (typ) | Y (typ) | T (typ) | H (typ) |
| CTX10-1-52-R | CTX10-1-52LP-R | 8.6 | 0.0 | 4.7 | 3.8 | 7.3 | 0.42 | 0.67 |
| CTX20-1-52-R | CTX20-1-52LP-R | 9.1 | 0.0 | 6.7 | 5.6 | 7.4 | 0.37 | 0.62 |
| CTX50-1-52-R | CTX50-1-52LP-R | 16.2 | 4.2 | 9.0 | 7.5 | 13.7 | 0.58 | 0.83 |
| CTX100-1-52-R | CTX100-1-52LP-R | 15.5 | 4.2 | 12.4 | 10.7 | 13.7 | 0.58 | 0.83 |
| CTX150-1-52-R | CTX150-1-52LP-R | 20.7 | 6.6 | 9.4 | 7.8 | 18.8 | 0.52 | 0.77 |
| CTX250-1-52-R | CTX250-1-52LP-R | 20.9 | 6.0 | 13.0 | 11.0 | 18.8 | 0.52 | 0.77 |
| CTX500-1-52-R | CTX500-1-52LP-R | 24.0 | 9.0 | 15.3 | 14.0 | 21.2 | 0.52 | 0.77 |
| CTX750-1-52-R | CTX750-1-52LP-R | 29.8 | 11.7 | 17.4 | 15.6 | 28.2 | 0.52 | 0.77 |
| CTX1000-1-52-R | CTX1000-1-52LP-R | 29.8 | 11.7 | 17.1 | 15.5 | 28.0 | 0.46 | 0.71 |
| CTX10-2-52-R | CTX10-2-52LP-R | 12.7 | 0.0 | 7.8 | 6.3 | 11.0 | 0.71 | 0.96 |
| CTX20-2-52-R | CTX20-2-52LP-R | 12.5 | 0.0 | 7.5 | 6.3 | 11.0 | 0.58 | 0.83 |
| CTX50-2-52-R | CTX50-2-52LP-R | 21.6 | 6.1 | 13.6 | 11.0 | 19.5 | 0.89 | 1.14 |
| CTX100-2-52-R | CTX100-2-52LP-R | 24.0 | 8.8 | 16.6 | 13.9 | 21.8 | 0.89 | 1.14 |
| CTX150-2-52-R | CTX150-2-52LP-R | 30.6 | 11.2 | 11.4 | 9.3 | 28.5 | 0.80 | 1.05 |
| CTX250-2-52-R | CTX250-2-52LP-R | 31.2 | 9.1 | 19.0 | 15.7 | 28.5 | 0.89 | 1.14 |
| CTX500-2-52-R | CTX500-2-52LP-R | 36.7 | 11.7 | 14.8 | 12.5 | 34.5 | 0.71 | 0.96 |
| CTX750-2-52-R | CTX750-2-52LP-R | 43.3 | 19.9 | 18.2 | 15.8 | 41.5 | 0.80 | 1.05 |
| CTX10-5-52-R | CTX10-5-52LP-R | 22.2 | 5.4 | 13.9 | 11.5 | 19.9 | 1.11 | 1.36 |
| CTX20-5-52-R | CTX20-5-52LP-R | 24.5 | 8.8 | 16.6 | 14.5 | 22.0 | 0.89 | 1.14 |
| CTX50-5-52-R | CTX50-5-52LP-R | 32.3 | 10.1 | 18.9 | 16.5 | 28.8 | 1.11 | 1.36 |
| CTX100-5-52-R | CTX100-5-52LP-R | 37.8 | 11.2 | 16.8 | 13.6 | 35.5 | 1.24 | 1.49 |
| CTX150-5-52-R | CTX150-5-52LP-R | 46.4 | 18.8 | 19.8 | 16.8 | 43.4 | 1.24 | 1.49 |
| CTX250-5-52-R | CTX250-5-52LP-R | 53.7 | 18.8 | 24.3 | 20.1 | 49.4 | 1.38 | 1.63 |
| CTX10-7-52-R | CTX10-7-52LP-R | 25.7 | 6.5 | 18.0 | 16.0 | 22.4 | 1.38 | 1.63 |
| CTX20-7-52-R | CTX20-7-52LP-R | 32.4 | 8.5 | 19.8 | 16.8 | 29.2 | 1.38 | 1.63 |
| CTX50-7-52-R | CTX50-7-52LP-R | 39.0 | 10.8 | 16.8 | 13.9 | 35.7 | 1.38 | 1.63 |
| CTX100-7-52-R | CTX100-7-52LP-R | 48.5 | 17.1 | 21.8 | 17.2 | 43.4 | 1.73 | 1.98 |
| CTX150-7-52-R | CTX150-7-52LP-R | 54.5 | 17.1 | 25.4 | 21.2 | 50.9 | 1.73 | 1.98 |
| CTX10-10-52-R | CTX10-10-52LP-R | 34.0 | 7.0 | 21.4 | 17.0 | 29.6 | 1.73 | 1.98 |
| CTX20-10-52-R | CTX20-10-52LP-R | 40.5 | 9.0 | 18.0 | 14.3 | 35.2 | 1.73 | 1.98 |
| CTX50-10-52-R | CTX50-10-52LP-R | 47.5 | 17.1 | 21.3 | 17.5 | 42.8 | 1.73 | 1.98 |
| CTX100-10-52-R | CTX100-10-52LP-R | 57.0 | 15.0 | 27.5 | 21.3 | 50.6 | 2.15 | 2.45 |
| CTX10-16-52-R | CTX10-16-52LP-R | 50.3 | 13.0 | 24.0 | 18.6 | 43.0 | 2.41 | 2.70 |
| CTX20-16-52-R | CTX20-16-52LP-R | 59.0 | 13.0 | 28.0 | 23.0 | 50.7 | 2.69 | 2.99 |


Note: All dimensions are in millimeters.



**VERTICAL
SELF LEADED
MOUNT**



**HORIZONTAL
SELF LEADED
MOUNT**



Drawings are not to scale.

Dimensions- mm

| Header Mounted Option | | | | | | | | | |
|-----------------------------------|---------------------|-----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|
| Header Mounted Part Number | See Figure # | OD (max) | A (max) | B (max) | C (max) | X (typ) | Y (typ) | T (typ) | H (typ) |
| CTX10-1-52M-R | 3 | 8.6 | 9.4 | 9.4 | 6.9 | 6.5 | 6.5 | — | — |
| CTX20-1-52M-R | 3 | 9.1 | 9.4 | 9.4 | 9.0 | 6.5 | 6.5 | — | — |
| CTX50-1-52M-R | 4 | 16.2 | 19.6 | 16.1 | 20.0 | 15.3 | 6.4 | — | — |
| CTX100-1-52M-R | 4 | 15.5 | 19.6 | 16.1 | 19.7 | 15.3 | 6.4 | — | — |
| CTX150-1-52M-R | 4 | 20.7 | 19.6 | 16.1 | 24.2 | 15.3 | 6.4 | — | — |
| CTX250-1-52M-R | 5 | 20.9 | 31.0 | 16.0 | 22.5 | 20.3 | 10.2 | 1.20 | 1.45 |
| CTX500-1-52M-R | 5 | 24.0 | 35.4 | 21.7 | 25.0 | 23.0 | 15.4 | 1.20 | 1.45 |
| CTX750-1-52M-R | 5 | 29.8 | 35.4 | 21.7 | 31.6 | 23.0 | 15.4 | 1.20 | 1.45 |
| CTX1000-1-52M-R | 5 | 29.8 | 35.4 | 21.7 | 31.2 | 23.0 | 15.4 | 1.20 | 1.45 |
| CTX10-2-52M-R | 3 | 12.7 | 13.6 | 11.4 | 11.7 | 10.8 | 7.5 | — | — |
| CTX20-2-52M-R | 3 | 12.5 | 13.6 | 11.4 | 11.4 | 10.8 | 7.5 | — | — |
| CTX50-2-52M-R | 5 | 21.6 | 31.0 | 16.0 | 23.5 | 20.3 | 10.2 | 1.20 | 1.45 |
| CTX100-2-52M-R | 5 | 24.0 | 35.4 | 21.7 | 26.0 | 23.0 | 15.4 | 1.20 | 1.45 |
| CTX150-2-52M-R | 5 | 30.6 | 31.0 | 16.0 | 32.5 | 20.3 | 10.2 | 1.20 | 1.45 |
| CTX250-2-52M-R | 5 | 31.2 | 35.4 | 21.7 | 33.4 | 23.0 | 15.4 | 1.20 | 1.45 |
| CTX500-2-52M-R | 5 | 36.7 | 31.0 | 16.0 | 38.4 | 20.3 | 10.2 | 1.20 | 1.45 |
| CTX750-2-52M-R | 5 | 43.3 | 35.4 | 21.7 | 45.4 | 23.0 | 15.4 | 1.20 | 1.45 |
| CTX10-5-52M-R | 5 | 22.2 | 31.0 | 16.0 | 22.7 | 20.3 | 10.2 | 1.20 | 1.45 |
| CTX20-5-52M-R | 5 | 24.5 | 35.4 | 21.7 | 25.5 | 23.0 | 15.4 | 1.20 | 1.45 |
| CTX50-5-52M-R | 5 | 32.3 | 35.4 | 21.7 | 33.7 | 23.0 | 15.4 | 1.11 | 1.36 |
| CTX100-5-52M-R | 5 | 37.8 | 35.4 | 21.7 | 40.2 | 23.0 | 15.4 | 1.24 | 1.49 |
| CTX150-5-52M-R | 5 | 46.4 | 35.4 | 21.7 | 47.0 | 23.0 | 15.4 | 1.24 | 1.49 |
| CTX10-7-52M-R | 5 | 25.7 | 35.4 | 21.7 | 26.7 | 23.0 | 15.4 | 1.38 | 1.63 |
| CTX20-7-52M-R | 5 | 32.4 | 35.4 | 21.7 | 34.2 | 23.0 | 15.4 | 1.38 | 1.63 |
| CTX50-7-52M-R | 5 | 39.0 | 35.4 | 21.7 | 40.3 | 23.0 | 15.4 | 1.38 | 1.63 |

Note: All dimensions are in millimeters.






Figure4

Core loss




Inductance characteristics



Wave solder profile- Through-hole components

Reflow soldering not recommended



Reference EN 61760-1:2006

| Profile Feature | Standard SnPb Solder | Lead (Pb) Free Solder |
|-------------------------------------|---|---|
| Preheat | • Temperature min. (T_{smin}) | 100°C |
| | • Temperature typ. (T_{styp}) | 120°C |
| | • Temperature max. (T_{smax}) | 130°C |
| | • Time (T_{smin} to T_{smax}) (t_s) | 70 seconds |
| Δ preheat to max Temperature | 150°C max. | 150°C max. |
| Peak temperature (T_p)* | 235°C – 260°C | 250°C – 260°C |
| Time at peak temperature (t_p) | 10 seconds max 5 seconds max each wave | 10 seconds max 5 seconds max each wave |
| Ramp-down rate | ~ 2 K/s min ~3.5 K/s typ ~5 K/s max | ~ 2 K/s min ~3.5 K/s typ ~5 K/s max |
| Time 25°C to 25°C | 4 minutes | 4 minutes |

Manual solder

350°C, 4-5 seconds. (by soldering iron), generally manual, hand soldering is not recommended.

Life Support Policy: Eaton does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin.

Eaton
Electronics Division
1000 Eaton Boulevard
Cleveland, OH 44122
United States
www.eaton.com/electronics

© 2017 Eaton
All Rights Reserved
Printed in USA
Publication No. 4304
July 2017

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А