


PCI-9221/9222/9223

16/32-CH 16-Bit 250/500 kS/s Multi-Function DAQ Cards with Encoder Input



Introduction

The PCI-9221/9222/9223 are ADLINK's high performance DAQ cards. PCI-9221/9222/9223 are 16-bit, 16/32-CH, 250/500 kS/s multi-function DAQ cards with 4/8 different input ranges. They also feature 2-CH 16-bit simultaneous analog outputs and programmable function I/O. The software-programmable function I/O supports a variety of applications, including TTL digital I/O, high-speed DIO (PCI-9222/9223 only), general-purpose timer/counter, pulse generation, encoder input, and PWM output. Analog input, analog output, and function I/O can operate at full speed simultaneously.

For the PCI-9222/9223, multiple cards can be synchronized through the SSI (System Synchronization Interface) bus if more channels are needed. Ideal for mixed-signal tests, laboratory research, and factory automation, the PCI-9221/9222/9223 are the best single-board solutions on the market providing the best integration capability of multiple tasks with high performance and an affordable price.

Features

- Supports a 32-bit 3.3 V or 5 V PCI bus
- Programmable gains for analog input: 1, 2, 4, 5, 8, 10, 20, 40 (PCI-9222/9223) 1, 5, 10, 25 (PCI-9221)
- 2-CH 16-bit simultaneous analog outputs, up to 1 MS/s analog output update rate (PCI-9222/9223)
- Programmable function I/O, supporting modes:
 - TTL DI and TTL DO
 - 2 MHz High-Speed DIO (PCI-9222/9223 only)
 - General-purpose timer/counter
 - PWM outputs
 - Encoder inputs
- Dedicated 2-CH 4 MHz encoder inputs, supporting AB phase, and CW/CCW (PCI-9222/9223)
- Dedicated DMA channels for A/D, D/A, and high-speed DIO (PCI-9222/9223)
- External digital trigger for A/D, D/A, and high-speed DIO (PCI-9222/9223)
- Multiple card synchronization through SSI (System Synchronization Interface) bus (PCI-9222/9223)
- Auto-calibration

Operating Systems

- Windows 7/Vista/2000/XP/Server 2003
- Linux

Recommended Software

- AD-Logger
- VB.NET/VC.NET/VB/VC++/BCB
- DAQBench

Driver Support

- DAQPilot for LabVIEW™
- DAQ-MTLB for MATLAB®
- PCIS-DASK for Windows
- PCIS-DASK/X for Linux

Terminal Boards & Cables

DIN-68S-01 (for PCI-9222/9223)

Terminal Board with One 68-pin SCSI-II Connector and DIN-Rail Mounting (Cables are not included.)

TB-9221-01 (for PCI-9221)

General-purpose Terminal Board with One 37-pin D-Sub Connector. Supports Differential to Single-ended Encoder Signal Conversion of PCI-9221's Function I/O Through Jumper Switching. (Cables are not included.)

DIN-37D-01 (for PCI-9221)

Terminal Board with One 37-pin D-sub Connector and DIN-Rail Mounting (Cables are not included.)

ACL-10568-I (for PCI-9222/9223)

68-pin SCSI-VHDCI cable (mating with AMP-787082-7), 1 M

ACL-10137-IMM (for PCI-9221)

37-pin D-sub male/male cable, 1 M

* For more information on mating cables, please refer to P2-61/62.

SSI Bus Cables (for PCI-9222/9223) (for multiple cards synchronization)

ACL-SSI-2/3/4

SSI Bus cable for two, three, and four devices

Ordering Information

PCI-9221


16-Bit Multi-Function DAQ Card with 2-CH Encoder Input

PCI-9222

16-CH 16-Bit 250 kS/s Multi-Function DAQ Card with Encoder Input

PCI-9223

32-CH 16-Bit 500 kS/s Multi-Function DAQ Card with Encoder Input



Pin Assignment

CNI pin assignment for PCI-9223

A10(AI10)	34	68	A116(AI10)
A11(AI11)	33	67	A117(AI11)
A12(AI12)	32	66	A118(AI12)
A13(AI13)	31	65	A119(AI13)
A14(AI14)	30	64	A120(AI14)
A15(AI15)	29	63	A121(AI15)
A16(AI16)	28	62	A122(AI16)
A17(AI17)	27	61	A123(AI17)
AGND	26	60	AISENSE
A18(AI18)	25	59	A124(AI18)
A19(AI19)	24	58	A125(AI19)
A10(AI10)	23	57	A126(AI10)
A11(AI11)	22	56	A127(AI11)
A12(AI12)	21	55	A128(AI12)
A13(AI13)	20	54	A129(AI13)
A14(AI14)	19	53	A130(AI14)
A15(AI15)	18	52	A131(AI15)
AGND	17	51	AGND
A00	16	50	AGND
A01	15	49	AGND
NC	14	48	NC
NC	13	47	NC
NC	12	46	NC
NC	11	45	NC
NC	10	44	NC
NC	9	43	NC
NC	8	42	NC
NC	7	41	NC
NC	6	40	NC
NC	5	39	NC
NC	4	38	NC
NC	3	37	NC
NC	2	36	NC
NC	1	35	NC

CNI pin assignment for PCI-9222

A10(AI10)	34	68	A18(AI10)
A11(AI11)	33	67	A19(AI11)
A12(AI12)	32	66	A10(AI12)
A13(AI13)	31	65	A11(AI13)
A14(AI14)	30	64	A12(AI14)
A15(AI15)	29	63	A13(AI15)
A16(AI16)	28	62	A14(AI16)
A17(AI17)	27	61	A15(AI17)
AGND	26	60	AISENSE
NC	25	59	NC
NC	24	58	NC
NC	23	57	NC
NC	22	56	NC
NC	21	55	NC
NC	20	54	NC
NC	19	53	NC
NC	18	52	NC
AGND	17	51	AGND
A00	16	50	AGND
A01	15	49	AGND
NC	14	48	NC
NC	13	47	NC
NC	12	46	NC
NC	11	45	NC
NC	10	44	NC
NC	9	43	NC
NC	8	42	NC
NC	7	41	NC
NC	6	40	NC
NC	5	39	NC
NC	4	38	NC
NC	3	37	NC
NC	2	36	NC
NC	1	35	NC

CNI pin assignment for PCI-9222/9223

GP10(GPTC_CLK0)	34	68	GP16(GPTC_CLK2)
GP10(GPTC_LD0)	33	67	GP16(GPTC_LD2)
GP10(GPTC_GATE0)	32	66	GP16(GPTC_GATE2)
GP10(GPTC_CLK1)	31	65	GP16(GPTC_CLK0)
GP10(GPTC_LD1)	30	64	GP16(GPTC_LD0)
GP10(GPTC_GATE1)	29	63	GP16(GPTC_GATE0)
GP10(GPTC_CLK2)	28	62	GP16(GPTC_CLK1)
GP10(GPTC_LD2)	27	61	GP16(GPTC_LD1)
GP10(GPTC_GATE2)	26	60	GP16(GPTC_GATE1)
GP10(GPTC_CLK3)	25	59	GP16(GPTC_CLK2)
GP10(GPTC_LD3)	24	58	GP16(GPTC_LD2)
GP10(GPTC_GATE3)	23	57	GP16(GPTC_GATE2)
GP10(GPTC_CLK4)	22	56	GP16(GPTC_CLK3)
GP10(GPTC_LD4)	21	55	GP16(GPTC_LD3)
GP10(GPTC_GATE4)	20	54	GP16(GPTC_GATE3)
GP10(GPTC_CLK5)	19	53	GP16(GPTC_CLK4)
GP10(GPTC_LD5)	18	52	GP16(GPTC_LD4)
GP10(GPTC_GATE5)	17	51	GP16(GPTC_GATE4)
GP10(GPTC_CLK6)	16	50	GP16(GPTC_CLK5)
GP10(GPTC_LD6)	15	49	GP16(GPTC_LD5)
GP10(GPTC_GATE6)	14	48	GP16(GPTC_GATE5)
GP10(GPTC_CLK7)	13	47	GP16(GPTC_CLK6)
GP10(GPTC_LD7)	12	46	GP16(GPTC_LD6)
GP10(GPTC_GATE7)	11	45	GP16(GPTC_GATE6)
GP10(GPTC_CLK8)	10	44	GP16(GPTC_CLK7)
GP10(GPTC_LD8)	9	43	GP16(GPTC_LD7)
GP10(GPTC_GATE8)	8	42	GP16(GPTC_GATE7)
GP10(GPTC_CLK9)	7	41	GP16(GPTC_CLK8)
GP10(GPTC_LD9)	6	40	GP16(GPTC_LD8)
GP10(GPTC_GATE9)	5	39	GP16(GPTC_GATE8)
GP10(GPTC_CLK10)	4	38	GP16(GPTC_CLK9)
GP10(GPTC_LD10)	3	37	GP16(GPTC_LD9)
GP10(GPTC_GATE10)	2	36	GP16(GPTC_GATE9)
GP10(GPTC_CLK11)	1	35	GP16(GPTC_CLK10)
GP10(GPTC_LD11)			GP16(GPTC_LD10)
GP10(GPTC_GATE11)			GP16(GPTC_GATE10)

CNI pin assignment for PCI-9221

GP02	1	20	GP01
D0ND	2	21	GP10(GPTC_OUT1)
GP02(GPTC_OUT0)	3	22	GP10(GPTC_OUT1)
GP16(GPTC_GATE1)	4	23	D0ND
GP16(GPTC_OUT1)	5	24	GP16(GPTC_OUT1)
GP16(GPTC_OUT0)	6	25	GP16(GPTC_OUT1)
D0ND	7	26	GP16(GPTC_OUT1)
GP16(GPTC_OUT0)	8	27	A01
AGND	9	28	A01
AGND	10	29	A15(AI15)
A17(AI17)	11	30	A14(AI14)
A16(AI16)	12	31	A13(AI13)
A15(AI15)	13	32	A12(AI12)
A14(AI14)	14	33	A13(AI13)
AGND	15	34	A11(AI11)
A13(AI13)	16	35	A12(AI12)
A12(AI12)	17	36	A11(AI11)
A11(AI11)	18	37	A10(AI10)
A10(AI10)	19		

Specifications

Model Name	PCI-9221	PCI-9222	PCI-9223
Analog Input			
Resolution	16 bits		
Number of channels	16 SE/ 8 DIFF	16 SE/ 8 DIFF	32 SE/ 16 DIFF
Maximum sampling rate (single channel)	250 kS/s	250 kS/s	500 kS/s
Programmable gain	1, 5, 10, 25	1, 2, 4, 5, 8, 10, 20, 40	1, 2, 4, 5, 8, 10, 20, 40
Input range	± 5 V, ± 1 V, ± 500 mV, ± 200 mV	± 10 V, ± 5 V, ± 2.5 V, ± 2 V, ± 1.25 V, ± 1 V, ± 500 mV, ± 250 mV	± 10 V, ± 5 V, ± 2.5 V, ± 2 V, ± 1.25 V, ± 1 V, ± 500 mV, ± 250 mV
Offset error	± 2.6 mV typical, before calibration, ± 0.5 mV typical, after calibration		
Gain error	$\pm 0.2\%$ of FSR, before calibration, $\pm 0.015\%$ of FSR, after calibration		
-3 dB small signal bandwidth (gain=1)	1.8 MHz	1.5 MHz	1.5 MHz
System noise (gain=1)	0.1 mV _{RMS}	0.5 mV _{RMS}	0.5 mV _{RMS}
CMRR (gain=1)	71 dB	93.5 dB	93.5 dB
SFDR (Spurious-free dynamic range, gain=1)	95 dB	95 dB	88 dB
SINAD (Signal-to-noise and distortion ratio, gain=1)	85 dB	86 dB	84 dB
THD (Total harmonic distortion, gain=1)	-93 dB	-94 dB	-90 dB
SNR (Signal-to-noise ratio, gain=1)	86 dB	87 dB	86 dB
ENOB (gain=1)	13.5 bits	13.9 bits	13.5 bits
FIFO buffer size	1 k samples		
Trigger sources	Software, external digital	Software, external digital, SSI	Software, external digital, SSI
Trigger mode	Post trigger	Post trigger, retrigger, gate trigger	Post trigger, retrigger, gate trigger
External conversion source	Yes (up to 250 kS/s)	Yes (up to 250 kS/s)	Yes (up to 500 kS/s)
Input coupling	DC		
Overvoltage protection	± 10 V	Continuous ± 30 V	Continuous ± 30 V
Input impedance	High impedance > 1 G Ω		
Data Transfer	Programmed I/O, Interrupt, Bus Mastering DMA		
Analog Output			
Number of channels	2 voltage outputs		
Resolution	16-bit		
Maximum update rate	1.25 kS/s (static)	1 MHz (simultaneous update)	1 MHz (simultaneous update)
FIFO	-	512	512
Output range	± 5 V	± 10 V	± 10 V
Output driving capacity	± 5 mA		
Slew rate	0.014 V/ μ s	20 V/ μ s	20 V/ μ s
Setting time (0.1% of full scale)	1396 μ s	2.6 μ s	2.6 μ s
Offset error	± 1 mV	± 0.1 mV	± 0.1 mV
Gain error	± 2 mV	± 0.1 mV	± 0.1 mV
Rising time	390 μ s	0.67 μ s	0.67 μ s
Falling time	395 μ s	0.705 μ s	0.705 μ s
Function I/O			
Mode	Digital I/O ⁽¹⁾ , General Timer/Counter ⁽¹⁾ , Pulse Generation ⁽¹⁾	Digital I/O, General Timer/Counter, Pulse Generation	Digital I/O, General Timer/Counter, Pulse Generation
Digital I/O	8 DI/4 DO (5 V TTL level)	16 DO (3.3 V TTL Level) / 16 DI (3.3 V or 5 V TTL Level)	16 DO (3.3 V TTL Level) / 16 DI (3.3 V or 5 V TTL Level)
General Timer/Counter	Two 32-bit, Base clock: 40 MHz, external to 10 MHz	Four 32-bit, Base clock: 80 MHz, external to 10 MHz	Four 32-bit, Base clock: 80 MHz, external to 10 MHz
Pulse generation	Two PWM outputs (Modulation frequency: 0.005 Hz to 5 MHz; Duty cycle: 1%-99%)	Four PWM outputs (Modulation frequency: 0.01 Hz to 5 MHz; Duty cycle: 1%-99%)	Four PWM outputs (Modulation frequency: 0.01 Hz to 5 MHz; Duty cycle: 1%-99%)
Encoder Input			
Number of channels	2 ⁽²⁾		
Encoder type	CW/CCW encoder, x 1 AB phase encoder, x 2 AB phase encoder, x 4 AB phase encoder		
General Specifications			
PCI Bus	5 V and 3.3 V universal PCI bus		
Auto-calibration	Yes		
I/O Connector	One 37-pin D-Sub connector	Two 68-pin SCSI-VHDCI female	Two 68-pin SCSI-VHDCI female
Operation temperature	0 to 45°C	0 to 55°C	0 to 55°C
Storage temperature	-20 to 80°C	-20 to 70°C	-20 to 70°C
Humidity	5 to 95% non-condensing		
Power requirements	+5 V 1A typical, +12 V 100mA typical, -12 V 100mA typical	+5 V 1.2 A typical +12 V 760 mA typical -12 V 50 mA typical	+5 V 1.2 A typical +12 V 760 mA typical -12 V 50 mA typical
Dimensions	120 mm x 87 mm	175 mm x 107 mm (not including connectors)	175 mm x 107 mm (not including connectors)

Note:

(1) The function I/O and encoder inputs share the same I/O pins of the PCI-9221. Only one of these modes can be selected.

(2) Dedicated

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А