ECU-P1706
ECU-P1702
ECU-P1300

250 KS/s, 16bit, Simultaneous 8-ch Analog input PCI-104
10 MS/s, 12bit, Simultaneous 4-ch Analog input PCI-104

Vibration Signal Modulate Card

NEW

Features

- Designed for Smart-Grid Applications
- ECU-P1706 focuses on the Vibration/ Substation Signal Analytics (Wind-Power / Smart Substations)
- ECU-P1702 focuses on the Partial Discharge Detection and Analytical Devices (Smart Substations)
- ECU-P1300 focuses on Vibration Applications (Wind-power / Smart Substations)
- Easy to install to ECU-1871 Energy Controller

ECU-P1706

Specifications

General

- **Power Consumption** Typical: 5V @ 850mA
- **Bus Type** PCI-104
- **I/O Connector** Plug-in Terminal Block
- **Operating Temperature** -20 ~ 70°C (-4 ~158°F) @ 5 ~ 85% RH
- **Storage Temperature** -40 ~ 80°C (-40 ~176°F)
- **Storage Humidity** 5 ~ 95% RH, non-condensing (IEC 60068-2-3)

Analog Input

- **Channels** 8 differential
- **Resolution** 16 bits
- **Max. Sampling Rate** 250 KS/s
- **FIFO Size** 8K samples
- **Overvoltage Protection** ±30V
- **Input Impedance** 18MΩ
- **Sampling Mode** Software, onboard programmable pacer and external (TTL Level)
- **Trigger mode** Delay To Start Trigger, Delay To Stop Trigger
- **Trigger Source** Analog Trigger, External Trigger
- **Input Range** (V. Software Programmable)

Bipolar	±10V	±5V	±2.5V	±1.25V
Accuracy % of FSR±1LSB	0.04	0.04	0.06	0.08

Timer Counter

- **Channels** 2
- **Resolution** 32 bits
- **Mode** In: Event counting, Frequency In, PWM In
- **Compatibility** Isolated 24V_{DC}
- **Max. Input Frequency** 1 MHz
- **Max. Output Frequency** 1 MHz

Ordering Information

- **ECU-P1706-AE** 250 KS/s, 16bit, Simultaneous 8-ch PCI-104

ECU-P1702

Specifications

General

- **Power Consumption** 5V @ 700mA (Max.) 3.3V @ 850mA (Max.)
- **Bus Type** PCI-104
- **I/O Connector** BNC
- **Operating Temperature** -20 ~ 70°C (-4 ~158°F) @ 5 ~ 85% RH
- **Storage Temperature** -40 ~ 80°C (-40 ~176°F)
- **Storage Humidity** 5 ~ 95% RH, non-condensing (IEC 60068-2-3)

Analog Input

- **Channels** 4 Single-ended
- **Resolution** 12 bits
- **Max. Sampling Rate** 10 MS/s
- **FIFO Size** 32K samples
- **Overvoltage Protection** ±15V
- **Input Impedance** 50 ohm/1M ohm/Hi Z switch selectable
- **Sampling Mode** Software, onboard programmable pacer and external (TTL Level)
- **Trigger mode** Delay To Start Trigger, Delay To Stop Trigger
- **Trigger Source** Analog Trigger, External Trigger
- **Input Range** ±5V, ±2.5V, ±1V, ±0.5V

Ordering Information

- **ECU-P1702-LAE** 10 MS/s, 12bit, Simultaneous 4-ch PCI-104

ECU-P1300

Specifications

General

- **Power Consumption** Typical: 5V @ 700mA; 12V @ 100mA
- **Operating Temperature** -20 ~ 70°C (-4 ~158°F) @ 5 ~ 85% RH
- **Storage Temperature** -40 ~ 80°C (-40 ~176°F)
- **Storage Humidity** 5 ~ 95% RH, non-condensing (IEC 60068-2-3)

Vibration Modulate

- **Channels** 8
- **Input Range** ±5V (Max.)
- **Output Range** ±10V
- **Input Coupling** AC
- **Sensor Current Supply** 4mA ±1%, 24V compliant
- **Precision** 0.1%
- **Drive Ability** 0 ~ 5K
- **Sensor Signal Gain** 1
- **Signal Gain** 1
- **Analog Filter** 8th order Lowpass Bessel Filters
- **Filter Adjustable** 0.1 Hz ~ 25KHz Adjustable by Software Program

Ordering Information

- **ECU-P1300-AE** Vibration Signal Modulate Card

All product specifications are subject to change without notice

Last updated : 5-May-2015

OCEAN CHIPS
Океан Электроники
Поставка электронных компонентов

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «**JONHON**», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «**FORSTAR**».

AVIC JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).

FORSTAR®

Телефон: 8 (812) 309-75-97 (многоканальный)
Факс: 8 (812) 320-03-32
Электронная почта: ocean@oceanchips.ru
Web: http://oceanchips.ru/
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А