

## FIN1002 LVDS 1-Bit High Speed Differential Receiver

### General Description

This single receiver is designed for high speed interconnects utilizing Low Voltage Differential Signaling (LVDS) technology. The receiver translates LVDS levels, with a typical differential input threshold of 100 mV, to LVTTTL signal levels. LVDS provides low EMI at ultra low power dissipation even at high frequencies. This device is ideal for high speed transfer of clock or data.

The FIN1002 can be paired with its companion driver, the FIN1001, or with any other LVDS driver.

### Features

- Greater than 400Mbps data rate
- 3.3V power supply operation
- 0.4ns maximum pulse skew
- 2.5ns maximum propagation delay
- Bus pin ESD (HBM) protection exceeds 10kV
- Power-Off over voltage tolerant input and output
- Fail safe protection for open-circuit and non-driven, shorted or terminated conditions
- High impedance output at  $V_{CC} < 1.5V$
- Meets or exceeds the TIA/EIA-644 LVDS standard
- 5-Lead SOT23 package saves space

### Ordering Code:


| Order Number | Package Number | Package Description                                             |
|--------------|----------------|-----------------------------------------------------------------|
| FIN1002M5    | MA05B          | 5-Lead SOT23, JEDEC MO-178, 1.6mm [250 Units on Tape and Reel]  |
| FIN1002M5X   | MA05B          | 5-Lead SOT23, JEDEC MO-178, 1.6mm [3000 Units on Tape and Reel] |

### Pin Descriptions

| Pin Name  | Description                |
|-----------|----------------------------|
| $R_{OUT}$ | LVTTL Data Output          |
| $R_{IN+}$ | Non-inverting Driver Input |
| $R_{IN-}$ | Inverting Driver Input     |
| $V_{CC}$  | Power Supply               |
| GND       | Ground                     |
| NC        | No Connect                 |

### Connection Diagram

Pin Assignment for SOT package



Top View

### Function Table

| Input               |           | Outputs   |
|---------------------|-----------|-----------|
| $R_{IN+}$           | $R_{IN-}$ | $R_{OUT}$ |
| L                   | H         | L         |
| H                   | L         | H         |
| Fail Safe Condition |           | H         |

H = HIGH Logic Level  
L = LOW Logic Level  
Fail Safe = Open, Shorted, Terminated

**Absolute Maximum Ratings**(Note 1)

|                                                       |                 |
|-------------------------------------------------------|-----------------|
| Supply Voltage ( $V_{CC}$ )                           | -0.5V to +4.6V  |
| DC Input Voltage ( $R_{IN+}$ , $R_{IN-}$ )            | -0.5V to +4.6V  |
| DC Output Voltage ( $D_{OUT}$ )                       | -0.5V to +6V    |
| DC Output Current ( $I_O$ )                           | 16 mA           |
| Storage Temperature Range ( $T_{STG}$ )               | -65°C to +150°C |
| Max Junction Temperature ( $T_J$ )                    | 150°C           |
| Lead Temperature ( $T_L$ )<br>(Soldering, 10 seconds) | 260°C           |

**Recommended Operating Conditions**

|                                                  |                                               |
|--------------------------------------------------|-----------------------------------------------|
| Supply Voltage ( $V_{CC}$ )                      | 3.0V to 3.6V                                  |
| Input Voltage ( $V_{IN}$ )                       | 0 to $V_{CC}$                                 |
| Magnitude of Differential Voltage ( $ V_{ID} $ ) | 100mV to $V_{CC}$                             |
| Common-mode Input Voltage ( $V_{IC}$ )           | (0V + $ V_{ID} /2$ ) to (2.4 - $ V_{ID} /2$ ) |
| Operating Temperature ( $T_A$ )                  | -40°C to +85°C                                |
| ESD (Human Body Model)                           |                                               |
| All Pins                                         | 8kV                                           |
| LVDS pins to GND                                 | 10kV                                          |
| ESD (Machine Model)                              | 400V                                          |

**Note 1:** The "Absolute Maximum Ratings" are those values beyond which damage to the device may occur. The databook specifications should be met, without exception, to ensure that the system design is reliable over its power supply, temperature and output/input loading variables. Fairchild does not recommend operation of circuits outside databook specification.

**DC Electrical Characteristics**

Over supply voltage and operating temperature ranges, unless otherwise specified

| Symbol       | Parameter                         | Test Conditions                                                                        | Min            | Typ<br>(Note 2) | Max      | Units   |
|--------------|-----------------------------------|----------------------------------------------------------------------------------------|----------------|-----------------|----------|---------|
| $V_{TH}$     | Differential Input Threshold HIGH | See Figure 1; $V_{IC} = +0.05V$ , 1.2V, or 2.35V                                       |                |                 | 100      | mV      |
| $V_{TL}$     | Differential Input Threshold LOW  | See Figure 1; $V_{IC} = +0.05V$ , 1.2V, or 2.35V                                       | -100           |                 |          | mV      |
| $I_{IN}$     | Input Current                     | $V_{IN} = 0V$ or $V_{CC}$                                                              |                |                 | $\pm 20$ | $\mu A$ |
| $I_{I(OFF)}$ | Power-OFF Input Current           | $V_{CC} = 0V$ , $V_{IN} = 0V$ or 3.6V                                                  |                |                 | $\pm 20$ | $\mu A$ |
| $V_{OH}$     | Output HIGH Voltage               | $I_{OH} = -100 \mu A$                                                                  | $V_{CC} - 0.2$ | 3.3             |          | V       |
|              |                                   | $I_{OH} = -8 mA$                                                                       | 2.4            | 3.1             |          |         |
| $V_{OL}$     | Output LOW Voltage                | $I_{OH} = 100 \mu A$                                                                   |                | 0.0             | 0.2      | V       |
|              |                                   | $I_{OL} = 8 mA$                                                                        |                | 0.16            | 0.5      |         |
| $V_{IK}$     | Input Clamp Voltage               | $I_{IK} = -18 mA$                                                                      | -1.5           | 0.8             |          | V       |
| $I_{CC}$     | Power Supply Current              | ( $R_{IN+} = 1V$ and $R_{IN-} = 1.4V$ ), or<br>( $R_{IN+} = 1.4V$ and $R_{IN-} = 1V$ ) |                | 4               | 7        | mA      |
| $C_{IN}$     | Input Capacitance                 | $V_{CC} = 3.3V$                                                                        |                | 2.3             |          | pF      |
| $C_{OUT}$    | Output Capacitance                | $V_{CC} = 0V$                                                                          |                | 2.8             |          | pF      |

**Note 2:** All typical values are at  $T_A = 25^\circ C$  and with  $V_{CC} = 3.3V$ .


**AC Electrical Characteristics**

Over supply voltage and operating temperature ranges, unless otherwise specified

| Symbol       | Parameter                          | Test Conditions                                                  | Min | Typ<br>(Note 3) | Max | Units |
|--------------|------------------------------------|------------------------------------------------------------------|-----|-----------------|-----|-------|
| $t_{PLH}$    | Propagation Delay LOW-to-HIGH      | $ V_{ID}  = 400 mV$ , $C_L = 10 pF$<br>See Figure 1 and Figure 2 | 0.9 | 1.5             | 2.5 | ns    |
| $t_{PHL}$    | Propagation Delay HIGH-to-LOW      |                                                                  | 0.9 | 1.5             | 2.5 | ns    |
| $t_{TLH}$    | Output Rise Time (20% to 80%)      |                                                                  |     | 0.6             |     | ns    |
| $t_{THL}$    | Output Fall Time (80% to 20%)      |                                                                  |     | 0.5             |     | ns    |
| $t_{SK(P)}$  | Pulse Skew ( $t_{PLH} - t_{PHL}$ ) |                                                                  |     | 0.02            | 0.4 | ns    |
| $t_{SK(PP)}$ | Part-to-Part Skew (Note 4)         |                                                                  |     |                 | 1.0 | ns    |

**Note 3:** All typical values are at  $T_A = 25^\circ C$  and with  $V_{CC} = 3.3V$ .


**Note 4:**  $t_{SK(PP)}$  is the magnitude of the difference in propagation delay times between any specified terminals of two devices switching in the same direction (either LOW-to-HIGH or HIGH-to-LOW) when both devices operate with the same supply voltage, same temperature, and have identical test circuits.



**Note A:** All input pulses have frequency = 10MHz,  $t_r$  or  $t_f = 1\text{ns}$


**Note B:**  $C_L$  includes all probe and fixture capacitances

**FIGURE 1. Differential Receiver Voltage Definitions and Propagation Delay and Transition Time Test Circuit**




**FIGURE 2. LVDS Input to LVTTL Output AC Waveforms**


## DC / AC Typical Performance Curves




**FIGURE 3. Output High Voltage vs. Power Supply Voltage**




**FIGURE 4. Output Low Voltage vs. Power Supply Voltage**




**FIGURE 5. Output Short Circuit Current vs. Power Supply Voltage**



**FIGURE 6. Power Supply Current vs. Frequency**



**FIGURE 7. Power Supply Current vs. Ambient Temperature**



**FIGURE 8. Differential Propagation Delay vs. Power Supply Voltage**

## DC / AC Typical Performance Curves (Continued)




FIGURE 9. Differential Propagation Delay vs. Ambient Temperature




FIGURE 10. Differential Skew vs. Power Supply Voltage




FIGURE 11. Differential Skew vs. Ambient Temperature




FIGURE 12. Differential Propagation Delay vs. Differential Input Voltage




FIGURE 13. Differential Propagation Delay vs. Common-Mode Voltage




FIGURE 14. Transition Time vs. Power Supply Voltage

## DC / AC Typical Performance Curves (Continued)




FIGURE 15. Transition Time vs. Ambient Temperature




FIGURE 16. Differential Propagation Delay vs. Load




FIGURE 17. Differential Propagation Delay vs. Load




FIGURE 18. Transition Time vs. Load




FIGURE 19. Transition Time vs. Load







FIGURE 20. Power Supply Current vs. Power Supply Voltage

# Physical Dimensions inches (millimeters) unless otherwise noted



LAND PATTERN RECOMMENDATION



NOTES: UNLESS OTHERWISE SPECIFIED  
 A) THIS PACKAGE CONFORMS TO JEDEC MO-178, ISSUE B, VARIATION AA, DATED JANUARY 1999.  
 B) ALL DIMENSIONS ARE IN MILLIMETERS.

MA05BRevC

5-Lead SOT23, JEDEC MO-178, 1.6mm  
 Package Number MA05B

Fairchild does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and Fairchild reserves the right at any time without notice to change said circuitry and specifications.

## LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

[www.fairchildsemi.com](http://www.fairchildsemi.com)

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,  
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А