

Precision Automotive Thin Film Chip Resistors, AEC-Q200 Qualified, 2 kV ESD Rating



These chip resistors are available in wraparound terminations styles in 8 case sizes. They incorporate self passivated enhanced tantalum nitride resistor film to give superior performance on moisture resistance, electrostatic discharge, voltage coefficient, power handling and resistance stability. The terminations consist of an adhesion layer, a leach resistant nickel barrier, and solder coating (lead (Pb)-free). This product will out-perform all requirements of AEC-Q200.

CONSTRUCTION



FEATURES

- Resistance range: 2.5 Ω to 3 M Ω
- AEC-Q200 qualified
- AEC-Q200 ESD rated class 1C (2 kV)
- Laser trimmed to any value
- Moisture resistant to MIL-STD-202, method 202
- Tantalum nitride resistor film on high purity alumina substrate
- 100 % visual inspected per MIL-PRF-55342
- Laser-trimmed tolerances to ± 0.1 %
- Load life stability < 0.05 % at 1000 h at 70 $^{\circ}$ C
- Very low noise and voltage coefficient (< -30 dB, < 0.1 ppm/V)
- Sulfur resistant (per ASTM B809-95 humid vapor test)
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912



RoHS
COMPLIANT
HALOGEN
FREE
GREEN
(5-2008)

TYPICAL PERFORMANCE

| | ABSOLUTE |
|------|----------|
| ■ | |
| TCR | 25 |
| TOL. | 0.1 |

STANDARD ELECTRICAL SPECIFICATIONS

| TEST | SPECIFICATIONS | CONDITIONS |
|--------------------------------|---|---------------------------------------|
| Material | Tantalum nitride | - |
| Resistance Range | 2.5 Ω to 3 M Ω | - |
| TCR: Absolute | ± 25 ppm/ $^{\circ}$ C to ± 100 ppm/ $^{\circ}$ C | -55 $^{\circ}$ C to +125 $^{\circ}$ C |
| Tolerance: Absolute | ± 0.1 % to ± 1.0 % | +25 $^{\circ}$ C |
| Stability: Absolute | ± 0.05 % | 2000 h at 70 $^{\circ}$ C rated power |
| Stability: Ratio | Not applicable | - |
| Voltage Coefficient | Less than 0.1 ppm/V | - |
| Working Voltage | 75 V to 200 V | - |
| Operating Temperature Range | -55 $^{\circ}$ C to +155 $^{\circ}$ C | - |
| Storage Temperature Range | -55 $^{\circ}$ C to +155 $^{\circ}$ C | - |
| Noise | < -30 dB | - |
| Shelf Life Stability: Absolute | 100 ppm | 1 year at 25 $^{\circ}$ C |

COMPONENT RATINGS

| CASE SIZE | POWER RATING (mW) | WORKING VOLTAGE (V) | RESISTANCE RANGE (Ω) |
|-----------|-------------------|---------------------|-------------------------------|
| 0402 | 50 | 75 | 20 to 51K |
| 0603 | 150 | 75 | 2.5 to 130K |
| 0805 | 200 | 100 | 10 to 301K |
| 1206 | 400 | 200 | 10 to 1M |
| 1505 | 400 | 150 | 10 to 1M |
| 2208 | 750 | 150 | 10 to 1.75M |
| 2010 | 800 | 200 | 10 to 2M |
| 2512 | 1000 | 200 | 10 to 3M |

| DIMENSIONS in inches | | | | | |
|----------------------|---------------|---------------|---------------|-------------------------|-------------------------|
| | | | | | |
| CASE SIZE | L | W | T | D | E |
| 0402 | 0.041 ± 0.003 | 0.022 ± 0.003 | 0.015 ± 0.003 | 0.010 ± 0.005 | 0.010 ± 0.005 |
| 0603 | 0.064 ± 0.006 | 0.032 ± 0.005 | 0.015 ± 0.003 | 0.012 ± 0.005 | 0.015 ± 0.005 |
| 0805 | 0.080 ± 0.006 | 0.050 ± 0.005 | 0.015 ± 0.003 | 0.015 ± 0.005 | 0.015 ± 0.005 |
| 1206 | 0.126 ± 0.008 | 0.063 ± 0.005 | 0.015 ± 0.003 | 0.020 + 0.005 / - 0.010 | 0.020 + 0.005 / - 0.010 |
| 1505 | 0.155 ± 0.007 | 0.050 ± 0.005 | 0.015 ± 0.003 | 0.015 ± 0.005 | 0.015 ± 0.005 |
| 2010 | 0.209 ± 0.009 | 0.098 ± 0.005 | 0.015 ± 0.003 | 0.020 ± 0.005 | 0.020 ± 0.005 |
| 2208 | 0.230 ± 0.007 | 0.075 ± 0.005 | 0.015 ± 0.003 | 0.020 ± 0.005 | 0.020 ± 0.005 |
| 2512 | 0.259 ± 0.009 | 0.124 ± 0.005 | 0.015 ± 0.003 | 0.020 ± 0.005 | 0.020 ± 0.005 |

| ENVIRONMENTAL TESTS (Vishay Performance vs. AEC-Q200 Requirements) | | | | |
|--|--------|--|---------------------|----------------------------|
| ENVIRONMENTAL TEST | | CONDITIONS | LIMITS PER AEC-Q200 | TYPICAL VISHAY PERFORMANCE |
| Resistance Temperature Characteristic | | -55 °C to +125 °C | ± 50 ppm/°C | ± 35 ppm/°C |
| Max. Ambient Temp. at Rated Wattage | | | +70 °C | +70 °C |
| Max. Ambient Temp. at Power Derating | | | +150 °C | +150 °C |
| High Temperature Storage | ΔR | MIL-STD-202, 108, 1000 h at 125 °C | ± 0.1 % | + 0.016 % |
| Temperature Cycling | ΔR | JESD22, JA-104, 1000 cycles, -55 °C to +125 °C | ± 0.15 % | + 0.013 % |
| Moisture Resistance | ΔR | MIL-STD-202, 106 | ± 0.20 % | + 0.0010 % |
| Biased Humidity | ΔR | MIL-STD-202, 103, 1000 h at 85 °C, 85 % RH, 10 % P | ± 0.10 % | + 0.004 % |
| Life | ΔR | MIL-STD-202, 108 at 125 °C, 1000 h | ± 0.1 % | + 0.0220 % |
| Mechanical Shock | ΔR | MIL-STD-202, method 213, condition C | ± 0.1 % | + 0.004 % |
| Vibration | ΔR | MIL-STD-202 method 204, 10 Hz to 2 kHz | ± 0.1 % | + 0.0030 % |
| Resistance to Soldering Heat | ΔR | MIL-STD-202 method 210, condition D | ± 0.10 % | + 0.0150 % |
| Electrostatic Discharge | ΔR | AEC-Q200-002 at 2 kV, human body | ± 0.10 % | - 0.032 % |
| Solderability | Visual | J-STD-002, method B and B1 | 95 % | Acceptable |
| Terminal Strength | ΔR | AEC-Q200-006 at 1 kg for 60 s | ± 0.10 % | + 0.009 % |
| Flame Retardance | Visual | AEC-Q200-001 para 4.0 | | Acceptable |





| GLOBAL PART NUMBER INFORMATION | | | | | | | | | | | | | | | |
|---|--|--|---|---|---|---|---|---|---|--|---|---|---|---|---|
| New Global Part Numbering: PAT1206E1002BST1 | | | | | | | | | | | | | | | |
| P | A | T | 1 | 2 | 0 | 6 | E | 1 | 0 | 0 | 2 | B | S | T | 1 |
| GLOBAL MODEL | CASE SIZE | TCR CHARACTERISTIC | | RESISTANCE | | TOLERANCE | | TERMINATION | | PACKAGING | | | | | |
| PAT | 0402 0603 0805 1206 1505 2010 2208 2512 | E = ± 25 ppm/°C H = ± 50 ppm/°C K = ± 100 ppm/°C L = ± 200 ppm/°C | | The first 3 digits are significant figures and the last digit specifies the number of zeros to follow. "R" designates the decimal point. Example: 10R0 = 10 Ω 1000 = 100 Ω 1002 = 10 kΩ | | B = ± 0.1 % D = ± 0.5 % F = ± 1.0 % G = ± 2.0 % J = ± 5.0 % | | S = wraparound lead (Pb)-free solder w/nickel barrier | | TAPE AND REEL T1 = 1000 min., 1000 mult ⁽¹⁾ TF = full reel TS = 100 min., 1 mult | | | | | |

Note

(1) Preferred packaging code

| RESISTANCE | TCR (ppm/°C) | TOLERANCE (%) |
|--------------|------------------|-------------------|
| 10 Ω to 1 MΩ | 25, 50, 100, 200 | 0.1, 0.5, 1, 2, 5 |
| 5 Ω to 10 Ω | 100, 200 | 1, 2, 5 |
| 1.0 Ω to 5 Ω | 200 | 1, 2, 5 |



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А