

Subminiature Fuse, 2.3 x 8 mm, Quick-Acting F, 125 VAC, 125 VDC



UL 248-14 · 125 VAC · 125 VDC · Quick-Acting F

See below:

[Approvals and Compliances](#)**Description**

- High breaking capacity

References[Packaging Details](#)**Weblinks**[pdf data sheet](#), [html datasheet](#), [General Product Information](#), [Packaging details](#), [Distributor-Stock-Check](#), [Detailed request for product](#)**Technical Data**

| | |
|------------------------------|-------------------------------|
| Rated Voltage | 32 - 125VAC, 32 - 125VDC |
| Rated current | 0.063 - 15 A |
| Breaking Capacity | 50A - 300A |
| Characteristic | Quick-Acting F |
| Admissible Ambient Air Temp. | -55 °C to 85 °C |
| Climatic Category | 55/085/56 acc. to IEC 60068-1 |
| Material: Tube | Ceramics |
| Material: Axial Leads | Tin-Plated Copper |
| Unit Weight | 0.46 g |
| Storage Conditions | 0 °C to 60 °C, max. 70% r.h. |
| Product Marking | Rated current |

| | |
|------------------------------|--|
| Soldering Methods | Wave Soldering Profile |
| Solderability | 235 °C / 2 sec acc. to IEC 60068-2-20, Test Ta, method 1 |
| Resistance to Soldering Heat | 260 °C / 5 sec acc. to IEC 60068-2-20, Test Tb, method 1A |



Approvals and CompliancesDetailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in [Details about Approvals](#)

SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

Approvals



The approval mark is used by the testing authorities to certify compliance with the safety requirements placed on electronic products.

Approval Reference Type: 172322

| Approval Logo | Certificates | Certification Body | Description |
|---|-------------------------------|--------------------|---------------------------------|
|  | UL Approvals | UL | UL File Number: E42088 |
|  | CSA Approvals | CSA | CSA Certification Record: 34549 |
| GAM T1 | | | |

Product standards

Product standards that are referenced

| Organization | Design | Standard | Description |
|---|-----------------------|--------------------|---|
|  | Designed according to | UL 248-14 | Low voltage fuses - Part 14: Additional fuses |
|  | Designed according to | CSA22.2 No. 248.14 | Low-Voltage Fuses - Part 14: Supplemental Fuses |





Application standards

Application standards where the product can be used



| Organization | Design | Standard | Description |
|--|--------------------------------|----------------|--|
|  | Designed for applications acc. | IEC/UL 62368-1 | IEC 62368-1 includes the basic requirements for safety of audio, video, information technology and office equipment. |

Compliances

The product complies with following Guide Lines

| Identification | Details | Initiator | Description |
|--|--|-------------|---|
|  | CE declaration of conformity | SCHURTER AG | The CE marking declares that the product complies with the applicable requirements laid down in the harmonisation of Community legislation on its affixing in accordance with EU Regulation 765/2008. |
|  | RoHS | SCHURTER AG | Directive RoHS 2011/65/EU, Amendment (EU) 2015/863 |
|  | China RoHS | SCHURTER AG | The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS. |
|  | REACH | SCHURTER AG | On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force. |

Dimension [mm]



In ≤ 10 A: ØA = 0.62 mm
 In > 10 A: ØA = 0.82 mm

Pre-Arcing Time

| Rated Current In | 1.0 x In min. | 1.5 x In max. | 2.0 x In max. | 2.75 x In max. | 4.0 x In max. | 10.0 x In max. |
|------------------|---------------|---------------|---------------|----------------|---------------|----------------|
| 0.063 A - 10 A | 4 h | 10 min | 5 s | 300 ms | 30 ms | 4 ms |
| 12 A - 15 A | 4 h | 10 min | 10 s | - | 60 ms | - |

Time-Current-Curves



All Variants

| Rated Current [A] | Rated Voltage [VAC] | Rated Voltage [VDC] | Breaking Capacity | Voltage Drop 1.0 I _n typ. [mV] | Power Dissipation 1.0 I _n typ. [mW] | Melting I ² t 10.0 I _n typ. [A ² s] |   GAM T1 | Order Number |
|-------------------|---------------------|---------------------|-------------------|---|--|--|---|--------------|
| 0.063 | 125 | 125 | 1) | 1050 | 66 | 0.0008 | ● ● | 7010.7010.13 |
| 0.063 | 125 | 125 | 1) | 1050 | 66 | 0.0008 | ● ● | 7010.7010.37 |
| 0.063 | 125 | 125 | 1) | 1050 | 66 | 0.0008 | ● ● | 7010.7010.39 |
| 0.063 | 125 | 125 | 1) | 1050 | 66 | 0.0008 | ● ● | 7010.7010.47 |
| 0.063 | 125 | 125 | 1) | 1050 | 66 | 0.0008 | ● ● | 7010.7010.49 |
| 0.125 | 125 | 125 | 1) | 900 | 115 | 0.0036 | ● ● ● | 7010.7020.13 |
| 0.125 | 125 | 125 | 1) | 900 | 115 | 0.0036 | ● ● ● | 7010.7020.37 |
| 0.125 | 125 | 125 | 1) | 900 | 115 | 0.0036 | ● ● ● | 7010.7020.39 |
| 0.125 | 125 | 125 | 1) | 900 | 115 | 0.0036 | ● ● ● | 7010.7020.47 |
| 0.125 | 125 | 125 | 1) | 900 | 115 | 0.0036 | ● ● ● | 7010.7020.49 |
| 0.25 | 125 | - | 2) | 325 | 82 | 0.0094 | ● ● ● | 7010.7030.13 |
| 0.25 | 125 | - | 2) | 325 | 82 | 0.0094 | ● ● ● | 7010.7030.37 |
| 0.25 | 125 | - | 2) | 325 | 82 | 0.0094 | ● ● ● | 7010.7030.39 |
| 0.25 | 125 | - | 2) | 325 | 82 | 0.0094 | ● ● ● | 7010.7030.47 |
| 0.25 | 125 | - | 2) | 325 | 82 | 0.0094 | ● ● ● | 7010.7030.49 |
| 0.375 | 125 | - | 2) | 245 | 92 | 0.019 | ● ● ● | 7010.7040.13 |
| 0.375 | 125 | - | 2) | 245 | 92 | 0.019 | ● ● ● | 7010.7040.37 |
| 0.375 | 125 | - | 2) | 245 | 92 | 0.019 | ● ● ● | 7010.7040.39 |
| 0.375 | 125 | - | 2) | 245 | 92 | 0.019 | ● ● ● | 7010.7040.47 |
| 0.375 | 125 | - | 2) | 245 | 92 | 0.019 | ● ● ● | 7010.7040.49 |
| 0.5 | 125 | - | 2) | 260 | 130 | 0.07 | ● ● ● | 7010.7050.13 |
| 0.5 | 125 | - | 2) | 260 | 130 | 0.07 | ● ● ● | 7010.7050.37 |
| 0.5 | 125 | - | 2) | 260 | 130 | 0.07 | ● ● ● | 7010.7050.39 |
| 0.5 | 125 | - | 2) | 260 | 130 | 0.07 | ● ● ● | 7010.7050.47 |
| 0.5 | 125 | - | 2) | 260 | 130 | 0.07 | ● ● ● | 7010.7050.49 |
| 0.75 | 125 | - | 2) | 245 | 185 | 0.18 | ● ● ● | 7010.7060.13 |
| 0.75 | 125 | - | 2) | 245 | 185 | 0.18 | ● ● ● | 7010.7060.37 |
| 0.75 | 125 | - | 2) | 245 | 185 | 0.18 | ● ● ● | 7010.7060.39 |

| Rated Current [A] | Rated Voltage [VAC] | Rated Voltage [VDC] | Breaking Capacity | Voltage Drop 1.0 I _n typ. [mV] | Power Dissipation 1.0 I _n typ. [mW] | Melting I ² t 10.0 I _n typ. [A ² s] |    | | | Order Number |
|-------------------|---------------------|---------------------|-------------------|---|--|--|--|---|---|--------------|
| 0.75 | 125 | - | 2) | 245 | 185 | 0.18 | ● | ● | ● | 7010.7060.47 |
| 0.75 | 125 | - | 2) | 245 | 185 | 0.18 | ● | ● | ● | 7010.7060.49 |
| 1 | 125 | - | 2) | 210 | 210 | 0.3 | ● | ● | ● | 7010.7070.13 |
| 1 | 125 | - | 2) | 210 | 210 | 0.3 | ● | ● | ● | 7010.7070.37 |
| 1 | 125 | - | 2) | 210 | 210 | 0.3 | ● | ● | ● | 7010.7070.39 |
| 1 | 125 | - | 2) | 210 | 210 | 0.3 | ● | ● | ● | 7010.7070.47 |
| 1 | 125 | - | 2) | 210 | 210 | 0.3 | ● | ● | ● | 7010.7070.49 |
| 1.5 | 125 | - | 2) | 230 | 345 | 0.38 | ● | ● | ● | 7010.7080.13 |
| 1.5 | 125 | - | 2) | 230 | 345 | 0.38 | ● | ● | ● | 7010.7080.37 |
| 1.5 | 125 | - | 2) | 230 | 345 | 0.38 | ● | ● | ● | 7010.7080.39 |
| 1.5 | 125 | - | 2) | 230 | 345 | 0.38 | ● | ● | ● | 7010.7080.47 |
| 1.5 | 125 | - | 2) | 230 | 345 | 0.38 | ● | ● | ● | 7010.7080.49 |
| 2 | 125 | - | 2) | 190 | 380 | 1.1 | ● | ● | ● | 7010.7090.13 |
| 2 | 125 | - | 2) | 190 | 380 | 1.1 | ● | ● | ● | 7010.7090.37 |
| 2 | 125 | - | 2) | 190 | 380 | 1.1 | ● | ● | ● | 7010.7090.39 |
| 2 | 125 | - | 2) | 190 | 380 | 1.1 | ● | ● | ● | 7010.7090.47 |
| 2 | 125 | - | 2) | 190 | 380 | 1.1 | ● | ● | ● | 7010.7090.49 |
| 2.5 | 125 | - | 2) | 175 | 440 | 1.4 | ● | ● | ● | 7010.7100.13 |
| 2.5 | 125 | - | 2) | 175 | 440 | 1.4 | ● | ● | ● | 7010.7100.39 |
| 2.5 | 125 | - | 2) | 175 | 440 | 1.4 | ● | ● | ● | 7010.7100.47 |
| 2.5 | 125 | - | 2) | 175 | 440 | 1.4 | ● | ● | ● | 7010.7100.49 |
| 3 | 125 | - | 2) | 170 | 510 | 2 | ● | ● | ● | 7010.7110.13 |
| 3 | 125 | - | 2) | 170 | 510 | 2 | ● | ● | ● | 7010.7110.39 |
| 3 | 125 | - | 2) | 170 | 510 | 2 | ● | ● | ● | 7010.7110.47 |
| 3 | 125 | - | 2) | 170 | 510 | 2 | ● | ● | ● | 7010.7110.49 |
| 3.5 | 125 | - | 2) | 160 | 560 | 2.6 | ● | ● | ● | 7010.7180.13 |
| 3.5 | 125 | - | 2) | 160 | 560 | 2.6 | ● | ● | ● | 7010.7180.37 |
| 3.5 | 125 | - | 2) | 160 | 560 | 2.6 | ● | ● | ● | 7010.7180.39 |
| 3.5 | 125 | - | 2) | 160 | 560 | 2.6 | ● | ● | ● | 7010.7180.47 |
| 3.5 | 125 | - | 2) | 160 | 560 | 2.6 | ● | ● | ● | 7010.7180.49 |
| 4 | 125 | - | 2) | 180 | 720 | 4 | ● | ● | ● | 7010.7120.13 |
| 4 | 125 | - | 2) | 180 | 720 | 4 | ● | ● | ● | 7010.7120.37 |
| 4 | 125 | - | 2) | 180 | 720 | 4 | ● | ● | ● | 7010.7120.39 |
| 4 | 125 | - | 2) | 180 | 720 | 4 | ● | ● | ● | 7010.7120.47 |
| 4 | 125 | - | 2) | 180 | 720 | 4 | ● | ● | ● | 7010.7120.49 |
| 5 | 125 | 125 | 1) | 170 | 850 | 6.2 | ● | ● | ● | 7010.7130.13 |
| 5 | 125 | 125 | 1) | 170 | 850 | 6.2 | ● | ● | ● | 7010.7130.37 |
| 5 | 125 | 125 | 1) | 170 | 850 | 6.2 | ● | ● | ● | 7010.7130.39 |
| 5 | 125 | 125 | 1) | 170 | 850 | 6.2 | ● | ● | ● | 7010.7130.47 |
| 5 | 125 | 125 | 1) | 170 | 850 | 6.2 | ● | ● | ● | 7010.7130.49 |
| 7 | 125 | 125 | 1) | 135 | 945 | 13 | ● | ● | ● | 7010.7140.13 |
| 7 | 125 | 125 | 1) | 135 | 945 | 13 | ● | ● | ● | 7010.7140.37 |
| 7 | 125 | 125 | 1) | 135 | 945 | 13 | ● | ● | ● | 7010.7140.39 |
| 7 | 125 | 125 | 1) | 135 | 945 | 13 | ● | ● | ● | 7010.7140.47 |
| 7 | 125 | 125 | 1) | 135 | 945 | 13 | ● | ● | ● | 7010.7140.49 |
| 10 | 125 | 125 | 1) | 130 | 1300 | 39 | ● | ● | ● | 7010.7150.13 |
| 10 | 125 | 125 | 1) | 130 | 1300 | 39 | ● | ● | ● | 7010.7150.37 |
| 10 | 125 | 125 | 1) | 130 | 1300 | 39 | ● | ● | ● | 7010.7150.39 |
| 10 | 125 | 125 | 1) | 130 | 1300 | 39 | ● | ● | ● | 7010.7150.47 |
| 10 | 125 | 125 | 1) | 130 | 1300 | 39 | ● | ● | ● | 7010.7150.49 |
| 12 | 32 | 32 | 3) | 130 | 1450 | 57 | ● | ● | ● | 7010.7160.13 |
| 12 | 32 | 32 | 3) | 130 | 1450 | 57 | ● | ● | ● | 7010.7160.37 |
| 12 | 32 | 32 | 3) | 130 | 1450 | 57 | ● | ● | ● | 7010.7160.39 |
| 12 | 32 | 32 | 3) | 130 | 1450 | 57 | ● | ● | ● | 7010.7160.47 |

| Rated Current [A] | Rated Voltage [VAC] | Rated Voltage [VDC] | Breaking Capacity | Voltage Drop 1.0 I _n typ. [mV] | Power Dissipation 1.0 I _n typ. [mW] | Melting I ² t 10.0 I _n typ. [A ² s] |  | Order Number |
|-------------------|---------------------|---------------------|-------------------|---|--|--|--|--------------|
| 12 | 32 | 32 | 3) | 130 | 1450 | 57 | ● ● ● | 7010.7160.49 |
| 15 | 32 | 32 | 3) | 120 | 1800 | 90 | ● ● ● | 7010.7170.13 |
| 15 | 32 | 32 | 3) | 120 | 1800 | 90 | ● ● ● | 7010.7170.37 |
| 15 | 32 | 32 | 3) | 120 | 1800 | 90 | ● ● ● | 7010.7170.47 |
| 15 | 32 | 32 | 3) | 120 | 1800 | 90 | ● ● ● | 7010.7170.49 |

Most Popular.

Availability for all products can be searched real-time: <https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER>

1) UL: 50 A @ 125 VAC, p.f. ≥ 0.95 / 300 A @ 125 VDC

1) CSA: 300 A @ 125 VAC/DC

2) UL: 50 A @ 125 VAC, p.f. ≥ 0.95

2) CSA: 300 A @ 125 VAC

3) UL: 50 A @ 32 VAC, p.f. ≥ 0.95 / 300 A @ 32 VDC

3) CSA: 300 A @ 32 VAC/DC

Packaging Unit

| | |
|-----------|---|
| .xx = .13 | Plastic Bag, Fuse Length 86 mm (100 pcs.) |
| .xx = .37 | Taped 19 cm Reel, Fuse Length 65 mm (1500 pcs.) |
| .xx = .39 | Taped 19 cm Reel, Fuse Length 65 mm (5000 pcs.) |
| .xx = .47 | Taped 19 cm Reel, Fuse Length 86 mm (1500 pcs.) |
| .xx = .49 | Taped 19 cm Reel, Fuse Length 85 mm (5000 pcs.) |

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А