

# General Specifications

## Electrical Capacity (Resistive Load)

**Logic Level:** 0.4VA maximum @ 28V AC/DC maximum  
(Applicable Range 0.1mA ~ 0.1A @ 20mV ~ 28V)  
Note: See Supplement section for explanation of operating range.

## Other Ratings

**Contact Resistance:** 80 milliohms maximum  
**Insulation Resistance:** 500 megohms minimum @ 500V DC  
**Dielectric Strength:** 500V AC minimum for 1 minute minimum  
**Mechanical Life:** 50,000 operations minimum  
**Electrical Life:** 50,000 operations minimum  
**Nominal Operating Force:** 1.6N for momentary & 1.7N for maintained  
**Angle of Throw:** 28°

## Materials & Finishes

**Actuator:** Polyphenylene sulfide (UL94V-0)  
**Case:** Polyphenylene sulfide (UL94V-0)  
**Sealing Rings:** Nitrile butadiene rubber  
**Movable Contacts:** Phosphor bronze with gold plating  
**Stationary Contacts:** Phosphor bronze with gold plating  
**Base:** Polyphenylene sulfide (UL94V-0)  
**Terminals:** Phosphor bronze with gold plating

## Environmental Data

**Operating Temperature Range:** -30°C through +85°C (-22°F through +185°F)  
**Humidity:** 90 ~ 95% humidity for 96 hours @ 40°C (104°F)  
**Vibration:** 10 ~ 500Hz with peak-to-peak amplitude of 1.5mm traversing the frequency range & returning in 1 minute; 3 right angled directions for 2 hours  
**Shock:** 50G (490m/s<sup>2</sup>) acceleration (tested in 6 right angled directions, with 5 shocks in each direction)

## Installation

**Mounting:** It is recommended that the body of models for upright mounting without bracket be fastened to a panel or similar support for protection of solder joints from mechanical stress.  
**Coplanarity:** See specifications in Terms & Acronyms in Supplement section

## Processing

**Soldering:** Reflow Soldering recommended. See Profile B in Supplement section.  
Manual Soldering: See Profile B in Supplement section.  
**Cleaning:** Automated cleaning. See Cleaning specifications in Supplement section.

## Standards & Certifications

**Flammability Standard:** UL94V-0 actuator, case & base  
The G3T Series toggles have not been tested for UL recognition or CSA certification.  
These switches are designed for use in a low-voltage, low-current, logic-level circuit.  
When used as intended in a logic-level circuit, the results do not produce hazardous energy.

# Distinctive Characteristics

Ultra-miniature size allows high density mounting, and extremely light weight of 0.6 gram makes these switches ideal for handheld equipment.

Tape-reel and stick-tube packaging allow rapid automated placement of surface mount devices. Tape-reel packaging meets EIA-481-D Standard.


Heat resistant resin used for housing, base, and lever allows vapor phase and infrared convection reflow soldering.

Combination of design features achieves total seal and allows automated processing techniques, including flux cleaning procedures: one-piece bushing and housing, rubber seals surrounding actuator and base, epoxy at joint of case and base, and molded-in, epoxy-sealed terminals.


Award-winning STC contact mechanism with benefits unavailable in conventional mechanisms: smoother, positive detent actuation, increased contact stability and unparalleled logic-level reliability. (Additional STC details in Terms & Acronyms; see Supplement section.)

Gull-wing terminals provide mechanical stability during soldering and simplified solder joint inspection.

Coplanarity: all considered surfaces must lie between two parallel planes that are a maximum distance apart of .0059" (0.15mm). (Additional coplanarity details in Terms and Acronyms in the Supplement section.)



Actual Size


A  
Toggles

Rockers

Pushbuttons

Illuminated PB

Programmable

Keylocks

Rotaries

Slides

Tactiles

Tilt

Touch

Indicators

Accessories

Supplement

### TYPICAL SWITCH ORDERING EXAMPLE

**G3T**

**1**

**2**

**A**

**H**

—

#### Poles

|   |      |
|---|------|
| 1 | SPDT |
| 2 | DPDT |

#### Actuator

|          |                                |
|----------|--------------------------------|
| <b>A</b> | .150" (3.8mm)<br>Column Toggle |
|----------|--------------------------------|

#### Packaging

|                                           |                                                               |
|-------------------------------------------|---------------------------------------------------------------|
| <b>R</b>                                  | Tape-Reel for<br>Right Angle Only<br>500 Pieces/Reel          |
| <b>S</b>                                  | Stick-Tube for<br>Upright Mount<br>50 Pieces/Stick            |
| <b>No<br/>Code</b>                        | Partitioned Tray for<br>Upright & Right Angle<br>Any Quantity |
| Packaging details at<br>end of G3T Series |                                                               |

#### Circuits

|          |      |      |      |
|----------|------|------|------|
| <b>2</b> | ON   | NONE | ON   |
| <b>3</b> | ON   | OFF  | ON   |
| <b>5</b> | ON   | NONE | (ON) |
| <b>8</b> | (ON) | OFF  | (ON) |
| <b>9</b> | ON   | OFF  | (ON) |

( ) = Momentary

#### Terminals


|          |                                          |
|----------|------------------------------------------|
| <b>P</b> | Gull Wing for Upright Mount              |
| <b>B</b> | Gull Wing for Upright with Bracket Mount |
| <b>H</b> | Gull Wing for Right Angle Mount          |

### DESCRIPTION FOR TYPICAL ORDERING EXAMPLE

**G3T12AH**




### POLES & CIRCUITS

|      |              | Toggle Position<br>( ) = Momentary                                                        |                                                                                               |                                                                                             | Connected Terminals                                                                       |                                                                                                |                                                                                               | Throw & Schematics                                                                            |
|------|--------------|-------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------|
|      |              | Up<br> | Center<br> | Down<br> | Up<br> | Center<br> | Down<br> |                                                                                               |
| Pole | Model        |                                                                                           |                                                                                               |                                                                                             |                                                                                           |                                                                                                |                                                                                               | Note: Terminal numbers are not actually on switch.                                            |
| SP   | <b>G3T12</b> | ON                                                                                        | NONE                                                                                          | ON                                                                                          | 5-6                                                                                       | OPEN                                                                                           | 5-4                                                                                           | SPDT<br> |
|      | <b>G3T13</b> | ON                                                                                        | OFF                                                                                           | ON                                                                                          |                                                                                           |                                                                                                |                                                                                               |                                                                                               |
|      | <b>G3T15</b> | ON                                                                                        | NONE                                                                                          | (ON)                                                                                        |                                                                                           |                                                                                                |                                                                                               |                                                                                               |
|      | <b>G3T18</b> | (ON)                                                                                      | OFF                                                                                           | (ON)                                                                                        |                                                                                           |                                                                                                |                                                                                               |                                                                                               |
|      | <b>G3T19</b> | ON                                                                                        | OFF                                                                                           | (ON)                                                                                        |                                                                                           |                                                                                                |                                                                                               |                                                                                               |
| DP   | <b>G3T22</b> | ON                                                                                        | NONE                                                                                          | ON                                                                                          | 5-6 2-3                                                                                   | OPEN                                                                                           | 5-4 2-1                                                                                       | DPDT<br> |
|      | <b>G3T23</b> | ON                                                                                        | OFF                                                                                           | ON                                                                                          |                                                                                           |                                                                                                |                                                                                               |                                                                                               |
|      | <b>G3T25</b> | ON                                                                                        | NONE                                                                                          | (ON)                                                                                        |                                                                                           |                                                                                                |                                                                                               |                                                                                               |
|      | <b>G3T28</b> | (ON)                                                                                      | OFF                                                                                           | (ON)                                                                                        |                                                                                           |                                                                                                |                                                                                               |                                                                                               |
|      | <b>G3T29</b> | ON                                                                                        | OFF                                                                                           | (ON)                                                                                        |                                                                                           |                                                                                                |                                                                                               |                                                                                               |

### ACTUATOR

**A**

.150" (3.8mm) Column Toggle



## A Toggles

## Rocker's



## Pushbuttons



## Keylocks



## Kotaries



### PACKAGING

**R**

#### Tape-Reel for Right Angle

500 pieces per reel

Switches must be ordered in 500-piece increments when tape-reel packaging is selected.

This packaging meets EIA-481-D Standard for "16mm and 24mm Embossed Carrier Taping of Surface Mount Components for Automatic Handling."



**S**

#### Stick-Tube for Upright Mount

50 pieces per stick

Switches must be ordered in 50-piece increments when stick-tube packaging is selected.



**No  
Code**

#### Partitioned Tray for Upright & Right Angle

Any quantity

If the G3 upright models are ordered in less than 50-piece increments or the right angle models in less than 500-piece increments, the switches are packaged in a partitioned tray. No code is required.




PACKAGING (CONTINUED)

Tape-Reel Packaging for Right Angle Mount


Each tape-reel of 550 pockets contains 500 switches.

Minimum Leader Length: 7.87" (200mm) Minimum Trailer Length: 1.97" (50mm)



Stick-Tube Packaging for Upright Mount

Each stick-tube contains 50 switches.



Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,  
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А