



Features

- Meets UL/EN/IEC60601-1-2, 4th edition for EMC*
- Approved to EN/IEC/UL60601-1, 3rd edition
- 2 MOPP input-output isolation
- Meets DoE Efficiency Level VI Requirements
 - No load input power
 - Average Efficiency
- Up to 30W of AC-DC Power
- Universal Input 90-264Vac Input Range
 - Desktop and Wall-Plug versions
- Meets EN55011/CISPR11, FCC Part 15.109 Class B Conducted & Radiated Emissions, with >6db margin
- E-cap life of >8 years
- >1,000,000 hours MTBF
- IP22 Rated Enclosure
- 3 Year Warranty

Description

A high performance AC to DC external power supply family designed for medical applications. The ME30A Medical Series low power external AC-DC power supplies are approved to safety EN/IEC/UL60601-1, 3rd edition with isolation levels which satisfy the 2 MOPP requirements and designed to UL/EN/IEC60601-1-2, 4th edition for EMC*. The ME30A Series models will operate at universal input range of 90 to 264Vac over the wide temperature range of -20°C to +50°C, delivering full rated output power up to +40°C and applicable output power derating at 50°C. These models are available in desktop and wall-plug versions, include an IP22 rating per IEC60529 for the enclosure, and output cable terminated at a variety of output connectors.

*Consult Factory for Table 9 compliance information.

Model Selection

| Model Number | Volts | Output Current | Output Power | Ripple & Noise ¹ | Line Regulation | Load Regulation | Overvoltage Trip Range | Output Connector | Input Configuration |
|--------------|-------|----------------|--------------|-----------------------------|-----------------|-----------------|------------------------|---|--|
| ME30A0503F01 | 5.0V | 4.00A | 20W | 75mV pk-pk | ±1% | ±5% | 5.75V-7.75V | 2.5 x 5.5 x 9.5mm Straight Barrel Type, center positive | Class I Desktop, IEC60320 C14 Receptacle |
| ME30A0903F01 | 9.0V | 3.00A | 27W | 90mV pk-pk | ±1% | ±5% | 11.7V-16.2V | | |
| ME30A1203F01 | 12.0V | 2.50A | 30W | 120mV pk-pk | ±1% | ±5% | 14.4V-16.8V | | |
| ME30A1503F01 | 15.0V | 2.00A | 30W | 150mV pk-pk | ±1% | ±5% | 18.0V-21.0V | | |
| ME30A1803F01 | 18.0V | 1.67A | 30W | 180mV pk-pk | ±1% | ±5% | 21.6V-25.2V | | |
| ME30A2403F01 | 24.0V | 1.33A | 30W | 240mV pk-pk | ±1% | ±5% | 28.8V-33.6V | | |
| ME30A4803F01 | 48.0V | 0.63A | 30W | 480mV pk-pk | ±1% | ±5% | 55.0V-60.0V | | |
| ME30A0503N01 | 5.0V | 4.00A | 20W | 75mV pk-pk | ±1% | ±5% | 5.75V-7.75V | 2.5 x 5.5 x 9.5mm Straight Barrel Type, center positive | Class II Desktop, IEC60320 C8 Receptacle |
| ME30A0903N01 | 9.0V | 3.00A | 27W | 90mV pk-pk | ±1% | ±5% | 11.7V-16.2V | | |
| ME30A1203N01 | 12.0V | 2.50A | 30W | 120mV pk-pk | ±1% | ±5% | 14.4V-16.8V | | |
| ME30A1503N01 | 15.0V | 2.00A | 30W | 150mV pk-pk | ±1% | ±5% | 18.0V-21.0V | | |
| ME30A1803N01 | 18.0V | 1.67A | 30W | 180mV pk-pk | ±1% | ±5% | 21.6V-25.2V | | |
| ME30A2403N01 | 24.0V | 1.33A | 30W | 240mV pk-pk | ±1% | ±5% | 28.8V-33.6V | | |
| ME30A4803N01 | 48.0V | 0.63A | 30W | 480mV pk-pk | ±1% | ±5% | 55.0V-60.0V | | |

Model Selection (continued)

| Model Number | Volts | Output Current | Output Power | Ripple & Noise ¹ | Line Regulation | Load Regulation | Overvoltage Trip Range | Output Connector | Input Configuration |
|--------------|-------|----------------|--------------|-----------------------------|-----------------|-----------------|------------------------|---|---|
| ME30A0503Q01 | 5.0V | 4.00A | 20W | 75mV pk-pk | ±1% | ±5% | 5.75V-7.75V | 2.5 x 5.5 x 9.5mm Straight Barrel Type, center positive | Class II Desktop, IEC60320 C18 Receptacle |
| ME30A0903Q01 | 9.0V | 3.00A | 27W | 90mV pk-pk | ±1% | ±5% | 11.7V-16.2V | | |
| ME30A1203Q01 | 12.0V | 2.50A | 30W | 120mV pk-pk | ±1% | ±5% | 14.4V-16.8V | | |
| ME30A1503Q01 | 15.0V | 2.00A | 30W | 150mV pk-pk | ±1% | ±5% | 18.0V-21.0V | | |
| ME30A1803Q01 | 18.0V | 1.67A | 30W | 180mV pk-pk | ±1% | ±5% | 21.6V-25.2V | | |
| ME30A2403Q01 | 24.0V | 1.33A | 30W | 240mV pk-pk | ±1% | ±5% | 28.8V-33.6V | | |
| ME30A4803Q01 | 48.0V | 0.63A | 30W | 480mV pk-pk | ±1% | ±5% | 55.0V-60.0V | 2.5 x 5.5 x 9.5mm Straight Barrel Type, center positive | Class II Wall-Plug, Interchangeable Blades (North American Blade included) ² |
| ME30A0503B01 | 5.0V | 4.00A | 20W | 75mV pk-pk | ±1% | ±5% | 5.75V-7.75V | | |
| ME30A0903B01 | 9.0V | 3.00A | 27W | 90mV pk-pk | ±1% | ±5% | 11.7V-16.2V | | |
| ME30A1203B01 | 12.0V | 2.50A | 30W | 120mV pk-pk | ±1% | ±5% | 14.4V-16.8V | | |
| ME30A1503B01 | 15.0V | 2.00A | 30W | 150mV pk-pk | ±1% | ±5% | 18.0V-21.0V | | |
| ME30A1803B01 | 18.0V | 1.67A | 30W | 180mV pk-pk | ±1% | ±5% | 21.6V-25.2V | | |
| ME30A2403B01 | 24.0V | 1.33A | 30W | 240mV pk-pk | ±1% | ±5% | 28.8V-33.6V | 2.5 x 5.5 x 9.5mm Straight Barrel Type, center positive | Class II Wall-Plug, Fixed North American Blades ³ |
| ME30A4803B01 | 48.0V | 0.63A | 30W | 480mV pk-pk | ±1% | ±5% | 55.0V-60.0V | | |
| ME30A0503C01 | 5.0V | 4.00A | 20W | 75mV pk-pk | ±1% | ±5% | 5.75V-7.75V | | |
| ME30A0903C01 | 9.0V | 3.00A | 27W | 90mV pk-pk | ±1% | ±5% | 11.7V-16.2V | | |
| ME30A1203C01 | 12.0V | 2.50A | 30W | 120mV pk-pk | ±1% | ±5% | 14.4V-16.8V | | |
| ME30A1503C01 | 15.0V | 2.00A | 30W | 150mV pk-pk | ±1% | ±5% | 18.0V-21.0V | | |
| ME30A1803C01 | 18.0V | 1.67A | 30W | 180mV pk-pk | ±1% | ±5% | 21.6V-25.2V | 28.8V-33.6V | |
| ME30A2403C01 | 24.0V | 1.33A | 30W | 240mV pk-pk | ±1% | ±5% | 28.8V-33.6V | | |
| ME30A4803C01 | 48.0V | 0.63A | 30W | 480mV pk-pk | ±1% | ±5% | 55.0V-60.0V | | |

- Notes:
1. Measured at the output connector, with noise probe directly across output and load terminated with 0.1µF ceramic and 10µF low ESR capacitors. For 5V and 6V models, values listed are typical, 100mV pk-pk maximum with 0.1µF ceramic and 47µF low ESR capacitors used at measurement point.
 2. Order blade kit KT-1027K for other blades (EU, UK, Australia)
 3. For EU fixed blades, replace "C" in the model number with "M", for UK blades, replace "C" with "G", for Australia blades, replace "C" with "H".
 4. All specifications are typical at nominal input, full load, at 25°C ambient unless noted.
 5. For Input Class I models: For AC GND connected to output common (-), insert a "B" in the part number where the "A" is located (ME30B1203F01).

General Specifications

| | | | |
|------------------------------|---|-----------------------------------|--|
| AC Input | 100-240Vac, ±10%, 47-63Hz, 1Ø | Turn On Time | Less than 700mS @115Vac, full load |
| Input Current | 115Vac: 1.2A, 230Vac:0.6A | Hold-up Time | 20mS min., at full Load, 100Vac input |
| Inrush Current | 264Vac, cold start: will not exceed 40A | Overtemperature Protection | Will shutdown upon an overtemperature condition, auto-recovery. |
| Input Fuses | F1, F2: 2.0A, 250Vac fuses (line & neutral lines) provided on all models | Overload Protection | 130 to 180% of rating, Hiccup Mode |
| Earth Leakage Current | Input-GND: <500µA@264Vac, 60Hz, NC Output-GND: <4mA@264Vac, 60Hz, NC | Short Circuit Protection | Hiccup Mode, auto recovery. |
| Efficiency | >87%, typical | Overvoltage Protection | Hiccup mode, see models chart for trip ranges. |
| Output Power | 20 to 30W continuous – See models chart for specific voltage model ratings. | Isolation | Input-Output: 2 MOPP Input-Ground: 1 MOPP Output-Ground: 1 MOPP |
| No Load Input Power | <0.1W per DoE Efficiency Level VI Requirements | Safety Standards | EN/IEC/UL60601-1-1, 3rd edition |
| Ripple and Noise | See models chart on pg 1. | Operating Temperature | -20°C to +50°C Start Up at -40°C, full load, (warmup period before all parameters are within published specifications). |
| Output Voltage | See models chart on pg 1. | Temperature Derating | Derate output power above 40°C to TBD at 50°C |
| Transient Response | 500µs response time for return to within 0.5% of final value for any 50% load step over the range of 5% to 100% of rated load, Δi/Δt< 0.2A/µs. Max. voltage deviation is +/-3.5%. | Storage Temperature | -40°C to +85°C |
| Regulation | See models chart on pg 1. | Altitude | Operating: to 5000m. Non-operating: -500 to 40,000 ft. |
| Drop Test | 1.4m from table top to wooden platform, 6 faces. | Relative Humidity | 5% to 95%, non-condensing |

General Specifications (continued)

| | | | |
|-------------------|--|-------------------|---|
| Vibration | Operating: 0.003g/Hz, 1.5grms overall, 3 axes, 10 min/axis, 1-500Hz. Non-Oper.: random waveform, 3 minutes per axis, 3 axes and Sine waveform, Vib. frequency/acceleration: 10-500Hz/1g, sweep rate of 1 octave / minutes, Vibration time of 10 sweeps / axes, 3 axes | Shock | Operating: Half-sine, 20gpk, 10mS, 3 axes, 6 shocks total Non-Operating: Half-sine waveform, impact acceleration of 100G, Pulse duration of 6 mS, Number of shocks: 3 for each of the three axis |
| Dimensions | See outline drawings | MTBF | >1,000,000 hours, full load, 110 & 220Vac input, 25°C amb., per Telcordia 332 Issue 6. |
| Weight | 250g | E-Cap Life | >8 year life based on calculations at 115Vac/60Hz & 230Vac/50Hz, ambient 25°C at 24 hrs per day, 365 days/year, 6 power up cycles per day. |

All specifications are typical at nominal input, full load, at 25°C ambient unless noted.


EMI/EMC Compliance

| | |
|--|---|
| Conducted Emissions: | EN55011/CISPR11 Class B, FCC Part 15.107, Class B: >6db margin typ, at 115 and 230Vac |
| Radiated Emissions: | EN55022/CISPR11 Class B, FCC Part 15.109, Class B: >3db margin typ, at 115 and 230Vac |
| Common Mode Noise: | High Frequency (100kHz-20MHz): <40mA pk-pk |
| Electro-Static Discharge (ESD) Immunity on Power ports: | EN55024/IEC61000-4-2, Level 4: +/- 8kV contact, +/- 15kV air, Criteria A IEC60601-1-2, 4 th Edition, Table 4 |
| Radiated RF EM Fields Susceptibility | EN55022/EN61000-4-3, 10V/m, 80MHz-2.7GHz, 80% AM at 1kHz IEC60601-1-2, 4 th Edition, Table 4 |
| Electrical Fast Transients (EFT) /Bursts: | EN55024/IEC61000-4-4, Level 4, +/- 4kV, 100Khz rep rate, 40A, Criteria A IEC60601-1-2, 4 th Edition, Table 5 |
| Surges, Line to Line (Diff Mode) and Line to GND (CMN Mode) | EN55024/IEC61000-4-5, Level 4, +/-2kV DM, +/-4kV CM, Criteria A Surpasses IEC60601-1-2, 4 th Edition requirements. |
| Conducted Disturbances induced by RF Fields | EN55022/IEC61000-4-6, 3.6V/m – Level 4, 0.15 to 80Mhz; and 12V/m) in ISM and amateur radio bands between 0.15Mhz and 80Mhz, 80% AM at 1KHz IEC60601-1-2, 4 th Edition, Table 5. |
| Rated Power frequency magnetic fields | EN55024/IEC1000-4-8, Level 4: 30A/m, 50/60 Hz IEC60601-1-2, 4 th Edition, Table 4 |
| Voltage Interruptions, Dips, Sags & Surges | EN55024/IECEN61000-4-11: --100% dip for 10 mS, at 0, 45, 90, 135, 180, 225, 270 and 315 degrees, 100% dip for 20mS, 0 deg., Criteria A --100% dip for 500mS (250/300 cycles), Criteria B -- 60% dip for 100mS, Criteria B -- 30% dip for 500mS, Criteria A IEC60601-1-2, 4 th Edition, Table 5 |
| Harmonic Current Emissions | EN55011/EN61000-3-2, Class A |
| Flicker Test | EN61000-3-3 |


All specifications are typical at nominal input, full load, at 25°C ambient unless noted. Consult factory for information regarding testing for or usage under special environments.

Output Power Derating

Output power is derated above 40°C as follows, for operation over the entire AC input range (90-264Vac).



Mechanical Drawing



IEC60320 C14 Receptacle, 2.5 x 5.5 x 9.5mm Barrel Connector

Interchangeable N.A. Blade, 2.5 x 5.5 x 9.5mm barrel connector

Notes:

1. All dimensions in mm.
2. Interchangeable blade models come with North American blade fitted. For other blades (EU, UK, Aust.) order blade kit KT1027K.
3. Cable length for 5V models is 1200 +/- 50mm.

Connector Information

Standard models include a 2.5 x 5.5 x 9.5mm straight barrel type connector (Ault #3), center positive. Other standard options are listed below. The "03" in the standard model number is replaced by the applicable digits below:

| Connector No. | Description | Connector No. | Description |
|---------------|--|---------------|---|
| 02 | 2.1 x 5.5 x 9.5mm straight barrel plug - Center Positive | 44 | 2.1 x 5.5 x 9.5mm straight barrel plug, locking - Center Positive |
| 03 | 2.5 x 5.5 x 9.5mm straight barrel plug - Center Positive (Standard Models) | 45 | 2.5 x 5.5 x 9.5mm straight barrel plug, locking - Center Positive |
| 12 | 5 pin DIN-180 male connector (Pins 3, 5 = (+), pins 1, 2, 4 = (-)) | 48 | 3 pin Snap n Lock, Kycon Kpp-3P or equivalent (Pin 1 = (+), pin 2 = (-)) |
| 22 | 6 pin DIN male connector (Pins 1, 2 = (+), pins 4, 5 = (-)) | 49 | 4 pin Snap n Lock, Kycon Kpp-4P or equivalent (Pins 1, 3 = (+), pins 2, 4 = (-)) |
| 23 | 8 pin DIN male connector (Pins 3, 7 = (+), pins 1, 4, 6, 8 = (-), shell = FG)) | 51 | 6 pin Minifit - Molex 39-01-2060 or equivalent (Pins 1, 4 = (+), pins 3, 6 = (-)) |
| 32 | 9 pin "D" type, female (Pin 8 = (+), pin 5 = (-), all others = NC) | 65 | Stripped and Tinned Leads |
| 33 | 2.5 x 5.5 x 12.5mm straight barrel plug - Center Positive | 70 | 2.1 x 5.5 x 11mm right angle barrel plug (high retention) - Center Positive |
| 40 | 2.1 x 5.5 x 9.5mm right angle barrel plug (high retention) - Center Positive | 71 | 2.5 x 5.5 x 11mm right angle barrel plug (high retention) - Center Positive |
| 41 | 2.5 x 5.5 x 9.5mm right angle barrel plug (high retention) - Center Positive | 72 | 2.1 x 5.5 x 9.5mm straight barrel plug (high retention, no spark) - Center Positive |
| 42 | 2.1 x 5.5 x 11mm straight barrel plug (high retention) - Center Positive | 73 | 2.5 x 5.5 x 9.5mm straight barrel plug (high retention, no spark) - Center Positive |
| 43 | 2.5 x 5.5 x 11mm straight barrel plug (high retention) - Center Positive | 74 | EIAJ#5 style connector - Center Positive |

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А