

# BAS19L, NSVBAS19L, BAS20L, SBAS20L, BAS21L, SBAS21L, BAS21DW5, SBAS21DW5

## High Voltage Switching Diode

### Features

- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant
- S and NSV Prefixes for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable

### MAXIMUM RATINGS

| Rating   | Symbol          | Value                | Unit   |
|--|-----------------|----------------------|--------|
| Continuous Reverse Voltage<br>BAS19, NSVBAS19<br>BAS20, SBAS20<br>BAS21, SBAS21      | $V_R$           | 120<br>200<br>250    | Vdc    |
| Repetitive Peak Reverse Voltage<br>BAS19, NSVBAS19<br>BAS20, SBAS20<br>BAS21, SBAS21 | $V_{RRM}$       | 120<br>200<br>250    | Vdc    |
| Continuous Forward Current   | $I_F$           | 200                  | mAdc   |
| Peak Forward Surge Current   | $I_{FM(surge)}$ | 625                  | mAdc   |
| Junction and Storage Temperature Range   | $T_J, T_{stg}$  | -55 to +150          | °C     |
| Power Dissipation (Note 1)   | $P_D$           | 385                  | mW     |
| Electrostatic Discharge  | ESD             | HM < 500<br>MM < 400 | V<br>V |

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.



1. Mounted on FR-5 Board = 1.0 x 0.75 x 0.062 in.




ON Semiconductor®

<http://onsemi.com>


## HIGH VOLTAGE SWITCHING DIODE




### MARKING DIAGRAMS



SOT-23 (TO-236)  
CASE 318  
STYLE 8



SC-88A (SOT-353)  
CASE 419A



- x = P, R, or S
- P = BAS19L, NSVBAS19L
- R = BAS20L, SBAS20L
- S = BAS21L, SBAS21L or BAS21DW5, SBAS21DW5
- M = Date Code
- = Pb-Free Package

(Note: Microdot may be in either location)

\*Date Code orientation and/or overbar may vary depending upon the manufacturing location.

### ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 4 of this data sheet.

**BAS19L, NSVBAS19L, BAS20L, SBAS20L, BAS21L, SBAS21L, BAS21DW5,  
SBAS21DW5**

**THERMAL CHARACTERISTICS (SOT-23)**

| Characteristic  | Symbol          | Max         | Unit                      |
|---|-----------------|-------------|---------------------------|
| Total Device Dissipation FR-5 Board<br>(Note 2)<br>$T_A = 25^\circ\text{C}$<br>Derate above $25^\circ\text{C}$        | $P_D$           | 225         | mW                        |
|   |                 | 1.8         | mW/ $^\circ\text{C}$      |
| Thermal Resistance<br>Junction-to-Ambient (SOT-23)  | $R_{\theta JA}$ | 556         | $^\circ\text{C}/\text{W}$ |
| Total Device Dissipation Alumina Substrate<br>(Note 3)<br>$T_A = 25^\circ\text{C}$<br>Derate above $25^\circ\text{C}$ | $P_D$           | 300         | mW                        |
|   |                 | 2.4         | mW/ $^\circ\text{C}$      |
| Thermal Resistance Junction-to-Ambient  | $R_{\theta JA}$ | 417         | $^\circ\text{C}/\text{W}$ |
| Junction and Storage<br>Temperature Range   | $T_J, T_{stg}$  | -55 to +150 | $^\circ\text{C}$          |

**THERMAL CHARACTERISTICS (SC-88A)**


| Characteristic   | Symbol          | Max         | Unit                      |
|--|-----------------|-------------|---------------------------|
| Power Dissipation (Note 4)   | $P_D$           | 385         | mW                        |
| Thermal Resistance -<br>Junction-to-Ambient<br>Derate Above $25^\circ\text{C}$ | $R_{\theta JA}$ | 328         | $^\circ\text{C}/\text{W}$ |
|  |                 | 3.0         | mW/ $^\circ\text{C}$      |
| Maximum Junction Temperature   | $T_{Jmax}$      | 150         | $^\circ\text{C}$          |
| Operating Junction and Storage Temperature Range                               | $T_J, T_{stg}$  | -55 to +150 | $^\circ\text{C}$          |

2. FR-5 = 1.0 × 0.75 × 0.062 in.
3. Alumina = 0.4 × 0.3 × 0.024 in. 99.5% alumina.
4. Mounted on FR-5 Board = 1.0 × 0.75 × 0.062 in.

**ELECTRICAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$  unless otherwise noted)**


| Characteristic   | Symbol     | Min           | Max             | Unit |
|--|------------|---------------|-----------------|------|
| Reverse Voltage Leakage Current<br>( $V_R = 100\text{ Vdc}$ )<br>( $V_R = 150\text{ Vdc}$ )<br>( $V_R = 200\text{ Vdc}$ )<br>( $V_R = 100\text{ Vdc}, T_J = 150^\circ\text{C}$ )<br>( $V_R = 150\text{ Vdc}, T_J = 150^\circ\text{C}$ )<br>( $V_R = 200\text{ Vdc}, T_J = 150^\circ\text{C}$ ) | $I_R$      | -             | BAS19, NSVBAS19 | 0.1  |
|  |            |               | BAS20, SBAS20   | 0.1  |
|  |            |               | BAS21, SBAS21   | 0.1  |
|  |            | BAS19         | -               | 100  |
|  |            | BAS20, SBAS20 | -               | 100  |
|  |            | BAS21, SBAS21 | -               | 100  |
| Reverse Breakdown Voltage<br>( $I_{BR} = 100\ \mu\text{A dc}$ )<br>( $I_{BR} = 100\ \mu\text{A dc}$ )<br>( $I_{BR} = 100\ \mu\text{A dc}$ )  | $V_{(BR)}$ | 120           | BAS19, NSVBAS19 | -    |
|  |            |               | BAS20, SBAS20   | 200  |
|  |            |               | BAS21, SBAS21   | 250  |
| Forward Voltage<br>( $I_F = 100\text{ mA dc}$ )<br>( $I_F = 200\text{ mA dc}$ )  | $V_F$      | -             | 1.0             | Vdc  |
|  |            | -             | 1.25            |      |
| Diode Capacitance ( $V_R = 0, f = 1.0\text{ MHz}$ )  | $C_D$      | -             | 5.0             | pF   |
| Reverse Recovery Time ( $I_F = I_R = 30\text{ mA dc}, I_{R(REC)} = 3.0\text{ mA dc}, R_L = 100$ )  | $t_{rr}$   | -             | 50              | ns   |

**BAS19L, NSVBAS19L, BAS20L, SBAS20L, BAS21L, SBAS21L, BAS21DW5, SBAS21DW5**




- Notes: 1. A 2.0 kΩ variable resistor adjusted for a Forward Current ( $I_F$ ) of 30 mA.  
 2. Input pulse is adjusted so  $I_{R(\text{peak})}$  is equal to 30 mA.  
 3.  $t_p \gg t_{rr}$


**Figure 1. Recovery Time Equivalent Test Circuit**



**Figure 2.  $V_F$  vs.  $I_F$**



**Figure 3.  $I_R$  vs.  $V_R$**



**Figure 4. Capacitance**

**BAS19L, NSVBAS19L, BAS20L, SBAS20L, BAS21L, SBAS21L, BAS21DW5,  
SBAS21DW5**

**ORDERING INFORMATION**

| <b>Device</b> | <b>Package</b>      | <b>Shipping†</b>    |
|---------------|---------------------|---------------------|
| BAS19LT1G     | SOT-23<br>(Pb-Free) | 3000 / Tape & Reel  |
| BAS19LT3G     | SOT-23<br>(Pb-Free) | 10000 / Tape & Reel |
| NSVBAS19LT1G* | SOT-23<br>(Pb-Free) | 3000 / Tape & Reel  |
| BAS20LT1G     | SOT-23<br>(Pb-Free) | 3000 / Tape & Reel  |
| BAS20LT3G     | SOT-23<br>(Pb-Free) | 10000 / Tape & Reel |
| SBAS20LT1G*   | SOT-23<br>(Pb-Free) | 3000 / Tape & Reel  |
| BAS21LT1G     | SOT-23<br>(Pb-Free) | 3000 / Tape & Reel  |
| SBAS21LT1G*   | SOT-23<br>(Pb-Free) | 3000 / Tape & Reel  |
| BAS21LT3G     | SOT-23<br>(Pb-Free) | 10000 / Tape & Reel |
| SBAS21LT3G*   | SOT-23<br>(Pb-Free) | 10000 / Tape & Reel |
| BAS21DW5T1G   | SC-88A<br>(Pb-Free) | 3000 / Tape & Reel  |
| SBAS21DW5T1G* | SC-88A<br>(Pb-Free) | 3000 / Tape & Reel  |
| SBAS21DW5T3G* | SC-88A<br>(Pb-Free) | 10000 / Tape & Reel |


†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

\*S and NSV Prefixes for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable.

# BAS19L, NSVBAS19L, BAS20L, SBAS20L, BAS21L, SBAS21L, BAS21DW5, SBAS21DW5

## PACKAGE DIMENSIONS

SOT-23 (TO-236)  
CASE 318-08  
ISSUE AP




- NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
  2. CONTROLLING DIMENSION: INCH.
  3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH THICKNESS. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.
  4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.

| DIM | MILLIMETERS |      |      | INCHES |       |       |
|-----|-------------|------|------|--------|-------|-------|
|     | MIN         | NOM  | MAX  | MIN    | NOM   | MAX   |
| A   | 0.89        | 1.00 | 1.11 | 0.035  | 0.040 | 0.044 |
| A1  | 0.01        | 0.06 | 0.10 | 0.001  | 0.002 | 0.004 |
| b   | 0.37        | 0.44 | 0.50 | 0.015  | 0.018 | 0.020 |
| c   | 0.09        | 0.13 | 0.18 | 0.003  | 0.005 | 0.007 |
| D   | 2.80        | 2.90 | 3.04 | 0.110  | 0.114 | 0.120 |
| E   | 1.20        | 1.30 | 1.40 | 0.047  | 0.051 | 0.055 |
| e   | 1.78        | 1.90 | 2.04 | 0.070  | 0.075 | 0.081 |
| L   | 0.10        | 0.20 | 0.30 | 0.004  | 0.008 | 0.012 |
| L1  | 0.35        | 0.54 | 0.69 | 0.014  | 0.021 | 0.029 |
| HE  | 2.10        | 2.40 | 2.64 | 0.083  | 0.094 | 0.104 |
| θ   | 0°          | ---  | 10°  | 0°     | ---   | 10°   |

- STYLE 8:  
PIN 1. ANODE  
2. NO CONNECTION  
3. CATHODE

### SOLDERING FOOTPRINT\*




\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

# BAS19L, NSVBAS19L, BAS20L, SBAS20L, BAS21L, SBAS21L, BAS21DW5, SBAS21DW5

## PACKAGE DIMENSIONS

SC-88A (SC-70-5/SOT-353)  
CASE 419A-02  
ISSUE K




NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. 419A-01 OBSOLETE. NEW STANDARD 419A-02.
4. DIMENSIONS A AND B DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.

| DIM | INCHES    |       | MILLIMETERS |      |
|-----|-----------|-------|-------------|------|
|     | MIN       | MAX   | MIN         | MAX  |
| A   | 0.071     | 0.087 | 1.80        | 2.20 |
| B   | 0.045     | 0.053 | 1.15        | 1.35 |
| C   | 0.031     | 0.043 | 0.80        | 1.10 |
| D   | 0.004     | 0.012 | 0.10        | 0.30 |
| G   | 0.026 BSC |       | 0.65 BSC    |      |
| H   | ---       | 0.004 | ---         | 0.10 |
| J   | 0.004     | 0.010 | 0.10        | 0.25 |
| K   | 0.004     | 0.012 | 0.10        | 0.30 |
| N   | 0.008 REF |       | 0.20 REF    |      |
| S   | 0.079     | 0.087 | 2.00        | 2.20 |

### SOLDERING FOOTPRINT\*



\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

### PUBLICATION ORDERING INFORMATION

**LITERATURE FULFILLMENT:**  
Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
Email: orderlit@onsemi.com

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada  
**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910  
**Japan Customer Focus Center**  
Phone: 81-3-5817-1050

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)  
**Order Literature:** <http://www.onsemi.com/orderlit>  
For additional information, please contact your local Sales Representative

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А