


## SPECIFICATION

- Part No. : **DSGP.1575.18.4.A.02**
- Description : GPS L1 / GALILEO E1 1575MHz SMT 18\*18\*4mm  
Ceramic Patch SMT Antenna
- Features : 4.20 dBi Peak Gain for GPS/GALILEO Band  
Dims: 18\*18\*4mm  
SMT Direct Mount Ceramic Patch Antenna  
Automotive TS16949 Approved  
**RoHS Compliant**



## **1. Introduction**

The DSGP.1575.18.4.A.02 is an 18mm square ceramic GPS L1 / GALILEO E1 passive patch antenna. 18mm square with a height of just 4mm, this low profile antenna is ideal for space constrained applications in telematics devices, vehicle tracking/fleet management systems, wearables and navigation.

The antenna has been tuned on a 50\*50mm ground plane, working at 1575.42MHz with a 4.20dBi gain. The radiation pattern is broadly hemispherical with a stable gain across elevations.

The ceramic patch is mounted via SMT process, ideal for high volume low cost assembly. It is manufactured and tested in a TS16949 first tier automotive approved facility.

For further optimization to customer specific device environments, custom tuned patch antennas can be supplied, subject to NRE and MOQ. For more details please contact your regional Taoglas sales office.


## 2. Specification

ELECTRICAL	
Application Bands	GPS/GALILEO
Operation Frequency	1575.42 ±1.023MHz
Return Loss	<-10dB
Gain at Zenith	4.20dBi
Efficiency	83.33%
Impedance	50Ω
MECHANICAL	
Ceramic Dimension	18*18*4mm
Weight	5.8g
ENVIRONMENTAL	
Operation Temperature	-40°C to 85°C
Humidity	Non-condensing 65°C 95% RH


\*Antenna properties were measured with the antenna mounted on 50\*50mm Ground Plane  
Taoglas Part # DSGPD.18A

### 3. Antenna Characteristics


#### 3.1. Return Loss




#### 3.2. Efficiency



### 3.3. Average Gain




### 3.4. Peak Gain






## 4. Antenna Radiation Pattern

### 4.1. Measurement Setup

The DSGP.1575.18.4 antenna is tested with 50\*50mm ground plane in a CTIA certified ETS-Lindgren Anechoic Chamber. The test setup is shown below.




## 4.2. 2D Radiation Pattern



### 4.3. 3D Radiation Pattern


1575.42MHz






## 5. Mechanical Drawing (Unit: mm)


Top View




Side View



Bottom View



## 6. Evaluation Board - DSGPD.18A (Unit: mm)




Unit:mm

	Name	Material	Finish	QTY
1	PCB SMA(F) ST	FR4	Gold	1
2	DSGP.1575.18.4.A.02 Antenna	Ceramic	Clear	1
3	PCB (50x50x1mm)	FR4 1.0t	Black	1

## 7. PCB Footprint Recommendation






### 7.1. Footprint Copper Keepout Area (Unit: mm)

Pads 1, 2, 3, 4, 5, 6, 7 and 9 are the same size. They should be connected to GND




➔ :  
Connected to 50 ohm  
transmission line.

#### NOTE:






- |                        |   |
|------------------------|---|
| 1. Ag Plated area      |  |
| 2. Solder Mask area    |  |
| 3. Copper area         |  |
| 4. Paste area          |  |
| 5. Copper Keepout area |  |
- 6. Copper Keepout should extend through all PCB layers.
  - 7. Any vias in pads should be either filled or tented to prevent solder from wicking away from the pad during reflow
  - 8. The dimension tolerances should follow standard PCB manufacturing guidelines

## 7.2. Paste Area (unit: mm)

Pads 1, 2, 3, 4, 5, 6, 7 and 9 are the same size.




### NOTE:






- |                        |   |
|------------------------|---|
| 1. Ag Plated area      |  |
| 2. Solder Mask area    |  |
| 3. Copper area         |  |
| 4. Paste area          |  |
| 5. Copper Keepout area |  |
6. Copper Keepout should extend through all PCB layers.
  7. Any vias in pads should be either filled or tented to prevent solder from wicking away from the pad during reflow
  8. The dimension tolerances should follow standard PCB manufacturing guidelines

### 7.3. Top Solder Mask (Unit: mm)


Pads 1, 2, 3, 4, 5, 6, 7 and 9 are the same size. This drawing is a negative of solder mask. Black regions are anti-mask.








**NOTE:**

- |                        |   |
|------------------------|---|
| 1. Ag Plated area      |  |
| 2. Solder Mask area    |  |
| 3. Copper area         |  |
| 4. Paste area          |  |
| 5. Copper Keepout area |  |
6. Copper Keepout should extend through all PCB layers.
  7. Any vias in pads should be either filled or tented to prevent solder from wicking away from the pad during reflow
  8. The dimension tolerances should follow standard PCB manufacturing guidelines

### 7.4. Composite Diagram (unit: mm)



**NOTE:**


- |                        |   |
|------------------------|---|
| 1. Ag Plated area      |  |
| 2. Solder Mask area    |  |
| 3. Copper area         |  |
| 4. Paste area          |  |
| 5. Copper Keepout area |  |
6. Copper Keepout should extend through all PCB layers.  
 7. Any vias in pads should be either filled or tented to prevent solder from wicking away from the pad during reflow  
 8. The dimension tolerances should follow standard PCB manufacturing guidelines

## 8. Recommended Reflow Soldering Profile

DSGP.18 can be assembled using lead-free process. According to the standard IPC/JEDEC J-STD-020C, the temperature profile suggested is as follows:

Phase	Profile Features	Pb-Free Assembly (SnAgCu)
PREHEAT	Temperature Min( $T_{smin}$ ) Temperature Max( $T_{smax}$ ) Time(ts) from ( $T_{smin}$ to $T_{smax}$ )	150°C 200°C 60-120 seconds
RAMP-UP	Avg. Ramp-up Rate ( $T_{smax}$ to TP)	3°C/second(max)
REFLOW	Temperature( $T_L$ ) Total Time above $T_L$ ( $t_L$ )	217°C 30-100 seconds
PEAK	Temperature( $T_P$ ) Time( $t_p$ )	260°C 2-5 seconds
RAMP-DOWN	Rate	3°C/second(max)
Time from 25°C to Peak Temperature		8 minutes max.
Composition of solder paste		96.5Sn/3Ag/0.5Cu
Solder Paste Model		SHENMAO PF606-P26

The graphic shows temperature profile for component assembly process in reflow ovens




Soldering Iron condition: Soldering iron temperature  $270^{\circ}\text{C} \pm 10^{\circ}\text{C}$ .

Apply preheating at  $120^{\circ}\text{C}$  for 2-3 minutes. Finish soldering for each terminal within 3 seconds, if soldering iron temperature over  $270^{\circ}\text{C} \pm 10^{\circ}\text{C}$  or 3 seconds, it will make cause component surface peeling or damage.

## 9. Packaging (Unit: mm)


### Packaging Specifications (1/2)

200 pc DSGP.1575.18.4.A.02 per reel  
 Dimensions - Ø330\*50mm  
 Weight - 1556.5g







1 pc reel in small in Anti-static Bag  
Dimensions - 340\*350\*70mm  
Weight - 1.86Kg



4 Reels in Anti-static Bags  
800 pcs in one carton  
Carton Dimensions - 370\*360\*305mm  
Weight - 8.2Kg



Pallet Dimensions 1200\*1000\*1420mm  
24 Cartons per Pallet  
6 Cartons per layer  
4 Layers



Taoglas makes no warranties based on the accuracy or completeness of the contents of this document and reserves the right to make changes to specifications and product descriptions at any time without notice. Taoglas reserves all rights to this document and the information contained herein.

Reproduction, use or disclosure to third parties without express permission is strictly prohibited.

Copyright © Taoglas Ltd.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А