


SPECIFICATION CONTROL DRAWING			SCD		44A012X																																																					
Title TWO CONDUCTOR CABLE, UNSHIELDED, UNJACKETED, GENERAL PURPOSE, 600 VOLT			Date 11-3-15		Revision E																																																					
This specification sheet forms a part of the latest issue of Raychem Specification 44.																																																										
COMPONENT WIRES - 44A011X  <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th colspan="5" style="padding: 5px;">CABLE CONSTRUCTION DETAILS</th> </tr> <tr> <th rowspan="2" style="padding: 5px;">PART NUMBER <u>1/</u></th> <th rowspan="2" style="padding: 5px;">CONDUCTOR SIZE (AWG)</th> <th colspan="2" style="padding: 5px;">OUTSIDE DIAMETER (inch)</th> <th rowspan="2" style="padding: 5px;">MAXIMUM WEIGHT (lbs/1000 ft.)</th> </tr> <tr> <th style="padding: 5px;">NOMINAL</th> <th style="padding: 5px;">MAXIMUM</th> </tr> </thead> <tbody> <tr><td style="padding: 5px;">44A012X-26-*</td><td style="padding: 5px;">26</td><td style="padding: 5px;">.068</td><td style="padding: 5px;">.072</td><td style="padding: 5px;">2.9</td></tr> <tr><td style="padding: 5px;">44A012X-24-*</td><td style="padding: 5px;">24</td><td style="padding: 5px;">.080</td><td style="padding: 5px;">.084</td><td style="padding: 5px;">4.3</td></tr> <tr><td style="padding: 5px;">44A012X-22-*</td><td style="padding: 5px;">22</td><td style="padding: 5px;">.094</td><td style="padding: 5px;">.098</td><td style="padding: 5px;">6.3</td></tr> <tr><td style="padding: 5px;">44A012X-20-*</td><td style="padding: 5px;">20</td><td style="padding: 5px;">.110</td><td style="padding: 5px;">.114</td><td style="padding: 5px;">9.4</td></tr> <tr><td style="padding: 5px;">44A012X-18-*</td><td style="padding: 5px;">18</td><td style="padding: 5px;">.130</td><td style="padding: 5px;">.134</td><td style="padding: 5px;">14.3</td></tr> <tr><td style="padding: 5px;">44A012X-16-*</td><td style="padding: 5px;">16</td><td style="padding: 5px;">.144</td><td style="padding: 5px;">.150</td><td style="padding: 5px;">18.1</td></tr> <tr><td style="padding: 5px;">44A012X-14-*</td><td style="padding: 5px;">14</td><td style="padding: 5px;">.178</td><td style="padding: 5px;">.185</td><td style="padding: 5px;">28.4</td></tr> <tr><td style="padding: 5px;">44A012X-12-*</td><td style="padding: 5px;">12</td><td style="padding: 5px;">.216</td><td style="padding: 5px;">.224</td><td style="padding: 5px;">44.3</td></tr> </tbody> </table> CABLE RATINGS AND ADDITIONAL REQUIREMENTS TEMPERATURE RATING: 150°C Maximum continuous conductor temperature VOLTAGE RATING: 600 volts (rms) at sea level DIELECTRIC WITHSTAND: 2500 volts (rms), 60 Hz, 1 minute INSULATION FLAWS: Spark Test, 5.7 kV (rms) at 3 kHz Impulse Dielectric Test, 8.0 kV (peak) <u>1/</u> PART NUMBER: The "X" in the part numbers above shall be replaced with a conductor material designator as follows: 1 tin-coated copper 2 silver-coated copper 3 nickel-coated copper 4 silver-coated high-strength copper alloy (AWG 26-16 only) The "*" in the part numbers above shall be replaced by color code designators with a slash separating the component wire colors. Example: AWG 20, tin-coated copper conductors; black and brown component wires: 44A0121-20-0/1							CABLE CONSTRUCTION DETAILS					PART NUMBER <u>1/</u>	CONDUCTOR SIZE (AWG)	OUTSIDE DIAMETER (inch)		MAXIMUM WEIGHT (lbs/1000 ft.)	NOMINAL	MAXIMUM	44A012X-26-*	26	.068	.072	2.9	44A012X-24-*	24	.080	.084	4.3	44A012X-22-*	22	.094	.098	6.3	44A012X-20-*	20	.110	.114	9.4	44A012X-18-*	18	.130	.134	14.3	44A012X-16-*	16	.144	.150	18.1	44A012X-14-*	14	.178	.185	28.4	44A012X-12-*	12	.216	.224	44.3
CABLE CONSTRUCTION DETAILS																																																										
PART NUMBER <u>1/</u>	CONDUCTOR SIZE (AWG)	OUTSIDE DIAMETER (inch)		MAXIMUM WEIGHT (lbs/1000 ft.)																																																						
		NOMINAL	MAXIMUM																																																							
44A012X-26-*	26	.068	.072	2.9																																																						
44A012X-24-*	24	.080	.084	4.3																																																						
44A012X-22-*	22	.094	.098	6.3																																																						
44A012X-20-*	20	.110	.114	9.4																																																						
44A012X-18-*	18	.130	.134	14.3																																																						
44A012X-16-*	16	.144	.150	18.1																																																						
44A012X-14-*	14	.178	.185	28.4																																																						
44A012X-12-*	12	.216	.224	44.3																																																						
NOTE: Nominal values are for information only. Nominal values are not requirements.																																																										
Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice. Tyco Electronics Corporation also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.																																																										
<u>1/</u> COLORS AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681. HOWEVER, DUE TO LENGTH LIMITATIONS OF THE RAYCHEM PART NUMBER, AN ALTERNATIVE COLOR CODE MAY REPLACE MIL-STD-681 COLOR CODE DESIGNATORS. (EXAMPLE: "901/902..." MAY BE REPLACED BY "Axxx".) OTHER CODES AND SUFFIXES MAY BE ADDED TO THE PART NUMBER, AS NECESSARY, TO CAPTURE ANY ADDITIONAL REQUIREMENTS IMPOSED BY THE PURCHASE ORDER.																																																										
Page 1 of 1	Raychem, TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks.		 Raychem Wire & Cable 501 Oakside Avenue Redwood City, CA 94063-3800 Phone: 1-800-227-8816 Fax: 1-650-361-6297																																																							
	DIMENSIONS ARE IN INCHES AND, UNLESS OTHERWISE DESIGNATED, ARE NOMINAL																																																									
	THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.																																																									

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А