MMBT3904WT1, NPN, SMMBT3904WT1, NPN, MMBT3906WT1, PNP

General Purpose Transistors

NPN and PNP Silicon

These transistors are designed for general purpose amplifier applications. They are housed in the SOT−323/SC−70 package which is designed for low power surface mount applications.

Features

- AEC−Q101 Qualified and PPAP Capable
- S Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements
- These Devices are Pb−Free, Halogen Free/BFR Free and are RoHS Compliant

ON Semiconductor®

http://onsemi.com





SC−70 (SOT−323)
CASE 419
STYLE 3

MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Collector − Emitter Voltage MMBT3904WT1, SMMBT3904WT1 MMBT3906WT1	V_{CEO}	 40 −40	Vdc
Collector − Base Voltage MMBT3904WT1, SMMBT3904WT1 MMBT3906WT1	V_{CBO}	 60 −40	Vdc
Emitter − Base Voltage MMBT3904WT1, SMMBT3904WT1 MMBT3906WT1	V_{EBO}	 6.0 −5.0	Vdc
Collector Current − Continuous MMBT3904WT1, SMMBT3904WT1 MMBT3906WT1	I_C	 200 −200	mAdc

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Total Device Dissipation (Note 1) @T_A = 25°C	P_D	150	mW
Thermal Resistance, Junction−to−Ambient	$R_{\theta JA}$	833	°C/W
Junction and Storage Temperature	T_J, T_{stg}	−55 to +150	°C

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

1. Device mounted on FR4 glass epoxy printed circuit board using the minimum recommended footprint.

MARKING DIAGRAM



xx = AM for MMBT3904WT1, SMMBT3904WT
= 2A for MMBT3906WT1
M = Date Code*
▪ = Pb−Free Package

(Note: Microdot may be in either location)

*Date Code orientation may vary depending upon manufacturing location.

ORDERING INFORMATION

Device	Package	Shipping†
MMBT3904WT1G	SC−70/ SOT−323 (Pb−Free)	3000 / Tape & Reel
SMMBT3904WT1G	SC−70/ SOT−323 (Pb−Free)	3000 / Tape & Reel
MMBT3906WT1G	SC−70/ SOT−323 (Pb−Free)	3000 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

© Semiconductor Components Industries, LLC, 2011

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted)

Characteristic		Symbol	Min	Max	Unit
OFF CHARACTERISTICS					
Collector – Emitter Breakdown Voltage (Note 2)		$V_{(BR)CEO}$			Vdc
(I_C = 1.0 mAdc, I_B = 0)	MMBT3904WT1, SMMBT3904WT1		40	–	
(I_C = –1.0 mAdc, I_B = 0)	MMBT3906WT1		–40	–	
Collector – Base Breakdown Voltage		$V_{(BR)CBO}$			Vdc
(I_C = 10 μAdc, I_E = 0)	MMBT3904WT1, SMMBT3904WT1		60	–	
(I_C = –10 μAdc, I_E = 0)	MMBT3906WT1		–40	–	
Emitter – Base Breakdown Voltage		$V_{(BR)EBO}$			Vdc
(I_E = 10 μAdc, I_C = 0)	MMBT3904WT1, SMMBT3904WT1		6.0	–	
(I_E = –10 μAdc, I_C = 0)	MMBT3906WT1		–5.0	–	
Base Cutoff Current		I_{BL}			nAdc
(V_{CE} = 30 Vdc, V_{EB} = 3.0 Vdc)	MMBT3904WT1, SMMBT3904WT1		–	50	
(V_{CE} = –30 Vdc, V_{EB} = –3.0 Vdc)	MMBT3906WT1		–	–50	
Collector Cutoff Current		I_{CEX}			nAdc
(V_{CE} = 30 Vdc, V_{EB} = 3.0 Vdc)	MMBT3904WT1, SMMBT3904WT1		–	50	
(V_{CE} = –30 Vdc, V_{EB} = –3.0 Vdc)	MMBT3906WT1		–	–50	
ON CHARACTERISTICS (Note 2)					
DC Current Gain		h_{FE}			–
(I_C = 0.1 mAdc, V_{CE} = 1.0 Vdc)	MMBT3904WT1, SMMBT3904WT1		40	–	
(I_C = 1.0 mAdc, V_{CE} = 1.0 Vdc)			70	–	
(I_C = 10 mAdc, V_{CE} = 1.0 Vdc)			100	300	
(I_C = 50 mAdc, V_{CE} = 1.0 Vdc)			60	–	
(I_C = 100 mAdc, V_{CE} = 1.0 Vdc)			30	–	
(I_C = –0.1 mAdc, V_{CE} = –1.0 Vdc)	MMBT3906WT1		60	–	
(I_C = –1.0 mAdc, V_{CE} = –1.0 Vdc)			80	–	
(I_C = –10 mAdc, V_{CE} = –1.0 Vdc)			100	300	
(I_C = –50 mAdc, V_{CE} = –1.0 Vdc)			60	–	
(I_C = –100 mAdc, V_{CE} = –1.0 Vdc)			30	–	
Collector – Emitter Saturation Voltage		$V_{CE(sat)}$			Vdc
(I_C = 10 mAdc, I_B = 1.0 mAdc)	MMBT3904WT1, SMMBT3904WT1		–	0.2	
(I_C = 50 mAdc, I_B = 5.0 mAdc)			–	0.3	
(I_C = –10 mAdc, I_B = –1.0 mAdc)	MMBT3906WT1		–	–0.25	
(I_C = –50 mAdc, I_B = –5.0 mAdc)			–	–0.4	
Base – Emitter Saturation Voltage		$V_{BE(sat)}$			Vdc
(I_C = 10 mAdc, I_B = 1.0 mAdc)	MMBT3904WT1, SMMBT3904WT1		0.65	0.85	
(I_C = 50 mAdc, I_B = 5.0 mAdc)			–	0.95	
(I_C = –10 mAdc, I_B = –1.0 mAdc)	MMBT3906WT1		–0.65	–0.85	
(I_C = –50 mAdc, I_B = –5.0 mAdc)			–	–0.95	

2. Pulse Test: Pulse Width ≤ 300 μs; Duty Cycle ≤ 2.0%.

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted) (Continued)

Characteristic		Symbol	Min	Max	Unit
SMALL−SIGNAL CHARACTERISTICS					
Current−Gain − Bandwidth Product		f_T			MHz
(I_C = 10 mAdc, V_{CE} = 20 Vdc, f = 100 MHz)	MMBT3904WT1, SMMBT3904WT1		300	−	
(I_C = −10 mAdc, V_{CE} = −20 Vdc, f = 100 MHz)	MMBT3906WT1		250	−	
Output Capacitance		C_{obo}			pF
(V_{CB} = 5.0 Vdc, I_E = 0, f = 1.0 MHz)	MMBT3904WT1, SMMBT3904WT1		−	4.0	
(V_{CB} = −5.0 Vdc, I_E = 0, f = 1.0 MHz)	MMBT3906WT1		−	4.5	
Input Capacitance		C_{ibo}			pF
(V_{EB} = 0.5 Vdc, I_C = 0, f = 1.0 MHz)	MMBT3904WT1, SMMBT3904WT1		−	8.0	
(V_{EB} = −0.5 Vdc, I_C = 0, f = 1.0 MHz)	MMBT3906WT1		−	10.0	
Input Impedance		h_{ie}			k Ω
(V_{CE} = 10 Vdc, I_C = 1.0 mAdc, f = 1.0 kHz)	MMBT3904WT1, SMMBT3904WT1		1.0	10	
(V_{CE} = −10 Vdc, I_C = −1.0 mAdc, f = 1.0 kHz)	MMBT3906WT1		2.0	12	
Voltage Feedback Ratio		h_{re}			X 10^{-4}
(V_{CE} = 10 Vdc, I_C = 1.0 mAdc, f = 1.0 kHz)	MMBT3904WT1, SMMBT3904WT1		0.5	8.0	
(V_{CE} = −10 Vdc, I_C = −1.0 mAdc, f = 1.0 kHz)	MMBT3906WT1		0.1	10	
Small−Signal Current Gain		h_{fe}			−
(V_{CE} = 10 Vdc, I_C = 1.0 mAdc, f = 1.0 kHz)	MMBT3904WT1, SMMBT3904WT1		100	400	
(V_{CE} = −10 Vdc, I_C = −1.0 mAdc, f = 1.0 kHz)	MMBT3906WT1		100	400	
Output Admittance		h_{oe}			μmhos
(V_{CE} = 10 Vdc, I_C = 1.0 mAdc, f = 1.0 kHz)	MMBT3904WT1, SMMBT3904WT1		1.0	40	
(V_{CE} = −10 Vdc, I_C = −1.0 mAdc, f = 1.0 kHz)	MMBT3906WT1		3.0	60	
Noise Figure		NF			dB
(V_{CE} = 5.0 Vdc, I_C = 100 μAdc, R_S = 1.0 k Ω, f = 1.0 kHz)	MMBT3904WT1, SMMBT3904WT1		−	5.0	
(V_{CE} = −5.0 Vdc, I_C = −100 μAdc, R_S = 1.0 k Ω, f = 1.0 kHz)	MMBT3906WT1		−	4.0	

SWITCHING CHARACTERISTICS

Characteristic	Condition	Symbol	Min	Max	Unit
Delay Time	(V_{CC} = 3.0 Vdc, V_{BE} = −0.5 Vdc) MMBT3904WT1, SMMBT3904WT1	t_d	−	35	ns
	(V_{CC} = −3.0 Vdc, V_{BE} = 0.5 Vdc) MMBT3906WT1		−	35	
Rise Time	(I_C = 10 mAdc, I_{B1} = 1.0 mAdc) MMBT3904WT1, SMMBT3904WT1	t_r	−	35	
	(I_C = −10 mAdc, I_{B1} = −1.0 mAdc) MMBT3906WT1		−	35	
Storage Time	(V_{CC} = 3.0 Vdc, I_C = 10 mAdc) MMBT3904WT1, SMMBT3904WT1	t_s	−	200	ns
	(V_{CC} = −3.0 Vdc, I_C = −10 mAdc) MMBT3906WT1		−	225	
Fall Time	(I_{B1} = I_{B2} = 1.0 mAdc) MMBT3904WT1, SMMBT3904WT1	t_f	−	50	
	(I_{B1} = I_{B2} = −1.0 mAdc) MMBT3906WT1		−	75	

MMBT3904WT1, SMMBT3904WT1





* Total shunt capacitance of test jig and connectors

Figure 1. Delay and Rise Time Equivalent Test Circuit

Figure 2. Storage and Fall Time Equivalent Test Circuit

MMBT3904WT1, SMMBT3904WT1

TYPICAL TRANSIENT CHARACTERISTICS



Figure 3. Turn – On Time



Figure 4. Rise Time



Figure 5. Storage Time



Figure 6. Fall Time

TYPICAL AUDIO SMALL–SIGNAL CHARACTERISTICS NOISE FIGURE VARIATIONS

(V_{CE} = 5.0 Vdc, T_A = 25°C, Bandwidth = 1.0 Hz)



Figure 7. Noise Figure



Figure 8. Noise Figure

MMBT3904WT1, SMMBT3904WT1

h PARAMETERS

(V_{CE} = 10 Vdc, f = 1.0 kHz, T_A = 25°C)



Figure 9. Current Gain



Figure 10. Output Admittance



Figure 11. Input Impedance



Figure 12. Voltage Feedback Ratio

TYPICAL STATIC CHARACTERISTICS



Figure 13. DC Current Gain

MMBT3904WT1, SMMBT3904WT1



Figure 14. Collector Saturation Region



Figure 15. Collector Emitter Saturation Voltage vs. Collector Current



Figure 16. Base Emitter Saturation Voltage vs. Collector Current



Figure 17. Base Emitter Voltage vs. Collector Current

MMBT3904WT1, SMMBT3904WT1



Figure 18. Temperature Coefficients



Figure 19. Capacitance



Figure 20. Current Gain Bandwidth Product vs. Collector Current



Figure 21. Safe Operating Area

MMBT3906WT1





* Total shunt capacitance of test jig and connectors

Figure 22. Delay and Rise Time Equivalent Test Circuit

Figure 23. Storage and Fall Time Equivalent Test Circuit

TYPICAL TRANSIENT CHARACTERISTICS



Figure 24. Turn – On Time



Figure 25. Fall Time

TYPICAL AUDIO SMALL – SIGNAL CHARACTERISTICS
NOISE FIGURE VARIATIONS

(V_{CE} = –5.0 Vdc, T_A = 25°C, Bandwidth = 1.0 Hz)



Figure 26.



Figure 27.

MMBT3906WT1

h PARAMETERS

(V_{CE} = −10 Vdc, f = 1.0 kHz, T_A = 25°C)



Figure 28. Current Gain



Figure 29. Output Admittance



Figure 30. Input Impedance



Figure 31. Voltage Feedback Ratio

STATIC CHARACTERISTICS



Figure 32. DC Current Gain

MMBT3906WT1



Figure 33. Collector Saturation Region



Figure 34. Collector Emitter Saturation Voltage vs. Collector Current



Figure 35. Base Emitter Saturation Voltage vs. Collector Current



Figure 36. Base Emitter Voltage vs. Collector Current

MMBT3906WT1



Figure 37. Temperature Coefficients



Figure 38. Capacitance



Figure 39. Current Gain Bandwidth Product vs. Collector Current



Figure 40. Safe Operating Area

PACKAGE DIMENSIONS

SC−70 (SOT−323)
CASE 419−04
ISSUE N



NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.

	MILLIMETERS			INCHES		
DIM	MIN	NOM	MAX	MIN	NOM	MAX
A	0.80	0.90	1.00	0.032	0.035	0.040
A1	0.00	0.05	0.10	0.000	0.002	0.004
A2	0.70 REF			0.028 REF		
b	0.30	0.35	0.40	0.012	0.014	0.016
c	0.10	0.18	0.25	0.004	0.007	0.010
D	1.80	2.10	2.20	0.071	0.083	0.087
E	1.15	1.24	1.35	0.045	0.049	0.053
e	1.20	1.30	1.40	0.047	0.051	0.055
e1	0.65 BSC			0.026 BSC		
L	0.20	0.38	0.56	0.008	0.015	0.022
H_E	2.00	2.10	2.40	0.079	0.083	0.095

STYLE 3:
PIN 1. BASE
2. EMITTER
3. COLLECTOR

SOLDERING FOOTPRINT*



SCALE 10:1 $\left(\frac{\text{mm}}{\text{inches}}\right)$

*For additional information on our Pb−Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and ON are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303−675−2175 or 800−344−3860 Toll Free USA/Canada
Fax: 303−675−2176 or 800−344−3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800−282−9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81−3−5817−1050

ON Semiconductor Website: **www.onsemi.com**

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative

MMBT3904WT1/D

OCEAN CHIPS
Океан Электроники
Поставка электронных компонентов

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «**JONHON**», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «**FORSTAR**».

AVIC JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).

FORSTAR®

Телефон: 8 (812) 309-75-97 (многоканальный)
Факс: 8 (812) 320-03-32
Электронная почта: ocean@oceanchips.ru
Web: http://oceanchips.ru/
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А