



Micro Commercial Components



Micro Commercial Components
 20736 Marilla Street Chatsworth
 CA 91311
 Phone: (818) 701-4933
 Fax: (818) 701-4939

**5KP5.0(C)
 THRU
 5KP250(C)A**


**5000 Watt
 Transient Voltage
 Suppressors
 5.0 to 250 Volts**

Features

- Unidirectional And Bidirectional
- UL Recognized File # E331408
- High Temp Soldering: 260°C for 10 Seconds At Terminals
- For Bidirectional Devices Add "C" To The Suffix Of The Part Number: i.e. 5KP6.5C or 5KP6.5CA for 5% Tolerance Devices
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Marking : Cathode band and type number
- Lead Free Finish/RoHS Compliant(Note 1) ("P" Suffix designates RoHS Compliant. See ordering information)

Maximum Ratings


- Operating Temperature: -55°C to +175°C
- Storage Temperature: -55°C to +175°C
- 5000 Watt Peak Power
- Response Time 1×10^{-12} Seconds For Unidirectional and 5×10^{-9} For Bidirectional
- Halogen free available upon request by adding suffix "-HF"
- Typical Thermal Resistance, Junction to Lead: 8.0°C/W
- Typical Thermal Resistance, Junction to Ambient: 40°C/W



Notes:1.High Temperature Solder Exemption Applied, see EU Directive Annex 7.

5KP5.0(C) thru 5KP250(C)A

Figure 3 - Typical Capacitance



Typical Capacitance (pf) – versus – Breakdown voltage

Figure 4 - Derating Curve



Peak Pulse Power (% P_{PP}) - Versus - Temperature °C

ELECTRICAL CHARACTERISTICS @25°C

| MCC PART NUMBER | | REVERSE STAND-OFF VOLTAGE V _{WM} (VOLTS) | BREAKDOWN VOLTAGE V _(BR) @ I _T (VOLTS) | | | MAXIMUM CLAMPING VOLTAGE @ I _{PP} (VOLTS) | PEAK PULSE CURRENT I _{PP} (AMPS) | MAXIMUM REVERSE LEAKAGE @ V _{WM} I _D (µA) |
|-----------------|----------|---------------------------------------------------------|--------------------------------------------------------------------|------|---------------------|-------------------------------------------------------|-------------------------------------------------|---------------------------------------------------------------------|
| UNI-POLAR | BI-POLAR | | MIN | MAX | I _T (mA) | | | |
| 5KP5.0 | 5KP5.0C | 5.0 | 6.40 | 7.30 | 50 | 9.6 | 520 | 5000 |
| 5KP5.0A | 5KP5.0CA | 5.0 | 6.40 | 7.00 | 50 | 9.2 | 543 | 5000 |
| 5KP6.0 | 5KP6.0C | 6.0 | 6.67 | 8.15 | 50 | 11.4 | 439 | 5000 |
| 5KP6.0A | 5KP6.0CA | 6.0 | 6.67 | 7.37 | 50 | 10.3 | 485 | 5000 |
| 5KP6.5 | 5KP6.5C | 6.5 | 7.22 | 8.82 | 50 | 12.3 | 407 | 2000 |
| 5KP6.5A | 5KP6.5CA | 6.5 | 7.22 | 7.98 | 50 | 11.2 | 447 | 2000 |
| 5KP7.0 | 5KP7.0C | 7.0 | 7.78 | 9.51 | 50 | 13.3 | 378 | 1000 |
| 5KP7.0A | 5KP7.0CA | 7.0 | 7.78 | 8.60 | 50 | 12.0 | 417 | 1000 |
| 5KP7.5 | 5KP7.5C | 7.5 | 8.33 | 10.2 | 5 | 14.3 | 350 | 250 |
| 5KP7.5A | 5KP7.5CA | 7.5 | 8.33 | 9.21 | 5 | 12.9 | 388 | 250 |
| 5KP8.0 | 5KP8.0C | 8.0 | 8.89 | 10.9 | 5 | 15.0 | 333 | 150 |
| 5KP8.0A | 5KP8.0CA | 8.0 | 8.89 | 9.83 | 5 | 13.6 | 367 | 150 |
| 5KP8.5 | 5KP8.5C | 8.5 | 9.44 | 11.5 | 5 | 15.9 | 314 | 50 |
| 5KP8.5A | 5KP8.5CA | 8.5 | 9.44 | 10.4 | 5 | 14.4 | 347 | 50 |
| 5KP9.0 | 5KP9.0C | 9.0 | 10.0 | 12.2 | 5 | 16.9 | 295 | 20 |
| 5KP9.0A | 5KP9.0CA | 9.0 | 10.0 | 11.1 | 5 | 15.4 | 325 | 20 |
| 5KP10 | 5KP10C | 10 | 11.1 | 13.6 | 5 | 18.8 | 266 | 15 |
| 5KP10A | 5KP10CA | 10 | 11.1 | 12.3 | 5 | 17.0 | 294 | 15 |
| 5KP11 | 5KP11C | 11 | 12.2 | 14.9 | 5 | 20.1 | 249 | 10 |
| 5KP11A | 5KP11CA | 11 | 12.2 | 13.5 | 5 | 18.2 | 274 | 10 |
| 5KP12 | 5KP12C | 12 | 13.3 | 16.3 | 5 | 22.0 | 227 | 10 |
| 5KP12A | 5KP12CA | 12 | 13.3 | 14.7 | 5 | 19.9 | 251 | 10 |
| 5KP13 | 5KP13C | 13 | 14.4 | 17.6 | 5 | 23.8 | 210 | 10 |
| 5KP13A | 5KP13CA | 13 | 14.4 | 15.9 | 5 | 21.5 | 232 | 10 |
| 5KP14 | 5KP14C | 14 | 15.6 | 19.1 | 5 | 25.8 | 194 | 10 |
| 5KP14A | 5KP14CA | 14 | 15.6 | 17.2 | 5 | 23.2 | 215 | 10 |
| 5KP15 | 5KP15C | 15 | 16.7 | 20.4 | 5 | 26.9 | 188 | 10 |
| 5KP15A | 5KP15CA | 15 | 16.7 | 18.5 | 5 | 24.4 | 206 | 10 |
| 5KP16 | 5KP16C | 16 | 17.8 | 21.8 | 5 | 28.8 | 176 | 10 |
| 5KP16A | 5KP16CA | 16 | 17.8 | 19.7 | 5 | 26.0 | 192 | 10 |
| 5KP17 | 5KP17C | 17 | 18.9 | 23.1 | 5 | 30.5 | 164 | 10 |
| 5KP17A | 5KP17CA | 17 | 18.9 | 20.9 | 5 | 27.6 | 181 | 10 |
| 5KP18 | 5KP18C | 18 | 20.0 | 24.4 | 5 | 32.2 | 155 | 10 |
| 5KP18A | 5KP18CA | 18 | 20.0 | 22.1 | 5 | 29.2 | 172 | 10 |
| 5KP20 | 5KP20C | 20 | 22.2 | 27.1 | 5 | 35.8 | 139 | 10 |
| 5KP20A | 5KP20CA | 20 | 22.2 | 24.5 | 5 | 32.4 | 154 | 10 |
| 5KP22 | 5KP22C | 22 | 24.4 | 29.8 | 5 | 39.4 | 127 | 10 |
| 5KP22A | 5KP22CA | 22 | 24.4 | 26.9 | 5 | 35.5 | 141 | 10 |

5KP5.0(C) thru 5KP250(C)A

ELECTRICAL CHARACTERISTICS @25°C

| MCC PART NUMBER | | REVERSE STAND-OFF VOLTAGE V_{WM} (VOLTS) | BREAKDOWN VOLTAGE $V_{(BR)}$ @ I_T (VOLTS) | | | MAXIMUM CLAMPING VOLTAGE @ I_{PP} (VOLTS) | PEAK PULSE CURRENT I_{PP} (AMPS) | MAXIMUM REVERSE LEAKAGE @ V_{WM} I_D (μ A) |
|-----------------|----------|--------------------------------------------|----------------------------------------------|------|------------|---------------------------------------------|------------------------------------|-----------------------------------------------------|
| UNI-POLAR | BI-POLAR | | MIN | MAX | I_T (mA) | | | |
| 5KP24 | 5KP24C | 24 | 26.7 | 32.6 | 5 | 43.0 | 116 | 10 |
| 5KP24A | 5KP24CA | 24 | 26.7 | 29.5 | 5 | 38.9 | 128 | 10 |
| 5KP26 | 5KP26C | 26 | 28.9 | 35.3 | 5 | 46.6 | 107 | 10 |
| 5KP26A | 5KP26CA | 26 | 28.9 | 31.9 | 5 | 42.1 | 119 | 10 |
| 5KP28 | 5KP28C | 28 | 31.1 | 38.0 | 5 | 50.0 | 99 | 10 |
| 5KP28A | 5KP28CA | 28 | 31.1 | 34.4 | 5 | 45.4 | 110 | 10 |
| 5KP30 | 5KP30C | 30 | 33.3 | 40.7 | 5 | 53.5 | 93 | 10 |
| 5KP30A | 5KP30CA | 30 | 33.3 | 36.8 | 5 | 48.4 | 103 | 10 |
| 5KP33 | 5KP33C | 33 | 36.7 | 44.9 | 5 | 59.0 | 85 | 10 |
| 5KP33A | 5KP33CA | 33 | 36.7 | 40.6 | 5 | 53.3 | 94 | 10 |
| 5KP36 | 5KP36C | 36 | 40.0 | 48.9 | 5 | 64.3 | 78 | 10 |
| 5KP36A | 5KP36CA | 36 | 40.0 | 44.2 | 5 | 58.1 | 86 | 10 |
| 5KP40 | 5KP40C | 40 | 44.4 | 54.3 | 5 | 71.4 | 70 | 10 |
| 5KP40A | 5KP40CA | 40 | 44.4 | 49.1 | 5 | 64.5 | 78 | 10 |
| 5KP43 | 5KP43C | 43 | 47.8 | 58.4 | 5 | 76.7 | 65 | 10 |
| 5KP43A | 5KP43CA | 43 | 47.8 | 52.8 | 5 | 69.4 | 72 | 10 |
| 5KP45 | 5KP45C | 45 | 50.0 | 61.1 | 5 | 80.3 | 62 | 10 |
| 5KP45A | 5KP45CA | 45 | 50.0 | 55.3 | 5 | 72.7 | 69 | 10 |
| 5KP48 | 5KP48C | 48 | 53.3 | 65.1 | 5 | 85.5 | 58 | 10 |
| 5KP48A | 5KP48CA | 48 | 53.3 | 58.9 | 5 | 77.4 | 65 | 10 |
| 5KP 51 | 5KP 51C | 51 | 56.7 | 69.3 | 5 | 91.1 | 55 | 10 |
| 5KP51A | 5KP51CA | 51 | 56.7 | 62.7 | 5 | 82.4 | 61 | 10 |
| 5KP54 | 5KP54C | 54 | 60.0 | 73.3 | 5 | 96.3 | 52 | 10 |
| 5KP54A | 5KP54CA | 54 | 60.0 | 66.3 | 5 | 87.1 | 57 | 10 |
| 5KP58 | 5KP58C | 58 | 64.4 | 78.7 | 5 | 103 | 49 | 10 |
| 5KP58A | 5KP58CA | 58 | 64.4 | 71.2 | 5 | 93.6 | 53 | 10 |
| 5KP60 | 5KP60C | 60 | 66.7 | 81.5 | 5 | 107 | 47 | 10 |
| 5KP60A | 5KP60CA | 60 | 66.7 | 73.7 | 5 | 96.8 | 52 | 10 |
| 5KP64 | 5KP64C | 64 | 71.1 | 86.9 | 5 | 114 | 44 | 10 |
| 5KP64A | 5KP64CA | 64 | 71.1 | 78.6 | 5 | 103 | 49 | 10 |
| 5KP70 | 5KP70C | 70 | 77.8 | 95.1 | 5 | 125 | 40 | 10 |
| 5KP70A | 5KP70CA | 70 | 77.8 | 86.0 | 5 | 113 | 44 | 10 |
| 5KP75 | 5KP75C | 75 | 83.3 | 102 | 5 | 134 | 37 | 10 |
| 5KP75A | 5KP75CA | 75 | 83.3 | 92.1 | 5 | 121 | 41 | 10 |
| 5KP78 | 5KP78C | 78 | 86.7 | 106 | 5 | 139 | 36 | 10 |
| 5KP78A | 5KP78CA | 78 | 86.7 | 95.8 | 5 | 126 | 40 | 10 |
| 5KP85 | 5KP85C | 85 | 94.4 | 115 | 5 | 151 | 33 | 10 |
| 5KP85A | 5KP85CA | 85 | 94.4 | 104 | 5 | 137 | 36 | 10 |
| 5KP90 | 5KP90C | 90 | 100 | 122 | 5 | 160 | 31 | 10 |
| 5KP90A | 5KP90CA | 90 | 100 | 111 | 5 | 146 | 34 | 10 |
| 5KP100 | 5KP100C | 100 | 111 | 136 | 5 | 179 | 28 | 10 |
| 5KP100A | 5KP100CA | 100 | 111 | 123 | 5 | 162 | 31 | 10 |
| 5KP110 | 5KP110C | 110 | 122 | 149 | 5 | 196 | 26 | 10 |
| 5KP110A | 5KP110CA | 110 | 122 | 135 | 5 | 177 | 28 | 10 |
| 5KP120A | 5KP120CA | 120 | 133 | 147 | 5 | 193 | 26.4 | 10 |
| 5KP130A | 5KP130CA | 130 | 144 | 159 | 5 | 209 | 24.4 | 10 |
| 5KP150A | 5KP150CA | 150 | 167 | 185 | 5 | 243 | 21.0 | 10 |
| 5KP160A | 5KP160CA | 160 | 178 | 197 | 5 | 259 | 19.7 | 10 |
| 5KP170A | 5KP170CA | 170 | 189 | 209 | 5 | 275 | 18.5 | 10 |
| 5KP180A | 5KP180CA | 180 | 200 | 221 | 5 | 292 | 17.5 | 10 |
| 5KP190A | 5KP190CA | 190 | 211 | 233 | 5 | 310 | 16.5 | 10 |
| 5KP200A | 5KP200CA | 200 | 222 | 246 | 5 | 329.2 | 15.5 | 10 |
| 5KP210A | 5KP210CA | 210 | 233 | 258 | 5 | 349.5 | 14.6 | 10 |
| 5KP220A | 5KP220CA | 220 | 244 | 270 | 5 | 371.1 | 13.7 | 10 |
| 5KP250A | 5KP250CA | 250 | 277 | 306 | 5 | 425 | 12.0 | 10 |



Micro Commercial Components

Ordering Information :

| Device | Packing |
|----------------|-------------------------------|
| Part Number-TP | Tape&Reel: 500pcs/Reel |
| Part Number-AP | Ammo Packing: 450pcs/Ammo Box |
| Part Number-BP | Bulk: 4.8Kpcs/Carton |

Note : Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

*****IMPORTANT NOTICE*****

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp .** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp .** and all the companies whose products are represented on our website, harmless against all damages.

*****LIFE SUPPORT*****

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

*****CUSTOMER AWARENESS*****

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А