

## 2505PTZ Composite - For PTZ Camercas: CCTV + Control + Power

**Picture  
Not Available**

For more Information  
please call

1-800-Belden1



### General Description:

PTZ (CCTV+Control+Power) Cable, Rated-CM, 1-RG59 20 AWG solid bare copper with foam polyolefin, 95% bare copper braid, 1-18 AWG stranded bare copper pair with PVC insulation and Beldfoil® shield, 2-16 AWG stranded bare copper conductors with PVC insulation, Siamese with PVC jacket, Aluminum interlocking armor

### Coax

#### Physical Characteristics

##### Conductor

AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (in.)
1	20	Solid	BC - Bare Copper	0.032

##### Insulation

Insulation Material:

Insulation Material	Dia. (in.)
Gas-injected FHDPE - Foam High Density Polyethylene	0.145

##### Outer Shield

Outer Shield Material:

Type	Outer Shield Material	Coverage (%)
Braid	BC - Bare Copper	95.000

##### Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

Outer Jacket Diameter:

Nom. Dia. (in.)
0.232

Outer Jacket Color Code Chart:

Number	Color
1	Black

### Applicable Specifications and Agency Compliance

#### Applicable Standards & Environmental Programs

NEC/(UL) Specification: CM

CEC/C(UL) Specification: CM

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 06/08/2007

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

RG Type: 59/U

#### Flame Test

UL Flame Test: UL1685 Vertical Tray Flame Test

#### Suitability

Suitability - Indoor: Yes

### Electrical Characteristics

Nom. Characteristic Impedance:

## 2505PTZ Composite - For PTZ Cameras: CCTV + Control + Power

**Impedance (Ohm)**

75

**Nom. Inductance:**

**Inductance (µH/ft)**

0.097

**Nom. Capacitance Conductor to Shield:**

**Capacitance (pF/ft)**

16.300

**Nominal Velocity of Propagation:**

**VP (%)**

83.000

**Nominal Delay:**

**Delay (ns/ft)**

1.220

**Nom. Conductor DC Resistance:**

**DCR @ 20°C (Ohm/1000 ft)**

10.000

**Nominal Outer Shield DC Resistance:**

**DCR @ 20°C (Ohm/1000 ft)**

3.500

**Nom. Attenuation:**

Freq. (MHz)	Attenuation (dB/100 ft.)
1.000	0.300
5.000	0.650
10.000	0.900
50.000	1.900
100.000	2.600
200.000	3.600
400.000	5.000
700.000	7.000
900.000	8.000
1000.000	8.500

**Max. Operating Voltage - UL:**

300 V RMS

### Twisted Pair

#### Physical Characteristics

##### Conductor

**AWG:**

# Pairs	AWG	Stranding	Conductor Material
1	18	7x26	BC - Bare Copper

##### Insulation

**Insulation Material:**

Insulation Material
PVC - Polyvinyl Chloride

**Twisted Pair Color Code Chart:**

Number	Color
1	Black
2	Red

##### Inner Shield

**Inner Shield Material:**

Inner Shield Trade Name	Type	Inner Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100

**Inner Shield Drain Wire AWG:**

AWG	Stranding	Conductor Material
24	7x32	TC - Tinned Copper

##### Individual Shield

##### Outer Jacket

**Outer Jacket Material:**

Outer Jacket Material
PVC - Polyvinyl Chloride

**Outer Jacket Diameter:**

**Nom. Dia. (in.)**

## 2505PTZ Composite - For PTZ Cameras: CCTV + Control + Power

0.165

**Outer Jacket Color Code Chart:**

Number	Color
1	Gray

**Applicable Specifications and Agency Compliance  
Applicable Standards & Environmental Programs**

NEC(UL) Specification: CMR

CEC/C(UL) Specification: CMG

**Flame Test**

UL Flame Test: UL1666 Vertical Shaft

**Suitability**

Suitability - Indoor: Yes

**Electrical Characteristics**

**Max. Operating Voltage - Other:**

**Voltage**  
300 V RMS

### Multi Conductor

**Physical Characteristics**

**Conductor**

**AWG:**

# Conductors	AWG	Stranding	Conductor Material
2	16	19x29	BC - Bare Copper

**Insulation**

**Insulation Material:**

**Insulation Material**  
PVC - Polyvinyl Chloride

**Insulation Color Code Chart:**

Number	Color
1	Red
2	Black

**Individual Shield**

**Outer Jacket**

**Outer Jacket Material:**

**Outer Jacket Material**  
PVC - Polyvinyl Chloride

**Outer Jacket Color Code Chart:**

Number	Color
1	White

**Applicable Specifications and Agency Compliance  
Applicable Standards & Environmental Programs**

NEC(UL) Specification: CMR

CEC/C(UL) Specification: CMG

**Flame Test**

UL Flame Test: UL1666 Vertical Shaft

**Suitability**

Suitability - Indoor: Yes

**Electrical Characteristics**

**Nom. Conductor DC Resistance:**

**DCR @ 20°C (Ohm/1000 ft)**  
4.200

**Max. Operating Voltage - Other:**

**Voltage**  
300 V RMS

**Max. Recommended Current:**

**Current**  
5 Amps per conductor @ 25°C

## 2505PTZ Composite - For PTZ Camercas: CCTV + Control + Power

### Physical Characteristics (Overall)

#### Conductor

#### Outer Shield

Outer Shield Separator Material: Polyester

#### Outer Jacket

##### Outer Jacket Material:

##### Outer Jacket Material

Unjacketed

#### Armor

Armor Type: Interlocking

Armor Material: Aluminum

#### Overall Cable

Overall Nominal Diameter: 0.496 in.

### Mechanical Characteristics (Overall)

Operating Temperature Range: -10°C To +75°C

Separation Temperature Range: 0°C To +75°C

Bulk Cable Weight: 142 lbs/1000 ft.

Max. Recommended Pulling Tension: 210 lbs.

Min. Bend Radius/Minor Axis: 9.500 in.

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

EU Directive 2011/65/EU (ROHS II): Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 06/08/2007

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

#### Plenum/Non-Plenum

Plenum (Y/N): No

### Notes (Overall)

**Notes:** RG59 CCTV + 2C 18 AWG Shld + 2 C 16 AWG CMR. Individually jacketed and color coded components, cabled with an overall aluminum interlocked armor.

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
2505PTZ 0001000	1,000 FT	158.000 LB	NONE	C	RG59 +2C18 +2C16 FS CMR ARM

#### Notes:

C = CRATE REEL PUT-UP.

Revision Number: 0 Revision Date: 06-16-2014

© 2016 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,  
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А