

Type SEK 105 °C Radial Leaded Aluminum Electrolytic Capacitors

Long Life, Aluminum Electrolytic



Type SEK is a radial leaded aluminum electrolytic capacitor with a +105 °C, long life rating. The volumetric efficient high CV product of the SEK makes it ideal for high density packaging in general purpose, coupling, decoupling, bypass and filtering circuit applications.

Highlights

- +105 °C
- Long life
- High CV product
- General purpose applications
- Available in T&R and ammo pack

Specifications

| | |
|-------------------------------------|--|
| Capacitance Range: | 0.47 to 15,000 μ F |
| Voltage Range: | 6.3 to 450 Vdc |
| Capacitance Tolerance: | \pm 20% |
| Operating Temperature Range: | -55 °C to +105 °C; 6.3 to 100 Vdc -40 °C to +105 °C; 160 to 400 Vdc -25 °C to +105 °C; 450 Vdc |
| Maximum DC Leakage Current: | After 2 minutes, with rated voltage at +20 °C 6.3 to 100 Vdc $I = .01CV$ or 3 μ A Max (whichever is greater) \geq 160 Vdc after 3 min, with rated voltage at +20 °C $I = .03CV$ or 10 μ A Max (whichever is greater) C = Capacitance in (μ F) V = Rated voltage I = Leakage current in μ A |

Dissipation Factor @ 120 Hz, +25 °C:

| WV (V) | 6.3 | 10 | 16 | 25 | 35 | 50 | 63 | 80 | 100 | 160-250 | 350-450 |
|--------|-----|----|----|----|----|----|----|----|-----|---------|---------|
| DF(%) | 26 | 22 | 18 | 16 | 14 | 12 | 10 | 10 | 10 | 15 | 20 |

For capacitors whose capacitance value exceeds 1000 μ F, the value of DF (%) is increased 2% for every additional 1000 μ F.

Ripple Multipliers for Voltage and Temperature:

| Rated WVDC | Ripple Multipliers | | | |
|------------|--------------------|-------|------|-------|
| | 60Hz | 120Hz | 1kHz | 10kHz |
| 6 to 25 | 0.80 | 1.0 | 1.1 | 1.2 |
| 35 to 100 | 0.75 | 1.0 | 1.3 | 1.4 |
| 160 to 250 | 0.70 | 1.0 | 1.4 | 1.6 |
| 350 to 400 | 0.60 | 1.0 | 1.5 | 1.8 |

| Ambient Temperature | Ripple Multiplier |
|---------------------|-------------------|
| +105 °C | 1.00 |
| +85 °C | 1.50 |
| +70 °C | 1.80 |



Complies with the EU Directive 2002/95/EC requirement restricting the use of Lead (Pb), Mercury (Hg), Cadmium (Cd), Hexavalent chromium (Cr(VI)), PolyBrominated Biphenyls (PBB) and PolyBrominated Diphenyl Ethers (PBDE).

- Load Life:** Apply WVDC for 2000 hours at +105 °C
Capacitance change within 20% of initial limit
DF not to exceed 200% of initial requirement
Leakage current not to exceed 200% of initial
- Shelf Life:** 1000 hrs with no voltage applied
Cap change within \pm 20% of initial values
DF not to exceed 200% of initial requirement
DC leakage current meets initial requirement

Type SEK 105 °C Radial Leaded Aluminum Electrolytic Capacitors

Outline Drawing

Outline Dimensions (Millimeters)



Case vented on diameters 6.3 and greater

Vinyl sleeve adds .5 Max. to diameter and 2.0 Max. to length



Part Numbering System

| Type | Capacitance Capacitance (μF) Tolerance (%) | Rated Voltage (Vdc) | Packaging | Lead Configuration | |
|------|---|------------------------------|------------------------------------|--|--|
| SEK | 100 M | 100 | S | T | |
| | 3R0 = 3 100 = 10 101 = 100 102 = 1000 | K = ± 10 M = ± 20 | 6R3 = 6.3 010 = 10 100 = 100 | A = Tape & Ammo E = Different Characteristic R = Tape & Reel S = Standard | 1 = Lead cut 2 = Lead form 4 = Lead crimp & cut (form) T = Standard |

Temperature Characteristics



Load Life Characteristics



Type SEK 105 °C Radial Leaded Aluminum Electrolytic Capacitors

Ratings

| Cap (μ F) | Catalog Part Number | Max ESR 120 Hz 25 °C (Ω) | Max Ripple 120 Hz 105 °C (mA) | Size in. (mm) | | | |
|--------------------------------|------------------------|--|--|-----------------|---------------|-------------------|------------------|
| | | | | Diameter (D) | Length (L) | Lead Space (S) | Lead Dia. (d) |
| 6.3 Vdc (8 Volts Surge) | | | | | | | |
| 100 | SEK101M6R3ST | 3.45 | 100 | .197 (5.0) | .433 (11.0) | .079 (2.0) | .0197 (0.5) |
| 220 | SEK221M6R3ST | 1.57 | 165 | .248 (6.3) | .433 (11.0) | .098 (2.5) | .0197 (0.5) |
| 330 | SEK331M6R3ST | 1.05 | 200 | .248 (6.3) | .453 (11.5) | .098 (2.5) | .0197 (0.5) |
| 470 | SEK471M6R3ST | 0.73 | 280 | .315 (8.0) | .453 (11.5) | .138 (3.5) | .0236 (0.6) |
| 1000 | SEK102M6R3ST | 0.35 | 470 | .394 (10.0) | .512 (13.0) | .197 (5.0) | .0236 (0.6) |
| 2200 | SEK222M6R3ST | 0.17 | 930 | .394 (10.0) | .827 (21.0) | .197 (5.0) | .0236 (0.6) |
| 3300 | SEK332M6R3ST | 0.12 | 1100 | .512 (13.0) | .827 (21.0) | .197 (5.0) | .0236 (0.6) |
| 4700 | SEK472M6R3ST | 0.10 | 1320 | .630 (16.0) | .984 (26.0) | .295 (7.5) | .0315 (0.8) |
| 6800 | SEK682M6R3ST | 0.07 | 1490 | .630 (16.0) | .984 (25.0) | .295 (7.5) | .0315 (0.8) |
| 10000 | SEK103M6R3ST | 0.06 | 1830 | .630 (16.0) | 1.26 (32.0) | .295 (7.5) | .0315 (0.8) |
| 15000 | SEK153M6R3ST | 0.05 | 2280 | .709 (18.0) | 1.40 (36.0) | .295 (7.5) | .0315 (0.8) |
| 10 Vdc (13 Volts Surge) | | | | | | | |
| 47 | SEK470M010ST | 6.21 | 75 | .197 (5.0) | .433 (11.0) | .079 (2.0) | .0197 (0.5) |
| 100 | SEK101M010ST | 2.92 | 110 | .197 (5.0) | .433 (11.0) | .079 (2.0) | .0197 (0.5) |
| 220 | SEK221M010ST | 1.33 | 180 | .248 (6.3) | .433 (11.0) | .098 (2.5) | .0197 (0.5) |
| 330 | SEK331M010ST | 0.88 | 255 | .315 (8.0) | .453 (11.5) | .138 (3.5) | .0236 (0.6) |
| 470 | SEK471M010ST | 0.62 | 305 | .315 (8.0) | .453 (11.5) | .138 (3.5) | .0236 (0.6) |
| 1000 | SEK102M010ST | 0.29 | 570 | .394 (10.0) | .630 (16.0) | .197 (5.0) | .0236 (0.6) |
| 2200 | SEK222M010ST | 0.14 | 1010 | .512 (13.0) | .827 (21.0) | .197 (5.0) | .0236 (0.6) |
| 3300 | SEK332M010ST | 0.10 | 1220 | .512 (13.0) | .984 (25.0) | .197 (5.0) | .0236 (0.6) |
| 4700 | SEK472M010ST | 0.08 | 1410 | .630 (16.0) | .984 (25.0) | .295 (7.5) | .0315 (0.8) |
| 6800 | SEK682M010ST | 0.07 | 1610 | .630 (16.0) | 1.26 (32.0) | .295 (7.5) | .0315 (0.8) |
| 10000 | SEK103M010ST | 0.05 | 1980 | .709 (18.0) | 1.40 (36.0) | .295 (7.5) | .0315 (0.8) |
| 15000 | SEK153M010ST | 0.04 | 3330 | .709 (18.0) | 1.65 (42.0) | .295 (7.5) | .0315 (0.8) |
| 16 Vdc (20 Volts Surge) | | | | | | | |
| 33 | SEK330M016ST | 7.24 | 70 | .197 (5.0) | .433 (11.0) | .079 (2.0) | .0197 (0.5) |
| 47 | SEK470M016ST | 5.08 | 85 | .197 (5.0) | .433 (11.0) | .079 (2.0) | .0197 (0.5) |
| 100 | SEK101M016ST | 2.39 | 135 | .248 (6.3) | .433 (11.0) | .098 (2.5) | .0197 (0.5) |
| 220 | SEK221M016ST | 1.09 | 235 | .315 (8.0) | .453 (11.5) | .138 (3.5) | .0236 (0.6) |
| 330 | SEK331M016ST | 0.72 | 285 | .315 (8.0) | .433 (11.0) | .138 (3.5) | .0236 (0.6) |
| 470 | SEK471M016ST | 0.51 | 395 | .394 (10.0) | .512 (13.0) | .197 (5.0) | .0236 (0.6) |
| 1000 | SEK102M016ST | 0.24 | 700 | .394 (10.0) | .827 (21.0) | .197 (5.0) | .0236 (0.6) |
| 2200 | SEK222M016ST | 0.12 | 1150 | .512 (13.0) | .827 (21.0) | .197 (5.0) | .0236 (0.6) |
| 3300 | SEK332M016ST | 0.09 | 1350 | .512 (13.0) | .984 (26.0) | .197 (5.0) | .0236 (0.6) |
| 4700 | SEK472M016ST | 0.07 | 1560 | .630 (16.0) | 1.26 (32.0) | .295 (7.5) | .0315 (0.8) |
| 6800 | SEK682M016ST | 0.06 | 1790 | .709 (18.0) | 1.40 (36.0) | .295 (7.5) | .0315 (0.8) |
| 10000 | SEK103M016ST | 0.05 | 2884 | .709 (18.0) | 1.65 (42.0) | .295 (7.5) | .0315 (0.8) |
| 25 Vdc (32 Volts Surge) | | | | | | | |
| 10 | SEK100M025ST | 21.23 | 50 | .197 (5.0) | .433 (11.0) | .079 (2.0) | .0197 (0.5) |
| 22 | SEK220M025ST | 9.65 | 60 | .197 (5.0) | .433 (11.0) | .079 (2.0) | .0197 (0.5) |
| 33 | SEK330M025ST | 6.43 | 75 | .197 (5.0) | .433 (11.0) | .079 (2.0) | .0197 (0.5) |
| 47 | SEK470M025ST | 4.52 | 90 | .197 (5.0) | .433 (11.0) | .079 (2.0) | .0197 (0.5) |
| 100 | SEK101M025ST | 2.12 | 145 | .248 (6.3) | .433 (11.0) | .098 (2.5) | .0197 (0.5) |
| 220 | SEK221M025ST | 0.97 | 250 | .315 (8.0) | .433 (11.0) | .138 (3.5) | .0236 (0.6) |
| 330 | SEK331M025ST | 0.64 | 355 | .394 (10.0) | .512 (13.0) | .197 (5.0) | .0236 (0.6) |

Type SEK 105 °C Radial Leaded Aluminum Electrolytic Capacitors

| Cap (μ F) | Catalog Part Number | Max ESR 120 Hz 25 °C (Ω) | Max Ripple 120 Hz 105 °C (mA) | Size in. (mm) | | | |
|--------------------------------|------------------------|--|--|-----------------|---------------|-------------------|------------------|
| | | | | Diameter (D) | Length (L) | Lead Space (S) | Lead Dia. (d) |
| 25 Vdc (32 Volts Surge) | | | | | | | |
| 470 | SEK471M025ST | 0.45 | 470 | .394 (10.0) | .630 (16.0) | .197 (5.0) | .0236 (0.6) |
| 1000 | SEK102M025ST | 0.21 | 855 | .512 (13.0) | .827 (21.0) | .197 (5.0) | .0236 (0.6) |
| 2200 | SEK222M025ST | 0.11 | 1230 | .512 (13.0) | .984 (26.0) | .197 (5.0) | .0236 (0.6) |
| 3300 | SEK332M025ST | 0.08 | 1450 | .630 (16.0) | 1.26 (32.0) | .295 (7.5) | .0315 (0.8) |
| 4700 | SEK472M025ST | 0.07 | 1690 | .709 (18.0) | 1.40 (36.0) | .295 (7.5) | .0315 (0.8) |
| 6800 | SEK682M025ST | 0.05 | 2856 | .709 (18.0) | 1.65 (42.0) | .295 (7.5) | .0315 (0.8) |
| 35 Vdc (44 Volts Surge) | | | | | | | |
| 22 | SEK220M035ST | 8.44 | 65 | .197 (5.0) | .433 (11.0) | .079 (2.0) | .0197 (0.5) |
| 33 | SEK330M035ST | 5.63 | 85 | .197 (5.0) | .433 (11.0) | .079 (2.0) | .0197 (0.5) |
| 47 | SEK470M035ST | 3.95 | 115 | .248 (6.3) | .433 (11.0) | .098 (2.5) | .0197 (0.5) |
| 100 | SEK101M035ST | 1.86 | 190 | .315 (8.0) | .453 (11.5) | .138 (3.5) | .0236 (0.6) |
| 220 | SEK221M035ST | 0.84 | 315 | .394 (10.0) | .512 (13.0) | .197 (5.0) | .0236 (0.6) |
| 330 | SEK331M035ST | 0.56 | 440 | .394 (10.0) | .630 (16.0) | .197 (5.0) | .0236 (0.6) |
| 470 | SEK471M035ST | 0.40 | 580 | .512 (13.0) | .787 (20.0) | .197 (5.0) | .0236 (0.6) |
| 1000 | SEK102M035ST | 0.19 | 995 | .512 (13.0) | .827 (21.0) | .197 (5.0) | .0236 (0.6) |
| 2200 | SEK222M035ST | 0.10 | 1450 | .630 (16.0) | 1.26 (32.0) | .295 (7.5) | .0315 (0.8) |
| 3300 | SEK332M035ST | 0.07 | 1660 | .709 (18.0) | 1.40 (36.0) | .295 (7.5) | .0315 (0.8) |
| 4700 | SEK472M035ST | 0.06 | 2674 | .709 (18.0) | 1.65 (42.0) | .295 (7.5) | .0315 (0.8) |
| 50 Vdc (63 Volts Surge) | | | | | | | |
| 0.47 | SEKR47M050ST | 338.80 | 7.0 | .197 (5.0) | .433 (11.0) | .079 (2.0) | .0197 (0.5) |
| 1.0 | SEK010M050ST | 159.24 | 12.0 | .197 (5.0) | .433 (11.0) | .079 (2.0) | .0197 (0.5) |
| 2.2 | SEK2R2M050ST | 72.38 | 18.0 | .197 (5.0) | .433 (11.0) | .079 (2.0) | .0197 (0.5) |
| 3.3 | SEK3R3M050ST | 48.25 | 25.0 | .197 (5.0) | .433 (11.0) | .079 (2.0) | .0197 (0.5) |
| 4.7 | SEK4R7M050ST | 33.88 | 30.0 | .197 (5.0) | .433 (11.0) | .079 (2.0) | .0197 (0.5) |
| 10 | SEK100M050ST | 15.92 | 50.0 | .197 (5.0) | .433 (11.0) | .079 (2.0) | .0197 (0.5) |
| 22 | SEK220M050ST | 7.24 | 75.0 | .197 (5.0) | .433 (11.0) | .079 (2.0) | .0197 (0.5) |
| 33 | SEK330M050ST | 4.83 | 105.0 | .248 (6.3) | .433 (11.0) | .098 (2.5) | .0197 (0.5) |
| 47 | SEK470M050ST | 3.39 | 125.0 | .248 (6.3) | .453 (11.5) | .098 (2.5) | .0197 (0.5) |
| 100 | SEK101M050ST | 1.59 | 210.0 | .315 (8.0) | .433 (11.0) | .138 (3.5) | .0236 (0.6) |
| 220 | SEK221M050ST | 0.72 | 400.0 | .394 (10.0) | .630 (16.0) | .197 (5.0) | .0236 (0.6) |
| 330 | SEK331M050ST | 0.48 | 535.0 | .394 (10.0) | .827 (21.0) | .197 (5.0) | .0236 (0.6) |
| 470 | SEK471M050ST | 0.34 | 730.0 | .512 (13.0) | .827 (21.0) | .197 (5.0) | .0236 (0.6) |
| 1000 | SEK102M050ST | 0.16 | 1110.0 | .630 (16.0) | .984 (25.0) | .295 (7.5) | .0315 (0.8) |
| 2200 | SEK222M050ST | 0.08 | 1530.0 | .709 (18.0) | 1.40 (36.0) | .295 (7.5) | .0315 (0.8) |
| 3300 | SEK332M050ST | 0.47 | 2478.0 | .709 (18.0) | 1.65 (42.0) | .295 (7.5) | .0315 (0.8) |
| 63 Vdc (79 Volts Surge) | | | | | | | |
| 4.7 | SEK4R7M063ST | 28.23 | 34 | .197 (5.0) | .433 (11.0) | .079 (2.0) | .0197 (0.5) |
| 10 | SEK100M063ST | 13.27 | 55 | .197 (5.0) | .433 (11.0) | .079 (2.0) | .0197 (0.5) |
| 22 | SEK220M063ST | 6.03 | 90 | .248 (6.3) | .433 (11.0) | .098 (2.5) | .0197 (0.5) |
| 33 | SEK330M063ST | 4.02 | 110 | .248 (6.3) | .433 (11.0) | .098 (2.5) | .0197 (0.5) |
| 47 | SEK470M063ST | 2.82 | 155 | .315 (8.0) | .433 (11.0) | .138 (3.5) | .0236 (0.6) |
| 100 | SEK101M063ST | 1.33 | 260 | .394 (10.0) | .512 (13.0) | .197 (5.0) | .0236 (0.6) |
| 220 | SEK221M063ST | 0.60 | 460 | .394 (10.0) | .827 (21.0) | .197 (5.0) | .0236 (0.6) |
| 330 | SEK331M063ST | 0.40 | 650 | .512 (13.0) | .827 (21.0) | .197 (5.0) | .0236 (0.6) |
| 470 | SEK471M063ST | 0.28 | 800 | .512 (13.0) | .984 (26.0) | .197 (5.0) | .0236 (0.6) |
| 1000 | SEK102M063ST | 0.13 | 1200 | .630 (16.0) | 1.26 (32.0) | .295 (7.5) | .0315 (0.8) |

Type SEK 105 °C Radial Leaded Aluminum Electrolytic Capacitors

| Cap (μ F) | Catalog Part Number | Max ESR 120 Hz 25 °C (Ω) | Max Ripple 120 Hz 105 °C (mA) | Size in. (mm) | | | |
|----------------------------------|------------------------|--|--|-----------------|---------------|-------------------|------------------|
| | | | | Diameter (D) | Length (L) | Lead Space (S) | Lead Dia. (d) |
| 100 Vdc (125 Volts Surge) | | | | | | | |
| 0.47 | SEKR47M100ST | 282.33 | 10 | .197 (5.0) | .433 (11.0) | .079 (2.0) | .0197 (0.5) |
| 1.0 | SEK010M100ST | 132.70 | 15 | .197 (5.0) | .433 (11.0) | .079 (2.0) | .0197 (0.5) |
| 2.2 | SEK2R2M100ST | 60.32 | 22 | .197 (5.0) | .433 (11.0) | .079 (2.0) | .0197 (0.5) |
| 3.3 | SEK3R3M100ST | 40.21 | 29 | .197 (5.0) | .433 (11.0) | .079 (2.0) | .0197 (0.5) |
| 4.7 | SEK4R7M100ST | 28.23 | 37 | .197 (5.0) | .433 (11.0) | .079 (2.0) | .0197 (0.5) |
| 10.0 | SEK100M100ST | 13.27 | 65 | .248 (6.3) | .433 (11.0) | .098 (2.5) | .0197 (0.5) |
| 22.0 | SEK220M100ST | 6.03 | 115 | .315 (8.0) | .433 (11.0) | .138 (3.5) | .0236 (0.6) |
| 33.0 | SEK330M100ST | 4.02 | 160 | .394 (10.0) | .512 (13.0) | .197 (5.0) | .0236 (0.6) |
| 47.0 | SEK470M100ST | 2.82 | 210 | .394 (10.0) | .630 (16.0) | .197 (5.0) | .0236 (0.6) |
| 100.0 | SEK101M100ST | 1.33 | 385 | .512 (13.0) | .787 (20.0) | .197 (5.0) | .0236 (0.6) |
| 220.0 | SEK221M100ST | 0.60 | 590 | .630 (16.0) | .984 (25.0) | .295 (7.5) | .0315 (0.8) |
| 330.0 | SEK331M100ST | 0.40 | 720 | .630 (16.0) | .984 (25.0) | .295 (7.5) | .0315 (0.8) |
| 470.0 | SEK471M100ST | 0.28 | 875 | .630 (16.0) | 1.26 (32.0) | .295 (7.5) | .0315 (0.8) |
| 160 Vdc (200 Volts Surge) | | | | | | | |
| 0.47 | SEKR47M160ST | 423.50 | 12 | .248 (6.3) | .433 (11.0) | .098 (2.5) | .0197 (0.5) |
| 1.0 | SEK010M160ST | 199.04 | 17 | .248 (6.3) | .433 (11.0) | .098 (2.5) | .0197 (0.5) |
| 2.2 | SEK2R2M160ST | 90.47 | 25 | .248 (6.3) | .433 (11.0) | .098 (2.5) | .0197 (0.5) |
| 3.3 | SEK3R3M160ST | 60.32 | 36 | .248 (6.3) | .433 (11.0) | .098 (2.5) | .0197 (0.5) |
| 4.7 | SEK4R7M160ST | 42.35 | 43 | .248 (6.3) | .433 (11.0) | .098 (2.5) | .0197 (0.5) |
| 10 | SEK100M160ST | 19.90 | 70 | .315 (8.0) | .433 (11.0) | .138 (3.5) | .0236 (0.6) |
| 22 | SEK220M160ST | 9.05 | 130 | .394 (10.0) | .630 (16.0) | .197 (5.0) | .0236 (0.6) |
| 33 | SEK330M160ST | 6.03 | 180 | .394 (10.0) | .827 (21.0) | .197 (5.0) | .0236 (0.6) |
| 47 | SEK470M160ST | 4.23 | 270 | .512 (13.0) | .827 (21.0) | .197 (5.0) | .0236 (0.6) |
| 100 | SEK101M160ST | 1.99 | 330 | .512 (13.0) | .984 (26.0) | .197 (5.0) | .0236 (0.6) |
| 220 | SEK221M160ST | 0.90 | 500 | .630 (16.0) | 1.42 (36.0) | .295 (7.5) | .0315 (0.8) |
| 330 | SEK331M160ST | 0.60 | 850 | .709 (18.0) | 1.65 (42.0) | .295 (7.5) | .0315 (0.8) |
| 200 Vdc (250 Volts Surge) | | | | | | | |
| 0.47 | SEKR47M200ST | 423.50 | 12 | .248 (6.3) | .433 (11.0) | .098 (2.5) | .0197 (0.5) |
| 1.0 | SEK010M200ST | 199.04 | 17 | .248 (6.3) | .433 (11.0) | .098 (2.5) | .0197 (0.5) |
| 2.2 | SEK2R2M200ST | 90.47 | 25 | .248 (6.3) | .453 (11.5) | .098 (2.5) | .0197 (0.5) |
| 3.3 | SEK3R3M200ST | 60.32 | 36 | .248 (6.3) | .453 (11.5) | .098 (2.5) | .0197 (0.5) |
| 4.7 | SEK4R7M200ST | 42.35 | 50 | .315 (8.0) | .433 (11.0) | .138 (3.5) | .0236 (0.6) |
| 10 | SEK100M200ST | 19.90 | 80 | .394 (10.0) | .512 (13.0) | .197 (5.0) | .0236 (0.6) |
| 22 | SEK220M200ST | 9.05 | 140 | .394 (10.0) | .827 (21.0) | .197 (5.0) | .0236 (0.6) |
| 33 | SEK330M200ST | 6.03 | 190 | .512 (13.0) | .827 (21.0) | .197 (5.0) | .0236 (0.6) |
| 47 | SEK470M200ST | 4.23 | 220 | .512 (13.0) | .827 (21.0) | .197 (5.0) | .0236 (0.6) |
| 100 | SEK101M200ST | 1.99 | 335 | .630 (16.0) | .984 (25.0) | .295 (7.5) | .0315 (0.8) |
| 220 | SEK221M200ST | 0.90 | 515 | .709 (18.0) | 1.65 (42.0) | .295 (7.5) | .0315 (0.8) |
| 250 Vdc (300 Volts Surge) | | | | | | | |
| 0.47 | SEKR47M250ST | 423.50 | 12 | .248 (6.3) | .433 (11.0) | .098 (2.5) | .0197 (0.5) |
| 1.0 | SEK010M250ST | 199.04 | 17 | .248 (6.3) | .433 (11.0) | .098 (2.5) | .0197 (0.5) |
| 2.2 | SEK2R2M250ST | 90.47 | 29 | .248 (6.3) | .453 (11.5) | .098 (2.5) | .0197 (0.5) |
| 3.3 | SEK3R3M250ST | 60.32 | 42 | .315 (8.0) | .433 (11.0) | .138 (3.5) | .0236 (0.6) |
| 4.7 | SEK4R7M250ST | 42.35 | 50 | .315 (8.0) | .433 (11.0) | .138 (3.5) | .0236 (0.6) |
| 10.0 | SEK100M250ST | 19.90 | 88 | .394 (10.0) | .630 (16.0) | .197 (5.0) | .0236 (0.6) |

Type SEK 105 °C Radial Leaded Aluminum Electrolytic Capacitors

| Cap (μ F) | Catalog Part Number | Max ESR 120 Hz 25 °C (Ω) | Max Ripple 120 Hz 105 °C (mA) | Size in. (mm) | | | |
|----------------------------------|------------------------|--|--|-----------------|---------------|-------------------|------------------|
| | | | | Diameter (D) | Length (L) | Lead Space (S) | Lead Dia. (d) |
| 250 Vdc (300 Volts Surge) | | | | | | | |
| 22 | SEK220M250ST | 9.05 | 155 | .512 (13.0) | .827 (21.0) | .197 (5.0) | .0236 (0.6) |
| 33 | SEK330M250ST | 6.03 | 190 | .512 (13.0) | .827 (21.0) | .197 (5.0) | .0236 (0.6) |
| 47 | SEK470M250ST | 4.23 | 230 | .512 (13.0) | .984 (26.0) | .197 (5.0) | .0236 (0.6) |
| 100 | SEK101M250ST | 1.99 | 340 | .630 (16.0) | 1.26 (32.0) | .295 (7.5) | .0315 (0.8) |
| 350 Vdc (400 Volts Surge) | | | | | | | |
| 0.47 | SEKR47M350ST | 564.67 | 14 | .315 (8.0) | .433 (11.0) | .138 (3.5) | .0236 (0.6) |
| 1.0 | SEK010M350ST | 265.39 | 20 | .315 (8.0) | .433 (11.0) | .138 (3.5) | .0236 (0.6) |
| 2.2 | SEK2R2M350ST | 120.63 | 35 | .315 (8.0) | .453 (11.5) | .138 (3.5) | .0236 (0.6) |
| 3.3 | SEK3R3M350ST | 80.42 | 47 | .394 (10.0) | .512 (13.0) | .197 (5.0) | .0236 (0.6) |
| 4.7 | SEK4R7M350ST | 56.47 | 55 | .394 (10.0) | .512 (13.0) | .197 (5.0) | .0236 (0.6) |
| 10 | SEK100M350ST | 26.54 | 95 | .394 (10.0) | .827 (21.0) | .197 (5.0) | .0236 (0.6) |
| 22 | SEK220M350ST | 12.06 | 165 | .512 (13.0) | .984 (26.0) | .197 (5.0) | .0236 (0.6) |
| 33 | SEK330M350ST | 8.04 | 195 | .512 (13.0) | .984 (25.0) | .197 (5.0) | .0236 (0.6) |
| 47 | SEK470M350ST | 5.65 | 240 | .630 (16.0) | 1.42 (36.0) | .295 (7.5) | .0315 (0.8) |
| 100 | SEK101M350ST | 2.65 | 360 | .709 (18.0) | 1.65 (42.0) | .295 (7.5) | .0315 (0.8) |
| 400 Vdc (450 Volts Surge) | | | | | | | |
| 0.47 | SEKR47M400ST | 564.67 | 14 | .315 (8.0) | .433 (11.0) | .138 (3.5) | .0236 (0.6) |
| 1.0 | SEK010M400ST | 265.39 | 20 | .315 (8.0) | .433 (11.0) | .138 (3.5) | .0236 (0.6) |
| 2.2 | SEK2R2M400ST | 120.63 | 35 | .394 (10.0) | .512 (13.0) | .197 (5.0) | .0236 (0.6) |
| 3.3 | SEK3R3M400ST | 80.42 | 50 | .394 (10.0) | .512 (13.0) | .197 (5.0) | .0236 (0.6) |
| 4.7 | SEK4R7M400ST | 56.47 | 58 | .394 (10.0) | .630 (16.0) | .197 (5.0) | .0236 (0.6) |
| 10 | SEK100M400ST | 26.54 | 100 | .512 (13.0) | .787 (20.0) | .197 (5.0) | .0236 (0.6) |
| 22 | SEK220M400ST | 12.06 | 170 | .512 (13.0) | .984 (26.0) | .197 (5.0) | .0236 (0.6) |
| 33 | SEK330M400ST | 8.04 | 205 | .630 (16.0) | 1.26 (32.0) | .295 (7.5) | .0315 (0.8) |
| 47 | SEK470M400ST | 5.65 | 255 | .709 (18.0) | 1.40 (36.0) | .295 (7.5) | .0315 (0.8) |
| 450 Vdc (500 Volts Surge) | | | | | | | |
| 0.47 | SEKR47M450ST | 564.67 | 14 | .315 (8.0) | .433 (11.0) | .138 (3.5) | .0236 (0.6) |
| 1.0 | SEK010M450ST | 265.39 | 20 | .315 (8.0) | .433 (11.0) | .138 (3.5) | .0236 (0.6) |
| 2.2 | SEK2R2M450ST | 120.63 | 35 | .394 (10.0) | .512 (13.0) | .197 (5.0) | .0236 (0.6) |
| 3.3 | SEK3R3M450ST | 80.42 | 50 | .394 (10.0) | .512 (13.0) | .197 (5.0) | .0236 (0.6) |
| 4.7 | SEK4R7M450ST | 56.47 | 58 | .394 (10.0) | .630 (16.0) | .197 (5.0) | .0236 (0.6) |
| 10 | SEK100M450ST | 26.54 | 100 | .512 (13.0) | .827 (21.0) | .197 (5.0) | .0236 (0.6) |
| 22 | SEK220M450ST | 12.06 | 170 | .512 (13.0) | .984 (26.0) | .197 (5.0) | .0236 (0.6) |
| 33 | SEK330M450ST | 8.04 | 205 | .630 (16.0) | 1.26 (32.0) | .295 (7.5) | .0315 (0.8) |
| 47 | SEK470M450ST | 5.65 | 255 | .709 (18.0) | 1.40 (36.0) | .295 (7.5) | .0315 (0.8) |

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А