Features

Regulated Converters

- Long 5 Year Warranty
- 2MOPP/250VAC
- Suitable for built in Class II Applications
- Wide Input Voltage Range (85-264VAC)
- Low Leakage Current (<75µA)
- 5000m Operation
- -40°C to +85°C Operating Temperature

RECOM
AC/DC Converter

RACM40

40 Watt Enclosed & Open Frame Case Style Single Output

Description

The RACM40 is a compact 3.6"x2.38" high efficiency AC/DC power supply with 2xMOPP safety approval for medical applications. These space saving enclosed power supplies have an universal input voltage range (85-264VAC), 4kVAC isolation, require no minimum load and can be used at ambient temperatures of between -40°C and +85°C. The 5V, 12V, 15V, 24V or 48V output voltages are fully protected and have tolerances of less than ±0.2% over the entire input voltage range and less than ±0.5% over the entire load range. The output voltage can be trimmed over a ±10% range. The RACM40 series is certified to medical safety standard IEC/ES/EN-60601-1 3rd Edition and feature BF rated outputs with less than 75µA leakage current. It has a built-in Class B EMI filter and comes with a 5 year warranty.

Selection Guide

Part Number	Input Voltage Range (VAC)	Output Voltage (VDC)	Output Current (A)	Efficiency typ. (%)
RACM40-05S (1,2)	85-264	5	8.0	90
RACM40-12S (1,2)	85-264	12	3.34	92
RACM40-15S (1,2)	85-264	15	2.67	92
RACM40-24S (1,2)	85-264	24	1.67	92
RACM40-48S (1,2)	85-264	48	0.84	93

2MOPP
250VAC

E314885

Model Numbering

RACM40- __ S / __ -

- Output Power
- Output Voltage
- Single
- Connections (2)
- Case Style (1)

Notes:

Note1: Case Style: without suffix, standard enclosed case
add suffix "/OF" for open frame style

Note2: Connections: without suffix, standard connection with connector
with suffix "-ST" connection with screw terminals

Examples:

RACM40-12S = 12Vout, standard enclosed case
RACM40-48S/OF = 24Vout, open frame style
RACD40-15S/OF-ST = 15Vout, open frame style with screw terminal connection

EN-55011 (Pending)
EN-55022 (Pending)
IEC/EN-60601 Certified
ANSI/AAMI ES-60601 Certified

Specifications (measured at T_a= 25°C, 250VAC, full load and after warm-up)

BASIC CHARACTERISTICS

Parameter	Condition	Min.	Typ.	Max.
Input Voltage		85VAC 100VDC (3)	230VAC	264VAC 370VDC
Input Current	115VAC, fulll load 230VAC, full load			1.0A 0.5A
Inrush Current	230VAC			60A
Input Power @ No Load				0.11W
Input Frequency Range	AC Input		50/60Hz	440Hz (3)
Start-up Time				1 Second
Rise Time			20ms	
Hold up Time	115VAC, full load		25ms	
Minimum Load				0%
Operating Frequency Range	5VDC, 230VAC others, 230VAC		70kHz 120kHz	
Output Ripple and Noise (measured @ 20MHz BW)	5VDC, 12VDC and 15VDC with 10µF/25V MLCC 24VDC, with 1µF/50V MLCC 48VDC, with 0.1µF/100V MLCC		75mVp-p 75mVp-p 150mVp-p	

Notes:

Note3: Confirmed performance, but not covered in certificates. 100VDC inpult voltage with derating.

RACM40-24









Specifications (measured at T_a= 25°C, 250VAC, full load and after warm-up)

REGULATIONS		
Parameter	**Condition**	**Value**
Set Voltage Accuracy	230VAC, full load	±1%
Line Voltage Regulation	low line to high line, full load	±0.2%
Load Voltage Regulation	0% to 100% load 5VDC others 10% to 90% load 5VDC others	±0.7% ±0.5% ±0.6% ±0.4%
Output Voltage Trim	on-board trimpot.	±10%
Transient Peak Deviation	load step from 50% - 75% change at 2.5A/µs	3% Vout max.
Transient Recovery Time	load step from 50% - 75% change at 2.5A/µs	500µs typ.

PROTECTIONS		
Parameter	**Condition**	**Value**
Input Fuse	internal line and neutral	2x T3.15A / 250VAC, slow blow type
Short Circuit Protection (SCP)		continuous, auto-recovery
Over Load Protection (OLP)	% of Iout rated (Hiccup)	145% typ.
Over Voltage Protection (OVP)	% of Vout nominal (Latch off)	125% min / 140% max.
Isolation Voltgage (2MOPP insulation)	I/P to O/P I/P to Chassis, O/P to Chassis working voltage	4kVAC / 1 minunte 2.5kVAC / 1 minute 250VAC / continuous
Means of Protection		2MOPP
Leakage Current	264VAC	75µA max.
Medical Device Classification		Type BF applied device
Internal Clearance Creepage	I/P to O/P I/P to O/P	8mm min. 8mm min.
Isolation Resistance	500VDC	100MΩ min.
Insulation Grade		Reinforced Insulation

ENVIRONMENTAL		
Parameter	**Condition**	**Value**
Operating Humidity	non-condensing	5% to 95% RH
Temperature Coefficient		±0.02% / °C
Operating Temperature Range	115/230VAC, with derating	-40°C to +85°C
Operating Altitude		5000m max.
MTBF	according to MIL-HDBK-217F, full load, +25°C	3010 x 10^3 hours

Derating Graph

RACM40-05S(/OF)



RACM40-12,15,24,48S(/OF)



Specifications (measured at T_a= 25°C, 250VAC, full load and after warm-up)

SAFETY AND CERTIFICATIONS		
Certificate Type	**Report / File Number**	**Standard**
IEC/EN Medical Safety (CB Scheme)	151101302	IEC60601-1, 3rd Edition, 2012 EN60601-1, 3rd Edition, 2014
ANSI/AAMI Medical Safety		ES60601-1, 2012
Risk Managment	151101301_2037	ISO 14971:2007 EN ISO 14971:2012

EMC Compliance	Condition	Standard / Criterion
EMI Standard		EN55011 + EN55022 + FCC18, Class B
ESD	Air ±8kV; Contact ±6kV	EN61000-4-2, Criteria A
Radiated Immunity	20V/m	EN61000-4-3, Criteria A
Fast Transient	±2kV	EN61000-4-4, Criteria A
Surge	L-N ±1kV and L-GND/N-GND ±2kV	EN61000-4-5, Criteria A
Conducted Immunity	20Vr.m.s	EN61000-4-6, Criteria A
Power Frequency Magnetic Field	10A/m	EN61000-4-8, Criteria A
Harmonic Current	full load	EN61000-3-2, Class A
Voltage Flicker		EN61000-3-3
Shock		IEC60068-2-27
Vibration		IEC60068-2-6
Dip and Interruptions, 230VAC 50Hz	30% 500ms 60% 100ms >95% 10ms >95% 5000ms	EN60601-1-2, Criteria A EN60601-1-2, Criteria A EN60601-1-2, Criteria A EN60601-1-2, Criteria B

DIMENSION and PHYSICAL CHARACTERISTICS		
Parameter	**Type**	**Value**
Package Dimension (LxWxH)	enclosed case open frame	91.4 x 60.5 x 33.3mm 76.2 x 50.8 x 26.5mm
Package Weight	enclosed case open frame + "-ST" Version	169g 154g
Case Material	enclosed case	Aluminum

Dimension Drawing Enclosed Case (mm)

Top View



AC Input Connector CON1

Pin1 Line
Pin3 Neutral

Pin Connector: Molex KK156

DC Output Connector CON2

Pin1,2 -Vout
Pin3,4 +Vout

Pin Connector: Molex KK156

Tolerance: ±0.5mm
FC: fixing center

continued on next page

Specifications (measured at T_a= 25°C, 250VAC, full load and after warm-up)

Side View



Bottom View



Dimension Drawing Open Frame (/OF) (mm)

Top View



Side View



AC Input Connector CON1

Pin1 Line
Pin3 Neutral

Pin Connector: Molex KK156

DC Output Connector CON2

Pin1,2 -Vout
Pin3,4 +Vout

Pin Connector: Molex KK156

Tolerance: ±0.5mm
FC: fixing center

continued on next page

Specifications (measured at T_a= 25°C, 250VAC, full load and after warm-up)

Screw Terminal Connection "-ST"

Enclosed Version



Open Frame Version



AC Input Connector CON1

Pin1 Line
Pin3 Neutral

Screw Terminal: ETB30

DC Output Connector CON2

Pin1,2 -Vout
Pin3,4 +Vout

Screw Terminal: ETB30

Tolerance: ±0.5mm
FC: fixing center

PACKAGING INFORMATION			
Parameter	**Type**		**Value**
Packaging Dimension (LxWxH)	cardboard box	enclosed case	111.0 x 94.0 x 51.0mm
		open frame	120.0 x 80.0 x 85.0mm
Packaging Quantity			1pcs
Storage Temperature Range			-40°C to +85°C

The product information and specifications are subject to change without prior notice. RECOM products are not authorized for use in safety-critical applications (such as life support) without RECOM's explicit written consent. A safety-critical application is defined as an application where a failure of a RECOM product may reasonably be expected to endanger or cause loss of life, inflict bodily harm or damage property. The buyer shall indemnify and hold harmless RECOM, its affiliated companies and its representatives against any damage claims in connection with the unauthorized use of RECOM products in such safety-critical applications.

OCEAN CHIPS
Океан Электроники
Поставка электронных компонентов

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «**JONHON**», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «**FORSTAR**».

AVIC JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).

FORSTAR®

Телефон: 8 (812) 309-75-97 (многоканальный)
Факс: 8 (812) 320-03-32
Электронная почта: ocean@oceanchips.ru
Web: http://oceanchips.ru/
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А