

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0428786410

Status:

Active

Overview:

modular_plugs_jacks

Description:

Modular Jack, Vertical, Low Profile, 6/4

Documents:

3D Model

Drawing (PDF)

Product Specification PS-42878 (PDF)

RoHS Certificate of Compliance (PDF)

Agency Certification

CSA

LR19980

UL

E107635

General

Product Family

Modular Jacks/Plugs

Series

42878

Comments

Flush Mount|Flangeless|2 PCB Thick

Component Type

PCB Jack

Magnetic

No

Overview

modular_plugs_jacks

Performance Category

3

Power over Ethernet (PoE)

N/A

Product Name

RJ11

Physical

Boot Color

N/A

Color - Resin

Black

Durability (mating cycles max)

500

Flammability

94V-0

Inverted / Top Latch

N/A

Lightpipes/LEDs

None

Material - Metal

Phosphor Bronze

Material - Plating Mating

Gold

Material - Plating Termination

Tin

Material - Resin

Polyester

Orientation

Vertical (Top Entry)

PCB Locator

Yes

PCB Retention

Yes

PCB Thickness Recommended (in)

0.125 In

PCB Thickness Recommended (mm)

3.18 mm

Packaging Type

Tray

Pitch - Mating Interface (in)

0.040 In

Pitch - Mating Interface (mm)

1.02 mm

Pitch - Term. Interface (in)

0.050 In

Pitch - Term. Interface (mm)

1.27 mm

Plating min: Mating (µin)

50

Plating min: Mating (µm)

1.25

Plating min: Termination (µin)

100

Plating min: Termination (µm)

2.5

Ports

1

Positions / Loaded Contacts

6/4

Surface Mount Compatible (SMC)

No

Temperature Range - Operating

-40°C to +85°C

Termination Interface: Style

Through Hole

Waterproof / Dustproof

No

Wire/Cable Type

N/A



image - Reference only

Series

EU RoHS

ELV and RoHS

Compliant

REACH SVHC

Not Reviewed

Halogen-Free

Status

Not Reviewed

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com

For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

42878Series

Mates With

FCC 68 Plugs

Electrical

Current - Maximum per Contact	1.5A
Shielded	No
Voltage - Maximum	150V AC (RMS)

Solder Process Data

Duration at Max. Process Temperature (seconds)	5
Lead-free Process Capability	Wave Capable (TH only)
Max. Cycles at Max. Process Temperature	1
Process Temperature max. C	235

Material Info

Reference - Drawing Numbers

Packaging Specification	PK-42878-492
Product Specification	PS-42878
Sales Drawing	SDA-42878-****
Test Summary	TS-42878-001

This document was generated on 06/07/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

tb_frame_D_P_ME_T
Rev. E 2006/04/15

	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1																																																																																																																																																																																																																																																																																																																																																																																														
M	<table><tr><td rowspan="2">X*NOT TOOLED</td><td rowspan="2">ASSEMBLY NUMBER</td><td colspan="4">PART CHARACTERISTICS</td></tr><tr><td>EXTERNAL CONNECTOR SIZE</td><td>NUMBER OF POSITIONS</td><td>P. C. BOARD THICKNESS</td><td>MOUNTING EARS OPTION</td></tr><tr><td rowspan="6">L</td><td>42878-4216</td><td>4 POS. BODY</td><td>4</td><td>.062</td><td>YES</td></tr><tr><td>42878-4218</td><td>↑</td><td>4</td><td>.062</td><td>NO</td></tr><tr><td>42878-4264</td><td></td><td>4</td><td>.125</td><td>YES</td></tr><tr><td>42878-4266</td><td></td><td>4</td><td>.125</td><td>NO</td></tr><tr><td>42878-4360</td><td></td><td>2</td><td>.062</td><td>YES</td></tr><tr><td>42878-4362</td><td></td><td>2</td><td>.062</td><td>NO</td></tr><tr><td rowspan="6">K</td><td>42878-4408</td><td>↓</td><td>2</td><td>.125</td><td>YES</td></tr><tr><td>42878-4410</td><td>4 POS. BODY</td><td>2</td><td>.125</td><td>NO</td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td rowspan="6">J</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td rowspan="6">I</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td rowspan="6">H</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td rowspan="6">G</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td rowspan="6">F</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td rowspan="6">E</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td rowspan="6">D</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td rowspan="6">C</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td rowspan="6">B</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td rowspan="6">A</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr></table>																				X*NOT TOOLED	ASSEMBLY NUMBER	PART CHARACTERISTICS				EXTERNAL CONNECTOR SIZE	NUMBER OF POSITIONS	P. C. BOARD THICKNESS	MOUNTING EARS OPTION	L	42878-4216	4 POS. BODY	4	.062	YES	42878-4218	↑	4	.062	NO	42878-4264		4	.125	YES	42878-4266		4	.125	NO	42878-4360		2	.062	YES	42878-4362		2	.062	NO	K	42878-4408	↓	2	.125	YES	42878-4410	4 POS. BODY	2	.125	NO																					J																															I																															H																															G																															F																															E																															D																															C																															B																															A																														
X*NOT TOOLED	ASSEMBLY NUMBER	PART CHARACTERISTICS																																																																																																																																																																																																																																																																																																																																																																																																																
		EXTERNAL CONNECTOR SIZE	NUMBER OF POSITIONS	P. C. BOARD THICKNESS	MOUNTING EARS OPTION																																																																																																																																																																																																																																																																																																																																																																																																													
L	42878-4216	4 POS. BODY	4	.062	YES																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-4218	↑	4	.062	NO																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-4264		4	.125	YES																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-4266		4	.125	NO																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-4360		2	.062	YES																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-4362		2	.062	NO																																																																																																																																																																																																																																																																																																																																																																																																													
K	42878-4408	↓	2	.125	YES																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-4410	4 POS. BODY	2	.125	NO																																																																																																																																																																																																																																																																																																																																																																																																													
J																																																																																																																																																																																																																																																																																																																																																																																																																		
I																																																																																																																																																																																																																																																																																																																																																																																																																		
H																																																																																																																																																																																																																																																																																																																																																																																																																		
G																																																																																																																																																																																																																																																																																																																																																																																																																		
F																																																																																																																																																																																																																																																																																																																																																																																																																		
E																																																																																																																																																																																																																																																																																																																																																																																																																		
D																																																																																																																																																																																																																																																																																																																																																																																																																		
C																																																																																																																																																																																																																																																																																																																																																																																																																		
B																																																																																																																																																																																																																																																																																																																																																																																																																		
A																																																																																																																																																																																																																																																																																																																																																																																																																		
<table><tr><td rowspan="2">X*NOT TOOLED</td><td rowspan="2">ASSEMBLY ITEM NUMBER</td><td colspan="4">PART CHARACTERISTICS</td></tr><tr><td>EXTERNAL CONNECTOR SIZE</td><td>NUMBER OF POSITIONS</td><td>P. C. BOARD THICKNESS</td><td>MOUNTING EARS OPTION</td></tr><tr><td rowspan="12"></td><td>42878-6216</td><td>6 POS. BODY</td><td>6</td><td>.062</td><td>YES</td></tr><tr><td>42878-6218</td><td>↑</td><td>6</td><td>.062</td><td>NO</td></tr><tr><td>42878-6264</td><td></td><td>6</td><td>.125</td><td>YES</td></tr><tr><td>42878-6266</td><td></td><td>6</td><td>.125</td><td>NO</td></tr><tr><td>42878-6360</td><td></td><td>4</td><td>.062</td><td>YES</td></tr><tr><td>42878-6362</td><td></td><td>4</td><td>.062</td><td>NO</td></tr><tr><td>42878-6408</td><td></td><td>4</td><td>.125</td><td>YES</td></tr><tr><td>42878-6410</td><td></td><td>4</td><td>.125</td><td>NO</td></tr><tr><td>42878-6504</td><td></td><td>2</td><td>.062</td><td>YES</td></tr><tr><td>42878-6506</td><td></td><td>2</td><td>.062</td><td>NO</td></tr><tr><td>42878-6552</td><td>↓</td><td>2</td><td>.125</td><td>YES</td></tr><tr><td>42878-6554</td><td>6 POS. BODY</td><td>2</td><td>.125</td><td>NO</td></tr><tr><td rowspan="6"></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td></tr></table>																				X*NOT TOOLED	ASSEMBLY ITEM NUMBER	PART CHARACTERISTICS				EXTERNAL CONNECTOR SIZE	NUMBER OF POSITIONS	P. C. BOARD THICKNESS	MOUNTING EARS OPTION		42878-6216	6 POS. BODY	6	.062	YES	42878-6218	↑	6	.062	NO	42878-6264		6	.125	YES	42878-6266		6	.125	NO	42878-6360		4	.062	YES	42878-6362		4	.062	NO	42878-6408		4	.125	YES	42878-6410		4	.125	NO	42878-6504		2	.062	YES	42878-6506		2	.062	NO	42878-6552	↓	2	.125	YES	42878-6554	6 POS. BODY	2	.125	NO																																																																																																																																																																																																																																																																																																																								
X*NOT TOOLED	ASSEMBLY ITEM NUMBER	PART CHARACTERISTICS																																																																																																																																																																																																																																																																																																																																																																																																																
		EXTERNAL CONNECTOR SIZE	NUMBER OF POSITIONS	P. C. BOARD THICKNESS	MOUNTING EARS OPTION																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-6216	6 POS. BODY	6	.062	YES																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-6218	↑	6	.062	NO																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-6264		6	.125	YES																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-6266		6	.125	NO																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-6360		4	.062	YES																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-6362		4	.062	NO																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-6408		4	.125	YES																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-6410		4	.125	NO																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-6504		2	.062	YES																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-6506		2	.062	NO																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-6552	↓	2	.125	YES																																																																																																																																																																																																																																																																																																																																																																																																													
	42878-6554	6 POS. BODY	2	.125	NO																																																																																																																																																																																																																																																																																																																																																																																																													
<table><tr><td colspan="5">CHARACTERISTICS LEGEND</td></tr><tr><td colspan="5">EXTERNAL CONNECTOR BODY DIMENSIONS: AVAILABLE IN 4, 6, AND 8 POSITION BODY</td></tr><tr><td colspan="5">NUMBER OF CONTACT POSITIONS: CONNECTOR SIZE 4 ACCOMMODATES 2, 4, OR 4 TERMINALS, CONNECTOR SIZE 6 ACCOMMODATES 2, 4, OR 6 TERMINALS, CONNECTOR SIZE 8 ACCOMMODATES 2, 4, 6, 8, OR 10 TERMINALS</td></tr><tr><td colspan="5">POLARIZATION OPTION: (AVAILABLE ON CONNECTOR SIZE 8 ONLY) "NO"= WITHOUT KEYING SLOT "YES"= WITH KEYING SLOT</td></tr><tr><td colspan="5">MOUNTING EARS OPTION: "YES"= PART WITH MOUNTING EARS "NO"= PART WITHOUT MOUNTING EARS</td></tr><tr><td colspan="5">(SEE SHEET 1 & 2 FOR PART DESCRIPTIONS AND DIMENSIONS)</td></tr></table>																				CHARACTERISTICS LEGEND					EXTERNAL CONNECTOR BODY DIMENSIONS: AVAILABLE IN 4, 6, AND 8 POSITION BODY					NUMBER OF CONTACT POSITIONS: CONNECTOR SIZE 4 ACCOMMODATES 2, 4, OR 4 TERMINALS, CONNECTOR SIZE 6 ACCOMMODATES 2, 4, OR 6 TERMINALS, CONNECTOR SIZE 8 ACCOMMODATES 2, 4, 6, 8, OR 10 TERMINALS					POLARIZATION OPTION: (AVAILABLE ON CONNECTOR SIZE 8 ONLY) "NO"= WITHOUT KEYING SLOT "YES"= WITH KEYING SLOT					MOUNTING EARS OPTION: "YES"= PART WITH MOUNTING EARS "NO"= PART WITHOUT MOUNTING EARS					(SEE SHEET 1 & 2 FOR PART DESCRIPTIONS AND DIMENSIONS)																																																																																																																																																																																																																																																																																																																																																																					
CHARACTERISTICS LEGEND																																																																																																																																																																																																																																																																																																																																																																																																																		
EXTERNAL CONNECTOR BODY DIMENSIONS: AVAILABLE IN 4, 6, AND 8 POSITION BODY																																																																																																																																																																																																																																																																																																																																																																																																																		
NUMBER OF CONTACT POSITIONS: CONNECTOR SIZE 4 ACCOMMODATES 2, 4, OR 4 TERMINALS, CONNECTOR SIZE 6 ACCOMMODATES 2, 4, OR 6 TERMINALS, CONNECTOR SIZE 8 ACCOMMODATES 2, 4, 6, 8, OR 10 TERMINALS																																																																																																																																																																																																																																																																																																																																																																																																																		
POLARIZATION OPTION: (AVAILABLE ON CONNECTOR SIZE 8 ONLY) "NO"= WITHOUT KEYING SLOT "YES"= WITH KEYING SLOT																																																																																																																																																																																																																																																																																																																																																																																																																		
MOUNTING EARS OPTION: "YES"= PART WITH MOUNTING EARS "NO"= PART WITHOUT MOUNTING EARS																																																																																																																																																																																																																																																																																																																																																																																																																		
(SEE SHEET 1 & 2 FOR PART DESCRIPTIONS AND DIMENSIONS)																																																																																																																																																																																																																																																																																																																																																																																																																		
<table><tr><td rowspan="2">SEE SHEET ONE</td><td rowspan="2">REV</td><td rowspan="2">DESCRIPTION</td><td rowspan="2">QUALITY SYMBOLS</td><td colspan="2">GENERAL TOLERANCES (UNLESS SPECIFIED)</td><td rowspan="2">SCALE</td><td rowspan="2">DESIGN UNITS</td><td rowspan="2">THIRD ANGLE PROJECTION</td><td rowspan="2">REVISE ON CAD ONLY</td></tr><tr><td>mm</td><td>INCH</td></tr><tr><td rowspan="4">H</td><td rowspan="4"></td><td rowspan="4"></td><td rowspan="4">▽.0</td><td>4 PLACES</td><td>±.---</td><td>±.---</td><td rowspan="4">IN/MM</td><td rowspan="4">DRAWN BY</td><td rowspan="4">DATE</td><td rowspan="4">TITLE</td></tr><tr><td>3 PLACES</td><td>±.---</td><td>±.---</td></tr><tr><td>2 PLACES</td><td>±.---</td><td>±.---</td></tr><tr><td>1 PLACE</td><td>±.---</td><td>±.---</td></tr><tr><td rowspan="4"></td><td rowspan="4"></td><td rowspan="4"></td><td rowspan="4">▽.0</td><td colspan="2">ANGULAR ±1/2°</td><td rowspan="4">APPROVED BY</td><td rowspan="4">DATE</td><td rowspan="4">MATERIAL NO.</td><td rowspan="4">DOCUMENT NO.</td><td rowspan="4">SHEET NO.</td></tr><tr><td colspan="2">DRAFT WHERE APPLICABLE</td></tr><tr><td colspan="2">MUST REMAIN WITHIN DIMENSIONS</td></tr><tr><td colspan="2">THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION</td></tr></table>																				SEE SHEET ONE	REV	DESCRIPTION	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)		SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION	REVISE ON CAD ONLY	mm	INCH	H			▽.0	4 PLACES	±.---	±.---	IN/MM	DRAWN BY	DATE	TITLE	3 PLACES	±.---	±.---	2 PLACES	±.---	±.---	1 PLACE	±.---	±.---				▽.0	ANGULAR ±1/2°		APPROVED BY	DATE	MATERIAL NO.	DOCUMENT NO.	SHEET NO.	DRAFT WHERE APPLICABLE		MUST REMAIN WITHIN DIMENSIONS		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION																																																																																																																																																																																																																																																																																																																																															
SEE SHEET ONE	REV	DESCRIPTION	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)		SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION	REVISE ON CAD ONLY																																																																																																																																																																																																																																																																																																																																																																																																									
				mm	INCH																																																																																																																																																																																																																																																																																																																																																																																																													
H			▽.0	4 PLACES	±.---	±.---	IN/MM	DRAWN BY	DATE	TITLE																																																																																																																																																																																																																																																																																																																																																																																																								
				3 PLACES	±.---	±.---																																																																																																																																																																																																																																																																																																																																																																																																												
				2 PLACES	±.---	±.---																																																																																																																																																																																																																																																																																																																																																																																																												
				1 PLACE	±.---	±.---																																																																																																																																																																																																																																																																																																																																																																																																												
			▽.0	ANGULAR ±1/2°		APPROVED BY	DATE	MATERIAL NO.	DOCUMENT NO.	SHEET NO.																																																																																																																																																																																																																																																																																																																																																																																																								
				DRAFT WHERE APPLICABLE																																																																																																																																																																																																																																																																																																																																																																																																														
				MUST REMAIN WITHIN DIMENSIONS																																																																																																																																																																																																																																																																																																																																																																																																														
				THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION																																																																																																																																																																																																																																																																																																																																																																																																														
<table><tr><td>to frame D.P.M.E.T Rev. C 2002/05/05</td><td>19</td><td>18</td><td>17</td><td>16</td><td>15</td><td>14</td><td>13</td><td>12</td><td>11</td><td>10</td><td>9</td><td>8</td><td>7</td><td>6</td><td>5</td><td>4</td><td>3</td><td>2</td><td>1</td></tr></table>																				to frame D.P.M.E.T Rev. C 2002/05/05	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1																																																																																																																																																																																																																																																																																																																																																																											
to frame D.P.M.E.T Rev. C 2002/05/05	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1																																																																																																																																																																																																																																																																																																																																																																																															

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А