



DETAIL A
KEY SLOTS #2 & #4 SHOWN
SCALE 2:1



| | | | | | | | | | | |
|---------------|---------------------------------------|------|------------|-------------|------------|----|---|---------------|--------------------|----------|
| spec ref | --- | dr | Stu Stoner | 2008/02/05 | projection | MM | size | A3 | scale | 1:1 |
| tolerance std | --- | eng | Tom Feng | 2014/09/24 | | | ecn no | ELX-N-18883-1 | rel level | Released |
| --- | TOLERANCES UNLESS OTHERWISE SPECIFIED | chr | - | - | | | | | | |
| surface | ✓ | appr | Delhy Liu | 2014/09/24 | | | title FINAL CABLE ASSEMBLY-ALTERNATE CABLE Mini SAS 2.0/SATA (CRKT) | | dwg no 10084749 | rev H |
| --- | linear | 0.X | ±0.3 | www.fci.com | cat. no. | - | Product - Customer Drw | sheet 1 of 6 | | |
| --- | angular | 0° | ±2° | | | | | | | |



KEY SLOT 2, 4 & 6
 ○ ◇ UNVERSIAL PORT



KEY SLOT 2 & 4
 ◇ OUT PORT



KEY SLOT 4 & 6
 ○ IN PORT

MINI SAS 2.0

| PRODUCT NUMBER SEE NOTE 4 | HUAWEI PART NUMBER | DESCRIPTION | GAUGE | "DIM L" LENGTH | END P1 KEY SLOT | END P2 KEY SLOT | IDENTIFIER |
|------------------------------|-----------------------|-----------------------|--------|-------------------|--------------------|--------------------|--|
| I0084749-M060002LF | / | X4 SAS CABLE ASSEMBLY | 24 AWG | 6M | 4, 6 | 4, 6 | SUBTRACTIVE ROUTING (IN PORT), SAS |
| I0084749-N040002LF | / | X4 SAS CABLE ASSEMBLY | 26 AWG | 4M | 4, 6 | 4, 6 | |
| I0084749-N050002LF | / | X4 SAS CABLE ASSEMBLY | 26 AWG | 5M | 4, 6 | 4, 6 | |
| I0084749-P010002LF | / | X4 SAS CABLE ASSEMBLY | 28 AWG | 1M | 4, 6 | 4, 6 | |
| I0084749-P020002LF | / | X4 SAS CABLE ASSEMBLY | 28 AWG | 2M | 4, 6 | 4, 6 | |
| I0084749-P030002LF | / | X4 SAS CABLE ASSEMBLY | 28 AWG | 3M | 4, 6 | 4, 6 | |
| I0084749-M060003LF | / | X4 SAS CABLE ASSEMBLY | 24 AWG | 6M | 2, 4, 6 | 2, 4, 6 | UNIVERSAL KEY, SAS |
| I0084749-N030003LF | / | X4 SAS CABLE ASSEMBLY | 26 AWG | 3M | 2, 4, 6 | 2, 4, 6 | |
| I0084749-N040003LF | / | X4 SAS CABLE ASSEMBLY | 26 AWG | 4M | 2, 4, 6 | 2, 4, 6 | |
| I0084749-N050003LF | / | X4 SAS CABLE ASSEMBLY | 26 AWG | 5M | 2, 4, 6 | 2, 4, 6 | |
| I0084749-P002503LF | / | X4 SAS CABLE ASSEMBLY | 28 AWG | 0.25M | 2, 4, 6 | 2, 4, 6 | |
| I0084749-P010003LF | / | X4 SAS CABLE ASSEMBLY | 28 AWG | 1M | 2, 4, 6 | 2, 4, 6 | |
| I0084749-P015003LF | / | X4 SAS CABLE ASSEMBLY | 28 AWG | 1.5M | 2, 4, 6 | 2, 4, 6 | |
| I0084749-P020003LF | / | X4 SAS CABLE ASSEMBLY | 28 AWG | 2M | 2, 4, 6 | 2, 4, 6 | |
| I0084749-P025003LF | / | X4 SAS CABLE ASSEMBLY | 28 AWG | 2.5M | 2, 4, 6 | 2, 4, 6 | |
| I0084749-P030003LF | / | X4 SAS CABLE ASSEMBLY | 28 AWG | 3M | 2, 4, 6 | 2, 4, 6 | |
| I0084749-M060006LF | / | X4 SAS CABLE ASSEMBLY | 24 AWG | 6M | 2, 4 | 4, 6 | SAS, TABLE ROUTING (OUT PORT), TO SUBTRACTIVE ROUTING (IN PORT) |
| I0084749-N010006LF | / | X4 SAS CABLE ASSEMBLY | 26 AWG | 1M | 2, 4 | 4, 6 | |
| I0084749-N030006LF | / | X4 SAS CABLE ASSEMBLY | 26 AWG | 3M | 2, 4 | 4, 6 | |
| I0084749-N040006LF | / | X4 SAS CABLE ASSEMBLY | 26 AWG | 4M | 2, 4 | 4, 6 | |
| I0084749-N050006LF | / | X4 SAS CABLE ASSEMBLY | 26 AWG | 5M | 2, 4 | 4, 6 | |
| I0084749-P010006LF | 0405G005 | X4 SAS CABLE ASSEMBLY | 28 AWG | 1M | 2, 4 | 4, 6 | |
| I0084749-P020006LF | / | X4 SAS CABLE ASSEMBLY | 28 AWG | 2M | 2, 4 | 4, 6 | |
| I0084749-P030006LF | 0405G003 | X4 SAS CABLE ASSEMBLY | 28 AWG | 3M | 2, 4 | 4, 6 | |

MINI SAS 2.0 KEYING OPTIONS

| | | | | | | | | | | | |
|---------------|---------------------------------------|-------------|------------|--------------------------|--------------------------------------|------------------------|----------|-----------------|-----------|------------------------|--------------|
| spec ref | --- | dr | Stu Stoner | 2008/02/05 | projection | MM | size | A3 | scale | 1:1 | |
| tolerance std | --- | eng | Tom Feng | 2014/09/24 | | | ecn no | ELX-N-18883-1 | rel level | Released | |
| --- | TOLERANCES UNLESS OTHERWISE SPECIFIED | chr | - | - | | | | | | | |
| surface | ✓ | appr | Delhy Liu | 2014/09/24 | product family | MiniSAS/SATA | dwg no | | 10084749 | rev | H |
| linear | 0.X ±0.3 | | | title | FINAL CABLE ASSEMBLY-ALTERNATE CABLE | | cat. no. | | - | Product - Customer Drw | sheet 2 of 6 |
| linear | 0.XX ±0.10 | www.fci.com | | Mini SAS 2.0/SATA (CRKT) | | Product - Customer Drw | | STATUS:Released | | Printed: Sep 24, 2014 | |
| linear | 0.XXX ±0.050 | | | | | | | | | | |
| angular | 0° ±2° | | | | | | | | | | |

SATA

| PRODUCT NUMBER SEE NOTE 4 | DESCRIPTION | GAUGE | "DIM L" LENGTH | END P1 KEY SLOT | END P2 KEY SLOT | IDENTIFIER |
|------------------------------|------------------------|--------|-------------------|--------------------|--------------------|---------------|
| 10084749-M060004LF | X4 SATA CABLE ASSEMBLY | 24 AWG | 6M | 1,4 | 1,4 | X CABLE, SATA |
| 10084749-N020004LF | X4 SATA CABLE ASSEMBLY | 26 AWG | 2M | 1,4 | 1,4 | |
| 10084749-N040004LF | X4 SATA CABLE ASSEMBLY | 26 AWG | 4M | 1,4 | 1,4 | |
| 10084749-N050004LF | X4 SATA CABLE ASSEMBLY | 26 AWG | 5M | 1,4 | 1,4 | |
| 10084749-P010004LF | X4 SATA CABLE ASSEMBLY | 28 AWG | 1M | 1,4 | 1,4 | |
| 10084749-P030004LF | X4 SATA CABLE ASSEMBLY | 28 AWG | 3M | 1,4 | 1,4 | |
| 10084749-M060005LF | X4 SATA CABLE ASSEMBLY | 24 AWG | 6M | 7 | 7 | M CABLE, SATA |
| 10084749-N020005LF | X4 SATA CABLE ASSEMBLY | 26 AWG | 2M | 7 | 7 | |
| 10084749-N040005LF | X4 SATA CABLE ASSEMBLY | 26 AWG | 4M | 7 | 7 | |
| 10084749-N050005LF | X4 SATA CABLE ASSEMBLY | 26 AWG | 5M | 7 | 7 | |
| 10084749-P010005LF | X4 SATA CABLE ASSEMBLY | 28 AWG | 1M | 7 | 7 | |
| 10084749-P030005LF | X4 SATA CABLE ASSEMBLY | 28 AWG | 3M | 7 | 7 | |



**BEND RADIUS
(24 AWG SHOWN)**

| CABLE | DIM "A" | DIM "B" |
|--------|---------|-----------|
| 24 AWG | (R46.9) | (Ø 9.5mm) |
| 26 AWG | (R41.7) | (Ø 8.3mm) |
| 28 AWG | (R37.7) | (Ø 7.6mm) |



KEY SLOT 1 & 4
X CABLE, SATA



KEY SLOT 7
M CABLE, SATA

SATA KEYING OPTIONS

| | | | | | | | | | | |
|---------------|---------------------------------------|-------|------------|-------------|------------|----|------------------------|---------------|-----------|----------|
| spec ref | --- | dr | Stu Stoner | 2008/02/05 | projection | MM | size | A3 | scale | 1:1 |
| tolerance std | --- | eng | Tom Feng | 2014/09/24 | | | ecn no | ELX-N-18883-1 | rel level | Released |
| --- | TOLERANCES UNLESS OTHERWISE SPECIFIED | chr | - | --- | | | | | | |
| surface | ✓ | appr | Delhly Liu | 2014/09/24 | | | dwg no | 10084749 | rev | H |
| --- | linear | 0.X | ±0.3 | www.fci.com | cat. no. | - | Product - Customer Drw | sheet 3 of 6 | | |
| | | 0.XX | ±0.10 | | | | | | | |
| | | 0.XXX | ±0.050 | | | | | | | |
| | angular | 0° | ±2° | | | | | | | |

A

B

C

D

A

B

C

D

WIRING LIST SEE NOTE 7



| | | | | | |
|----|-------|-----|---|-----|-------|
| | GND | A1 | — | B1 | GND |
| | Rx 0+ | A2 | ← | B2 | Tx 0+ |
| | Rx 0- | A3 | ← | B3 | Tx 0- |
| | GND | A4 | — | B4 | GND |
| | Rx 1+ | A5 | ← | B5 | Tx 1+ |
| | Rx 1- | A6 | ← | B6 | Tx 1- |
| | GND | A7 | — | B7 | GND |
| | Rx 2+ | A8 | ← | B8 | Tx 2+ |
| | Rx 2- | A9 | ← | B9 | Tx 2- |
| | GND | A10 | — | B10 | GND |
| | Rx 3+ | A11 | ← | B11 | Tx 3+ |
| | Rx 3- | A12 | ← | B12 | Tx 3- |
| | GND | A13 | — | B13 | GND |
| P1 | GND | B1 | — | A1 | GND |
| | Tx 0+ | B2 | → | A2 | Rx 0+ |
| | Tx 0- | B3 | → | A3 | Rx 0- |
| | GND | B4 | — | A4 | GND |
| | Tx 1+ | B5 | → | A5 | Rx 1+ |
| | Tx 1- | B6 | → | A6 | Rx 1- |
| | GND | B7 | — | A7 | GND |
| | Tx 2+ | B8 | → | A8 | Rx 2+ |
| | Tx 2- | B9 | → | A9 | Rx 2- |
| | GND | B10 | — | A10 | GND |
| | Tx 3+ | B11 | → | A11 | Rx 3+ |
| | Tx 3- | B12 | → | A12 | Rx 3- |
| | GND | B13 | — | A13 | GND |
| | | | | | P2 |



Copyright FCI.

| | | | | | | | | | | |
|---------------|---------------------------------------|-------------|------------|--|------------------------|-----------------|--------------|---------------|-----------|----------|
| spec ref | --- | dr | Stu Stoner | 2008/02/05 | projection | MM | size | A3 | scale | 1:1 |
| tolerance std | --- | eng | Tom Feng | 2014/09/24 | | | ecn no | ELX-N-18883-1 | rel level | Released |
| --- | TOLERANCES UNLESS OTHERWISE SPECIFIED | chr | - | - | | | | | | |
| surface | ✓ | appr | Delhy Liu | 2014/09/24 | product family | MiniSAS/SATA | | | | |
| linear | 0.X ±0.3 | | | title FINAL CABLE ASSEMBLY-ALTERNATE CABLE Mini SAS 2.0/SATA (CRKT) | | dwg no 10084749 | | rev H | | |
| | 0.XX ±0.10 | | | | | | | | | |
| | 0.XXX ±0.050 | | | | | | | | | |
| angular | 0° ±2° | www.fci.com | cat. no. | - | Product - Customer Drw | | sheet 4 of 6 | | | |

NOTES:

- ① - MATERIAL:
 BACK SHELLS: ZINC DIECAST
 PULL TAB: MOLDED THERMOPLASTIC
 LATCH: STAINLESS STEEL
 JET MELT: POLYAMIDE POLYMER
- 2 - ELECTRICAL PERFORMANCE PER CURRENT REVISION
 OF SERIAL ATA, T10/I760-D (SAS-2 REQUIREMENTS).
- ③ - THIS PRODUCT MEETS THE RESTRICTION OF HAZARDOUS SUBSTANCES IN
 ELECTRICAL AND ELECTRONIC EQUIPMENT (RoHS) DIRECTIVE (2002/95/EC)

4 - PART NUMBER DESCRIPTION

10084749 - X XX XX XX LF



- ⑤ - UNLESS OTHERWISE SPECIFIED ASSEMBLED LENGTH TOLERANCE IS TO BE:
 < 1 METER = $\pm 25.0\text{mm}$
 > 1 METER TO 6 METERS = $\pm 2\%$ OF "DIM L"

| | | | | | | | | | | |
|---------------|---------------------------------------|-------------|------------|--------------------------------------|------------|------------------------|----------------|--------------|---------------|-----|
| spec ref | --- | dr | Stu Stoner | 2008/02/05 | projection | MM | size | A3 | scale | 1:1 |
| tolerance std | --- | eng | Tom Feng | 2014/09/24 | | | ecn no | | ELX-N-18883-1 | |
| --- | TOLERANCES UNLESS OTHERWISE SPECIFIED | chr | - | - | | | product family | MiniSAS/SATA | rel level | |
| surface | ✓ | appr | Delhy Liu | 2014/09/24 | title | | dwg no | | rev | |
| --- | linear | www.fci.com | | FINAL CABLE ASSEMBLY-ALTERNATE CABLE | | 10084749 | | H | | |
| | angular | | | Mini SAS 2.0/SATA (CRKT) | | | | | | |
| | | | | cat. no. | | Product - Customer Drw | | sheet 5 of 6 | | |



Copyright FCI.

NOTES CONTINUED:

- ⑥ - UNLESS OTHERWISE SPECIFIED LABEL POSITION IS TO BE 100mm FROM REAR OF CONNECTOR.
LABEL DETAILS:



FONT SHALL BE CLEARLY VISIBLE AND BLACK IN COLOR.

- ⑦ - ALL CABLE ASSEMBLIES SHALL BE 100% TESTED FOR CONTINUITY AS DEFINED IN WIRING LIST.
- ⑧ - UNLESS OTHERWISE SPECIFIED ALL CABLE ASSEMBLIES SHALL BE 100% HI-POT TESTED BY APPLYING 300V DC FOR A MINIMUM OF 10ms, UNLESS ACTIVE COMPONENTS ARE USED IN THIS ASSEMBLY.
- 9 - OTHER TESTING PERFORMED AS REQUIRED BY PRODUCT SPECIFICATION: GS-12-548.
- 10 - PACKAGING OF LEAD FREE PRODUCTS MEETS LABELING AND PACKAGING PER SPECIFICATION GS-14-920. PACKAGE CABLE ASSEMBLIES PER GS-14-1272. ADD DUST COVER ON MINI-SAS CONNECTOR WHEN PACKAGE FOR SHIPPMENT NEED STICK BELOW LABEL ON PE BAG.



11. THIS DIMENSION IS A FINISHED PRODUCT LENGTH.

12. A "△" SYMBOL WILL BE NEXT TO ANY DIMENSION, VIEW, OR NOTE WHICH HAS BEEN MODIFIED WITH THE CURRENT DRAWING REVISION. THE CURRENT REVISION WILL BE SHOWN IN THE SYMBOL.

| | | | | | | | | | | | | | | | | | | | |
|---------------|--|-------|------------|------------|------------|------|------------------------|---------------|-----------|----------|---------|----|-----|--|---|--------------------|----------|--|--|
| spec ref | --- | dr | Stu Stoner | 2008/02/05 | projection | MM | size | A3 | scale | 1:1 | | | | | | | | | |
| tolerance std | TOLERANCES UNLESS OTHERWISE SPECIFIED | eng | Tom Feng | 2014/09/24 | | | ecn no | ELX-N-18883-1 | | | | | | | | | | | |
| --- | | chr | - | - | | | product family | MiniSAS/SATA | rel level | Released | | | | | | | | | |
| surface | <table border="1"> <tr> <td rowspan="3">✓</td> <td rowspan="3">linear</td> <td>0.X</td> <td>±0.3</td> </tr> <tr> <td>0.XX</td> <td>±0.10</td> </tr> <tr> <td>0.XXX</td> <td>±0.050</td> </tr> <tr> <td>---</td> <td>angular</td> <td>0°</td> <td>±2°</td> </tr> </table> | ✓ | linear | 0.X | ±0.3 | 0.XX | ±0.10 | 0.XXX | ±0.050 | --- | angular | 0° | ±2° | | title FINAL CABLE ASSEMBLY-ALTERNATE CABLE Mini SAS 2.0/SATA (CRKT) | dwg no 10084749 | rev H | | |
| ✓ | linear | | | 0.X | ±0.3 | | | | | | | | | | | | | | |
| | | | | 0.XX | ±0.10 | | | | | | | | | | | | | | |
| | | 0.XXX | ±0.050 | | | | | | | | | | | | | | | | |
| --- | angular | 0° | ±2° | | | | | | | | | | | | | | | | |
| --- | | appr | Delhy Liu | 2014/09/24 | cat. no. | - | Product - Customer Drw | sheet 6 of 6 | | | | | | | | | | | |



Copyright FCI.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А