

SMPS Molded Radial MLC Capacitors



SXP Style for High Temperature Applications up to 200°C



SXP-style, encapsulated radial leaded MLC capacitors are ideally suited for high temperature applications up to 200°C. This product is intended for downhole oil exploration, including logging while drilling, geophysical probes, as well as space, aerospace and hybrid automotive applications. This product supplements the SMX family of capacitors and offers mechanical protection to the ceramic element in extreme harsh environment. The high temperature solder utilized in the construction of SXP-style parts assures reliable operation in high temperature and rugged environments. The SXP-style capacitors are ideally suited for applications as DC filters in high power, high frequency motor drives, high pulsed-current circuitry, as well as standard electronic equipment designed for high temperature applications.

SXP-style, switch mode power supply capacitors are characterized with excellent performance. The main benefits of SXP product include:

- Low ESR, low ESL
- Low DC leakage
- Excellent high frequency performance

Not RoHS Compliant

HOW TO ORDER

| | | | | | | | |
|------------------|-------------------------------------|--|--|---|--|-----------------------------------|--|
| SXP | 3 | 1 | C | 104 | M | A | A |
| AVX Style | Size See Dimensions chart | Voltage Code 50V = 5 100V = 1 200V = 2 500V = 7 1000V = A 1500V = S 2000V = G 3000V = H | Temperature Coefficient COG = A VHT = C | Capacitance Code (2 significant digits + number of zeros) 100 pF = 101 22,000 pF = 223 1µF = 105 | Capacitance Tolerance COG: J = ±5% K = ±10% M = ±20% X7R: J = ±5% K = ±10% M = ±20% Z = +80%, -20% | Test Level A = Standard | Leads A = Standard Sn/Pb (min. 5% Pb) |
| | | | | | Tighter tolerances available upon request | | |

ELECTRICAL SPECIFICATIONS

Temperature Coefficient

COG: A Temperature Coefficient 0 ±30 ppm/°C, -55° to +200°C
 VHT: C Temperature Coefficient ±15%, -55°C to +125°C
 +15% - 56%, -55°C to +200°C

Capacitance Test (MIL-STD-202 Method 305)
 25°C, 1.0±0.2 Vrms (open circuit voltage) at 1KHz

Dissipation Factor 25°C

COG: 0.15% Max @ 25°C, 1.0±0.2 Vrms (open circuit voltage) at 1KHz
 X7R/X9U: 2.5% Max @ 25°C, 1.0±0.2 Vrms (open circuit voltage) at 1KHz

Insulation Resistance 25°C

(MIL-STD-202 Method 302)
 100K MΩ or 1000 MΩ-µF, whichever is less.

Insulation Resistance 125°C

(MIL-STD-202 Method 302)
 10K MΩ or 100 MΩ-µF, whichever is less.

Insulation Resistance 200°C

(MIL-STD-202 Method 302)
 1k MΩ or 10 MΩ -µF, whichever is less.

Dielectric Withstanding Voltage 25°C

(Flash Test)
 250% rated voltage for 5 seconds with 50 mA max charging current. (150% for 500 VDC and 120% for 1000 VDC and higher voltage ratings)



SMPS Molded Radial MLC Capacitors



SXP Style for High Temperature Applications up to 200°C

STYLE



DIMENSIONS

millimeters (inches)

| AVX Style | Length (L) ±0.25 (±0.010) | Height (H) ±0.25 (±0.010) | Thickness (T) ±0.25 (±0.010) | Lead Spacing ±0.76 (±0.030) | LD ±0.05 (±0.002) |
|-----------|------------------------------|------------------------------|---------------------------------|--------------------------------|----------------------|
| SXP1 | 8.9 (0.350) | 8.9 (0.350) | 5.08 (0.200) | 5.08 (0.200) | 0.51 (0.020) |
| SXP2 | 11.4 (0.450) | 11.4 (0.450) | 5.08 (0.200) | 5.08 (0.200) | 0.51 (0.020) |
| SXP3 | 12.7 (0.500) | 12.7 (0.500) | 5.08 (0.200) | 10.2 (0.400) | 0.64 (0.025) |
| SXP4 | 22.4 (0.880) | 16.3 (0.640) | 5.84 (0.230) | 19.8 (0.780) | 0.81 (0.032) |

CAPACITANCE RANGE

COG

| Style | 50V | 100V | 200V | 500V | 1000V | 1500V | 2000V | 3000V |
|------------|--------|--------|--------|--------|--------|--------|--------|--------|
| SXP1 (MIN) | 1000pF | 1000pF | 1000pF | 100pF | 100pF | 100pF | 100pF | 100pF |
| SXP1 (MAX) | .047μF | .027μF | 8200pF | 4700pF | 2200pF | 1000pF | 560pF | 270pF |
| SXP2 (MIN) | .01μF | 1000pF | 1000pF | 100pF | 100pF | 100pF | 100pF | 100pF |
| SXP2 (MAX) | .10μF | .056μF | .018μF | 8200pF | 4700pF | 1800pF | 1200pF | 560pF |
| SXP3 (MIN) | .01μF | 1000pF | 1000pF | 1000pF | 1000pF | 100pF | 100pF | 100pF |
| SXP3 (MAX) | .15μF | .068μF | .022μF | .012μF | 6800pF | 2700pF | 1500pF | 1000pF |
| SXP4 (MIN) | .01μF | .01μF | 1000pF | 1000pF | 1000pF | 1000pF | 100pF | 100pF |
| SXP4 (MAX) | .39μF | .22μF | .068μF | .033μF | .018μF | 8200pF | 4700pF | 2700pF |

VHT

| Style | 50V | 100V | 200V | 500V | 1000V | 1500V | 2000V | 3000V |
|------------|-------|-------|-------|-------|--------|--------|--------|--------|
| SXP1 (MIN) | .1μF | .01μF | .01μF | .01μF | .01μF | .01μF | 1000pF | 1000pF |
| SXP1 (MAX) | 1.5μF | 1.0μF | .33μF | .12μF | .056μF | .022μF | .012μF | 4700pF |
| SXP2 (MIN) | .1μF | .1μF | .01μF | .01μF | .01μF | .01μF | .01μF | 1000pF |
| SXP2 (MAX) | 2.7μF | 1.8μF | .68μF | .27μF | .10μF | .056μF | .022μF | 8200pF |
| SXP3 (MIN) | .01μF | .1μF | .01μF | .01μF | .01μF | .01μF | .01μF | .01μF |
| SXP3 (MAX) | 3.9μF | 2.7μF | 1.0μF | .33μF | .15μF | .082μF | .033μF | .015μF |
| SXP4 (MIN) | 1μF | .1μF | .1μF | .01μF | .01μF | .01μF | .01μF | .01μF |
| SXP4 (MAX) | 12μF | 8.2μF | 2.7μF | 1.0μF | .47μF | .22μF | .10μF | .039μF |

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «**JONHON**», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «**FORSTAR**».



JONHON

«**JONHON**» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«**FORSTAR**» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А