


## 1172A Multi-Conductor - Four-Conductor Star Quad, Low-Impedance Cable



For more Information  
please call

1-800-Belden1



### General Description:

26 AWG stranded (30x40) high-conductivity BC conductors, polyethylene insulation, tinned copper "French Braid" shield (95% coverage), BC drain wire, PVC jacket.

### Physical Characteristics (Overall)

#### Conductor

AWG:

# Conductors	AWG	Stranding	Conductor Material	Dia. (in.)
4	26	30x40	SBC - Soft Bare Copper	.021

Total Number of Conductors: 4

#### Insulation

Insulation Material:

Insulation Material	Dia. (in.)
PE - Polyethylene	.045

#### Outer Shield

Outer Shield Material:

Type	Outer Shield Material	Coverage (%)
French Braid	TC - Tinned Copper	95

Outer Shield Drain Wire AWG:

AWG	Stranding	Drain Wire Conductor Material
28	Stranded	BC - Bare Copper

#### Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

#### Overall Cable

Overall Cabling Color Code Chart:

Number	Color
1	Blue
2	White
3	Blue w/White Stripe
4	White w/Blue Stripe

Overall Nominal Diameter: 0.190 in.

### Mechanical Characteristics (Overall)

Operating Temperature Range: -20°C To +60°C

Non-UL Temperature Rating: 60°C

Bulk Cable Weight: 25 lbs/1000 ft.

Max. Recommended Pulling Tension: 37 lbs.

Min. Bend Radius/Minor Axis: 2 in.

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

EU Directive 2011/65/EU (ROHS II): Yes

EU CE Mark: No

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 01/01/2004

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

## 1172A Multi-Conductor - Four-Conductor Star Quad, Low-Impedance Cable

CA Prop 65 (CJ for Wire & Cable):	Yes
MIL Order #39 (China RoHS):	Yes
<b>Plenum/Non-Plenum</b>	
Plenum (Y/N):	No

### Electrical Characteristics (Overall)

**Nom. Characteristic Impedance:**

Impedance (Ohm)  
40

**Nom. Inductance:**

Inductance (µH/ft)  
.21

**Nom. Capacitance Conductor to Conductor:**

Capacitance (pF/ft)  
39.2

**Nom. Cap. Between Cond. in a Quad Config.:**

Capacitance (pF/ft)  
57.4

**Nominal Velocity of Propagation:**

VP (%)  
66

**Nom. Conductor DC Resistance:**

DCR @ 20°C (Ohm/1000 ft)  
36

**Nominal Outer Shield DC Resistance:**

DCR @ 20°C (Ohm/1000 ft)  
6.8

**Max. Operating Voltage - UL:**

Voltage  
100 V RMS

**Max. Recommended Current:**

Current  
1.9 Amps per conductor @ 25°C

**Other Electrical Characteristic 1:** 2/c 23 AWG equivalent DCR when connected to a 3-pin XLR

### Notes (Overall)

**Notes:** Quad connection scheme: The two blue wires (or wires directly opposite one another) are connected together to form one conductor, and similarly the two white wires (or remaining wires) are connected together to form the second conductor.

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
1172A B591000	1,000 FT	26.000 LB	BLACK, MATTE	C	4 #26 PE FBRD PVC
1172A B59500	500 FT	13.500 LB	BLACK, MATTE		4 #26 PE FBRD PVC
1172A G7V1000	1,000 FT	26.000 LB	RED, MATTE		4 #26 PE FBRD PVC
1172A G7W1000	1,000 FT	26.000 LB	GREEN, MATTE		4 #26 PE FBRD PVC
1172A G7X1000	1,000 FT	26.000 LB	BLUE, MATTE		4 #26 PE FBRD PVC
1172A G7Y1000	1,000 FT	26.000 LB	WHITE, MATTE		4 #26 PE FBRD PVC
1172A G8M1000	1,000 FT	26.000 LB	YELLOW, MATTE		4 #26 PE FBRD PVC
1172A U901000	1,000 FT	26.000 LB	GRAY, MATTE		4 #26 PE FBRD PVC

**Notes:**  
C = CRATE REEL PUT-UP.

Revision Number: 2    Revision Date: 10-04-2012

© 2015 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the

1172A Multi-Conductor - Four-Conductor Star Quad, Low-Impedance Cable

product.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А