MAX336/MAX337

16-Channel/Dual 8-Channel, Low-Leakage, CMOS Analog Multiplexers

General Description

The MAX336/MAX337 are monolithic, CMOS analog multiplexers (muxes). The 16-channel MAX336 is designed to connect one of 16 inputs to a common output by control of a 4-bit binary address. The dual, 8-channel MAX337 is designed to connect one of eight inputs to a common output by control of a 3-bit binary address. Both devices can be used as either a mux or a demux. On-resistance is 400Ω (max), and the devices conduct current equally well in both directions.

These muxes feature extremely low off leakages (less than 20pA at +25°C) and on-channel leakages (less than 50pA at +25°C). The new design offers guaranteed low charge injection (3.5pC, typ) and electrostatic discharge (ESD) protection greater than 2000V, per method 3015.7. These improved muxes are pin-compatible upgrades for the industry-standard DG506 and DG507.

The MAX336/MAX337 operate from a single +4.5V to +30V supply or from dual ±4.5V to ±20V supplies. All control inputs (whether address or enable) are TTL compatible (0.8V to 2.4V) over the full specied temperature range and over the ±4.5V to ±18V supply range.

Applications

- Precision Data Acquisition
- Precision Signal Routing
- Test Equipment

Benefits and Features

- < 400Ω (max) On-Resistance
- < 500ns Transition Time
- < 10Ω On-Resistance Match
- < 20pA NO-Off Leakage Current at +25°C
- 3.5pC Charge Injection
- +4.5V to +30V Single Supply
  ±4.5V to ±20V Dual Supplies
- Plug-In Upgrade for Industry-Standard DG506/DG507
- Bidirectional Rail-to-Rail® Signal Handling
- TTL/CMOS-Logic Compatible
- > 2000V ESD Protection, per Method 3015.7

Ordering Information

PART	TEMP- RANGE	PIN-PACKAGE
MAX336CPI+	0°C to +70°C	28 Plastic DIP
MAX336CWI+	0°C to +70°C	28 Wide SO
MAX336CAI+	0°C to +70°C	28 SSOP
MAX336C/D	0°C to +70°C	Dice*

Ordering Information **appears at end of data sheet.**

** Contact factory for dice specications.*

+Denotes lead(Pb)-free/RoHS-compliant package.

Pin Configurations/Functional Diagrams/Truth Tables



DIP/SO/SSOP/TSSOP

N.C. = NO INTERNAL CONNECTION



MAX336 16-CHANNEL SINGLE-ENDED MULTIPLEXER

MAX336					
A3	A2	A1	A0	EN	ON SWITCH
X	X	X	X	0	NONE
0	0	0	0	1	1
0	0	0	1	1	2
0	0	1	0	1	3
0	0	1	1	1	4
0	1	0	0	1	5
0	1	0	1	1	6
0	1	1	0	1	7
0	1	1	1	1	8
1	0	0	0	1	9
1	0	0	1	1	10
1	0	1	0	1	11
1	0	1	1	1	12
1	1	0	0	1	13
1	1	0	1	1	14
1	1	1	0	1	15
1	1	1	1	1	16

LOGIC "0" = $V_{AL} \leq 0.8V$, LOGIC "1" = $V_{AH} \geq 2.4V$

Continued at end of data sheet.

Rail-to-Rail is a registered trademark of Nippon Motorola Ltd.

19-1193; Rev 1; 10/14

Absolute Maximum Ratings

Voltage Referenced to V-
V+..... -0.3V, 44V
GND..... -0.3V, 25V
Digital Inputs, A_, EN_, NO, COM
(Note 1).....(V- - 0.3V) to (V+ + 0.3V)
or 30mA (whichever occurs first)
Continuous Current (any terminal)..... 30mA
Peak Current, NO or COM
(pulsed at 1ms, 10% duty cycle max)..... 100mA
Continuous Power Dissipation (T_A = +70 °C)
Plastic DIP (derate 14.29mW/°C above +70°C)..... 1.14W
Plastic DIP (derate 14.30,W/°C above +70°C).....1142.90mW
TSSOP (derate 12.80mW/°C aboce +70°C).....1025.60mW
Wide SO (derate 12.50mW/°C above +70°C).....1.00W
SSOP (derate 9.10mW/°C above +70°C).....727.3mW
CERDIP (derate 16.67mW/°C above +70°C).....1.33W
Operating Temperature Ranges
MAX336C_I/MAX337C_I.....0°C to +70°C
MAX336E_I/MAX337E_I.....-40°C to +85°C
MAX336MJI/MAX337MJI.....-55°C to +125°C
Storage Temperature Range .....-65°C to +150°C
Lead Temperature (soldering, 10sec) .....+300°C
Soldering Temperature (reflow)..... +260°C

Note 1: Signals on any terminal exceeding V+ or V- are clamped by internal diodes. Limit forward current to maximum current rating.

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

Electrical Characteristics—Dual Supplies

(V+ = +15V, V- = -15V, GND = 0V, V_{AH} = +2.4V, V_{AL} = +0.8V, T_A = T_{MIN} to T_{MAX}, unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS				MIN	TYP (Note 2)	MAX	UNITS
SWITCH									
Analog Signal Range	V_{NO}, V_{COM}	(Note 3)				-15		15	V
On-Resistance	R_{ON}	I_{NO} = 0.2mA, V_{COM} = ±10V		T_A = +25 °C			220	400	Ω
				T_A = T_{MIN} to T_{MAX}				500	
On-Resistance Matching Between Channels	ΔR_{ON}	I_{NO} = 0.2mA, V_{COM} = ±10V (Note 4)		T_A = +25 °C			5	10	Ω
				T_A = T_{MIN} to T_{MAX}				15	
NO-Off Leakage Current (Note 5)	$I_{NO(OFF)}$	V_{COM} = ±10V, V_{NO} = ±10V, V_{EN} = 0V		T_A = +25 °C		-0.02	0.001	0.02	nA
				T_A = T_{MIN} to T_{MAX}	C, E	-1.25		1.25	
					M	-20		20	
COM-Off Leakage Current (Note 5)	$I_{COM(OFF)}$	V_{NO} =±10V, V_{COM} = ±10V, V_{EN} = 0V	MAX336	T_A = +25 °C		-0.05		0.05	nA
				T_A = T_{MIN} to T_{MAX}	C, E	-6.5		6.5	
					M	-80		80	
		V_{NO} = ±10V, V_{COM} = ±10V, V_{EN} = 0V	MAX337	T_A = +25 °C		-0.05		0.05	
				T_A = T_{MIN} to T_{MAX}	C, E	-3.25		3.25	
					M	-40		40	
COM-On Leakage Current (Note 5)	$I_{COM(ON)}$	V_{COM} = ±10V, V_{NO} = ±10V, sequence each switch on	MAX336	T_A = +25 °C		-0.05		0.05	nA
				T_A = T_{MIN} to T_{MAX}	C, E	-6.5		6.5	
					M	-80		80	
			MAX337	T_A = +25 °C		-0.05		0.05	
				T_A = T_{MIN} to T_{MAX}	C, E	-3.25		3.25	
					M	-40		40	

Electrical Characteristics—Dual Supplies (continued)

(V+ = +15V, V- = -15V, GND = 0V, V_{AH} = +2.4V, V_{AL} = +0.8V, T_A = T_{MIN} to T_{MAX}, unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS		MIN	TYP (Note 2)	MAX	UNITS
INPUT							
Input Current with Input Voltage High	I_{AH}	V_A = 2.4V or 15V		-1.0	0.001	1.0	µA
Input Current with Input Voltage Low	I_{AL}	V_{EN} = 0V or 2.4V, V_A = 0V		-1.0		1.0	µA
SUPPLY							
Power-Supply Range				±4.5		±20	V
Positive Supply Current	I+	V_{EN} = V_A = 0V	T_A = +25°C	-1	0.01	1	µA
			T_A = T_{MIN} to T_{MAX}	-10		10	
		V_{EN} = 2.4V, $V_{A(ALL)}$ = 2.4V	T_A = +25°C		400	700	
			T_A = T_{MIN} to T_{MAX}			1100	
Negative Supply Current	I-	V_{EN} = 0V or 2.4V; $V_{A(ALL)}$ = 0V, 2.4V, or 5V	T_A = +25°C	-1		1	µA
			T_A = T_{MIN} to T_{MAX}	-10		10	
DYNAMIC							
Transition Time	t_{TRANS}	Figure 2, T_A = +25°C			200	500	ns
Break-Before-Make Interval	t_{OPEN}	Figure 4, T_A = +25°C		10	50		ns
Enable Turn-On Time	$t_{ON(EN)}$	Figure 3	T_A = +25°C		250	500	ns
			T_A = T_{MIN} to T_{MAX}			750	
Enable Turn-Off Time	$t_{OFF(EN)}$	Figure 3	T_A = +25°C		100	500	ns
			T_A = T_{MIN} to T_{MAX}			750	
Charge Injection (Note 3)	Q	C_L = 100pF, V_{NO} = 0V, R_S = 0Ω, Figure 6, T_A = +25°C			3.5	10	pC
Off Isolation (Note 6)	V_{ISO}	V_{EN} = 0V, R_L = 1kΩ, f = 100kHz, T_A = +25°C			-82		dB
Crosstalk Between Channels	V_{CT}	V_{EN} = 2.4V, f = 100kHz, V_{GEN} = 1Vp-p, R_L = 1kΩ, Figure 7, T_A = +25°C			-86		dB
Logic Input Capacitance	C_{IN}	f = 1MHz, T_A = +25°C			2		pF
NO-Off Capacitance	$C_{NO(OFF)}$	f = 1MHz, V_{EN} = V_{NO} = 0V, Figure 8, T_A = +25°C			2		pF
COM-Off Capacitance	$C_{COM(OFF)}$	f = 1MHz, V_{EN} = 0.8V, V_{COM} = 0V, Figure 8, T_A = +25°C	MAX336		20		pF
			MAX337		10		
COM-On Capacitance	$C_{COM(ON)}$	f = 1MHz, V_{EN} = 2.4V, V_{COM} = 0V, Figure 8, T_A = +25°C	MAX336		22		pF
			MAX337		12		

Electrical Characteristics—Single Supply

(V+ = +12V, V- = 0V, GND = 0V, V_{AH} = +2.4V, V_{AL} = +0.8V, T_A = T_{MIN} to T_{MAX}, unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP (Note 2)	MAX	UNITS
SWITCH						
Analog Signal Range	V_{NO}, V_{COM}	(Note 3)	0		12	V
On-Resistance	R_{ON}	I_{NO} = 0.2mA, V_{COM} = 3V or 10V, T_A = +25°C		460	700	Ω
DYNAMIC						
Transition Time (Note 3)	t_{TRANS}	$V_{NO_}$ = ±5V, V_{IN} = 2.4V, Figure 1, T_A = +25°C		350	600	ns
Enable Turn-On Time (Note 3)	$t_{ON(EN)}$	V_{INH} = 2.4V, V_{INL} = 0V, V_{NO1} = 5V, Figure 3, T_A = +25°C		350	600	ns
Enable Turn-Off Time (Note 3)	$t_{OFF(EN)}$	V_{INH} = 2.4V, V_{INL} = 0V, V_{NO1} = 5V, Figure 3, T_A = +25°C		110	500	ns
Charge Injection (Note 3)	Q	C_L = 100pF, V_{NO} = 0V, R_S = 0Ω, T_A = +25°C		5.0	10	pC

Note 2: The algebraic convention where the most negative value is a minimum and the most positive value a maximum is used in this data sheet.
Note 3: Guaranteed by design.
Note 4: $\Delta R_{ON} = R_{ON(MAX)} - R_{ON(MIN)}$.
Note 5: Leakage parameters are 100% tested at the maximum rated hot temperature and guaranteed by correlation at T_A = +25°C.
Note 6: Worst-case isolation is on channel 4 because of its proximity to the drain pin. Off isolation = 20log V_{COM}/V_{NO}, where V_{COM} = output and V_{NO} = input to off switch.

Typical Operating Characteristics

(T_A = +25°C, unless otherwise noted.)

FREQUENCY RESPONSE



TOTAL HARMONIC DISTORTION vs. FREQUENCY



SUPPLY CURRENT vs. INPUT VOLTAGE



Typical Operating Characteristics (continued)

(T_A = +25°C, unless otherwise noted.)

ON-RESISTANCE vs. V_{COM}



ON-RESISTANCE vs. V_{COM} OVER TEMPERATURE (DUAL SUPPLIES)



ON-RESISTANCE vs. V_{COM} (SINGLE SUPPLY)



ON-RESISTANCE vs. V_{COM} OVER TEMPERATURE (SINGLE SUPPLY)



OFF LEAKAGE vs. TEMPERATURE



ON LEAKAGE vs. TEMPERATURE



CHARGE INJECTION vs. V_{COM}



SUPPLY CURRENT vs. TEMPERATURE



TRANSITION TIME vs. POWER SUPPLIES



Pin Description

PIN		NAME	FUNCTION
MAX336	MAX337		
1	1	V+	Positive Supply-Voltage Input
2, 3, 13	3, 13, 14	N.C.	No Internal Connection
—	2	COMB	Analog Signal B Output* (bidirectional)
4–11	—	NO16-NO9	Analog Signal Inputs* (bidirectional)
—	4–11	NO8B–NO1B	Analog Signal B Inputs* (bidirectional)
12	12	GND	Logic Ground
14–17	—	A3–A0	Logic Address Inputs
—	15, 16, 17	A2, A1, A0	Logic Address Inputs
18	18	EN	Logic Enable Input
19–26	—	NO1–NO8	Analog Signal Inputs* (bidirectional)
—	19–26	NO1A–NO8A	Analog Signal A Inputs* (bidirectional)
27	27	V-	Negative Supply-Voltage Input. Connect to GND for single-supply operation.
28	—	COM	Analog Signal Output* (bidirectional)
—	28	COMA	Analog Signal A Output* (bidirectional)

** Analog signal inputs and outputs are names of convenience only; they are identical and interchangeable.*

Applications Information

Operation with Supply Voltages Other than 15V

Using supply voltages less than ±15V will reduce the analog signal range. The MAX336/MAX337 switches operate with ±4.5V to ±20V bipolar supplies or with a +4.5V to +30V single supply. Connect V- to GND when operating with a single supply. Both device types can also operate with unbalanced supplies such as +24V and -5V. The *Typical Operating Characteristics* graphs show typical on-resistance with 20V, 15V, 10V, and 5V supplies. (Switching times increase by a factor of two or more for operation at 5V.)

Overvoltage Protection

Proper power-supply sequencing is recommended for all CMOS devices. Do not exceed the absolute maximum ratings, because stresses beyond the listed ratings may cause permanent damage to the devices. Always sequence V+ on first, then V-, followed by the logic inputs NO and COM. If power-supply sequencing is not possible, add two small signal diodes in series with supply pins for overvoltage protection (Figure 1). Adding diodes reduces the analog signal range to 1V below V+ and 1V above V-, but does not significantly affect the devices' low switch resistance and low leakage characteristics. Device operation is unchanged, and the difference between V+ and V- should not exceed 44V.



Figure 1. Overvoltage Protection Using External Blocking Diodes

Test Circuits/Timing Diagrams



Figure 2. Transition Time



Figure 3. Enable Switching Time

Test Circuits/Timing Diagrams (continued)



Figure 4. Break-Before-Make Interval



Figure 5. Charge Injection (V_{CTE})

Test Circuits/Timing Diagrams (continued)



Figure 6. Off Isolation



Figure 7. Crosstalk



Figure 8. NO/COM Capacitance

Pin Configurations/Functional Diagrams/Truth Tables (continued)



DIP/SO/SSOP/TSSOP



MAX337 8-CHANNEL DIFFERENTIAL MULTIPLEXER

MAX337				
A2	**A1**	**A0**	**EN**	**ON SWITCH**
X	X	X	0	NONE
0	0	0	1	1
0	0	1	1	2
0	1	0	1	3
0	1	1	1	4
1	0	0	1	5
1	0	1	1	6
1	1	0	1	7
1	1	1	1	8

LOGIC "0" = $V_{AL} \leq 0.8V$, LOGIC "1" = $V_{AH} \geq 2.4V$

Ordering Information (continued)

PART	TEMP- RANGE	PIN-PACKAGE
MAX336EPI+	-40° C to +85° C	28 Plastic DIP
MAX336EWI+	-40° C to +85° C	28 Wide SO
MAX336EAI+	-40° C to +85° C	28 SSOP
MAX336EJI	-40° C to +85° C	28 CERDIP**
MAX336MJI	-55° C to +125° C	28 CERDIP**
MAX337CPI+	0° C to +70° C	28 Plastic DIP
MAX337CWI+	0° C to +70° C	28 Wide SO
MAX337CAI+	0° C to +70° C	28 SSOP
MAX337C/D	0° C to +70° C	Dice*
MAX337EPI+	-40° C to +85° C	28 Plastic DIP
MAX337EWI+	-40° C to +85° C	28 Wide SO
MAX337EAI+	-40° C to +85° C	28 SSOP
MAX337EJI	-40° C to +85° C	28 CERDIP**
MAX337MJI	-55° C to +125° C	28 CERDIP**

** Contact factory for dice specications.*

*** Contact factory for availability.*

+ Denotes lead(Pb)-free/RoHS compliant package.

Chip Information

PROCESS: BiCMOS

Package Information

For the latest package outline information and land patterns (footprints), go to **www.maximintegrated.com/packages**. Note that a "+", "#", or "-" in the package code indicates RoHS status only. Package drawings may show a different suffix character, but the drawing pertains to the package regardless of RoHS status.

PACKAGE TYPE	PACKAGE CODE	OUTLINE NO.	LAND PATTERN NO.
28 Plastic DIP	P28+2	**21-0044**	—
28 SSOP	A28+1	**21-0056**	**90-0095**
28 TSSOP	U28+2	**21-0066**	**90-0171**
28 WIDE SO	W28+6	**21-0042**	**90-0109**

Revision History

REVISION NUMBER	REVISION DATE	DESCRIPTION	PAGES CHANGED
0	4/97	Initial release	—
1	10/14	Adding MAX336CUI/EUI to Ordering Information and adding TSSOP package	1, 2, 11, 12

For pricing, delivery, and ordering information, please contact Maxim Direct at 1-888-629-4642, or visit Maxim Integrated's website at www.maximintegrated.com.

Maxim Integrated cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim Integrated product. No circuit patent licenses are implied. Maxim Integrated reserves the right to change the circuitry and specifications without notice at any time. The parametric values (min and max limits) shown in the Electrical Characteristics table are guaranteed. Other parametric values quoted in this data sheet are provided for guidance.

Maxim Integrated and the Maxim Integrated logo are trademarks of Maxim Integrated Products, Inc. © 2014 Maxim Integrated Products, Inc.

OCEAN CHIPS
Океан Электроники
Поставка электронных компонентов

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «**JONHON**», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «**FORSTAR**».

AVIC JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).

FORSTAR®

Телефон: 8 (812) 309-75-97 (многоканальный)
Факс: 8 (812) 320-03-32
Электронная почта: ocean@oceanchips.ru
Web: http://oceanchips.ru/
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А