

Silicon carbide Power MOSFET 1200 V, 45 A, 90 mΩ (typ., $T_J = 150\text{ }^{\circ}\text{C}$), in an HiP247™ long leads package

Datasheet - production data





Figure 1: Internal schematic diagram



Features

- Very tight variation of on-resistance vs. temperature
- Very high operating junction temperature capability ($T_J = 200\text{ }^{\circ}\text{C}$)
- Very fast and robust intrinsic body diode
- Low capacitance

Applications

- Solar inverters, UPS
- Motor drives
- High voltage DC-DC converters
- Switch mode power supply

Description

This silicon carbide Power MOSFET is produced exploiting the advanced, innovative properties of wide bandgap materials. This results in unsurpassed on-resistance per unit area and very good switching performance almost independent of temperature. The outstanding thermal properties of the SiC material allow designers to use an industry-standard outline with significantly improved thermal capability. These features render the device perfectly suitable for high-efficiency and high power density applications.

Table 1: Device summary

Order code	Marking	Package	Packaging
SCTWA30N120	SCT30N120	HiP247™ long leads	Tube

Contents

1	Electrical ratings	3
2	Electrical characteristics	4
	2.1 Electrical characteristics (curves).....	6
3	Package information	10
	3.1 HiP247 long leads package information	10
4	Revision history	12

1 Electrical ratings

Table 2: Absolute maximum ratings

Symbol	Parameter	Value	Unit
V_{DS}	Drain-source voltage	1200	V
V_{GS}	Gate-source voltage	-10 to 25	V
I_D	Drain current (continuous) at $T_C = 25\text{ °C}$ (limited by die)	45	A
I_D	Drain current (continuous) at $T_C = 25\text{ °C}$ (limited by package)	40	A
I_D	Drain current (continuous) at $T_C = 100\text{ °C}$	34	A
$I_{DM}^{(1)}$	Drain current (pulsed)	90	A
P_{TOT}	Total dissipation at $T_C = 25\text{ °C}$	270	W
T_{stg}	Storage temperature range	-55 to 200	°C
T_j	Operating junction temperature range		

Notes:

⁽¹⁾Pulse width limited by safe operating area.

Table 3: Thermal data

Symbol	Parameter	Value	Unit
$R_{thj-case}$	Thermal resistance junction-case	0.65	°C/W
$R_{thj-amb}$	Thermal resistance junction-amb	40	°C/W

2 Electrical characteristics

($T_{\text{case}} = 25\text{ }^{\circ}\text{C}$ unless otherwise specified)

Table 4: On /off states

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
I_{DSS}	Zero gate voltage drain current	$V_{\text{GS}} = 0\text{ V}$, $V_{\text{DS}} = 1200\text{ V}$		1	25	μA
		$V_{\text{GS}} = 0\text{ V}$, $V_{\text{DS}} = 1200\text{ V}$, $T_{\text{J}} = 200\text{ }^{\circ}\text{C}$		50		μA
I_{GSS}	Gate-body leakage current	$V_{\text{DS}} = 0\text{ V}$, $V_{\text{GS}} = -10\text{ to }22\text{ V}$			± 100	nA
$V_{\text{GS(th)}}$	Gate threshold voltage	$V_{\text{DS}} = V_{\text{GS}}$, $I_{\text{D}} = 1\text{ mA}$	1.8	3.5		V
$R_{\text{DS(on)}}$	Static drain-source on-resistance	$V_{\text{GS}} = 20\text{ V}$, $I_{\text{D}} = 20\text{ A}$		80	100	m Ω
		$V_{\text{GS}} = 20\text{ V}$, $I_{\text{D}} = 20\text{ A}$ $T_{\text{J}} = 150\text{ }^{\circ}\text{C}$		90		m Ω
		$V_{\text{GS}} = 20\text{ V}$, $I_{\text{D}} = 20\text{ A}$ $T_{\text{J}} = 200\text{ }^{\circ}\text{C}$		100		m Ω

Table 5: Dynamic

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
C_{iss}	Input capacitance	$V_{\text{GS}} = 0\text{ V}$, $V_{\text{DS}} = 400\text{ V}$, $f = 1\text{ MHz}$	-	1700	-	pF
C_{oss}	Output capacitance		-	130	-	pF
C_{rss}	Reverse transfer capacitance		-	25	-	pF
R_{G}	Intrinsic gate resistance	$f = 1\text{ MHz}$, $I_{\text{D}} = 0\text{ A}$	-	5	-	Ω
Q_{g}	Total gate charge	$V_{\text{DD}} = 800\text{ V}$, $I_{\text{D}} = 20\text{ A}$ $V_{\text{GS}} = 0\text{ to }20\text{ V}$	-	105	-	nC
Q_{gs}	Gate-source charge		-	16	-	nC
Q_{gd}	Gate-drain charge		-	40	-	nC

Table 6: Switching energy (inductive load)

Symbol	Parameter	Test conditions	Min.	Typ.	Max	Unit
E_{on}	Turn-on switching energy	$V_{\text{DD}} = 800\text{ V}$, $I_{\text{D}} = 20\text{ A}$, $R_{\text{G}} = 6.8\text{ }\Omega$, $V_{\text{GS}} = -2\text{ to }20\text{ V}$	-	500	-	μJ
E_{off}	Turn-off switching energy		-	350	-	μJ
E_{on}	Turn-on switching energy	$V_{\text{DD}} = 800\text{ V}$, $I_{\text{D}} = 20\text{ A}$, $R_{\text{G}} = 6.8\text{ }\Omega$, $V_{\text{GS}} = -2\text{ to }20\text{ V}$ $T_{\text{J}} = 150\text{ }^{\circ}\text{C}$	-	500	-	μJ
E_{off}	Turn-off switching energy		-	400	-	μJ

Table 7: Switching times

Symbol	Parameter	Test conditions	Min.	Typ.	Max	Unit
$t_{\text{d(on)V}}$	Turn-on delay time	$V_{\text{DD}} = 800\text{ V}$, $I_{\text{D}} = 20\text{ A}$, $R_{\text{G}} = 0\text{ }\Omega$, $V_{\text{GS}} = 0\text{ to }20\text{ V}$	-	19	-	ns
$t_{\text{r(V)}}$	Fall time		-	28	-	ns
$t_{\text{d(off)V}}$	Turn-off-delay time		-	45	-	ns
$t_{\text{r(V)}}$	Rise time		-	20	-	ns

Table 8: Reverse SiC diode characteristics

Symbol	Parameter	Test conditions	Min.	Typ.	Max	Unit
V_{SD}	Diode forward voltage	$I_F = 10\text{ A}$, $V_{GS} = 0\text{ V}$	-	3.5	-	V
t_{rr}	Reverse recovery time	$I_{SD} = 20\text{ A}$, $di/dt = 100\text{ A}/\mu\text{s}$ $V_{DD} = 800\text{ V}$	-	140	-	ns
Q_{rr}	Reverse recovery charge		-	140		nC
I_{RRM}	Reverse recovery current		-	2		A

2.1 Electrical characteristics (curves)

Figure 2: Safe operating area




Figure 3: Thermal impedance





Figure 4: Output characteristics ($T_J = 25^\circ\text{C}$)Figure 5: Output characteristics ($T_J = 150^\circ\text{C}$)Figure 6: Output characteristics ($T_J = 200^\circ\text{C}$)

Figure 7: Transfer characteristics




Figure 8: Power dissipation




Figure 9: Gate charge vs gate-source voltage




Figure 10: Capacitance variations




Figure 11: Switching energy vs. drain current




Figure 12: Switching energy vs. junction temperature



Figure 13: Normalized $V_{(BR)DSS}$ vs. temperature









Figure 14: Normalized gate threshold voltage vs. temperature**Figure 15: Normalized on-resistance vs. temperature****Figure 16: Body diode characteristics ($T_J = -50^\circ\text{C}$)****Figure 17: Body diode characteristics ($T_J = 25^\circ\text{C}$)****Figure 18: Body diode characteristics ($T_J = 150^\circ\text{C}$)****Figure 19: 3rd quadrant characteristics ($T_J = -50^\circ\text{C}$)**


Figure 20: 3rd quadrant characteristics ($T_J = 25\text{ }^{\circ}\text{C}$)Figure 21: 3rd quadrant characteristics ($T_J = 150\text{ }^{\circ}\text{C}$)

3 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: www.st.com. ECOPACK® is an ST trademark.

3.1 HiP247 long leads package information

Figure 22: HiP247™ long leads package outline



7395426_7.0

Table 9: HiP247™ long leads package mechanical data

Dim.	mm		
	Min.	Typ.	Max.
A	4.90		5.15
D	1.85		2.10
E	0.55		0.67
F	1.07		1.32
F1	1.90		2.38
F2	2.87		3.38
G	10.90 BSC		
H	15.77		16.02
L	20.82		21.07
L1	4.16		4.47
L2	5.49		5.74
L3	20.05		20.30
L4	3.68		3.93
L5	6.04		6.29
M	2.25		2.55
V		10°	
V1		3°	
V3		20°	
DIA	3.55		3.66

4 Revision history

Table 10: Document revision history

Date	Revision	Changes
11-Jan-2016	1	First release.
19-Jun-2017	2	Updated title, features in cover page. Minor text edit in Section 1: "Electrical ratings" and Section 2: "Electrical characteristics" . Updated Figure 2: "Safe operating area" , Figure 3: "Thermal impedance" , Figure 13: "Normalized V(BR)DSS vs. temperature" , Figure 14: "Normalized gate threshold voltage vs. temperature" and Figure 15: "Normalized on-resistance vs. temperature" . Document status promoted from preliminary to production data.

IMPORTANT NOTICE – PLEASE READ CAREFULLY

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2017 STMicroelectronics – All rights reserved

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А