


## C5F1100000 Cable Assemblies - Cat 5e Shielded Modular Cord



For more Information  
please call

1-800-Belden1



### General Description:

Cat 5e Shielded Patchcord, 4 Pair, 24 AWG Solid, CMR, T568A/B-T568A/B,

### Usage (Overall)

**Suitable Applications:** IBDN Shielded System Cat 5e, TIA Category 5e, ISO Class D, 1000BASE-T  
**Related Parts:** Cat 5e Shielded KeyConnect Modular Jacks, Shielded Patch Panels

### Multi Conductor

#### Physical Characteristics

##### Conductor

AWG:

# Conductors	# Pairs	AWG	Stranding	Conductor Material
8	4	24	Solid	BC - Bare Copper

##### Insulation

Insulation Material:

Insulation Material
PO - Polyolefin

##### Outer Shield

Outer Shield Material:

Outer Shield Trade Name	Type	Outer Shield Material
Shield	Foil	AL - Aluminum

##### Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

##### Overall Diameter

**Overall Nominal Diameter:** 6.985 mm  
**Individual Cable Diameter:** 6.985 mm

### Cable Characteristics (Connectivity)

#### Outer Shield

**Outer Shield Drain Wire Diameter:** 26 AWG

### Physical Characteristics (Connectivity)

#### Materials

Materials:

Description	Type	Material
Shielded Plug	RJ45	Phosphor Bronze with Tin Plating over Nickel
Boot		Elastomer
Front Connection	Blades	Phosphor Bronze with 50u inch Gold over Nickel Plating

#### Color

**Boot Color:** Same as Cable

#### Wiring Scheme

**Wiring Scheme:** T568A/B-T568A/B

#### Packaging

**Packaging:** Individually packaged in a clear plastic bag.

### Mechanical Characteristics (Connectivity)

**Plug / Jack Compatibility:** RJ45

#### Termination Interface:

Termination	Connection	Durabilities
RJ45	Mated Connection	750 Cycles

## METRIC MEASUREMENT VERSION

### C5F1100000 Cable Assemblies - Cat 5e Shielded Modular Cord

Max. Recommended Pull Tension:	50.042 N
Min. Bend Radius (Overall Cable):	55.880 mm

#### Applicable Specifications and Agency Compliance (Overall)

##### Applicable Standards & Environmental Programs

UL Rating:	Riser
Other Standards:	FCC Part 68, Subpart F, IEC 60603-7
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2011
MIL Order #39 (China RoHS):	EUP 50
Telecommunications Standards:	Category 5e - TIA 568.C.2, Class D - ISO/IEC 11801:2002
Safety Listing:	Bi-national Standard Listed

##### Suitability

Suitability - Indoor:	Yes
-----------------------	-----

#### Transmission Characteristics (Connectivity)

Dielectric Strength:	1,000 V RMS @ 60 Hz for 1 minute
Current Rating:	1.500 A
Insulation Resistance:	500 M-Ohm Minimum
Max. Contact Resistance:	20 m-Ohm

#### Notes (Overall)

**Notes:** Last 3-digits 'xxx' specify length in feet; Available from 1 ft (001) to 15 ft (015) by increment of 1 ft, 20 ft (025) and 25 ft (025).

#### Product Family

##### Product List:

Length	Blue	Gray	White	Black
1 ft. (0.3 m)	C5F1106001	C5F1108001	C5F1109001	C5F1100001
2 ft. (0.6 m)	C5F1106002	C5F1108002	C5F1109002	C5F1100002
3 ft. (0.9 m)	C5F1106003	C5F1108003	C5F1109003	C5F1100003
4 ft. (1.2 m)	C5F1106004	C5F1108004	C5F1109004	C5F1100004
5 ft. (1.5 m)	C5F1106005	C5F1108005	C5F1109005	C5F1100005
6 ft. (1.8 m)	C5F1106006	C5F1108006	C5F1109006	C5F1100006
7 ft. (2.1 m)	C5F1106007	C5F1108007	C5F1109007	C5F1100007
8 ft. (2.4 m)	C5F1106008	C5F1108008	C5F1109008	C5F1100008
9 ft. (2.7 m)	C5F1106009	C5F1108009	C5F1109009	C5F1100009
10 ft. (3.0 m)	C5F1106010	C5F1108010	C5F1109010	C5F1100010
11 ft. (3.4 m)	C5F1106011	C5F1108011	C5F1109011	C5F1100011
12 ft. (3.7 m)	C5F1106012	C5F1108012	C5F1109012	C5F1100012
13 ft. (4.0 m)	C5F1106013	C5F1108013	C5F1109013	C5F1100013
14 ft. (4.3 m)	C5F1106014	C5F1108014	C5F1109014	C5F1100014
15 ft. (4.6 m)	C5F1106015	C5F1108015	C5F1109015	C5F1100015
20 ft. (6.1 m)	C5F1106020	C5F1108020	C5F1109020	C5F1100020
25 ft. (7.6 m)	C5F1106025	C5F1108025	C5F1109025	C5F1100025

#### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

Revision Number: 0    Revision Date: 08-16-2012

© 2014 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А