



Model: ZZxD-Nx-xR series

Wireless Modbus I/O

Modular and Customizable Wireless Replacement!

Introduction

Wireless Modbus I/O - flexible enough to fit your applications. Zlinx plug-n-play modular units from B&B Electronics combine traditional Modbus RTU remote analog and discrete I/O with built-in wireless connectivity - reducing cost, simplifying installation and support. Wireless RTU serves as Modbus slave RTU in radio-based SCADA systems, or as a peer-to-peer communication platform.

Features

DIN Rail Package 3 Ranges Available

Easy installation; conserves panel space (versus panel mount modems).
Short, Medium, Long range. Don't spend more money on longer distance radios if you don't need the distance.

Active Repeaters

Place I/O modules where they need to go, by the sensors. With repeater built-in functionality (-MR and -LR models only), you can build up a security path for all your critical communications. Customize it to your application. Just snap on your I/O and you're ready to go.

Modular 10-48 VDC Power Input

Rugged input power circuit allows insertion to most control power configurations. Can utilize industrial power supply.

Wide Temperature/ Industrial Grade Modbus Compatible

Meets most indoor or outdoor applications. Rugged circuitry prevents signal degradation versus lower temperature rated wireless devices.

Interface using industry standard Modbus protocol. Connect to Wonderware, Labview or other Modbus compatible software. Allows data to be brought directly into most PLC systems.

Base Modules

Model No.	Frequency	Radio Power	RF Range (indoor/outdoor with included antenna)	I/O			
				DI	DO	AI	AO
ZZ24D-NA-SR	2.4 GHz	100 mW	Up to 91 m(300ft)/Up to 1.6 km (1 mi)	2	2	2	2
ZZ24D-NB-SR	2.4 GHz	100 mW	Up to 91 m (300 ft) /Up to 1.6 km (1 mi)	4	4	0	0
ZZ24D-NA-MR	2.4 GHz	50 mW	Up to 183 m (600 ft)/Up to 4.8 km (3 mi)	2	2	2	2
ZZ24D-NB-MR	2.4 GHz	50 mW	Up to 183 m (600 ft)/Up to 4.8 km (3 mi)	4	4	0	0
ZZ9D-NA-MR	900 MHz	100 mW	Up to 457 m (1500 ft)/Up to 11.3 km (7 mi)	2	2	2	2
ZZ9D-NB-MR	900 MHz	100 mW	Up to 457 m (1500 ft)/Up to 11.3 km (7 mi)	4	4	0	0
ZZ9D-NA-LR	900 MHz	1W	Up to 914 m (3000 ft)/Up to 22.5 km (14 mi)	2	2	2	2
ZZ9D-NB-LR	900 MHz	1W	Up to 914 m (3000 ft)/Up to 22.5 km (14 mi)	4	4	0	0

I/O Expansion Modules

Model No.	Digital Inputs	Digital Outputs	Analog Inputs	Analog Outputs
ZZ-8DI-DC	8			
ZZ-8DO-T		8		
ZZ-4DI4DO-DCT	4	4		
ZZ-4AI			4	
ZZ-4AO				4
ZZ-2AI2AO			2	2
ZZ-8DO-R		8 (relays)		
ZZ-4RTD1			4 (RTD)	



International Headquarters: 707 Dayton Road PO Box 1040 Ottawa, IL 61350 USA
815-433-5100 Fax 433-5104 www.bb-elec.com orders@bb-elec.com support@bb-elec.com

European Headquarters: Westlink Commercial Park Oranmore Co. Galway Ireland
+353 91 792444 Fax +353 91 792445 www.bb-europe.com orders@bb-europe.com support@bb-europe.com

Software Options

Model No.	Description
ZZ-PROG1	Programming module with cable
ZZ-PROGKIT	Programming module, cable and software CD

Specifications

Operating Systems Supported:	Windows ME/98/2000/XP
Dimensions:	1.15 x 3.65 x 5 in (2.92 x 9.27 x 12.7 cm)
Expansion Feature:	1 base module and up to 6 expansion modules
Radio Properties	
Short Range (SR) Option:	Up to 300 ft indoors / 1 mile outdoors (LOS)
Medium Range (MR) Option:	Up to 1500 ft indoors / 7 miles outdoors (LOS)
Long Range (LR) Option:	Up to 3000 ft indoors / 14 miles outdoors (LOS)
Antennas:	For 2.4 GHz models: 4.25 inch omni-directional rubber duck antenna. PN: ZZ24D-ANT1 For 900 MHz models: 6.5 inch omni-directional rubber duck antenna. PN: ZZ9D-ANT1 (RPSMA connector for db gain antennas)
LED Indicators	
Receive Signal Strength Indicator:	Tri-color LED (Off = no signal, Red = weak, Yellow = OK, Green = Strong)
RF Data Indicator:	Green LED (blinks with TD or RD data traffic, Off = no data traffic)
Local Bus Data Indicator:	Green LED (blinks with TD or RD data traffic, Off = no data traffic)
Power Indicator:	Red LED
I/O Connectors:	Removable screw terminal (2, 4 or 8 position) block, 3.5 mm spacing
Digital Inputs	
Voltage Range:	0 to 48 VDC
Low Voltage (0):	0.8 V maximum
High Voltage (1):	4.0 V minimum
Pull up/down current:	38 μ A
Frequency Input:	Two DI inputs per module software selectable as Frequency Counters, 0 to 5 kHz range
Digital Outputs	
Voltage Range:	10 to 45 VDC (for sourcing outputs), 0 to 48 VDC (for sinking outputs)
Open Source:	40 mA per output
Analog Inputs/Outputs	
Ranges:	0 to 10 VDC or 0 to 20 mA
Resolution:	12 bit
Input Accuracy:	0.2 % full scale reading typical
Output Accuracy:	0.27 % full scale reading typical
AI Load Resistance:	100 Mega Ohms when configured for voltage input 250 Ohms when configured for current input
AO Max Output Current:	1 mA when configured for voltage output
AO Max Load:	450 Ohms when configured for current output
Input Protection:	Overvoltage to 2x max input voltage
Power Supply Voltage Requirements:	Sourcing modules: 10 VDC to 46 VDC, 24 VAC $\pm$ 10% Sinking modules: 10 VDC to 48 VDC, 24 VAC $\pm$ 10%
Power Supply:	Not included
Base Module Power Connector:	Removable screw terminal (2) block, 3.5 mm spacing
Relay Outputs	
Number of relays:	8
Type:	C (normally open and normally closed)
Output Connection:	3.5mm removable terminal block (2 per output)
Common connection:	3.5mm removable terminal block (1 per bank of 4 output)
Ratings:	250VAC @ 8A, 30VDC @ 5A (maximum per bank of 4 as grouped on the label)
RTD Inputs	
Number of RTD:	4
Wire configuration:	2, 3, and 4 wire
Type:	PT100*, PT1000*, Cu10** *Optimized for temperature coefficient of 385 **Optimized for temperature coefficient of 427
Input Connection:	3.5mm removable terminal block (4 per output)
Temperature range:	PT100 = -200 to 650°C PT1000 = -200 to 100°C Cu10 = -100 to 260°C
Resolution:	0.1°C across -40 to 85°C
Accuracy @ 25°C:	$\pm$ 0.5°C typical
Accuracy -40 to 85°C:	$\pm$ 2.0°C maximum



International Headquarters: 707 Dayton Road PO Box 1040 Ottawa, IL 61350 USA
815-433-5100 Fax 433-5104 www.bb-elec.com orders@bb-elec.com support@bb-elec.com

European Headquarters: Westlink Commercial Park Oranmore Co. Galway Ireland
+353 91 792444 Fax +353 91 792445 www.bb-europe.com orders@bb-europe.com support@bb-europe.com

Power Consumption - Base Modules

ZZ24D-NA-SR	10W
ZZ24D-NB-SR	10W
ZZ24D-NC-SR	10W
ZZ24D-ND-SR	10W
ZZ24D-NA-MR	9.5W
ZZ24D-NB-MR	9.5W
ZZ24D-NC-MR	9.5W
ZZ24D-ND-MR	9.5W
ZZ9D-NA-MR	9.5W
ZZ9D-NB-MR	9.5W
ZZ9D-NC-MR	9.5W
ZZ9D-ND-MR	9.5W
ZZ9D-NA-LR	13.1W
ZZ9D-NB-LR	13.1W
ZZ9D-NC-LR	13.1W
ZZ9D-ND-LR	13.1W
ZZ9D-NA-LR-AU	13.1W
ZZ9D-NB-LR-AU	13.1W
ZZ9D-NC-LR-AU	13.1W
ZZ9D-ND-LR-AU	13.1W

Power Consumption - Expansion Modules:

ZZ-4AI	1.0W
ZZ-4AO	1.1W
ZZ-2AI2AO	1.2W
ZZ-8DI-T	0.4W
ZZ-8DO-T	15.8W
ZZ-8DO-T1	1.1W
ZZ-4DI4DO-DCT	8.1W
ZZ-4DI4DO-DCT1	1.0W
ZZ-8DO-R	3.2W
ZZ-4RTD1	0.4W

Additional Specifications

Operating Temperature:	- 40 to 80 °C (- 40 to 176 °F), - 40 to 65 °C (- 40 to 149 °F) for ZZ-8DO-R ONLY
Storage Temperature:	- 40 to 85 °C (- 40 to 185 °F)
Humidity:	10% to 90% R.H. non-condensing
Enclosure Rating:	IP30
Mounting:	DIN rail mount, 35 mm
CD-ROM Disc:	Zlinx I/O Manager; PDF of Zlinx I/O User Manual; PDF of Quick Start guide
Certifications:	FCC: Part 15 Class A CISPR (EN55022) Class A EN61000-6-1 Generic Standards for Residential, Commercial & Light Industrial EN61000-4-2 ESD EN61000-4-3 RFI EN61000-4-4 EFT EN61000-4-5 Surge EN61000-4-6 CI EN61000-4-8 Power Frequency Magnetic EN61000-4-11 Voltage Dips & Interruptions

Accessories and Replacement Parts:	ZZ-DIN1	DIN clip and spring for all ZZ products, 4 spare screws for enclosure
	ZZ-TB1	Removable terminal block for all ZZ modules and shroud cover for local bus
	ZZ24D-ANT1	2.4 GHz band antenna
	ZZ9D-ANT1	900 MHz band antenna
	ZZ-PROGKIT	Programming Module and CD with Zlinx I/O Manager software and hardcopy of Quick Start Guide
	ZZ-PROG1	Programming Module and hardcopy of Quick Start Guide
	195M-SLSW-24	Antenna cable

Programming Module ZZ-PROG1

Power Source:	Supplied through local bus connector from powered base module
Power Consumption:	5 VDC @ 40 mA max
LED Indicators:	Power ON: Red LED illuminated steady
Local Bus:	Data present on TD or RD line – Green LED blinks
Serial Connector:	DB-9F 9 pin D-type female connector (configured as DCE)
Interface Lines Supported:	RS-232 - TD, RD, RTS, CTS, DTR, DSR, DCD, GND
Serial Data Rates Supported:	115200 bps
Parity:	None
Data Bits:	8
Stop Bits:	1
Flow control:	None
Cable:	Gray straight-through DB9M to DB9F, 6 foot (included – Part No. 9PAMF6 recommended)
Local Bus Connection:	14 pin dual row 2mm connector
Temperature:	Operating: -40°C to 85°C Storage: -40°C to 85°C
Dimensions	1.15 x 3.65 x 5 in (2.92 x 9.27 x 12.7 cm)
Operating Humidity:	10 to 90% non-condensing



International Headquarters: 707 Dayton Road PO Box 1040 Ottawa, IL 61350 USA
815-433-5100 Fax 433-5104 www.bb-elec.com orders@bb-elec.com support@bb-elec.com

European Headquarters: Westlink Commercial Park Oranmore Co. Galway Ireland
+353 91 792444 Fax +353 91 792445 www.bb-europe.com orders@bb-europe.com support@bb-europe.com

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А