

# High-Voltage Types Application Guide, Transmitting Mica

## Types 271, 272, 273 — Rectangular Case, High-Current and High-Voltage Circuits



Types 271, 272, 273 are designed for frequencies ranging from 100 kHz to 3 MHz and are well suited for high-current and high-voltage radio transmitter circuit applications. Cast in rectangular cases, these capacitors are electrically equivalent to MIL-C-5 Styles CM65 through CM73 in capacitance and current ratings, but are far superior in environmental capability, temperature range, physical size, mounting configuration and reliability.

### Highlights

- Type 273 permits stand-off mounting
- Highly shock resistant
- Optional aluminum mounting plates
- Convenient mounting
- Cast in rectangular cases

### Specifications

|   |                                      |
|---|--------------------------------------|
| Capacitance Range                       | 47 pF to 0.1 $\mu$ F                 |
| Capacitance Tolerance                   | $\pm$ 5% (J)                         |
| Rated Voltage                           | 1 to 60 kVpk                         |
| Operating Temperature Range with Ripple | -55 $^{\circ}$ C to 125 $^{\circ}$ C |

### Type 271 Ratings

| Cap<br>(pF)            | Catalog<br>Part Number | Maximum AC Current at 65 $^{\circ}$ C |              |                |                |
|------------------------|------------------------|---------------------------------------|--------------|----------------|----------------|
|                        |                        | 3 MHz<br>(A)                          | 1 MHz<br>(A) | 300 kHz<br>(A) | 100 kHz<br>(A) |
| <b>250 Peak Volts</b>  |                        |                                       |              |                |                |
| 47000                  | 27102B473JO0           | 11.0                                  | 11.0         | 9.1            | 4.7            |
| 50000                  | 27102B503JO0           | 11.0                                  | 11.0         | 9.1            | 4.7            |
| 51000                  | 27102B513JO0           | 11.0                                  | 11.0         | 9.1            | 4.7            |
| 56000                  | 27102B563JO0           | 11.0                                  | 11.0         | 9.1            | 4.7            |
| 62000                  | 27102B623JO0           | 11.0                                  | 11.0         | 9.1            | 5.1            |
| 68000                  | 27102B683JO0           | 11.0                                  | 11.0         | 9.1            | 5.1            |
| 75000                  | 27102B753JO0           | 11.0                                  | 11.0         | 9.1            | 5.1            |
| 82000                  | 27102B823JO0           | 11.0                                  | 11.0         | 9.1            | 5.1            |
| 91000                  | 27102B913JO0           | 11.0                                  | 11.0         | 9.1            | 5.6            |
| 100000                 | 27102B104JO0           | 11.0                                  | 11.0         | 9.1            | 5.6            |
| <b>500 Peak Volts</b>  |                        |                                       |              |                |                |
| 27000                  | 27105B273JO0           | 11.0                                  | 11.0         | 7.5            | 3.9            |
| 30000                  | 27105B303JO0           | 11.0                                  | 11.0         | 8.2            | 3.9            |
| 33000                  | 27105B333JO0           | 11.0                                  | 11.0         | 8.2            | 4.3            |
| 36000                  | 27105B363JO0           | 11.0                                  | 11.0         | 8.2            | 4.3            |
| 39000                  | 27105B393JO0           | 11.0                                  | 11.0         | 8.2            | 4.3            |
| 43000                  | 27105B433JO0           | 11.0                                  | 11.0         | 9.1            | 4.7            |
| <b>1000 Peak Volts</b> |                        |                                       |              |                |                |
| 10000                  | 27110B103JO0           | 10.0                                  | 9.1          | 5.1            | 2.4            |
| 11000                  | 27110B113JO0           | 11.0                                  | 10.0         | 5.6            | 2.7            |
| 12000                  | 27110B123JO0           | 11.0                                  | 10.0         | 6.2            | 3.0            |
| 13000                  | 27110B133JO0           | 11.0                                  | 11.0         | 6.8            | 3.0            |
| 15000                  | 27110B153JO0           | 11.0                                  | 11.0         | 6.8            | 3.3            |
| 16000                  | 27110B163JO0           | 11.0                                  | 11.0         | 6.8            | 3.3            |
| 18000                  | 27110B183JO0           | 11.0                                  | 11.0         | 7.5            | 3.3            |
| 20000                  | 27110B203JO0           | 11.0                                  | 11.0         | 7.5            | 3.6            |
| 22000                  | 27110B223JO0           | 11.0                                  | 11.0         | 7.5            | 3.6            |
| 24000                  | 27110B243JO0           | 11.0                                  | 11.0         | 7.5            | 3.6            |

| Cap<br>(pF)            | Catalog<br>Part Number | Maximum AC Current at 65 $^{\circ}$ C |              |                |                |
|------------------------|------------------------|---------------------------------------|--------------|----------------|----------------|
|                        |                        | 3 MHz<br>(A)                          | 1 MHz<br>(A) | 300 kHz<br>(A) | 100 kHz<br>(A) |
| <b>1500 Peak Volts</b> |                        |                                       |              |                |                |
| 8000                   | 27115B802JO0           | 10.0                                  | 8.2          | 4.7            | 2.2            |
| 8200                   | 27115B822JO0           | 10.0                                  | 8.2          | 4.7            | 2.2            |
| 9100                   | 27115B912JO0           | 10.0                                  | 8.2          | 4.7            | 2.4            |
| 2700                   | 27120B272JO0           | 6.8                                   | 5.1          | 2.7            | 1.3            |
| <b>2000 Peak Volts</b> |                        |                                       |              |                |                |
| 3000                   | 27120B302JO0           | 7.5                                   | 5.1          | 3.0            | 1.3            |
| 3300                   | 27120B332JO0           | 7.5                                   | 5.6          | 3.0            | 1.5            |
| 3600                   | 27120B362JO0           | 7.5                                   | 5.6          | 3.3            | 1.5            |
| 3900                   | 27120B392JO0           | 8.2                                   | 6.2          | 3.3            | 1.6            |
| 4000                   | 27120B402JO0           | 8.2                                   | 6.2          | 3.3            | 1.6            |
| 4300                   | 27120B432JO0           | 8.2                                   | 6.2          | 3.6            | 1.6            |
| 4700                   | 27120B472JO0           | 8.2                                   | 6.8          | 3.6            | 1.8            |
| 5000                   | 27120B502JO0           | 8.2                                   | 6.8          | 3.6            | 1.8            |
| 5100                   | 27120B512JO0           | 8.2                                   | 6.8          | 3.6            | 1.8            |
| 5600                   | 27120B562JO0           | 9.1                                   | 7.5          | 3.9            | 2.0            |
| 6000                   | 27120B602JO0           | 9.1                                   | 7.5          | 4.3            | 2.0            |
| 6200                   | 27120B622JO0           | 9.1                                   | 7.5          | 4.3            | 2.0            |
| 6800                   | 27120B682JO0           | 10.0                                  | 7.5          | 4.3            | 2.0            |
| 7500                   | 27120B752JO0           | 10.0                                  | 8.2          | 4.7            | 2.2            |
| <b>3000 Peak Volts</b> |                        |                                       |              |                |                |
| 47                     | 27130B470JO0           | 1.2                                   | 0.5          | 0.2            | 0.1            |
| 51                     | 27130B510JO0           | 1.3                                   | 0.5          | 0.2            | 0.1            |
| 56                     | 27130B560JO0           | 1.3                                   | 0.6          | 0.2            | 0.1            |
| 62                     | 27130B620JO0           | 1.5                                   | 0.6          | 0.2            | 0.1            |
| 68                     | 27130B680JO0           | 1.5                                   | 0.6          | 0.2            | 0.1            |
| 75                     | 27130B750JO0           | 1.5                                   | 0.6          | 0.3            | 0.1            |
| 82                     | 27130B820JO0           | 1.6                                   | 0.7          | 0.3            | 0.1            |
| 91                     | 27130B910JO0           | 1.6                                   | 0.7          | 0.3            | 0.1            |

# High-Voltage Types Application Guide, Transmitting Mica

## Type 271 Ratings

| Cap<br>(pF)            | Catalog<br>Part Number | Maximum AC Current at 65 °C |              |                |                |
|------------------------|------------------------|-----------------------------|--------------|----------------|----------------|
|                        |                        | 3 MHz<br>(A)                | 1 MHz<br>(A) | 300 kHz<br>(A) | 100 kHz<br>(A) |
| <b>3000 Peak Volts</b> |                        |                             |              |                |                |
| 100                    | 27105B273J00           | 11.0                        | 11.0         | 7.5            | 3.9            |
| 110                    | 27130B111J00           | 1.8                         | 0.8          | 0.4            | 0.1            |
| 120                    | 27130B121J00           | 2.0                         | 0.9          | 0.4            | 0.2            |
| 130                    | 27130B131J00           | 2.0                         | 0.9          | 0.4            | 0.2            |
| 150                    | 27130B151J00           | 2.2                         | 1.0          | 0.5            | 0.2            |
| 160                    | 27130B161J00           | 2.2                         | 1.1          | 0.5            | 0.2            |
| 180                    | 27130B181J00           | 2.4                         | 1.1          | 0.6            | 0.2            |
| 200                    | 27130B201J00           | 2.4                         | 1.2          | 0.6            | 0.2            |
| 220                    | 27130B221J00           | 2.7                         | 1.3          | 0.6            | 0.3            |
| 240                    | 27130B241J00           | 2.7                         | 1.3          | 0.7            | 0.3            |
| 250                    | 27130B251J00           | 2.7                         | 1.3          | 0.7            | 0.3            |
| 270                    | 27130B271J00           | 3.1                         | 1.5          | 0.8            | 0.3            |
| 300                    | 27130B301J00           | 3.0                         | 1.5          | 0.8            | 0.4            |
| 330                    | 27130B331J00           | 3.0                         | 1.6          | 0.8            | 0.4            |
| 360                    | 27130B361J00           | 3.3                         | 1.6          | 0.9            | 0.4            |
| 390                    | 27130B391J00           | 3.3                         | 1.8          | 0.9            | 0.4            |
| 430                    | 27130B431J00           | 3.6                         | 1.8          | 1.0            | 0.5            |
| 470                    | 27130B471J00           | 3.6                         | 2.0          | 1.1            | 0.5            |
| 500                    | 27130B501J00           | 3.6                         | 2.0          | 1.1            | 0.5            |
| 510                    | 27130B511J00           | 3.6                         | 2.0          | 1.1            | 0.5            |
| 560                    | 27130B561J00           | 3.9                         | 2.2          | 1.2            | 0.5            |
| 620                    | 27130B621J00           | 3.9                         | 2.4          | 1.2            | 0.6            |
| 680                    | 27130B681J00           | 4.3                         | 2.4          | 1.3            | 0.6            |
| 750                    | 27130B751J00           | 4.3                         | 2.7          | 1.3            | 0.6            |
| 820                    | 27130B821J00           | 4.3                         | 2.7          | 1.5            | 0.7            |
| 910                    | 27130B911J00           | 4.7                         | 3.0          | 1.5            | 0.7            |
| 1000                   | 27130B102J00           | 4.7                         | 3.0          | 1.6            | 0.8            |
| 1100                   | 27130B112J00           | 5.1                         | 3.3          | 1.6            | 0.8            |
| 1200                   | 27130B122J00           | 5.1                         | 3.3          | 1.8            | 0.8            |
| 1300                   | 27130B132J00           | 5.6                         | 3.6          | 1.8            | 0.9            |
| 1500                   | 27130B152J00           | 5.6                         | 3.9          | 2.0            | 0.9            |
| 1600                   | 27130B162J00           | 5.6                         | 3.9          | 2.0            | 1.0            |
| 1800                   | 27130B182J00           | 6.2                         | 4.3          | 2.2            | 1.1            |
| 2000                   | 27130B202J00           | 6.2                         | 4.3          | 2.4            | 1.1            |
| 2200                   | 27130B222J00           | 6.8                         | 4.7          | 2.4            | 1.2            |

### Type 272 Ratings

| Cap<br>(pF)           | Catalog<br>Part Number | Maximum AC Current at 65 °C |              |                |                |
|-----------------------|------------------------|-----------------------------|--------------|----------------|----------------|
|                       |                        | 3 MHz<br>(A)                | 1 MHz<br>(A) | 300 kHz<br>(A) | 100 kHz<br>(A) |
| <b>250 Peak Volts</b> |                        |                             |              |                |                |
| 250000                | 27202B254J00           | 15.0                        | 18.0         | 15.0           | 8.2            |

| Cap<br>(pF)            | Catalog<br>Part Number | Maximum AC Current at 65 °C |              |                |                |
|------------------------|------------------------|-----------------------------|--------------|----------------|----------------|
|                        |                        | 3 MHz<br>(A)                | 1 MHz<br>(A) | 300 kHz<br>(A) | 100 kHz<br>(A) |
| <b>500 Peak Volts</b>  |                        |                             |              |                |                |
| 82000                  | 27205B823J00           | 15.0                        | 18.0         | 15.0           | 8.2            |
| 91000                  | 27205B913J00           | 15.0                        | 18.0         | 15.0           | 8.2            |
| 100000                 | 27205B104J00           | 15.0                        | 18.0         | 15.0           | 8.2            |
| 200000                 | 27205B204J00           | 15.0                        | 18.0         | 15.0           | 8.2            |
| <b>1000 Peak Volts</b> |                        |                             |              |                |                |
| 56000                  | 27210B563J00           | 15.0                        | 16.0         | 15.0           | 8.2            |
| 62000                  | 27210B623J00           | 15.0                        | 18.0         | 15.0           | 8.2            |
| 68000                  | 27210B683J00           | 15.0                        | 18.0         | 15.0           | 8.2            |
| 75000                  | 27215B333J00           | 15.0                        | 18.0         | 15.0           | 8.2            |
| <b>1500 Peak Volts</b> |                        |                             |              |                |                |
| 24000                  | 27215B243J00           | 13.0                        | 15.0         | 12.0           | 6.8            |
| 27000                  | 27215B273J00           | 13.0                        | 15.0         | 12.0           | 6.8            |
| 30000                  | 27215B303J00           | 13.0                        | 15.0         | 12.0           | 6.8            |
| 33000                  | 27215B333J00           | 13.0                        | 15.0         | 13.0           | 7.5            |
| 36000                  | 27215B363J00           | 13.0                        | 16.0         | 13.0           | 7.5            |
| 39000                  | 27215B393J00           | 15.0                        | 16.0         | 13.0           | 7.5            |
| 43000                  | 27215B433J00           | 15.0                        | 16.0         | 13.0           | 7.5            |
| 47000                  | 27215B473J00           | 15.0                        | 16.0         | 13.0           | 7.5            |
| 50000                  | 27215B503J00           | 15.0                        | 16.0         | 15.0           | 7.5            |
| 51000                  | 27215B513J00           | 15.0                        | 16.0         | 15.0           | 7.5            |
| <b>2000 Peak Volts</b> |                        |                             |              |                |                |
| 8200                   | 27220B822J00           | 10.0                        | 10.0         | 7.5            | 3.9            |
| 9100                   | 27220B912J00           | 11.0                        | 10.0         | 8.2            | 4.3            |
| 10000                  | 27220B103J00           | 11.0                        | 11.0         | 8.2            | 4.3            |
| 11000                  | 27220B113J00           | 11.0                        | 11.0         | 8.2            | 4.7            |
| 12000                  | 27220B123J00           | 11.0                        | 11.0         | 9.1            | 4.7            |
| 13000                  | 27220B133J00           | 12.0                        | 12.0         | 9.1            | 5.1            |
| 15000                  | 27220B153J00           | 12.0                        | 12.0         | 10.0           | 5.1            |
| 16000                  | 27220B163J00           | 12.0                        | 12.0         | 10.0           | 5.6            |
| 18000                  | 27220B183J00           | 12.0                        | 13.0         | 10.0           | 5.6            |
| 20000                  | 27220B203J00           | 13.0                        | 13.0         | 11.0           | 6.2            |
| 22000                  | 27220B223J00           | 13.0                        | 13.0         | 11.0           | 6.2            |
| <b>3000 Peak Volts</b> |                        |                             |              |                |                |
| 2700                   | 27230B272J00           | 8.2                         | 6.8          | 4.3            | 2.2            |
| 3000                   | 27230B302J00           | 8.2                         | 6.8          | 4.7            | 2.2            |
| 3300                   | 27230B332J00           | 8.2                         | 6.8          | 4.7            | 2.4            |
| 3600                   | 27230B362J00           | 8.2                         | 7.5          | 5.1            | 2.4            |
| 3900                   | 27230B392J00           | 9.1                         | 7.5          | 5.6            | 2.7            |
| 4300                   | 27230B432J00           | 9.1                         | 7.5          | 5.6            | 2.7            |
| 4700                   | 27230B472J00           | 9.1                         | 8.2          | 6.2            | 3.0            |
| 5000                   | 27230B502J00           | 9.1                         | 8.2          | 6.2            | 3.0            |

# High-Voltage Types Application Guide, Transmitting Mica

## Type 272 Ratings

| Cap<br>(pF)            | Catalog<br>Part Number | Maximum AC Current at 65 °C |              |                |                |
|------------------------|------------------------|-----------------------------|--------------|----------------|----------------|
|                        |                        | 3 MHz<br>(A)                | 1 MHz<br>(A) | 300 kHz<br>(A) | 100 kHz<br>(A) |
| <b>3000 Peak Volts</b> |                        |                             |              |                |                |
| 5100                   | 27230B512J00           | 9.1                         | 8.2          | 6.2            | 3.0            |
| 5600                   | 27230B562J00           | 9.1                         | 9.1          | 6.2            | 3.3            |
| 6000                   | 27230B602J00           | 10.0                        | 9.1          | 6.8            | 3.6            |
| 6200                   | 27230B622J00           | 10.0                        | 9.1          | 6.8            | 3.6            |
| 6800                   | 27230B682J00           | 10.0                        | 9.1          | 6.8            | 3.6            |
| 7500                   | 27230B752J00           | 10.0                        | 9.1          | 6.8            | 3.9            |
| <b>5000 Peak Volts</b> |                        |                             |              |                |                |
| 47                     | 27250B470J00           | 1.5                         | 0.6          | 0.2            | 0.1            |
| 51                     | 27250B510J00           | 1.6                         | 0.7          | 0.2            | 0.1            |
| 56                     | 27250B560J00           | 1.8                         | 0.8          | 0.3            | 0.1            |
| 62                     | 27250B620J00           | 1.8                         | 0.8          | 0.3            | 0.1            |
| 68                     | 27250B680J00           | 2.0                         | 0.9          | 0.3            | 0.1            |
| 75                     | 27250B750J00           | 2.0                         | 1.0          | 0.4            | 0.1            |
| 82                     | 27250B820J00           | 2.2                         | 1.1          | 0.4            | 0.1            |
| 91                     | 27250B910J00           | 2.4                         | 1.2          | 0.4            | 0.1            |
| 100                    | 27250B101J00           | 2.4                         | 1.2          | 0.4            | 0.1            |
| 110                    | 27250B111J00           | 2.7                         | 1.3          | 0.5            | 0.2            |
| 120                    | 27250B121J00           | 2.7                         | 1.5          | 0.6            | 0.2            |
| 130                    | 27250B131J00           | 3.0                         | 1.6          | 0.6            | 0.2            |
| 150                    | 27250B151J00           | 3.3                         | 1.8          | 0.7            | 0.2            |
| 160                    | 27250B161J00           | 3.3                         | 1.8          | 0.8            | 0.3            |
| 180                    | 27250B181J00           | 3.3                         | 2.0          | 0.8            | 0.3            |
| 200                    | 27250B201J00           | 3.6                         | 2.0          | 0.8            | 0.3            |
| 220                    | 27250B221J00           | 3.6                         | 2.2          | 0.9            | 0.4            |
| 240                    | 27250B241J00           | 3.6                         | 2.4          | 1.0            | 0.4            |
| 250                    | 27250B251J00           | 3.6                         | 2.4          | 1.0            | 0.4            |
| 270                    | 27250B271J00           | 3.9                         | 2.4          | 1.1            | 0.5            |
| 300                    | 27250B301J00           | 3.9                         | 2.7          | 1.1            | 0.5            |
| 330                    | 27250B331J00           | 4.3                         | 2.7          | 1.2            | 0.5            |
| 360                    | 27250B361J00           | 4.3                         | 2.7          | 1.3            | 0.6            |
| 390                    | 27250B391J00           | 4.3                         | 2.7          | 1.3            | 0.6            |
| 430                    | 27250B431J00           | 4.7                         | 3.0          | 1.5            | 0.7            |
| 470                    | 27250B471J00           | 4.7                         | 3.3          | 1.5            | 0.7            |
| 500                    | 27250B501J00           | 4.7                         | 3.3          | 1.6            | 0.8            |
| 510                    | 27250B511J00           | 4.7                         | 3.3          | 1.6            | 0.8            |
| 560                    | 27250B561J00           | 5.1                         | 3.6          | 1.8            | 0.8            |
| 600                    | 27250B601J00           | 5.1                         | 3.6          | 1.8            | 0.8            |
| 620                    | 27250B621J00           | 5.1                         | 3.6          | 1.8            | 0.8            |
| 680                    | 27250B681J00           | 2.1                         | 3.6          | 1.8            | 0.8            |
| 750                    | 27250B751J00           | 5.6                         | 3.9          | 2.2            | 0.9            |

| Cap<br>(pF)             | Catalog<br>Part Number | Maximum AC Current at 65 °C |              |                |                |
|-------------------------|------------------------|-----------------------------|--------------|----------------|----------------|
|                         |                        | 3 MHz<br>(A)                | 1 MHz<br>(A) | 300 kHz<br>(A) | 100 kHz<br>(A) |
| <b>5000 Peak Volts</b>  |                        |                             |              |                |                |
| 820                     | 27250B821J00           | 5.6                         | 3.9          | 2.4            | 1.0            |
| 910                     | 27250B911J00           | 5.6                         | 4.3          | 2.4            | 1.1            |
| 1000                    | 27250B102J00           | 6.2                         | 4.3          | 2.4            | 1.2            |
| 1100                    | 27250B112J00           | 6.2                         | 4.7          | 2.7            | 1.2            |
| 1200                    | 27250B122J00           | 6.2                         | 4.7          | 2.7            | 1.3            |
| 1300                    | 27250B132J00           | 6.8                         | 5.1          | 3.0            | 1.3            |
| 1500                    | 27250B152J00           | 6.8                         | 5.1          | 3.3            | 1.5            |
| 1600                    | 27250B162J00           | 6.8                         | 5.6          | 3.6            | 1.5            |
| 1800                    | 27250B182J00           | 7.5                         | 5.6          | 3.6            | 1.6            |
| 2000                    | 27250B202J00           | 7.5                         | 6.2          | 3.6            | 1.8            |
| 2200                    | 27250B222J00           | 7.5                         | 6.2          | 3.9            | 2.0            |
| 2400                    | 27250B242J00           | 8.2                         | 6.2          | 4.3            | 2.0            |
| <b>40000 Peak Volts</b> |                        |                             |              |                |                |
| 1100                    | 272400B112J00          | 15.5                        | 12.7         | 8.0            | 4.7            |
| 1300                    | 272400B132J00          | 18.7                        | 15.5         | 9.8            | 5.9            |
| 1500                    | 272400B152J00          | 19.4                        | 16.4         | 10.5           | 6.3            |
| <b>50000 Peak Volts</b> |                        |                             |              |                |                |
| 900                     | 272500B901J00          | 16.4                        | 13.1         | 8.2            | 4.9            |
| 1000                    | 272500B102J00          | 16.6                        | 13.5         | 8.6            | 5.1            |
| 1200                    | 272500B122J00          | 18.1                        | 14.9         | 9.4            | 5.6            |
| <b>60000 Peak Volts</b> |                        |                             |              |                |                |
| 800                     | 272600B801J00          | 16.0                        | 12.5         | 7.7            | 4.6            |
| 900                     | 272600B901J00          | 16.4                        | 13.1         | 8.2            | 4.9            |
| 1000                    | 272600B102J00          | 16.3                        | 13.3         | 8.5            | 5.1            |

## Type 273 Ratings

| <b>400 Peak Volts</b>  |              |      |      |      |      |
|------------------------|--------------|------|------|------|------|
| 1000000                | 27304B204J00 | 18.0 | 25.0 | 22.0 | 12.0 |
| <b>600 Peak Volts</b>  |              |      |      |      |      |
| 200000                 | 27306B204J00 | 18.0 | 25.0 | 22.0 | 12.0 |
| 250000                 | 27306B254J00 | 18.0 | 25.0 | 22.0 | 12.0 |
| 300000                 | 27306B304J00 | 18.0 | 25.0 | 22.0 | 12.0 |
| 400000                 | 27306B404J00 | 18.0 | 25.0 | 22.0 | 12.0 |
| 500000                 | 27306B504J00 | 18.0 | 25.0 | 22.0 | 12.0 |
| 600000                 | 27306B604J00 | 18.0 | 25.0 | 22.0 | 12.0 |
| 750000                 | 27306B754J00 | 18.0 | 25.0 | 22.0 | 12.0 |
| <b>2000 Peak Volts</b> |              |      |      |      |      |
| 100000                 | 27320B104J00 | 18.0 | 23.0 | 18.0 | 10.5 |
| <b>4000 Peak Volts</b> |              |      |      |      |      |
| 25000                  | 27340B253J00 | 18.0 | 24.0 | 19.0 | 11.5 |
| 30000                  | 27340B303J00 | 18.0 | 24.0 | 19.0 | 11.5 |

# High-Voltage Types Application Guide, Transmitting Mica

## Type 273 Ratings

| Cap<br>(pF)            | Catalog<br>Part Number | Maximum AC Current at 65 °C |              |                |                |
|------------------------|------------------------|-----------------------------|--------------|----------------|----------------|
|                        |                        | 3 MHz<br>(A)                | 1 MHz<br>(A) | 300 kHz<br>(A) | 100 kHz<br>(A) |
| <b>4000 Peak Volts</b> |                        |                             |              |                |                |
| 40000                  | 27340B403JO0           | 18.0                        | 24.0         | 20.0           | 12.0           |
| 50000                  | 27340B503JO0           | 18.0                        | 25.0         | 21.0           | 12.0           |
| <b>5000 Peak Volts</b> |                        |                             |              |                |                |
| 20000                  | 27350B203JO0           | 18.0                        | 23.0         | 18.0           | 10.5           |
| <b>8000 Peak Volts</b> |                        |                             |              |                |                |
| 200                    | 27380B201JO0           | 7.5                         | 5.0          | 1.5            | 0.5            |
| 250                    | 27380B251JO0           | 7.5                         | 5.0          | 1.5            | 0.5            |
| 500                    | 27380B501JO0           | 8.5                         | 6.0          | 3.0            | 1.0            |

| Cap<br>(pF)            | Catalog<br>Part Number | Maximum AC Current at 65 °C |              |                |                |
|------------------------|------------------------|-----------------------------|--------------|----------------|----------------|
|                        |                        | 3 MHz<br>(A)                | 1 MHz<br>(A) | 300 kHz<br>(A) | 100 kHz<br>(A) |
| <b>8000 Peak Volts</b> |                        |                             |              |                |                |
| 1000                   | 27380B102JO0           | 10.0                        | 8.5          | 4.5            | 1.5            |
| 2000                   | 27380B202JO0           | 11.5                        | 11.5         | 7.5            | 3.0            |
| 3000                   | 27380B302JO0           | 12.5                        | 13.5         | 9.5            | 4.0            |
| 4000                   | 27380B402JO0           | 13.5                        | 15.5         | 10.5           | 5.0            |
| 4500                   | 27380B452JO0           | 14.0                        | 16.0         | 11.5           | 6.0            |
| 5000                   | 27380B502JO0           | 14.0                        | 16.0         | 11.5           | 6.0            |
| 6000                   | 27380B602JO0           | 15.0                        | 17.0         | 12.5           | 6.5            |
| 8000                   | 27380B802JO0           | 16.0                        | 19.0         | 14.0           | 7.5            |
| 60000                  | 27380B103JO0           | 17.0                        | 20.0         | 15.0           | 8.5            |


## Dimensions

### Type 271



# High-Voltage Types Application Guide, Transmitting Mica

## Type 272



## Type 272 (30 kVpk to 60 kVpk)



# High-Voltage Types Application Guide, Transmitting Mica

## Type 273



Tolerances Unless  
Otherwise Specified  $\pm .031$


**Type 271 (CM 66)**  
**Rated Current Versus Frequency**



**Type 273**  
**Rated Current Versus Frequency**



**Type 272 (CM 71)**  
**Rated Current Versus Frequency**




# High-Voltage Types Ordering Information, Mica Capacitors

## Ordering Information

Ordering Information: Order by complete part number, as below. For other options, write your requirements on your quote request or purchase order.

## Cast-Case Part Numbering System



|          | Temp. Coeff.<br>ppm/°C | Capacitance Drift | Standard Cap. Range |
|----------|------------------------|-------------------|---------------------|
| <b>B</b> | Not specified          | Not specified     |                     |
| <b>C</b> | -200 to +200           | ±(0.5% +0.1pF)    | 1-18 pF             |
| <b>D</b> | -100 to +100           | ±(0.3% +0.1pF)    |                     |
| <b>E</b> | - 20 to +100           | ±(0.1% +0.1pF)    | 20-82 pF            |



## Specifications

**Capacitance** is within tolerance when measured at these frequencies:

- 1–1000 pF @ 1 MHz
- > 1000 pF @ 1 kHz

**Dissipation Factor** is typically less than 0.05% when measured as above. Dissipation factor (DF) equals  $2\pi fRC$ , where  $f$  is the test frequency,  $R$  is the equivalent series resistance ( $\Omega$ ), and  $C$  is nominal capacitance (F).  $Q$  is the reciprocal of the dissipation factor.

**Operating Temperature Range** is  $-55\text{ }^{\circ}\text{C}$  to  $+125\text{ }^{\circ}\text{C}$ . Insulation Resistance is no less than  $7500\text{ M}\Omega$  when measured at 100 Vdc.

**Temperature Coefficient and Capacitance Drift:** Measure the capacitors' capacitance at  $25\text{ }^{\circ}\text{C}$ ,  $55\text{ }^{\circ}\text{C}$ ,  $25\text{ }^{\circ}\text{C}$ ,  $125\text{ }^{\circ}\text{C}$ , and at  $25\text{ }^{\circ}\text{C}$  after stabilizing at each temperature. The capacitance will meet the limits of the Characteristic table shown in Ordering Information.

**Rated Peak Voltage** is not to be exceeded in actual use. Voltage ratings are in the listings and apply under the following conditions:

- Temperature: Within the specified operating temperature range.
- Altitude: Up to 50,000 feet or 3.4 inches of mercury.
- Relative Humidity: Up to 80%.
- Frequency: As specified.
- Where pulse conditions are encountered, contact us.

**Withstanding Voltage:** Capacitors will withstand application of an ac potential between terminals having an rms value equal to the rated peak voltage at a frequency of 100 Hz or less without damage, arcing or breakdown. Apply the potential by raising the voltage from zero to the specified value. Apply the full potential for a minimum of 5 seconds.

**Case Insulation:** Capacitor cases will withstand, without damage, arcing or breakdown, a 60-Hz peak ac potential equal to twice the rated peak voltage applied between the terminals connected together and a metal electrode touching the case. Apply this potential for 1 to 5 seconds.

**Current Ratings** at various frequencies are in the listings and apply under the following conditions:

- Temperature:  $65\text{ }^{\circ}\text{C}$  maximum
- Derating Factor: None

**Vibration:** Capacitors will withstand vibrational forces occurring at rates of from 10 to 55 Hz for  $4\frac{1}{2}$  hours. The total excursion during vibration is 0.06 inches. At the end of this period, make the following inspections and tests:

Visual and Mechanical Inspection: No perceptible deterioration. Withstanding Voltage: As specified under Withstanding Voltage.

Insulation Resistance: No less than  $7500\text{ M}\Omega$ .

Capacitance Change: Not to exceed 3% of the nominal value or one picofarad, whichever is greater.

**Temperature and Immersion Cycling:** Capacitors will withstand the temperature and immersion cycles indicated in the tables below. Follow three temperature cycles by two immersion cycles. Make the measurements listed below no more than 30 minutes following the final immersion cycle:

Withstanding Voltage: As specified under Withstanding Voltage.

Insulation Resistance: No less than  $7500\text{ M}\Omega$ .

Capacitance: Change not to exceed 4% of the nominal value or one picofarad, whichever is greater.

## Temperature Cycling Test Conditions

| Steps | Temp (°C)         | Interval (Minutes) |
|-------|-------------------|--------------------|
| 1     | $-55 + 0$<br>$-3$ | 30                 |
| 2     | $25 + 10$<br>$-5$ | 10 to 15           |
| 3     | $125 + 3$<br>$-0$ | 30                 |
| 4     | $25 + 10$<br>$-5$ | 10 to 15           |

## Immersion Test Conditions

- Number of cycles: 2
- Duration of each immersion: 15 minutes
- Immersion bath: Saturated solution of sodium chloride and water
- Temp. of hot bath:  $65 - 0 + 5\text{ }^{\circ}\text{C}$
- Temp. of cold bath:  $25 - 0 + 10\text{ }^{\circ}\text{C}$

**Life Test:** Subject all capacitors to a temperature of  $55\text{ }^{\circ}\text{C}$  for 48 hours. Then subject units cast in rectangular cases (Types 271, 272, and 273) to a 60-Hz rms voltage equal to the rated peak voltage for 250 hours. Subject units cast in cylindrical cases (Types 291, 292, 293, and 294) to a 60-Hz rms voltage equal to 90% of the rated peak voltage for 250 hours. In both tests, maintain the temperature at  $125\text{ }^{\circ}\text{C}$ . After test, the capacitors will meet these requirements:

Withstanding Voltage: As specified under Withstanding Voltage.

Insulation Resistance: No less than  $7500\text{ M}\Omega$ .

Capacitance Change: Within the limits given in the table below or one picofarad, whichever is greater.

## Characteristic Maximum Cap.

|          |           |
|----------|-----------|
| <b>B</b> | $\pm 8\%$ |
| <b>C</b> | $\pm 3\%$ |
| <b>D</b> | $\pm 3\%$ |
| <b>E</b> | $\pm 3\%$ |

In addition, the capacitor must show no visual damage and the markings must be legible.

## High-Voltage Types **Application Guide, Transmitting Mica**

---

**Notice and Disclaimer:** All product drawings, descriptions, specifications, statements, information and data (collectively, the "Information") in this datasheet or other publication are subject to change. The customer is responsible for checking, confirming and verifying the extent to which the Information contained in this datasheet or other publication is applicable to an order at the time the order is placed. All Information given herein is believed to be accurate and reliable, but it is presented without any guarantee, warranty, representation or responsibility of any kind, expressed or implied. Statements of suitability for certain applications are based on the knowledge that the Cornell Dubilier company providing such statements ("Cornell Dubilier") has of operating conditions that such Cornell Dubilier company regards as typical for such applications, but are not intended to constitute any guarantee, warranty or representation regarding any such matter – and Cornell Dubilier specifically and expressly disclaims any guarantee, warranty or representation concerning the suitability for a specific customer application, use, storage, transportation, or operating environment. The Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by Cornell Dubilier with reference to the use of any Cornell Dubilier products is given gratis (unless otherwise specified by Cornell Dubilier), and Cornell Dubilier assumes no obligation or liability for the advice given or results obtained. Although Cornell Dubilier strives to apply the most stringent quality and safety standards regarding the design and manufacturing of its products, in light of the current state of the art, isolated component failures may still occur. Accordingly, customer applications which require a high degree of reliability or safety should employ suitable designs or other safeguards (such as installation of protective circuitry or redundancies or other appropriate protective measures) in order to ensure that the failure of an electrical component does not result in a risk of personal injury or property damage. Although all product-related warnings, cautions and notes must be observed, the customer should not assume that all safety measures are indicated in such warnings, cautions and notes, or that other safety measures may not be required.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А