



LOC	DIST	REVISIONS						
		P	LTR	DESCRIPTION	DATE	DWN	APVD	
GP	00		A	RELEASED	24MAR2010	RG	MS	
			B	REV PER ECO-10-017024	31AUG2010	RG	MS	
			C	REV PER ECO-11-006492	13APR2011	RG	MS	
			C1	REV PER ECR-13-001498	28JAN2012	OL	SZ	



ISOMETRIC FRONT VIEW



ISOMETRIC REAR VIEW

△ HOUSING: GLASS FILLED LIQUID CRYSTAL POLYMER, COLOR: BLACK, UL 94V-0 RATED.
SIGNAL CONTACT: PHOSPHOR BRONZE.
SIGNAL OVERMOLD: GLASS FILLED POLYESTER.
POWER CONTACT: COPPER ALLOY.

△ SIGNAL CONTACT: 0.00127mm MIN NICKEL ALL OVER,
MATING AREA: 0.00076mm MIN GOLD OR 0.00008mm MIN GOLD OVER
0.00076mm MIN PALLADIUM-NICKEL.
TAIL AREA: 0.0005mm MIN MATTE TIN.

POWER CONTACT: 0.00127mm MIN NICKEL ALL OVER,
MATING AREA: 0.00076mm MIN GOLD OR
0.00008mm MIN GOLD OVER 0.00076mm MIN PALLADIUM-NICKEL,
TAIL AREA: 0.0005mm MIN MATTE TIN.

3 CONTACT MATING AREA LUBRICATED WITH BELLCORE APPROVED LUBRICANT,
TECHNICAL REFERENCE: GR-1217-CORE, ISSUE 1, NOVEMBER 1995.

4 CONNECTOR ASSEMBLY MARKED WITH PART NUMBER AND DATE CODE.

△ DATUMS AND BASIC DIMENSIONS TO BE ESTABLISHED BY CUSTOMER.

△ PC BOARD THICKNESS 1.4mm MIN.
WAVE SOLDER PC BOARD THICKNESS 2.6S MAX

△ SEE APPLICATION SPEC 114-13215 FOR PLATED THRU HOLE INFORMATION

8. SEE CUSTOMER DRAWING 1926733 OR 1926731 FOR MATING RECEPTACLE CONNECTOR.

△ CUSTOMER TO SPECIFY LOAD PATTERNS. SEE PAGE 3 FOR WORKSHEET





△ #4-40 UNC PAN HEAD SCREW WITH HEX NUT NOT SHOWN,
SUPPLIED BY CUSTOMER.

△ UNPLATED HOLES

12. THIS CONNECTOR EMPLOYS UL RECOGNIZED Z-PACK 2mm HM CONNECTOR
AT SIGNALS.

(1) DIMENSION 11-2 CONTAINED INFORMATION IS THE PROPERTY OF THE ORGANIZATION AND IS NOT TO BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM.		DWN G. PETERS 15FEB2010	 Tyco Electronics Corporation Harrisburg, PA 17105-3608	
DIMENSIONS:		CHK M. SYKES 15FEB2010		
mm	TOLERANCES UNLESS OTHERWISE SPECIFIED:	APVD M. SYKES	NAME	PLUG ASSEMBLY, RIGHT ANGLE, PASSIVE GUIDE, SIGNAL/POWER WITH SCREW MOUNT, SEQUENCED, MINIPAK HDL
	0 PLC ±" 1 PLC ±" 2 PLC ±0.13 3 PLC ±" 4 PLC ±" ANGLES ±" FINISH #1	PRODUCT SPEC 108-2325 APPLICATION SPEC 114-13215	SIZE	CAGE CODE DRAWING NO A100779C-1926736
MATERIAL 		WEIGHT -	RESTRICTED TO	
Customer Drawing		SCALE 1:1 SHEET 1 OF 4 REV C		

LOC	DIST	REVISIONS				
		P	LTR	DESCRIPTION	DATE	DWN
GP	00	-	-	SEE SHEET 1	-	-



52.71	60	25	9	4	47.31	51.71	1926736-3
52.71	60	25	9	4	47.31	51.71	1926736-2
52.71	60	25	9	4	47.31	51.71	1926736-1
G	F QTY	E QTY	"D" SPACES	"C" SPACES	B	A	PART NUMBER

100% PROPERTY OF TYCO ELECTRONICS CORPORATION IT IS SUBJECT TO CHANGE WITHOUT NOTICE TYCO ELECTRONICS CORPORATION SHOULD BE CONTACTED FOR THE LATEST REVISION		DWN G. PETERS 15FEB2010	Tyco Electronics Corporation Harrisburg, PA 17105-3608	
DIMENSIONS: mm		CHK M. SYKES 15FEB2010	NAME PLUG ASSEMBLY, RIGHT ANGLE, PASSIVE GUIDE, SIGNAL/POWER WITH SCREW MOUNT, SEQUENCED, MINIPAK HDL	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD M. SYKES	PRODUCT SPEC	
0 PLC ±		108-2325	APPLICATION SPEC	
1 PLC ±0.13		114-13215	SIZE	
2 PLC ±		114-13215	CAGE CODE	
3 PLC ±		114-13215	DRAWING NO	
4 PLC ±		114-13215	RESTRICTED TO	
ANGLES ±#1		114-13215	A100779C=1926736	
FINISH		114-13215	Customer Drawing	
MATERIAL		114-13215	SCALE 1:1	
		114-13215	SHEET 2 OF 4	
		114-13215	REV C1	


LOC	DIST	REVISIONS					
GP	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
			-	SEE SHEET 1	-	-	-

CUSTOM LOADING WORKSHEET FOR SIGNAL & POWER SEQUENCING LEVELS																																	
MINIPAK HDL - MATING FACE OF PLUG CONNECTOR***																																	
E									COLUMNS																								
D																																	
C																																	
B																																	
A																																	
ROWS	1	2	3	4	5	6	7	8		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24
	SIGNAL CHICKLETS*									POWER CONTACTS**																							


*LOAD WITH CHOICE OF 3 CHICKLETS
SEE SECTIONS KA, KB, & KC FOR
AVAILABLE LENGTH OPTIONS.

** LOAD WITH CHOICE OF 2 POWER
CONTACT MATING LENGTHS, SEE SEC.
MM FOR AVAILABLE LENGTH OPTIONS.


***CUSTOM LOADING WORKSHEET SHOWN AT MAXIMUM SIZE CONFIGURABLE (40S X 24P),
SIGNALS AVAILABLE IN 2,3,4 THRU 8 POSITIONS, POWERS AVAILABLE IN 4,6,8,
10,THRU 24 POSITIONS IN EVEN QUANTITIES ONLY.




SECTION KA
(LEVEL 2: ALL LONGEST CONTACT)




SECTION KB
(LEVEL 12222:
LEVEL 1 ROW "A" ONLY
LEVEL 2 ROWS "B" THRU "E")



SECTION KC
(LEVEL 1: SHORTEST CONTACT)



SECTION R
LEVEL 2, SHORTEST
MATING CONTACTS



SECTION M
LEVEL 3, LONGEST
MATING CONTACT

1ST PREPARED BY: G. PETERS 1ST IS SUBJECT TO COMPANY'S QUALITY CONTROL AND INSPECTION ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION.		DWN: G. PETERS 15FEB2010 CHK: M. SYKES 15FEB2010		Tyco Electronics Corporation Harrisburg, PA 17105-3608	
DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ±.1 1 PLC ±.13 2 PLC ±.13 3 PLC ±.13 4 PLC ±.13 ANGLES ±.1 FINISH		NAME: PLUG ASSEMBLY, RIGHT ANGLE, PASSIVE GUIDE, SIGNAL/POWER WITH SCREW MOUNT, SEQUENCED, MINIPAK HDL	
MATERIAL: -		PRODUCT SPEC: 108-2325 APPLICATION SPEC: 114-13215 WEIGHT: -		SIZE: A100779 CAGE CODE: C=1926736 DRAWING NO: -	
Customer Drawing		SCALE: 1:1		SHEET 3 OF 4 REV C1	

LOC	DIST	REVISIONS					
GP	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
		-	SEE SHEET 1		-	-	-

PART NUMBER	ROWS			SIGNALS					POWERS												
				1	2	3	4	5	1	2	3	4	5	6	7	8	9	10			
1926736-1	A			KA	KA	2	3	2	2	KA	KA	R	R	R	R	R	R	R	R	R	
	B						2	3													
	C																				
	D																				
	E																				
25S X 10P																					

-1 PRELIMINARY

PART NUMBER	ROWS			SIGNALS					POWERS										
				1	2	3	4	5	1	2	3	4	5	6	7	8	9	10	
1926736-2	A			KA	KA	KB	KA	KA	R	R	R	R	R	R	R	R	R		
	B																		
	C																		
	D																		
	E																		
25S X 10P																			

PART NUMBER	ROWS		SIGNALS					POWERS										
			1	2	3	4	5	1	2	3	4	5	6	7	8	9	10	
1926736-3	A		KA	KA	KA	KA	KC	R	R	R	R	R	R	R	R	R	R	
	B																	
	C																	
	D																	
	E																	
25S X 10P																		

THIS DRAWING IS A CONTROLLED DOCUMENT FOR TYCO ELECTRONICS CORPORATION. IT IS SUBJECT TO CHANGE AND REVISIONS. ANY CHANGES TO THIS DRAWING SHOULD BE CONTACTED FOR THE LATEST REVISION.		DWN G. PETERS 15FEB2010	Tyco Electronics Corporation Harrisburg, PA 17105-3608	
DIMENSIONS: mm		CHK M. SYKES 15FEB2010	NAME PLUG ASSEMBLY, RIGHT ANGLE, PASSIVE GUIDE, SIGNAL/POWER WITH SCREW MOUNT, SEQUENCED, MINIPAK HDL	
		APVD M. SYKES		
	TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± 1 PLC ± 2 PLC ±0.13 3 PLC ± 4 PLC ± ANGLES ± FINISH	PRODUCT SPEC		SIZE A100779
		108-2325		
		APPLICATION SPEC		
		114-13215		
MATERIAL	-	WEIGHT	Customer Drawing	
	-		SCALE	1:1
			SHEET	4 OF 4
			REV	C

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А