


# Book-style EMC/RFI Filter for Inverters and Power Drive Systems



- Industry standard EMC solution for three-phase PDS filtering
- Slim space-saving book-style housing
- Solid safety connector blocks or optional wire output connections
- Excellent attenuation performance
- HV versions for up to 690 VAC
- HVIT versions for IT distribution networks
- P/L versions with low leakage current




## Performance indicators

Attenuation performance



Rated current [A]



## Technical specifications

|                                                  |                                                                                                                                                                                                                                                                                                                                            |
|--------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Maximum continuous operating voltage</b>      | 3x 520/300 VAC (FN 258, FN 258 L, FN 258 P)<br>3x 760/440 VAC (FN 258 HV, FN 258 HVIT)                                                                                                                                                                                                                                                     |
| <b>Rated currents</b>                            | 7 to 250 A @50°C (480 V filters)                                                                                                                                                                                                                                                                                                           |
| <b>Operating frequency</b>                       | DC to 60 Hz                                                                                                                                                                                                                                                                                                                                |
| <b>High potential test voltage</b>               | P → E 2650 VDC for 2 sec (FN 258)<br>P → P 2100 VDC for 2 sec (FN 258)<br>P → E 2000 VAC for 2 sec (FN 258L)<br>P → P 2100 VDC for 2 sec (FN 258L)<br>P → E 3000 VDC for 2 sec (FN 258P)<br>P → P 2100 VDC for 2 sec (FN 258P)<br>P → E 3200 VDC for 2 sec (FN 258HV and FN 258HVIT)<br>P → P 3270 VDC for 2 sec (FN 258HV and FN 258HVIT) |
| <b>Protection category</b>                       | IP 20                                                                                                                                                                                                                                                                                                                                      |
| <b>Overload capability</b>                       | 4x rated current at switch on,<br>1.5x rated current for 1 minute, once per hour                                                                                                                                                                                                                                                           |
| <b>Temperature range (operation and storage)</b> | -25°C to +100°C (25/100/21)                                                                                                                                                                                                                                                                                                                |
| <b>Flammability corresponding to</b>             | UL 94 V-2 or better                                                                                                                                                                                                                                                                                                                        |
| <b>Design corresponding to</b>                   | UL 1283, CSA 22.2 No. 8 1986, IEC/EN 60939                                                                                                                                                                                                                                                                                                 |
| <b>MTBF @ 50°C/400 V (Mil-HB-217F)</b>           | 220,000 hours                                                                                                                                                                                                                                                                                                                              |

## Approvals



UL/CSA: FN 258 up to 180 A (ex. -180-07)


## Features and benefits

- FN 258 range of filters provides state-of-the-art EMI attenuation based on an innovative multi-stage filter topology. They help to ensure compliance with Class A or even Class B limits
- The slim book-style shape allows a convenient and space-saving installation next to inverters and motor drives
- With 480 VAC rating and filter modules from 7 to 250 A, FN 258 are ready for the most diverse applications worldwide
- FN 258 HV filters up to 130 A are designed for 690 VAC distribution networks
- FN 258 HVIT filters up to 130 A meet the special requirements for the application in industrial 690 VAC IT distribution networks
- FN 258 L and FN 258 P filters help to fulfill tough requirements in respect of leakage current limitation and provide an excellent solution to overcome problems with nuisance tripping of sensitive earth leakage detectors

## Typical applications

- Three-phase variable speed drives and power drive systems (PDS)
- IT power distribution networks (FN 258 HVIT)
- Applications comprising energy conversion devices (inverters, converters)
- Process automation equipment
- Three-phase power supplies and UPS
- Applications with low-leakage current requirements (FN 258 L and FN 258 P)

## Typical electrical schematic



Note: HVIT versions without discharge resistor to ground.

## Filter selection table

| Filter*            | Rated current<br>@ 50°C (40°C)<br>[A] | Typical drive<br>power rating**<br>[kW] | Leakage current***<br>@ 520/760 VAC/50 Hz<br>[mA] | Power loss<br>@ 25°C/50 Hz<br>[W] | Input<br>connections | Output<br>connections |     | Weight<br>[kg] |
|--------------------|---------------------------------------|-----------------------------------------|---------------------------------------------------|-----------------------------------|----------------------|-----------------------|-----|----------------|
|                    |                                       |                                         |                                                   |                                   |                      |                       |     |                |
| FN 258-7-..        | 7 (7.7)                               | 4                                       | 2.0                                               | 9                                 | -29                  | -07                   | -29 | 1.0            |
| FN 258-16-..       | 16 (17.5)                             | 7.5                                     | 2.1                                               | 20                                | -29                  | -07                   | -29 | 1.4            |
| FN 258-30-..       | 30 (33)                               | 15                                      | 2.9                                               | 21                                | -33                  | -07                   | -33 | 1.7            |
| FN 258-42-..       | 42 (46)                               | 22                                      | 3.0                                               | 30                                | -33                  | -07                   | -33 | 2.5            |
| FN 258-55-..       | 55 (60)                               | 30                                      | 3.0                                               | 30                                | -34                  | -07                   | -34 | 2.9            |
| FN 258-75-34       | 75 (82)                               | 37                                      | 3.0                                               | 24                                | -34                  |                       | -34 | 3.9            |
| FN 258-100-35      | 100 (110)                             | 55                                      | 3.0                                               | 51                                | -35                  |                       | -35 | 5.5            |
| FN 258-130-35      | 130 (143)                             | 75                                      | 3.5                                               | 50                                | -35                  |                       | -35 | 6.9            |
| FN 258-180-..      | 180 (197)                             | 90                                      | 3.5                                               | 73                                | -40                  | -07                   | -40 | 11.0           |
| FN 258-250-..      | 250 (275)                             | 132                                     | 3.4                                               | 79                                | -40                  | -07                   | -40 | 12.0           |
| FN 258 HV-7-29     | 7 (7.7)                               | 5.5                                     | 1.6                                               | 9                                 | -29                  |                       | -29 | 1.0            |
| FN 258 HV-16-29    | 16 (17.5)                             | 11                                      | 2.3                                               | 20                                | -29                  |                       | -29 | 1.5            |
| FN 258 HV-30-33    | 30 (33)                               | 22                                      | 2.3                                               | 21                                | -33                  |                       | -33 | 1.8            |
| FN 258 HV-42-33    | 42 (46)                               | 30                                      | 2.6                                               | 30                                | -33                  |                       | -33 | 2.6            |
| FN 258 HV-55-34    | 55 (60)                               | 45                                      | 2.6                                               | 30                                | -34                  |                       | -34 | 3.0            |
| FN 258 HV-75-34    | 75 (82)                               | 55                                      | 2.6                                               | 24                                | -34                  |                       | -34 | 4.3            |
| FN 258 HV-100-35   | 100 (110)                             | 90                                      | 2.6                                               | 51                                | -35                  |                       | -35 | 5.6            |
| FN 258 HV-130-35   | 130 (143)                             | 110                                     | 2.9                                               | 50                                | -35                  |                       | -35 | 7.1            |
| FN 258 HVIT-7-29   | 7 (7.7)                               | 5.5                                     | 0.1                                               | 9                                 | -29                  |                       | -29 | 1.0            |
| FN 258 HVIT-16-29  | 16 (17.5)                             | 11                                      | 0.1                                               | 20                                | -29                  |                       | -29 | 1.5            |
| FN 258 HVIT-30-33  | 30 (33)                               | 22                                      | 0.1                                               | 21                                | -33                  |                       | -33 | 1.8            |
| FN 258 HVIT-42-33  | 42 (46)                               | 30                                      | 0.1                                               | 30                                | -33                  |                       | -33 | 2.6            |
| FN 258 HVIT-55-34  | 55 (60)                               | 45                                      | 2.6                                               | 30                                | -34                  |                       | -34 | 3.0            |
| FN 258 HVIT-75-34  | 75 (82)                               | 55                                      | 2.6                                               | 24                                | -34                  |                       | -34 | 4.3            |
| FN 258 HVIT-100-35 | 100 (110)                             | 90                                      | 2.6                                               | 51                                | -35                  |                       | -35 | 5.6            |
| FN 258 HVIT-130-35 | 130 (143)                             | 110                                     | 2.9                                               | 50                                | -35                  |                       | -35 | 7.1            |
| FN 258 L-7-..      | 7 (7.7)                               | 4                                       | 0.1                                               | 9                                 | -29                  | -07                   | -29 | 1.0            |
| FN 258 L-16-..     | 16 (17.5)                             | 7.5                                     | 0.1                                               | 20                                | -29                  | -07                   | -29 | 1.4            |
| FN 258 L-30-..     | 30 (33)                               | 15                                      | 0.1                                               | 21                                | -33                  | -07                   | -33 | 1.7            |
| FN 258 L-42-..     | 42 (46)                               | 22                                      | 0.1                                               | 30                                | -33                  | -07                   | -33 | 2.5            |
| FN 258 L-55-..     | 55 (60)                               | 30                                      | 0.1                                               | 30                                | -34                  | -07                   | -34 | 2.9            |
| FN 258 L-75-34     | 75 (82)                               | 37                                      | 0.1                                               | 24                                | -34                  |                       | -34 | 3.9            |
| FN 258 L-100-35    | 100 (110)                             | 55                                      | 0.1                                               | 51                                | -35                  |                       | -35 | 5.5            |
| FN 258 L-130-35    | 130 (143)                             | 75                                      | 0.1                                               | 50                                | -35                  |                       | -35 | 6.9            |
| FN 258 L-180-..    | 180 (197)                             | 90                                      | 0.1                                               | 73                                | -40                  | -07                   | -40 | 11.0           |
| FN 258 L-250-07    | 250 (275)                             | 132                                     | 0.1                                               | 79                                | -40                  | -07                   |     | 12.0           |
| FN 258 P-7-..      | 7 (7.7)                               | 4                                       | 0.4                                               | 9                                 | -29                  | -07                   | -29 | 1.0            |
| FN 258 P-16-..     | 16 (17.5)                             | 7.5                                     | 0.4                                               | 20                                | -29                  | -07                   | -29 | 1.4            |
| FN 258 P-30-..     | 30 (33)                               | 15                                      | 0.4                                               | 21                                | -33                  | -07                   | -33 | 1.7            |
| FN 258 P-42-..     | 42 (46)                               | 22                                      | 0.4                                               | 30                                | -33                  | -07                   | -33 | 2.5            |
| FN 258 P-55-..     | 55 (60)                               | 30                                      | 0.4                                               | 30                                | -34                  | -07                   | -34 | 2.9            |
| FN 258 P-75-34     | 75 (82)                               | 37                                      | 0.4                                               | 24                                | -34                  |                       | -34 | 3.9            |
| FN 258 P-100-35    | 100 (110)                             | 55                                      | 0.4                                               | 51                                | -35                  |                       | -35 | 5.5            |
| FN 258 P-130-35    | 130 (143)                             | 75                                      | 0.4                                               | 50                                | -35                  |                       | -35 | 6.9            |
| FN 258 P-180-..    | 180 (197)                             | 90                                      | 0.4                                               | 73                                | -40                  | -07                   | -40 | 11.0           |
| FN 258 P-250-07    | 250 (275)                             | 132                                     | 0.4                                               | 79                                | -40                  | -07                   |     | 12.0           |

\* To compile a complete part number, please replace the -.. with the required output connection style.


\*\* Calculated at rated current, 440 VAC (FN 258)/690 VAC (FN 258 HV) and  $\cos \phi = 0.8$ . The exact value depends upon the efficiency of the drive, the motor and the entire application.

\*\*\* Standardized calculated leakage current acc. IEC60939 under normal operating conditions (FN 258 at 520 VAC and FN 258 HV at 760 VAC).


## Typical filter attenuation

Per CISPR 17; A=50  $\Omega$ /50  $\Omega$  sym; B=50  $\Omega$ /50  $\Omega$  asym; C=0.1  $\Omega$ /100  $\Omega$  sym; D=100  $\Omega$ /0.1  $\Omega$  sym


7 to 30 A types




42 to 100 A types



130 A types




180 and 250 A types




Note: typical attenuation performance of FN 258 standard filters. The behavior of FN 258 HV, FN 258 HVT, FN 258 P and FN 258 L may be slightly different.

## Mechanical data


7 to 55 A types (-07)




7 to 130 A types (-29, -33, -34, -35)



180 and 250 A types (-07)



180 and 250 A types (-40)



Note: in favour of a better readability, connectors and earth studs are not shown in the horizontal projection.

## Dimensions

|           | 7 A     | 16 A    | 30 A    | 42 A    | 55 A    | 75 A | 100 A | 130 A | 180 A              | 250 A              |
|-----------|---------|---------|---------|---------|---------|------|-------|-------|--------------------|--------------------|
| <b>A</b>  | 255     | 305     | 335     | 329     | 329     | 329  | 379   | 439   | 438                | 478                |
| <b>B</b>  | 50      | 55      | 60      | 70      | 80      | 80   | 90    | 110   | 110                | 110                |
| <b>C</b>  | 126     | 142     | 150     | 185     | 185     | 220  | 220   | 240   | 240                | 240                |
| <b>D</b>  | 225     | 275     | 305     | 300     | 300     | 300  | 350   | 400   | 400                | 440                |
| <b>E</b>  | 240     | 290     | 320     | 314     | 314     | 314  | 364   | 414   | 413                | 453                |
| <b>F</b>  | 25      | 30      | 35      | 45      | 55      | 55   | 65    | 80    | 80                 | 80                 |
| <b>G</b>  | 6.5     | 6.5     | 6.5     | 6.5     | 6.5     | 6.5  | 6.5   | 6.5   | 6.5                | 6.5                |
| <b>H</b>  | 1       | 1       | 1       | 1.5     | 1.5     | 1.5  | 1.5   | 3     | 4                  | 4                  |
| <b>I</b>  | 10.9    | 10.9    | 25      | 25      | 39      | 39   | 45    | 45    | 51                 | 51                 |
| <b>J</b>  | M5      | M5      | M5      | M6      | M6      | M6   | M10   | M10   | M10                | M10                |
| <b>K</b>  | 25      | 27.5    | 30      | 35      | 40      | 40   | 45    | 55    | 55                 | 55                 |
| <b>L</b>  | 85      | 100     | 110     | 130     | 105     | 140  | 130   | 140   | 110                | 110                |
| <b>X*</b> | AWG 16  | AWG 14  | AWG 10  | AWG 8   | AWG 6   |      |       |       | 50 mm <sup>2</sup> | 70 mm <sup>2</sup> |
| <b>Y*</b> | 300 ±10 | 300 ±10 | 400 ±10 | 500 ±10 | 500 ±10 |      |       |       | 500 ±10            | 500 ±10            |
| <b>Z*</b> | 9       | 9       | 9       | 12      | 12      |      |       |       | 15                 | 15                 |

\* Filters with output wire connections (-07) only.

All dimensions in mm; 1 inch = 25.4 mm

Tolerances according: ISO 2768-m/EN 22768-m

## Filter input/output connector cross sections

|                           | -29                                                                                 | -33                                                                                 | -34                                                                                 | -35                                                                                   | -40                                                                                   |
|---------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
|                           |  |  |  |  |  |
| <b>Solid wire</b>         | 6 mm <sup>2</sup>                                                                   | 16 mm <sup>2</sup>                                                                  | 35 mm <sup>2</sup>                                                                  | 50 mm <sup>2</sup>                                                                    | 95 mm <sup>2</sup>                                                                    |
| <b>Flex wire</b>          | 4 mm <sup>2</sup>                                                                   | 10 mm <sup>2</sup>                                                                  | 25 mm <sup>2</sup>                                                                  | 50 mm <sup>2</sup>                                                                    | 95 mm <sup>2</sup>                                                                    |
| <b>AWG type wire</b>      | AWG 10                                                                              | AWG 6                                                                               | AWG 2                                                                               | AWG 1/0                                                                               | AWG 4/0                                                                               |
| <b>Recommended torque</b> | 0.6-0.8 Nm                                                                          | 1.5-1.8 Nm                                                                          | 4.0-4.5 Nm                                                                          | 7-8 Nm                                                                                | 17-20 Nm                                                                              |

Please visit [www.schaffner.com](http://www.schaffner.com) to find more details on filter connectors.



## Headquarters, global innovation and development

### Switzerland

#### Schaffner Group

Nordstrasse 11  
4542 Luterbach  
T +41 32 681 66 26  
[info@schaffner.com](mailto:info@schaffner.com)  
[www.schaffner.com](http://www.schaffner.com)



## Sales and application centers

### China

#### Schaffner EMC Ltd. Shanghai

T20-3 C, No 565 Chuangye Road,  
Pudong district  
201201 Shanghai  
T +86 21 3813 9500  
[cschina@schaffner.com](mailto:cschina@schaffner.com)  
[www.schaffner.com.cn](http://www.schaffner.com.cn)

### Finland

#### Schaffner Oy

Sauvonrinne 19 H  
08500 Lohja  
T +358 50 468 7284  
[finlandsales@schaffner.com](mailto:finlandsales@schaffner.com)

### France

#### Schaffner EMC S.A.S.

16-20 Rue Louis Rameau  
95875 Bezons  
T +33 1 34 34 30 60  
F +33 1 39 47 02 28  
[francesales@schaffner.com](mailto:francesales@schaffner.com)

### Germany

#### Schaffner Deutschland GmbH

Schoemperlenstrasse 12B  
76185 Karlsruhe  
T +49 721 56910  
F +49 721 569110  
[germanysales@schaffner.com](mailto:germanysales@schaffner.com)

### India

#### Schaffner India Pvt. Ltd

REGUS WORLD TRADE CENTRE  
WTC, 22nd Floor Unit No 2238, Brigade  
Gateway Campus, 26/1, Dr. Rajkumar Road  
Malleshwaram (W)  
560055 Bangalore  
T +91 80 67935355  
[indiasales@schaffner.com](mailto:indiasales@schaffner.com)

### Italy

#### Schaffner EMC S.r.l.

Via Ticino, 30  
20900 Monza (MB)  
T +39 039 21 41 070  
[italysales@schaffner.com](mailto:italysales@schaffner.com)

### Japan

#### Schaffner EMC K.K.

1-32-12, Kamiuma, Setagaya-ku  
7F Mitsui-seimei Sangenjaya Bldg.  
154-0011 Tokyo  
T +81 3 5712 3650  
F +81 3 5712 3651  
[japansales@schaffner.com](mailto:japansales@schaffner.com)  
[www.schaffner.jp](http://www.schaffner.jp)

### Singapore

#### Schaffner EMC Pte Ltd.

#05-09, Kg Ubi Ind. Estate  
408705 Singapore  
T +65 6377 3283  
F +65 6377 3281  
[singaporesales@schaffner.com](mailto:singaporesales@schaffner.com)

### Spain

#### Schaffner EMC España

Calle Caléndula 93, Miniparc III, Edificio E  
El Soto de Moraleja, Alcobendas  
28109 Madrid  
T +34 917 912 900  
F +34 917 912 901  
[spainsales@schaffner.com](mailto:spainsales@schaffner.com)

### Sweden

#### Schaffner EMC AB

Tegeluddsvägen 76, 2tr  
115 28 Stockholm  
T +46 8 5050 2425  
[swedensales@schaffner.com](mailto:swedensales@schaffner.com)  
[www.schaffner.com](http://www.schaffner.com)

### Switzerland

#### Schaffner EMV AG

Nordstrasse 11  
4542 Luterbach  
T +41 32 681 66 26  
[switzerlandsales@schaffner.com](mailto:switzerlandsales@schaffner.com)

### Taiwan R.O.C.

#### Schaffner EMV Ltd.

20 Floor-2, No 97, Section 1, XinTai 5th Road  
22175 XiZhi District New Taipei City 22175  
T +886 2 2697 5500  
F +886 2 2697 5533  
[taiwansales@schaffner.com](mailto:taiwansales@schaffner.com)  
[www.schaffner.com.tw](http://www.schaffner.com.tw)

### Thailand

#### Schaffner EMC Co. Ltd.

Northern Region Industrial Estate  
67 Moo 4 Tambon Ban Klang  
Amphur Muang P.O. Box 14  
51000 Lamphun  
T +66 53 58 11 04  
F +66 53 58 10 19  
[thailandsales@schaffner.com](mailto:thailandsales@schaffner.com)

### United Kingdom

#### Schaffner Ltd.

5 Ashville Way, Molly Millars Lane  
Wokingham  
RG41 2PL Berkshire  
T +44 118 9770070  
F +44 118 9792969  
[uksales@schaffner.com](mailto:uksales@schaffner.com)

### USA

#### Schaffner EMC Inc.

52 Mayfield Avenue  
08837 Edison, New Jersey  
T +1 800 367 5566  
T +1 732 225 9533  
F +1 732 225 4789  
[usasales@schaffner.com](mailto:usasales@schaffner.com)  
[www.schaffnerusa.com](http://www.schaffnerusa.com)

#### Schaffner North America

6722 Thirlane Road  
24019 Roanoke, Virginia  
T +1 276 228 7943  
F +1 276 228 7953

#### Schaffner North America

823 Fairview Road  
24382 Wytheville, Virginia  
T +1 276 228 7943  
F +1 276 228 7258

To find your local partner within Schaffner's global network: [www.schaffner.com](http://www.schaffner.com)

© 2018 Schaffner Group

The content of this document has been carefully checked and understood. However, neither Schaffner nor its subsidiaries assume any liability whatsoever for any errors or inaccuracies of this document and the consequences thereof. Published specifications are subject to change without notice. Product suitability for any area of application must ultimately be determined by the customer. In all cases, products must never be operated outside their published specifications. Schaffner does not guarantee the availability of all published products. This disclaimer shall be governed by substantive Swiss law and resulting disputes shall be settled by the courts at the place of business of Schaffner Holding AG. Latest publications and a complete disclaimer can be downloaded from the Schaffner website. All trademarks recognized.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,  
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А