



T H E R M O M E T R I C S
A C O M M I T M E N T T O E X C E L L E N C E

NTC Diode

Thermometrics

Thermistors



A range of NTC chip thermistors in DO-35 style glass package (diode outline) with axial solder-coated copper-clad steel wires.

- Designed for accurate temperature measurement, control and compensation
- Tight tolerances on resistance and B value
- Operation up to 482°F (250°C) with excellent stability
- Glass body provides hermetic seal and voltage insulation and excellent stability
- Designed for cost effective solid state sensor
- Lead-wires metallurgically bonded to thermistor element for improved reliability (Type GE only)
- Resistant to corrosive atmospheres and harsh environments
- Available on axial bandolier to IEC-286-1/ EIA-468A and packet taped to EIA RS-481 for MELF.
- Also available loose-packed with axial, radial and SMD wire forms
- Suitable for automotive, telecom (battery packs), HVAC and white goods applications
- Temperature sensing for household appliances such as rice cookers, electronic ranges, ovens, etc.
- Temperature sensing for industrial products such as pharmaceuticals, chemicals, food, etc. components.

Amphenol
Advanced Sensors

Type DK Specifications

Chip thermistor in DO-35 glass package

Options

- Other resistance values within the ranges shown; e.g. code DKA302*2 for 3000 Ω $\pm 2\%$ at 77°F (25°C)
- Reference temperatures in the range 0°F to 302°F (-18°C to 150°C)
- Operation to 572°F (300°C) (no solder coating on wires)
- Wire lengths 0.16 in to 1.26 in (4 mm to 32 mm) ± 0.04 in (± 1 mm) for DK-N; up to 1.02 in (26 mm) for DK-H

Coding

Replace * in the codes shown below as follows:

- Axial, loose-packed: N
- Axial, bandoliered: B
- Radial, loose-packed: H
- Surface mount, loose-packed: M



NTC Type DK wires should not be bent within 0.08 in (2 mm) of glass body

Data

- Operating temperature: -40°F to 482°F (-40°C to 250°C)
- Thermal time constant: 7 seconds (cooling in air)
- Dissipation factor: 3.0 mW/K
- Mass: 0.2 g
- Packing/MOQ: 1000/box (loose), 5000/reel (bandoliered)

| R25 Ω | Material system | B 25/85 K | Code R25 $\pm 2\%$ | Code R25 $\pm 3\%$ | Code R25 $\pm 5\%$ | Code R25 $\pm 10\%$ |
|--------------|-----------------|----------------|--------------------|--------------------|--------------------|---------------------|
| 2000 | 2 | 3540 $\pm 1\%$ | DKA202*2 | DKA202*3 | DKA202*5 | DKA202*10 |
| 5000 | 2 | 3540 $\pm 1\%$ | DKA502*2 | DKA502*3 | DKA502*5 | DKA502*10 |
| 10,000 | 2 | 3540 $\pm 1\%$ | DKA103*2 | DKA103*3 | DKA103*5 | DKA103*10 |
| 10,000 | 5A | 3730 $\pm 2\%$ | | DKC103*3 | DKC103*5 | DKC103*10 |
| 12,000 | 5A | 3730 $\pm 2\%$ | DKC123*2 | DKC123*3 | DKC123*5 | DKC123*10 |
| 10,000 | 3 | 3960 $\pm 1\%$ | DKF103*2 | DKF103*3 | DKF103*5 | DKF103*10 |
| 20,000 | 3 | 3960 $\pm 1\%$ | DKF203*2 | DKF203*3 | DKF203*5 | DKF203*10 |
| 30,000 | 3 | 3960 $\pm 1\%$ | DKF303*2 | DKF303*3 | DKF303*5 | DKF303*10 |
| 50,000 | 3 | 3960 $\pm 1\%$ | DKF503*2 | DKF503*3 | DKF503*5 | DKF503*10 |
| 100,000 | 3 | 3960 $\pm 1\%$ | DKF104*2 | DKF104*3 | DKF104*5 | DKF104*10 |
| 200,000 | G | 4263 $\pm 2\%$ | | | DKG204*5 | DKG204*10 |
| 500,000 | D | 4573 $\pm 2\%$ | | | DKD504*5 | DKD504*10 |
| 1,000,000 | D | 4573 $\pm 2\%$ | | | DKD105*5 | DKD105*10 |

See separate tables for resistance-temperature data.
Consult factory for additional tolerance requirements.

Type DKM Specifications

Glass encapsulated SMD thermistor

Description

A range of thermistors in DO-35 style glass package (diode outline formed for surface lead-wires and applications) with solder-coated copper-clad steel lead-wires.



NTC Type DKM wires should not be bent within 0.08 in (2 mm) of glass body

Options

- Other resistance values within the ranges shown; e.g. code DKA302M2 for 3000 Ω ±2% at 77°F (25°C)
- Reference temperatures in the range 32°F to 302°F (0°C to 150°C)
- For tape and reel, add suffix “AB”
- Operation to 572°F (300°C); no solder coating on lead-wires

Data

- Operating temperature: -40°F to 482°F (-40°C to 250°C)
- Thermal time constant: 7 seconds (cooling in air)
- Dissipation factor: 3.0 mW/K
- Mass: 0.2 g
- Packing/MOQ: 1000/box (loose)

| R25 Ω | Material System | B 25/85 K | Code R25 ±2% | Code R25 ±3% | Code R25 ±5% | Code R25 ±10% |
|-----------|-----------------|-----------|--------------|--------------|--------------|---------------|
| 2000 | 2 | 3540 ±1% | DKA202M2 | DKA202M3 | DKA202M5 | DKA202M10 |
| 5000 | 2 | 3540 ±1% | DKA502M2 | DKA502M3 | DKA502M5 | DKA502M10 |
| 10,000 | 2 | 3540 ±1% | DKA103M2 | DKA103M3 | DKA103M5 | DKA103M10 |
| 10,000 | 5A | 3730 ±2% | | DKC103M3 | DKC103M5 | DKC103M10 |
| 10,000 | 3 | 3960 ±1% | DKF103M2 | DKF103M3 | DKF103M5 | DKF103M10 |
| 20,000 | 3 | 3960 ±1% | DKF203M2 | DKF203M3 | DKF203M5 | DKF203M10 |
| 30,000 | 3 | 3960 ±1% | DKF303M2 | DKF303M3 | DKF303M5 | DKF303M10 |
| 50,000 | 3 | 3960 ±1% | DKF503M2 | DKF503M3 | DKF503M5 | DKF503M10 |
| 100,000 | 3 | 3960 ±1% | DKF104M2 | DKF104M3 | DKF104M5 | DKF104M10 |
| 200,000 | G | 4263 ±2% | | | DKG204M5 | DKG204M10 |
| 500,000 | D | 4573 ±2% | | | DKD504M5 | DKD504M10 |
| 1,000,000 | D | 4573 ±2% | | | DKD105M5 | DKD105M10 |

See separate tables for resistance-temperature data.
Consult factory for additional tolerance requirements.

Type GE Specifications

Glass encapsulated DO-35 package

Options

- For reel taping
- Nickel leads for welding
- Other resistances in the range 250 Ω to 5 MΩ
- Other tolerances, tolerances at other temperatures
- Alternative leads lengths, lead materials
- Can be expanded to 572°F (300°C) with nickel leads



NTC Type GE dimensions

Data

- Standard resistance tolerance: ±10% @ 77°F (25°C)
- Dissipation constant: 3.0 mW/K
- Time constant: 7 seconds
- Operating range: -58°F to 400°F (-50°C to 204°C)
- Lead Wires metallurgically bonded to thermistor element for improved reliability

| R ₀ @25°C (Ω) | Material System | Beta 25/85 | Type Number |
|--------------------------|-----------------|------------|-----------------------|
| 250 | GE5.5* | 2983 | AL03006-165.9-55-G1 |
| 500 | GE5.5* | 2983 | AL03006-331.8-55-G1 |
| 1K | GE7.3 | 3499 | AL03006-624-73-G1 |
| 2K | GE7.3 | 3499 | AL03006-1248-73-G1 |
| 2786 | GE10.1 | 4102 | AL03006-1576-101-G1 |
| 3K | GE7.6 | 3553 | AL03006-1847-76-G1 |
| 4K | GE7.6 | 3553 | AL03006-2463-76-G1 |
| 5K | GE7.6 | 3553 | AL03006-3079-76-G1 |
| 10K | GE9.7A | 3992 | AL03006-5818-97-G1 |
| 20K | GE9.8 | 3974 | AL03006-11.7K-98-G1 |
| 30K | GE9.8 | 3974 | AL03006-17.53K-98-G1 |
| 50K | GE9.7B | 3952 | AL03006-29.1K-97-G1 |
| 100K | GE9.7B | 3952 | AL03006-58.2K-97-G1 |
| 200K | GE12.3 | 4365 | AL03006-111.3K-123-G1 |
| 500K | GE13.8 | 4567 | AL03006-269.8K-138-G1 |
| 1M | GE14.5 | 4661 | AL03006-535K-145-G1 |
| 5M | GE16.4 | 4848 | AL03006-2.6M-164-G1 |

*maximum operating temperature 302°F (150°C)

Type MELF Specifications

Glass encapsulated SMD thermistor

Description

Hermetically sealed, glass encapsulated thermistor in SOD-80 SMD package.

Options

- Pocket Taping
- Other resistances in the range 250 Ω to 5 M Ω available
- Other tolerances, tolerances at other temperatures



NTC Type MELF dimensions

Data

- Standard resistance tolerance: $\pm 10\%$ @ 77°F (25°C)
- Dissipation constant: 3.0 mW/°C
- Time constant: 7 seconds
- Operating range: -58°F to 400°F (-50°C to 204°C)

| R ₀ @25° C (Ω) | Material System | Beta 25/85 | Type Number |
|------------------------------------|-----------------|------------|-----------------------|
| 250 | GE5.5* | 2983 | 03006-165.9-55-G100 |
| 500 | GE5.5* | 2983 | 03006-331.8-55-G100 |
| 1K | GE7.3 | 3499 | 03006-624-73-G100 |
| 2K | GE7.3 | 3499 | 03006-1248-73-G100 |
| 2786 | GE10.1 | 4102 | 03006-1576-101-G100 |
| 3K | GE7.6 | 3553 | 03006-1847-76-G100 |
| 4K | GE7.6 | 3553 | 03006-2463-76-G100 |
| 5K | GE7.6 | 3553 | 03006-3079-76-G100 |
| 10K | GE9.7A | 3992 | 03006-5818-97-G100 |
| 20K | GE9.8 | 3974 | 03006-11.7K-98-G100 |
| 30K | GE9.8 | 3974 | 03006-17.53K-98-G100 |
| 50K | GE9.7B | 3952 | 03006-29.1K-97-G100 |
| 100K | GE9.7B | 3952 | 03006-58.2-97-G100 |
| 200K | GE12.3 | 4365 | 03006-111.3K-123-G100 |
| 500K | GE13.8 | 4567 | 03006-269.8K-138-G100 |
| 1M | GE14.5 | 4661 | 03006-535K-145-G100 |
| 5M | GE16.4 | 4848 | 03006-2.6M-164-G100 |

*maximum operating temperature 302°F (150°C)

Type TH Specifications

Glass encapsulated radial lead thermistor

| Part Number | Resistance (25 Ω) | β Constant (25/50) | Recommended Maximum Operating Current at 77°F (25°C) | Maximum Permissible Current at 77°F (25°C) |
|-------------|-------------------|--------------------|--|--|
| TH220J33G | 2.0 K | 3375 K | 0.22 mA | 30.0 mA |
| TH225J13G | 2.545 K | 3745 K | 0.22 mA | 30.0 mA |
| TH238J34G | 3.896 K | 3434 K | 0.20 mA | 26.5 mA |
| TH253J34G | 5.369 K | 3434 K | 0.16 mA | 24.0 mA |
| TH310J34G | 10.74 K | 3434 K | 0.13 mA | 20.0 mA |
| TH310J36G | 10.0 K | 3684 K | 0.14 mA | 20.0 mA |
| TH310J39G | 10.0 K | 3933 K | 0.14 mA | 20.0 mA |
| TH315J39G | 15.0 K | 3933 K | 0.12 mA | 17.0 mA |
| TH320J39G | 20.0 K | 3952 K | 0.10 mA | 15.0 mA |
| TH349J39G | 49.12 K | 3952 K | 0.06 mA | 10.0 mA |
| TH350J39G | 50.0 K | 3952 K | 0.06 mA | 10.0 mA |
| TH398J40G | 98.63 K | 4014 K | 0.045 mA | 5.0 mA |
| TH410J40G | 100.0 K | 4014 K | 0.045 mA | 5.0 mA |
| TH420J34G | 200.0 K | 3450 K | 0.015 mA | 3.5 mA |
| TH423J41G | 231.4 K | 4176 K | 0.015 mA | 3.5 mA |
| TH510J44G | 1,000 K | 4491 K | 0.007 mA | 1.5 mA |
| TH513J44G | 1,388 K | 4491 K | 0.005 mA | 1.0 mA |

- The tolerance of resistance is ±5% for standard device
- The tolerance of B constant is ±2% for standard device The constant is determined by the equation:
 $B = 3853.9 \ln (R_{25}/R_{50})$
 R25 and R50 represent the thermistor resistance at 77°F and 122°F (25°C and 50°C) respectively
- Others: For non-standard devices, consult Thermometrics

| Dissipation Factor (in still air) | Time Constant (in still air) | Operating Temperature Range | Rated Power at 77°F (25°C) |
|-----------------------------------|------------------------------|------------------------------------|----------------------------|
| 2.0 (mW/°C) | 25 (seconds) | -40°F to 482°F (-40°C to 250°C) | 25 mW |



NTC Type TH dimensions

Explanation of Part Number

| | | | | | | | | |
|-----|-----|-----|-----|-----|-----|-----|---|-----|
| TH | 410 | S | 40 | F | D | SN | - | T5 |
| (1) | (2) | (3) | (4) | (5) | (6) | (7) | | (8) |

| 1 | 2 | 3 / 5 | 4 | 6 | 7 | 8 |
|--------------------------|--|--|--|---|--|--|
| Type | Resistance R(25°C) | Resistance / B Value Tolerance | B Value Range | Standard Temperature | Lead Wire Type | Packing & Other Description |
| Diode Type Thermistor | 225:25x10 ² = 2.5kΩ 310:10x10 ³ =10kΩ 410:10x10 ⁴ =100kΩ | F : ± 1% G : ± 2% H : ± 3% J : ± 5% K : ± 10% L : ± 15% M : ± 20% : : <u>S : others</u> S : ± 1.5% | 33:3300k ~3399k 40:4000k ~4099k 42:4200k ~4299k | J : -18°C A : 0°C B : 25°C C : 50°C D : 75°C E : 85°C F : 100°C G : 150°C H : 200°C : : S : others | NR : CP wire NI : Ni plated Sn : Sn plated : : : : S : others | T5 : Taping (52mm, Ammo) ----- R3 : Reel (52mm, 3KP) ----- C11 : 11mm (Wire cutting) ----- Other Special Shape or Dim |

Amphenol

Advanced Sensors

www.amphenol-sensors.com

© 2017 Amphenol Corporation. All Rights Reserved. Specifications are subject to change without notice.
Other company names and product names used in this document are the registered trademarks or
trademarks of their respective owners.

AAS-920-320E - 08/2017

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol:

[DKA502H10](#) [DKA502B10](#) [DKA502N10](#) [DKA502N3](#) [DKA502B3](#) [DKA502N5](#) [DKA502B5](#) [TH420J34GBNI](#)
[TH410J42GBSN-T5](#) [TH450J44GBSN](#) [TH349G39GDSN](#) [TH248G39GSSN](#) [TH297G39FSSN](#) [TH248S39GSNI](#)
[TH250H39GBSN](#) [TH310F39FBSN-T5](#) [TH310J37GBSN](#) [TH350H39GBSN](#) [TH420J34GDNI](#) [TH420J41GBSN-T5](#)
[TH420H34GBNI](#) [TH423J41GBNI](#) [TH513J45GBSN](#) [TH350J39GBPS](#) [TH513F45GBSN](#) [TH310J32GBSN](#)
[TH238J34GBSN](#) [TH310H36GBSN-T5](#) [TH410H40GDNI](#) [TH310H39GBSN](#) [TH350J39GBNI](#) [TH410J34HBSN](#)
[TH422H41GHNI](#) [TH310H39FBSN-T5](#) [TH310H41GBSN](#) [TH310J34GBNI](#) [TH310F39FBSN](#) [TH310H34GBNR](#)
[TH410H40GSNI-C16](#) [TH423H41GGNI](#) [TH320H35GBSN](#) [TH349G39GFNI](#) [TH410J40GDNI](#) [TH510J44GBSN](#)
[TH423H41GBNI](#) [TH423H41GGNI-B](#) [TH423J41GGNI-B](#) [TH452J44HSSN](#) [TH310J39GBSN\(25/85\)](#) [TH410F39GBSN](#)
[TH320J39GBSN](#) [TH330H39GBSN](#) [TH349H39GFSN](#) [TH253J34GBSN-T5](#) [TH310H39GASN](#) [TH423H41GHNI](#)
[TH420H34GDNI](#) [TH420J41GBNI](#) [TH410H40GBNI](#) [TH410J40GBSN-T5](#) [TH420H34GBNI\(25/85\)](#) [TH423J41GHNI](#)
[TH253J34GBSN](#) [TH320S39GSSN](#) [TH350H39GBPS](#) [TH410J40GBNI](#) [TH349J39GSNI](#) [TH410J40GBPS](#)
[TH349G39GBSN](#) [TH333J40GBPS-T5](#) [TH250F34GBSN](#) [TH253G34GAPS](#) [TH310H36GBSN](#) [TH316S42GBNR](#)
[TH349G39GBPS](#) [TH349H39GFNI](#) [TH349J39GSSN](#) [TH330J39GBSN](#) [TH350H39GBNI](#) [TH358S39FFNI](#)
[TH310G39GBSN](#) [TH420J34GBPS](#) [TH450J44HBSN](#) [TH310H34GBSN](#) [TH349J39GBSN](#) [TH220J33GBSN](#)
[TH310J34GBSN](#) [TH310J39GBSN](#) [TH250J34GBSN](#) [TH310J34GBSN-T5](#) [TH225J37GBSN](#) [TH410J40GBSN](#)
[TH349H39GSSN](#) [TH320H39GBSN](#) [TH248H39GSSN](#) [TH297G39FSSN-C11.5](#) [TH310H34GASN](#) [TH350G39GBPS-T5](#)
[TH315J39GBSN](#) [TH350J39GBSN](#)

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А