

## Polypropylene (PP) Capacitors for Pulse Applications with Double-Sided Metallized Electrodes in PCM 7.5 mm to 52.5 mm. Capacitances from 1000 pF to 47 µF. Rated Voltages from 100 VDC to 3000 VDC.

### Special Features

- Pulse duty construction
- Self-healing
- Very low dissipation factor
- Negative capacitance change versus temperature
- According to RoHS 2011/65/EU

### Typical Applications

For pulse applications e.g.

- Switch mode power supplies
- TV and monitor sets
- Lighting
- Audio/video equipment


### Construction

**Dielectric:** Polypropylene (PP) film

**Capacitor electrodes:**

Double-sided metallized plastic film

**Internal construction:**



### Encapsulation:

Solvent-resistant, flame-retardant plastic case with epoxy resin seal, UL 94 V-0

**Terminations:** Tinned wire.

**Marking:** Colour: Red.

Marking: Black.

### Electrical Data

#### Capacitance range:

1000 pF to 47 µF (E12-values on request)

**Rated voltages:** 100 VDC, 250 VDC, 400 VDC, 630 VDC, 850 VDC, 1000 VDC, 1250 VDC, 1600 VDC, 2000 VDC, 2500 VDC, 3000 VDC

#### Capacitance tolerances:

±20%, ±10%, ±5%

#### Operating temperature range:

−55° C to +110° C

#### Insulation resistance at +20° C:

$C \leq 0.33 \mu\text{F}$ :  $\geq 1 \times 10^5 \text{ M}\Omega$

$C > 0.33 \mu\text{F}$ :  $\geq 30\,000 \text{ sec (M}\Omega \times \mu\text{F)}$

Measuring voltage: 100 V/1 min.

**Test voltage:** 2 sec.

| L      | $\leq 2000 \text{ VDC}$ | 2500 VDC  | $\geq 3000 \text{ VDC}$ |
|--------|-------------------------|-----------|-------------------------|
| < 41.5 | 1.6 $U_r$               | 1.4 $U_r$ | 1.2 $U_r$               |
| 41.5   | 1.4 $U_r$               | 1.4 $U_r$ | 1.2 $U_r$               |
| 57     | 1.2 $U_r$               | 1.2 $U_r$ | 1.2 $U_r$               |

#### Dissipation factors at +20° C: $\tan \delta$

| at f    | $C \leq 0.1 \mu\text{F}$ | $0.1 \mu\text{F} < C \leq 1.0 \mu\text{F}$ | $C > 1.0 \mu\text{F}$   |
|---------|--------------------------|--------------------------------------------|-------------------------|
| 1 kHz   | $\leq 6 \times 10^{-4}$  | $\leq 6 \times 10^{-4}$                    | $\leq 6 \times 10^{-4}$ |
| 10 kHz  | $\leq 6 \times 10^{-4}$  | $\leq 6 \times 10^{-4}$                    | –                       |
| 100 kHz | $\leq 15 \times 10^{-4}$ | –                                          | –                       |

#### Maximum pulse rise time for pulses equal to the rated voltage

| Capacitance<br>pF/µF | max. pulse rise time V/µsec at $T_A < 40^\circ \text{C}$ |         |         |         |         |          |          |          |          |          |          |  |
|----------------------|----------------------------------------------------------|---------|---------|---------|---------|----------|----------|----------|----------|----------|----------|--|
|                      | 100 VDC                                                  | 250 VDC | 400 VDC | 630 VDC | 850 VDC | 1000 VDC | 1250 VDC | 1600 VDC | 2000 VDC | 2500 VDC | 3000 VDC |  |
| 1000 ... 2200        | 1250                                                     | 2300    | 2300    | 2300    | 3500    | 3500     | 7000     | 7000     | 11500    | 11500    | –        |  |
| 3300 ... 6800        | 1150                                                     | 1500    | 1500    | 1500    | 3500    | 3500     | 7000     | 7000     | 11500    | 11500    | –        |  |
| 0.01 ... 0.022       | 900                                                      | 1400    | 1500    | 1500    | 2700    | 2700     | 3800     | 3800     | 4400     | 11500    | –        |  |
| 0.033 ... 0.068      | 500                                                      | 1000    | 1150    | 1400    | 2700    | 2700     | 2700     | 2700     | 2700     | 2700     | 2700     |  |
| 0.1 ... 0.22         | 250                                                      | 650     | 650     | 1150    | 1800    | 1800     | 1800     | 1800     | 1800     | 1800     | 1800     |  |
| 0.33 ... 0.68        | 130                                                      | 390     | 500     | 900     | 1150    | 1150     | 1150     | 1150     | 1150     | 1150     | 1150     |  |
| 1.0 ... 2.2          | 90                                                       | 250     | 250     | 500     | 500     | 500      | 650      | 650      | 650      | 650      | 500      |  |
| 3.3 ... 4.7          | 65                                                       | 100     | 130     | 190     | 230     | 230      | 330      | 330      | –        | –        | –        |  |
| 6.8 ... 15           | 45                                                       | 65      | 90      | 160     | –       | –        | –        | –        | –        | –        | –        |  |
| 22 ... 47            | 30                                                       | 45      | 45      | –       | –       | –        | –        | –        | –        | –        | –        |  |

### Mechanical Tests

#### Pull test on pins:

$d \leq 0.8 \text{ mm}$ : 10 N in direction of pins

$d > 0.8 \text{ mm}$ : 20 N in direction of pins

according to IEC 60068-2-21

**Vibration:** 6 hours at 10 ... 2000 Hz and 0.75 mm displacement amplitude or 10 g in accordance with IEC 60068-2-6

**Low air density:** 1 kPa = 10 mbar in accordance with IEC 60068-2-13

**Bump test:** 4000 bumps at 390 m/sec<sup>2</sup> in accordance with IEC 60068-2-29

#### Climatic test category:

55/100/56 in accordance with IEC

**Dielectric absorption:** 0.05 %

#### Voltage derating:

A voltage derating factor of 1.35 % per K must be applied from +85° C for DC voltages and from +75° C for AC voltages.

#### Reliability:

Operational life > 300 000 hours

Failure rate < 1 fit (0.5 x  $U_r$  and 40° C)

#### Specific dissipation:

| Box size*<br>WxHxL in mm | Specific dissipation in Watts per K<br>above the ambient temperature |
|--------------------------|----------------------------------------------------------------------|
| 35 x 50 x 57             | 0.132                                                                |
| 45 x 55 x 57             | 0.164                                                                |
| 45 x 65 x 57             | 0.184                                                                |

\* other box sizes see page 11.

### Packing

Available taped and reeled up to and including case size 15 x 26 x 31.5 / PCM 27.5 mm.

Detailed taping information and graphs at the end of the catalogue.

For further details and graphs please refer to Technical Information.

## Continuation

### General Data

| Capacitance | 100 VDC/63 VAC* |      |      |       |              | 250 VDC/180 VAC* |      |      |       |              |
|-------------|-----------------|------|------|-------|--------------|------------------|------|------|-------|--------------|
|             | W               | H    | L    | PCM** | Part number  | W                | H    | L    | PCM** | Part number  |
| 1000 pF     | 4               | 9    | 10   | 7.5   | MKP1D011002C | 4                | 9    | 10   | 7.5   | MKP1F011002C |
| 1500 "      | 4               | 9    | 10   | 7.5   | MKP1D011502C | 4                | 9    | 10   | 7.5   | MKP1F011502C |
| 2200 "      | 4               | 9    | 10   | 7.5   | MKP1D012202C | 4                | 9    | 10   | 7.5   | MKP1F012202C |
| 3300 "      | 4               | 9    | 10   | 7.5   | MKP1D013302C | 4                | 9    | 10   | 7.5   | MKP1F013302C |
| 4700 "      | 4               | 9    | 10   | 7.5   | MKP1D014702C | 4                | 9    | 10   | 7.5   | MKP1F014702C |
| 6800 "      | 4               | 9    | 10   | 7.5   | MKP1D016802C | 4                | 9    | 10   | 7.5   | MKP1F016802C |
| 0.01 µF     | 4               | 9    | 10   | 7.5   | MKP1D021002C | 4                | 9    | 10   | 7.5   | MKP1F021002C |
| 0.015 "     | 4               | 9    | 10   | 7.5   | MKP1D021502C | 4                | 9    | 13   | 10    | MKP1F021003C |
| 0.022 "     | 4               | 9    | 10   | 7.5   | MKP1D022202C | 4                | 9    | 10   | 7.5   | MKP1F021502C |
| 0.033 "     | 5               | 10.5 | 10.3 | 7.5   | MKP1D023302E | 4                | 9    | 13   | 10    | MKP1F021503C |
| 0.047 "     | 4               | 9    | 13   | 10    | MKP1D023303C | 4                | 9    | 10   | 7.5   | MKP1F022202C |
| 0.068 "     | 5               | 10.5 | 10.3 | 7.5   | MKP1D024702E | 4                | 9    | 13   | 10    | MKP1F022203C |
|             | 4               | 9    | 13   | 10    | MKP1D024703C | 5                | 10.5 | 10.3 | 7.5   | MKP1F023302E |
|             | 5               | 11   | 13   | 10    | MKP1D026803F | 4                | 9    | 13   | 10    | MKP1F023303C |
|             |                 |      |      |       |              | 5                | 11   | 13   | 10    | MKP1F024702E |
|             |                 |      |      |       |              | 5                | 11   | 18   | 15    | MKP1F024703C |
| 0.1 µF      | 6               | 12   | 13   | 10    | MKP1D031003G | 6                | 12   | 13   | 10    | MKP1F026803F |
| 0.15 "      | 6               | 12.5 | 18   | 15    | MKP1D031504C | 5                | 11   | 18   | 15    | MKP1F026804B |
| 0.22 "      | 7               | 14   | 18   | 15    | MKP1D032204D | 6                | 12.5 | 18   | 15    | MKP1F031003G |
| 0.33 "      | 8               | 15   | 18   | 15    | MKP1D033304F | 6                | 15   | 26.5 | 22.5  | MKP1F031004B |
| 0.47 "      | 9               | 16   | 18   | 15    | MKP1D034704J | 7                | 14   | 18   | 15    | MKP1F031504C |
| 0.68 "      | 7               | 16.5 | 26.5 | 22.5  | MKP1D034705D | 6                | 15   | 26.5 | 22.5  | MKP1F031505B |
|             | 8.5             | 18.5 | 26.5 | 22.5  | MKP1D036805F | 8                | 15   | 18   | 15    | MKP1F032204D |
|             |                 |      |      |       |              | 6                | 15   | 26.5 | 22.5  | MKP1F032205B |
|             |                 |      |      |       |              | 9                | 16   | 18   | 15    | MKP1F033304F |
|             |                 |      |      |       |              | 7                | 16.5 | 26.5 | 22.5  | MKP1F033305B |
|             |                 |      |      |       |              | 8.5              | 18.5 | 26.5 | 22.5  | MKP1F033305B |
|             |                 |      |      |       |              | 9                | 19   | 31.5 | 27.5  | MKP1F034704J |
| 1.0 µF      | 10.5            | 19   | 26.5 | 22.5  | MKP1D041005G | 11               | 21   | 26.5 | 22.5  | MKP1F034705D |
| 1.5 "       | 11              | 21   | 31.5 | 27.5  | MKP1D041506B | 11               | 21   | 31.5 | 27.5  | MKP1F036805F |
| 2.2 "       | 13              | 24   | 31.5 | 27.5  | MKP1D042206D | 13               | 24   | 31.5 | 27.5  | MKP1F036806A |
| 3.3 "       | 17              | 29   | 31.5 | 27.5  | MKP1D043306G | 13               | 24   | 41.5 | 37.5  | MKP1F041005I |
| 4.7 "       | 20              | 39.5 | 31.5 | 27.5  | MKP1D044706J | 15               | 26   | 31.5 | 27.5  | MKP1F041006B |
| 6.8 "       | 17              | 29   | 41.5 | 37.5  | MKP1D044707E | 13               | 24   | 41.5 | 37.5  | MKP1F041506D |
|             | 19              | 32   | 41.5 | 37.5  | MKP1D046807F | 17               | 29   | 31.5 | 27.5  | MKP1F041507C |
|             |                 |      |      |       |              | 17               | 29   | 41.5 | 37.5  | MKP1F042206F |
| 10 µF       | 20              | 39.5 | 41.5 | 37.5  | MKP1D051007G | 20               | 39.5 | 31.5 | 27.5  | MKP1F042207C |
| 15 "        | 24              | 45.5 | 41.5 | 37.5  | MKP1D051507H | 19               | 32   | 41.5 | 37.5  | MKP1F043306I |
|             | 31              | 46   | 41.5 | 37.5  | MKP1D051507I | 20               | 39.5 | 41.5 | 37.5  | MKP1F043307E |
| 22 "        | 35              | 50   | 41.5 | 37.5  | MKP1D052207J | 19               | 32   | 41.5 | 37.5  | MKP1F044706J |
| 33 "        | 40              | 55   | 41.5 | 37.5  | MKP1D053307K | 20               | 39.5 | 41.5 | 37.5  | MKP1F044707F |
|             | 35              | 50   | 57   | 52.5  | MKP1D053309F | 20               | 39.5 | 41.5 | 37.5  | MKP1F046807G |
| 47 "        | 45              | 65   | 57   | 52.5  | MKP1D054709J |                  |      |      |       |              |

\* AC voltage:  $f \leq 1000 \text{ Hz}$ ;  $1.4 \times U_{\text{rms}} + U_{\text{DC}} \leq U_r$

\*\* PCM = Printed circuit module = pin spacing

Dims. in mm.

Ionisation inception level in isolated cases may be lower than admissible rated AC voltage.

Rights reserved to amend design data without prior notification.

#### Part number completion:

Version code: 2-pin = 00  
4-pin = D4  
Tolerance: 20 % = M  
10 % = K  
5 % = J  
Packing: bulk = S  
Pin length: 6-2 = SD  
Taped version see page 149.

## Continuation

### General Data

| Capacitance | 400 VDC/250 VAC* |      |      |       |              | 630 VDC/400 VAC* |      |      |       |              |
|-------------|------------------|------|------|-------|--------------|------------------|------|------|-------|--------------|
|             | W                | H    | L    | PCM** | Part number  | W                | H    | L    | PCM** | Part number  |
| 1000 pF     | 4                | 9    | 10   | 7.5   | MKP1G011002C | 4                | 9    | 10   | 7.5*  | MKP1J011002C |
| 1500 "      | 4                | 9    | 10   | 7.5   | MKP1G011502C | 4                | 9    | 10   | 7.5*  | MKP1J011502C |
| 2200 "      | 4                | 9    | 10   | 7.5   | MKP1G012202C | 4                | 9    | 10   | 7.5*  | MKP1J012202C |
| 3300 "      | 4                | 9    | 10   | 7.5   | MKP1G013302C | 4                | 9    | 10   | 7.5*  | MKP1J013302C |
| 4700 "      | 4                | 9    | 10   | 7.5   | MKP1G014702C | 4                | 9    | 10   | 7.5*  | MKP1J014702C |
| 6800 "      | 4                | 9    | 10   | 7.5   | MKP1G016802C | 4                | 9    | 10   | 7.5*  | MKP1J016802C |
|             |                  |      |      |       |              | 4                | 9    | 13   | 10    | MKP1J016803C |
| 0.01 µF     | 4                | 9    | 10   | 7.5   | MKP1G021002C | 5                | 10.5 | 10.3 | 7.5*  | MKP1J021002E |
|             | 4                | 9    | 13   | 10    | MKP1G021003C | 4                | 9    | 13   | 10    | MKP1J021003C |
| 0.015 "     | 5                | 10.5 | 10.3 | 7.5   | MKP1G021502E | 5                | 11   | 13   | 10    | MKP1J021503F |
|             | 4                | 9    | 13   | 10    | MKP1G021503C | 5                | 11   | 18   | 15    | MKP1J021504B |
| 0.022 "     | 5                | 10.5 | 10.3 | 7.5   | MKP1G022202E | 5                | 11   | 13   | 10    | MKP1J022203F |
|             | 4                | 9    | 13   | 10    | MKP1G022203C | 5                | 11   | 18   | 15    | MKP1J022204B |
| 0.033 "     | 5.7              | 12.5 | 10.3 | 7.5   | MKP1G023302F | 6                | 12   | 13   | 10    | MKP1J023303G |
|             | 5                | 11   | 13   | 10    | MKP1G023303F | 5                | 11   | 18   | 15    | MKP1J023304B |
| 0.047 "     | 6                | 12   | 13   | 10    | MKP1G024703G | 6                | 12.5 | 18   | 15    | MKP1J024704C |
|             | 5                | 11   | 18   | 15    | MKP1G024704B | 6                | 15   | 26.5 | 22.5  | MKP1J024705B |
| 0.068 "     | 6                | 12.5 | 18   | 15    | MKP1G026804C | 7                | 14   | 18   | 15    | MKP1J026804D |
|             | 6                | 15   | 26.5 | 22.5  | MKP1G026805B | 6                | 15   | 26.5 | 22.5  | MKP1J026805B |
| 0.1 µF      | 7                | 14   | 18   | 15    | MKP1G031004D | 9                | 16   | 18   | 15    | MKP1J031004J |
|             | 6                | 15   | 26.5 | 22.5  | MKP1G031005B | 7                | 16.5 | 26.5 | 22.5  | MKP1J031005D |
| 0.15 "      | 8                | 15   | 18   | 15    | MKP1G031504F | 8.5              | 18.5 | 26.5 | 22.5  | MKP1J031505F |
|             | 6                | 15   | 26.5 | 22.5  | MKP1G031505B | 9                | 19   | 31.5 | 27.5  | MKP1J031506A |
| 0.22 "      | 9                | 16   | 18   | 15    | MKP1G032204J | 8.5              | 18.5 | 26.5 | 22.5  | MKP1J032205F |
|             | 7                | 16.5 | 26.5 | 22.5  | MKP1G032205D | 9                | 19   | 31.5 | 27.5  | MKP1J032206A |
| 0.33 "      | 8.5              | 18.5 | 26.5 | 22.5  | MKP1G033305F | 11               | 21   | 26.5 | 22.5  | MKP1J033305I |
|             | 9                | 19   | 31.5 | 27.5  | MKP1G033306A | 11               | 21   | 31.5 | 27.5  | MKP1J033306B |
| 0.47 "      | 10.5             | 19   | 26.5 | 22.5  | MKP1G034705G | 11               | 21   | 31.5 | 27.5  | MKP1J034706B |
|             | 9                | 19   | 31.5 | 27.5  | MKP1G034706A |                  |      |      |       |              |
| 0.68 "      | 11               | 21   | 26.5 | 22.5  | MKP1G036805I | 15               | 26   | 31.5 | 27.5  | MKP1J036806F |
|             | 11               | 21   | 31.5 | 27.5  | MKP1G036806B | 13               | 24   | 41.5 | 37.5  | MKP1J036807C |
| 1.0 µF      | 13               | 24   | 31.5 | 27.5  | MKP1G041006D | 17               | 29   | 31.5 | 27.5  | MKP1J041006G |
|             | 13               | 24   | 41.5 | 37.5  | MKP1G041007C | 15               | 26   | 41.5 | 37.5  | MKP1J041007D |
| 1.5 "       | 17               | 29   | 31.5 | 27.5  | MKP1G041506G | 20               | 39.5 | 31.5 | 27.5  | MKP1J041506J |
|             | 13               | 24   | 41.5 | 37.5  | MKP1G041507C | 19               | 32   | 41.5 | 37.5  | MKP1J041507F |
| 2.2 "       | 20               | 39.5 | 31.5 | 27.5  | MKP1G042206J | 20               | 39.5 | 41.5 | 37.5  | MKP1J042207G |
|             | 17               | 29   | 41.5 | 37.5  | MKP1G042207E |                  |      |      |       |              |
| 3.3 "       | 20               | 39.5 | 41.5 | 37.5  | MKP1G043307G | 24               | 45.5 | 41.5 | 37.5  | MKP1J043307H |
| 4.7 "       | 20               | 39.5 | 41.5 | 37.5  | MKP1G044707G | 35               | 50   | 41.5 | 37.5  | MKP1J044707J |
| 6.8 "       | 24               | 45.5 | 41.5 | 37.5  | MKP1G046807H | 40               | 55   | 41.5 | 37.5  | MKP1J046807K |
|             |                  |      |      |       |              | 35               | 50   | 57   | 52.5  | MKP1J046809F |
| 10 µF       | 35               | 50   | 41.5 | 37.5  | MKP1G051007J | 45               | 55   | 57   | 52.5  | MKP1J051009H |
|             | 35               | 50   | 57   | 52.5  | MKP1G051009F |                  |      |      |       |              |
| 15 "        | 40               | 55   | 41.5 | 37.5  | MKP1G051507K |                  |      |      |       |              |
|             | 35               | 50   | 57   | 52.5  | MKP1G051509F |                  |      |      |       |              |
| 22 "        | 45               | 65   | 57   | 52.5  | MKP1G052209J |                  |      |      |       |              |

\* AC voltage:  $f \leq 1000 \text{ Hz}$ ;  $1.4 \times U_{\text{rms}} + U_{\text{DC}} \leq U_r$

\*\* PCM = Printed circuit module = pin spacing

\* Admissible AC voltage 280 VAC.

Dims. in mm.

Ionisation inception level in isolated cases may be lower than admissible rated AC voltage.

#### Part number completion:

Version code: 2-pin = 00  
4-pin = D4  
Tolerance: 20 % = M  
10 % = K  
5 % = J  
Packing: bulk = S  
Pin length: 6-2 = SD

Taped version see page 149.

Rights reserved to amend design data without prior notification.

## Continuation

### General Data

| Capacitance | 850 VDC/450 VAC* |      |      |            |              | 1000 VDC/600 VAC* |      |      |            |              |
|-------------|------------------|------|------|------------|--------------|-------------------|------|------|------------|--------------|
|             | W                | H    | L    | PCM**      | Part number  | W                 | H    | L    | PCM**      | Part number  |
| 1000 pF     | 4                | 9    | 10   | <b>7.5</b> | MKP1M011002C | 4                 | 9    | 10   | <b>7.5</b> | MKP1O111002C |
|             | 4                | 9    | 13   | 10         | MKP1M011003C | 4                 | 9    | 13   | 10         | MKP1O111003C |
| 1500 "      | 4                | 9    | 10   | <b>7.5</b> | MKP1M011502C | 4                 | 9    | 10   | <b>7.5</b> | MKP1O111502C |
|             | 4                | 9    | 13   | 10         | MKP1M011503C | 4                 | 9    | 13   | 10         | MKP1O111503C |
| 2200 "      | 4                | 9    | 10   | <b>7.5</b> | MKP1M012202C | 4                 | 9    | 10   | <b>7.5</b> | MKP1O112202C |
|             | 4                | 9    | 13   | 10         | MKP1M012203C | 4                 | 9    | 13   | 10         | MKP1O112203C |
| 3300 "      | 4                | 9    | 10   | <b>7.5</b> | MKP1M013302C | 4                 | 9    | 10   | <b>7.5</b> | MKP1O113302C |
|             | 4                | 9    | 13   | 10         | MKP1M013303C | 4                 | 9    | 13   | 10         | MKP1O113303C |
| 4700 "      | 4.5              | 9.5  | 10.3 | <b>7.5</b> | MKP1M014702D | 4.5               | 9.5  | 10.3 | <b>7.5</b> | MKP1O114702D |
|             | 4                | 9    | 13   | 10         | MKP1M014703C | 4                 | 9    | 13   | 10         | MKP1O114703C |
| 6800 "      | 5.7              | 12.5 | 10.3 | <b>7.5</b> | MKP1M016802F | 5.7               | 12.5 | 10.3 | <b>7.5</b> | MKP1O116802F |
|             | 5                | 11   | 13   | 10         | MKP1M016803F | 5                 | 11   | 13   | 10         | MKP1O116803F |
| 0.01 µF     | 5                | 11   | 13   | 10         | MKP1M021003F | 5                 | 11   | 13   | 10         | MKP1O121003F |
|             | 5                | 11   | 18   | 15         | MKP1M021004B | 5                 | 11   | 18   | 15         | MKP1O121004B |
| 0.015 "     | 6                | 12   | 13   | 10         | MKP1M021503G | 6                 | 12   | 13   | 10         | MKP1O121503G |
|             | 5                | 11   | 18   | 15         | MKP1M021504B | 5                 | 11   | 18   | 15         | MKP1O121504B |
| 0.022 "     | 6                | 12.5 | 18   | 15         | MKP1M022204C | 6                 | 12.5 | 18   | 15         | MKP1O122204C |
|             | 6                | 15   | 26.5 | 22.5       | MKP1M022205B | 6                 | 15   | 26.5 | 22.5       | MKP1O122205B |
| 0.033 "     | 7                | 14   | 18   | 15         | MKP1M023304D | 7                 | 14   | 18   | 15         | MKP1O123304D |
|             | 6                | 15   | 26.5 | 22.5       | MKP1M023305B | 6                 | 15   | 26.5 | 22.5       | MKP1O123305B |
| 0.047 "     | 8                | 15   | 18   | 15         | MKP1M024704F | 8                 | 15   | 18   | 15         | MKP1O124704F |
|             | 6                | 15   | 26.5 | 22.5       | MKP1M024705B | 6                 | 15   | 26.5 | 22.5       | MKP1O124705B |
| 0.068 "     | 7                | 16.5 | 26.5 | 22.5       | MKP1M026805D | 7                 | 16.5 | 26.5 | 22.5       | MKP1O126805D |
| 0.1 µF      | 8.5              | 18.5 | 26.5 | 22.5       | MKP1M031005F | 8.5               | 18.5 | 26.5 | 22.5       | MKP1O131005F |
|             | 11               | 21   | 31.5 | 27.5       | MKP1M031006B | 11                | 21   | 31.5 | 27.5       | MKP1O131006B |
| 0.15 "      | 11               | 21   | 26.5 | 22.5       | MKP1M031505I | 11                | 21   | 26.5 | 22.5       | MKP1O131505I |
|             | 11               | 21   | 31.5 | 27.5       | MKP1M031506B | 11                | 21   | 31.5 | 27.5       | MKP1O131506B |
| 0.22 "      | 11               | 21   | 31.5 | 27.5       | MKP1M032206B | 11                | 21   | 31.5 | 27.5       | MKP1O132206B |
| 0.33 "      | 13               | 24   | 31.5 | 27.5       | MKP1M033306D | 13                | 24   | 31.5 | 27.5       | MKP1O133306D |
|             | 15               | 26   | 31.5 | 27.5       | MKP1M033306F | 15                | 26   | 31.5 | 27.5       | MKP1O133306F |
| 0.47 "      | 13               | 24   | 41.5 | 37.5       | MKP1M033307C | 13                | 24   | 41.5 | 37.5       | MKP1O133307C |
|             | 17               | 29   | 31.5 | 27.5       | MKP1M034706G | 17                | 29   | 31.5 | 27.5       | MKP1O134706G |
| 0.68 "      | 13               | 24   | 41.5 | 37.5       | MKP1M034707C | 13                | 24   | 41.5 | 37.5       | MKP1O134707C |
|             | 20               | 39.5 | 31.5 | 27.5       | MKP1M036806J | 20                | 39.5 | 31.5 | 27.5       | MKP1O136806J |
|             | 17               | 29   | 41.5 | 37.5       | MKP1M036807E | 17                | 29   | 41.5 | 37.5       | MKP1O136807E |
| 1.0 µF      | 20               | 39.5 | 41.5 | 37.5       | MKP1M041007G | 20                | 39.5 | 41.5 | 37.5       | MKP1O141007G |
| 1.5 "       | 24               | 45.5 | 41.5 | 37.5       | MKP1M041507H | 24                | 45.5 | 41.5 | 37.5       | MKP1O141507H |
| 2.2 "       | 31               | 46   | 41.5 | 37.5       | MKP1M042207I | 31                | 46   | 41.5 | 37.5       | MKP1O142207I |
| 3.3 "       | 40               | 55   | 41.5 | 37.5       | MKP1M043307K | 40                | 55   | 41.5 | 37.5       | MKP1O143307K |
|             | 35               | 50   | 57   | 52.5       | MKP1M043309F | 35                | 50   | 57   | 52.5       | MKP1O143309F |
| 4.7 "       | 45               | 55   | 57   | 52.5       | MKP1M044709H | 45                | 55   | 57   | 52.5       | MKP1O144709H |

\* AC voltage:  $f \leq 1000 \text{ Hz}$ ;  $1.4 \times U_{\text{rms}} + U_{\text{DC}} \leq U_r$

New range

\*\* PCM = Printed circuit module = pin spacing

Dims. in mm.

Ionisation inception level in isolated cases may be lower than admissible rated AC voltage.

#### Part number completion:

|                             |       |      |
|-----------------------------|-------|------|
| Version code:               | 2-pin | = 00 |
|                             | 4-pin | = D4 |
| Tolerance:                  | 20 %  | = M  |
|                             | 10 %  | = K  |
|                             | 5 %   | = J  |
| Packing:                    | bulk  | = S  |
| Pin length:                 | 6-2   | = SD |
| Taped version see page 149. |       |      |

Rights reserved to amend design data without prior notification.

Continuation page 69

## Continuation

### General Data

| Capacitance | 1250 VDC/600 VAC* |      |      |       |              | 1600 VDC/650 VAC* |      |      |       |              |
|-------------|-------------------|------|------|-------|--------------|-------------------|------|------|-------|--------------|
|             | W                 | H    | L    | PCM** | Part number  | W                 | H    | L    | PCM** | Part number  |
| 1000 pF     | 4                 | 9    | 13   | 10    | MKP1R011003C | 4                 | 9    | 13   | 10    | MKP1T011003C |
| 1500 "      | 4                 | 9    | 13   | 10    | MKP1R011503C | 4                 | 9    | 13   | 10    | MKP1T011503C |
| 2200 "      | 4                 | 9    | 13   | 10    | MKP1R012203C | 4                 | 9    | 13   | 10    | MKP1T012203C |
| 3300 "      | 4                 | 9    | 13   | 10    | MKP1R013303C | 4                 | 9    | 13   | 10    | MKP1T013303C |
| 4700 "      | 5                 | 11   | 13   | 10    | MKP1R014703F | 5                 | 11   | 13   | 10    | MKP1T014703F |
| 6800 "      | 6                 | 12   | 13   | 10    | MKP1R016803G | 6                 | 12   | 13   | 10    | MKP1T016803G |
|             | 5                 | 11   | 18   | 15    | MKP1R016804B | 5                 | 11   | 18   | 15    | MKP1T016804B |
| 0.01 µF     | 5                 | 11   | 18   | 15    | MKP1R021004B | 5                 | 11   | 18   | 15    | MKP1T021004B |
| 0.015 "     | 6                 | 12.5 | 18   | 15    | MKP1R021504C | 6                 | 12.5 | 18   | 15    | MKP1T021504C |
|             | 6                 | 15   | 26.5 | 22.5  | MKP1R021505B | 6                 | 15   | 26.5 | 22.5  | MKP1T021505B |
| 0.022 "     | 7                 | 14   | 18   | 15    | MKP1R022204D | 7                 | 14   | 18   | 15    | MKP1T022204D |
|             | 6                 | 15   | 26.5 | 22.5  | MKP1R022205B | 6                 | 15   | 26.5 | 22.5  | MKP1T022205B |
| 0.033 "     | 8                 | 15   | 18   | 15    | MKP1R023304F | 8                 | 15   | 18   | 15    | MKP1T023304F |
|             | 6                 | 15   | 26.5 | 22.5  | MKP1R023305B | 6                 | 15   | 26.5 | 22.5  | MKP1T023305B |
| 0.047 "     | 7                 | 16.5 | 26.5 | 22.5  | MKP1R024705D | 7                 | 16.5 | 26.5 | 22.5  | MKP1T024705D |
|             | 9                 | 19   | 31.5 | 27.5  | MKP1R024706A | 9                 | 19   | 31.5 | 27.5  | MKP1T024706A |
| 0.068 "     | 10.5              | 19   | 26.5 | 22.5  | MKP1R026805G | 10.5              | 19   | 26.5 | 22.5  | MKP1T026805G |
|             | 9                 | 19   | 31.5 | 27.5  | MKP1R026806A | 9                 | 19   | 31.5 | 27.5  | MKP1T026806A |
| 0.1 µF      | 11                | 21   | 26.5 | 22.5  | MKP1R031005I | 11                | 21   | 26.5 | 22.5  | MKP1T031005I |
|             | 11                | 21   | 31.5 | 27.5  | MKP1R031006B | 11                | 21   | 31.5 | 27.5  | MKP1T031006B |
| 0.15 "      | 13                | 24   | 31.5 | 27.5  | MKP1R031506D | 13                | 24   | 31.5 | 27.5  | MKP1T031506D |
| 0.22 "      | 15                | 26   | 31.5 | 27.5  | MKP1R032206F | 15                | 26   | 31.5 | 27.5  | MKP1T032206F |
|             | 13                | 24   | 41.5 | 37.5  | MKP1R032207C | 13                | 24   | 41.5 | 37.5  | MKP1T032207C |
| 0.33 "      | 17                | 34.5 | 31.5 | 27.5  | MKP1R033306I | 17                | 34.5 | 31.5 | 27.5  | MKP1T033306I |
|             | 17                | 29   | 41.5 | 37.5  | MKP1R033307E | 17                | 29   | 41.5 | 37.5  | MKP1T033307E |
| 0.47 "      | 20                | 39.5 | 31.5 | 27.5  | MKP1R034706J | 20                | 39.5 | 31.5 | 27.5  | MKP1T034706J |
|             | 19                | 32   | 41.5 | 37.5  | MKP1R034707F | 19                | 32   | 41.5 | 37.5  | MKP1T034707F |
| 0.68 "      | 20                | 39.5 | 41.5 | 37.5  | MKP1R036807G | 20                | 39.5 | 41.5 | 37.5  | MKP1T036807G |
| 1.0 µF      | 24                | 45.5 | 41.5 | 37.5  | MKP1R041007H | 24                | 45.5 | 41.5 | 37.5  | MKP1T041007H |
| 1.5 "       | 31                | 46   | 41.5 | 37.5  | MKP1R041507I | 31                | 46   | 41.5 | 37.5  | MKP1T041507I |
| 2.2 "       | 40                | 55   | 41.5 | 37.5  | MKP1R042207K | 40                | 55   | 41.5 | 37.5  | MKP1T042207K |
|             | 35                | 50   | 57   | 52.5  | MKP1R042209F | 35                | 50   | 57   | 52.5  | MKP1T042209F |
| 3.3 "       | 45                | 65   | 57   | 52.5  | MKP1R043309J | 45                | 65   | 57   | 52.5  | MKP1T043309J |

\* AC voltage:  $f \leq 1000 \text{ Hz}$ ;  $1.4 \times U_{\text{rms}} + \text{UDC} \leq U_r$

■ New range

\*\* PCM = Printed circuit module = pin spacing

Dims. in mm.


Ionisation inception level in isolated cases may be lower than admissible rated AC voltage.

#### Part number completion:


Version code: 2-pin = 00  
 4-pin = D4  
 Tolerance: 20 % = M  
 10 % = K  
 5 % = J  
 Packing: bulk = S  
 Pin length: 6-2 = SD

Taped version see page 149.

#### 2-pin version



#### 4-pin version



Rights reserved to amend design data without prior notification.

Continuation page 70

## Continuation

### General Data

| Capacitance | 2000 VDC/700 VAC* |      |      |       |                   | 2500 VDC/700 VAC* |      |      |       |                   |
|-------------|-------------------|------|------|-------|-------------------|-------------------|------|------|-------|-------------------|
|             | W                 | H    | L    | PCM** | Part number       | W                 | H    | L    | PCM** | Part number       |
| 1000 pF     | 4                 | 9    | 13   | 10    | MKP1U011003C_____ | 5                 | 11   | 18   | 15    | MKP1V011004B_____ |
| 1500 "      | 4                 | 9    | 13   | 10    | MKP1U011503C_____ | 6                 | 15   | 26.5 | 22.5  | MKP1V011005B_____ |
| 2200 "      | 5                 | 11   | 13   | 10    | MKP1U012203F_____ | 5                 | 11   | 18   | 15    | MKP1V011504B_____ |
| 3300 "      | 5                 | 11   | 18   | 15    | MKP1U012204B_____ | 6                 | 15   | 26.5 | 22.5  | MKP1V011505B_____ |
| 4700 "      | 5                 | 11   | 18   | 15    | MKP1U013304B_____ | 5                 | 11   | 18   | 15    | MKP1V012204B_____ |
| 6800 "      | 6                 | 15   | 26.5 | 22.5  | MKP1U014704B_____ | 6                 | 15   | 26.5 | 22.5  | MKP1V012205B_____ |
|             | 6                 | 15   | 26.5 | 22.5  | MKP1U014705B_____ | 5                 | 11   | 18   | 15    | MKP1V013304B_____ |
|             | 6                 | 12.5 | 18   | 15    | MKP1U016804C_____ | 6                 | 12.5 | 18   | 15    | MKP1V013305B_____ |
|             | 6                 | 15   | 26.5 | 22.5  | MKP1U016805B_____ | 6                 | 15   | 26.5 | 22.5  | MKP1V014704C_____ |
| 0.01 µF     | 7                 | 14   | 18   | 15    | MKP1U021004D_____ | 6                 | 15   | 26.5 | 22.5  | MKP1V014705B_____ |
| 0.015 "     | 8                 | 15   | 18   | 15    | MKP1U021504F_____ | 7                 | 14   | 18   | 15    | MKP1V016804D_____ |
| 0.022 "     | 9                 | 16   | 18   | 15    | MKP1U022204J_____ | 7                 | 16.5 | 26.5 | 22.5  | MKP1V016805D_____ |
| 0.033 "     | 8.5               | 18.5 | 26.5 | 22.5  | MKP1U023305F_____ | 8.5               | 18.5 | 26.5 | 22.5  | MKP1V021005F_____ |
| 0.047 "     | 9                 | 19   | 31.5 | 27.5  | MKP1U023306A_____ | 10.5              | 19   | 26.5 | 22.5  | MKP1V021505G_____ |
| 0.068 "     | 10.5              | 19   | 26.5 | 22.5  | MKP1U024705G_____ | 11                | 21   | 26.5 | 22.5  | MKP1V022205I_____ |
|             | 11                | 21   | 31.5 | 27.5  | MKP1U024706B_____ | 11                | 21   | 26.5 | 22.5  | MKP1V023305I_____ |
|             | 11                | 21   | 26.5 | 22.5  | MKP1U026805I_____ | 9                 | 19   | 31.5 | 27.5  | MKP1V023306A_____ |
|             | 11                | 21   | 31.5 | 27.5  | MKP1U026806B_____ | 11                | 21   | 31.5 | 27.5  | MKP1V024706B_____ |
| 0.1 µF      | 13                | 24   | 31.5 | 27.5  | MKP1U031006D_____ | 13                | 24   | 31.5 | 27.5  | MKP1V026806D_____ |
| 0.15 "      | 15                | 26   | 31.5 | 27.5  | MKP1U031506F_____ | 15                | 26   | 31.5 | 27.5  | MKP1V031006F_____ |
| 0.22 "      | 17                | 34.5 | 31.5 | 27.5  | MKP1U032206I_____ | 13                | 24   | 41.5 | 37.5  | MKP1V031007C_____ |
| 0.33 "      | 17                | 29   | 41.5 | 37.5  | MKP1U032207E_____ | 17                | 34.5 | 31.5 | 27.5  | MKP1V031506I_____ |
| 0.47 "      | 19                | 32   | 41.5 | 37.5  | MKP1U033307F_____ | 15                | 26   | 41.5 | 37.5  | MKP1V031507D_____ |
| 0.68 "      | 20                | 39.5 | 41.5 | 37.5  | MKP1U034707G_____ | 19                | 32   | 41.5 | 37.5  | MKP1V032207F_____ |
| 1.0 µF      | 24                | 45.5 | 41.5 | 37.5  | MKP1U036807H_____ | 24                | 45.5 | 41.5 | 37.5  | MKP1V033307H_____ |
| 1.5 "       | 35                | 50   | 41.5 | 37.5  | MKP1U041007J_____ | 31                | 46   | 41.5 | 37.5  | MKP1V034707I_____ |
| 2.2 "       | 40                | 55   | 41.5 | 37.5  | MKP1U041507K_____ | 35                | 50   | 41.5 | 37.5  | MKP1V036807J_____ |
|             | 35                | 50   | 57   | 52.5  | MKP1U041509F_____ | 40                | 55   | 41.5 | 37.5  | MKP1V041007K_____ |
|             | 45                | 55   | 57   | 52.5  | MKP1U042209H_____ | 35                | 50   | 57   | 52.5  | MKP1V041009F_____ |
|             |                   |      |      |       |                   | 45                | 55   | 57   | 52.5  | MKP1V041509H_____ |

\* AC voltage:  $f \leq 1000 \text{ Hz}$ ;  $1.4 \times U_{\text{rms}} + U_{\text{DC}} \leq U_r$

\*\* PCM = Printed circuit module = pin spacing

Dims. in mm.

Ionisation inception level in isolated cases may be lower than admissible rated AC voltage.

#### Part number completion:

|                             |       |      |
|-----------------------------|-------|------|
| Version code:               | 2-pin | = 00 |
|                             | 4-pin | = D4 |
| Tolerance:                  | 20 %  | = M  |
|                             | 10 %  | = K  |
|                             | 5 %   | = J  |
| Packing:                    | bulk  | = S  |
| Pin length:                 | 6-2   | = SD |
| Taped version see page 149. |       |      |

Rights reserved to amend design data without prior notification.

Continuation page 71

## Continuation

### General Data


| Capacitance        | W    | H    | L    | PCM** | Part number  | * AC voltage: $f \leq 1000 \text{ Hz}$ ; $1.4 \times U_{\text{rms}} + U_{\text{DC}} \leq U_r$<br>** PCM = Printed circuit module = pin spacing<br><br>Dims. in mm.<br><br>The box sizes according to the main catalogue 2015 are still available on request<br><br>Ionisation inception level in isolated cases may be lower than admissible rated AC voltage. |
|--------------------|------|------|------|-------|--------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 0.01 $\mu\text{F}$ | 8.5  | 18.5 | 26.5 | 22.5  | MKP1W021005F |                                                                                                                                                                                                                                                                                                                                                                |
| 0.015 "            | 10.5 | 19   | 26.5 | 22.5  | MKP1W021505G |                                                                                                                                                                                                                                                                                                                                                                |
| 0.022 "            | 11   | 21   | 26.5 | 22.5  | MKP1W022205I |                                                                                                                                                                                                                                                                                                                                                                |
| 0.033 "            | 11   | 21   | 26.5 | 22.5  | MKP1W023305L |                                                                                                                                                                                                                                                                                                                                                                |
|                    | 9    | 19   | 31.5 | 27.5  | MKP1W023306A |                                                                                                                                                                                                                                                                                                                                                                |
| 0.047 "            | 11   | 21   | 31.5 | 27.5  | MKP1W024706B |                                                                                                                                                                                                                                                                                                                                                                |
| 0.068 "            | 13   | 24   | 31.5 | 27.5  | MKP1W026806D |                                                                                                                                                                                                                                                                                                                                                                |
| 0.1 $\mu\text{F}$  | 15   | 26   | 31.5 | 27.5  | MKP1W031006F |                                                                                                                                                                                                                                                                                                                                                                |
|                    | 13   | 24   | 41.5 | 37.5  | MKP1W031007C |                                                                                                                                                                                                                                                                                                                                                                |
| 0.15 "             | 17   | 34.5 | 31.5 | 27.5  | MKP1W031506I |                                                                                                                                                                                                                                                                                                                                                                |
|                    | 15   | 26   | 41.5 | 37.5  | MKP1W031507D |                                                                                                                                                                                                                                                                                                                                                                |
| 0.22 "             | 19   | 32   | 41.5 | 37.5  | MKP1W032207F |                                                                                                                                                                                                                                                                                                                                                                |
| 0.33 "             | 24   | 45.5 | 41.5 | 37.5  | MKP1W033307H |                                                                                                                                                                                                                                                                                                                                                                |
| 0.47 "             | 31   | 46   | 41.5 | 37.5  | MKP1W034707I |                                                                                                                                                                                                                                                                                                                                                                |
| 0.68 "             | 35   | 50   | 41.5 | 37.5  | MKP1W036807J |                                                                                                                                                                                                                                                                                                                                                                |
| 1.0 $\mu\text{F}$  | 40   | 55   | 41.5 | 37.5  | MKP1W041007K |                                                                                                                                                                                                                                                                                                                                                                |
|                    | 35   | 50   | 57   | 52.5  | MKP1W041009F |                                                                                                                                                                                                                                                                                                                                                                |
| 1.5 "              | 45   | 55   | 57   | 52.5  | MKP1W041509H |                                                                                                                                                                                                                                                                                                                                                                |

| $\phi d$ | PCM       |
|----------|-----------|
| 0.6      | 7.5 - 10  |
| 0.8      | 15 - 27.5 |
| 1.0      | 37.5      |

| W  | PCM  | b    | $\phi d$ | c   |
|----|------|------|----------|-----|
| 17 | 37.5 | 10   | 1.0      | 0.4 |
| 19 | 37.5 | 10   | 1.0      | 0.4 |
| 20 | 37.5 | 12.5 | 1.0      | 0.4 |
| 24 | 37.5 | 12.5 | 1.0      | 0.4 |
| 31 | 37.5 | 20   | 1.0      | 0.4 |
| 35 | 37.5 | 20   | 1.0      | 0.4 |
| 40 | 37.5 | 20   | 1.0      | 0.4 |
| 45 | 52.5 | 20   | 1.2      | 0.8 |
| 45 | 52.5 | 20   | 1.2      | 0.8 |

Permissible AC voltage in relation to frequency at 10° C internal temperature rise (general guide).



## Recommendation for Processing and Application of Through-Hole Capacitors

### Soldering Process

Internal temperature of the capacitor must be kept as follows:

Polyester: preheating:  $T_{\max.} \leq 125^{\circ}\text{C}$   
soldering:  $T_{\max.} \leq 135^{\circ}\text{C}$

Polypropylene: preheating:  $T_{\max.} \leq 100^{\circ}\text{C}$   
soldering:  $T_{\max.} \leq 110^{\circ}\text{C}$

#### Single wave soldering

Soldering bath temperature:  $T < 260^{\circ}\text{C}$


Dwell time:  $t < 5\text{ sec}$

#### Double wave soldering

Soldering bath temperature:  $T < 260^{\circ}\text{C}$

Dwell time:  $\Sigma t < 5\text{ sec}$

Due to different soldering processes and heat requirements the graphs are to be regarded as a recommendation only.



## WIMA Quality and Environmental Philosophy

### ISO 9001:2015 Certification

ISO 9001:2015 is an international basic standard of quality assurance systems for all branches of industry. The approval according to ISO 9001:2015 of our factories by the infaz (Institut für Auditierung und Zertifizierung) certifies that organisation, equipment and monitoring of quality assurance in our factories correspond to internationally recognized standards.

### WIMA WPCS

The WIMA Process Control System (WPCS) is a quality surveillance and optimization system developed by WIMA. WPCS is a major part of the quality-oriented WIMA production. Points of application during production process:

- incoming material inspection
- metallization
- film inspection
- schoopage
- pre-healing
- pin attachment
- cast resin preparation/encapsulation
- 100% final inspection
- Testing as per customer requirements

### WIMA Environmental Policy

All WIMA capacitors, irrespective of whether through-hole devices or SMD, are made of environmentally friendly materials. Neither during manufacture nor in the product itself any toxic substances are used, e.g.

- |                        |            |
|------------------------|------------|
| - Lead                 | - PBB/PBDE |
| - PCB                  | - Arsenic  |
| - CFC                  | - Cadmium  |
| - Hydrocarbon chloride | - Mercury  |
| - Chromium 6+          | - etc.     |

We merely use pure, recyclable materials for packing our components, such as:

- carton
- cardboard
- adhesive tape made of paper
- polystyrene

We almost completely refrain from using packing materials such as:

- adhesive tapes made of plastic
- metal clips

### RoHS Compliance

According to the RoHS Directive 2011/65/EU as amended from time to time certain hazardous substances like e.g. lead, cadmium, mercury must not be used any longer in electronic equipment as of July 1st, 2006. For the sake of the environment WIMA has refrained from using such substances since years already.



WIMA Kondensatoren sind bleifrei konform RoHS 2011/65/EU

WIMA capacitors are lead free in accordance with RoHS 2011/65/EU

Tape for lead-free WIMA capacitors

### DIN EN ISO 14001:2004

WIMA's environmental management has been established in accordance with the guidelines of DIN EN ISO 14001:2004 to optimize the production processes with regard to energy and resources.

## Typical Dimensions for Taping Configuration




Diagram 1:  
PCM 2.5/5/7.5mm




Diagram 2: PCM 10/15 mm

Diagram 3: PCM 22.5 and 27.5\*mm

\*PCM 27.5 taping possible with two feed holes between components

| Designation                                      | Symbol         | Dimensions for Radial Taping                             |                                                          |                                                           |                                                           |                                                           |                                                           |                                                                     |
|--------------------------------------------------|----------------|----------------------------------------------------------|----------------------------------------------------------|-----------------------------------------------------------|-----------------------------------------------------------|-----------------------------------------------------------|-----------------------------------------------------------|---------------------------------------------------------------------|
|                                                  |                | PCM 2.5 taping                                           | PCM 5 taping                                             | PCM 7.5 taping                                            | PCM 10 taping*                                            | PCM 15 taping*                                            | PCM 22.5 taping                                           | PCM 27.5 taping                                                     |
| Carrier tape width                               | W              | 18.0 ±0.5                                                | 18.0 ±0.5                                                | 18.0 ±0.5                                                 | 18.0 ±0.5                                                 | 18.0 ±0.5                                                 | 18.0 ±0.5                                                 | 18.0 ±0.5                                                           |
| Hold-down tape width                             | W <sub>0</sub> | 6.0 for hot-sealing adhesive tape                        | 6.0 for hot-sealing adhesive tape                        | 12.0 for hot-sealing adhesive tape                        | 12.0 for hot-sealing adhesive tape                        | 12.0 for hot-sealing adhesive tape                        | 12.0 for hot-sealing adhesive tape                        | 12.0 for hot-sealing adhesive tape                                  |
| Hole position                                    | W <sub>1</sub> | 9.0 ±0.5                                                 | 9.0 ±0.5                                                 | 9.0 ±0.5                                                  | 9.0 ±0.5                                                  | 9.0 ±0.5                                                  | 9.0 ±0.5                                                  | 9.0 ±0.5                                                            |
| Hold-down tape position                          | W <sub>2</sub> | 0.5 to 3.0 max.                                          | 0.5 to 3.0 max.                                          | 0.5 to 3.0 max.                                           | 0.5 to 3.0 max.                                           | 0.5 to 3.0 max.                                           | 0.5 to 3.0 max.                                           | 0.5 to 3.0 max.                                                     |
| Feed hole diameter                               | D <sub>0</sub> | 4.0 ±0.2                                                 | 4.0 ±0.2                                                 | 4.0 ±0.2                                                  | 4.0 ±0.2                                                  | 4.0 ±0.2                                                  | 4.0 ±0.2                                                  | 4.0 ±0.2                                                            |
| Pitch of component                               | P              | 12.7 ±1.0                                                | 12.7 ±1.0                                                | 12.7 ±1.0                                                 | 25.4 ±1.0                                                 | 25.4 ±1.0                                                 | 38.1 ±1.5                                                 | 38.1 ±1.5 or 50.8 ±1.5                                              |
| Feed hole pitch                                  | P <sub>0</sub> | 12.7 ±0.3<br>cumulative pitch error max. 1.0 mm/20 pitch | 12.7 ±0.3<br>cumulative pitch error max. 1.0 mm/20 pitch | 12.7 ±0.3<br>cumulative pitch error max. 1.0 mm/20 pitch  | 12.7 ±0.3<br>cumulative pitch error max. 1.0 mm/20 pitch  | 12.7 ±0.3<br>cumulative pitch error max. 1.0 mm/20 pitch  | 12.7 ±0.3<br>cumulative pitch error max. 1.0 mm/20 pitch  | 12.7 ±0.3<br>cumulative pitch error max. 1.0 mm/20 pitch            |
| Feed hole centre to pin                          | P <sub>1</sub> | 5.1 ±0.5                                                 | 3.85 ±0.7                                                | 2.6 ±0.7                                                  | 7.7 ±0.7                                                  | 5.2 ±0.7                                                  | 7.8 ±0.7                                                  | 5.3 ±0.7                                                            |
| Hole centre to component centre                  | P <sub>2</sub> | 6.35 ±1.3                                                | 6.35 ±1.3                                                | 6.35 ±1.3                                                 | 12.7 ±1.3                                                 | 12.7 ±1.3                                                 | 19.05 ±1.3                                                | 19.05 ±1.3                                                          |
| Feed hole centre to bottom edge of the component | H              | 16.5 ±0.3<br>18.5 ±0.5                                   | 16.5 ±0.3<br>18.5 ±0.5                                   | 16.5 ±0.5<br>18.5 ±0.5                                    | 16.5 ±0.5<br>18.5 ±0.5                                    | 16.5 ±0.5<br>18.5 ±0.5                                    | 16.5 ±0.5<br>18.5 ±0.5                                    | 16.5 ±0.5<br>18.5 ±0.5                                              |
| Feed hole centre to top edge of the component    | H <sub>1</sub> | H+H <sub>component</sub> < H <sub>1</sub><br>32.25 max.  | H+H <sub>component</sub> < H <sub>1</sub><br>32.25 max.  | H+H <sub>component</sub> < H <sub>1</sub><br>24.5 to 31.5 | H+H <sub>component</sub> < H <sub>1</sub><br>25.0 to 31.5 | H+H <sub>component</sub> < H <sub>1</sub><br>26.0 to 37.0 | H+H <sub>component</sub> < H <sub>1</sub><br>30.0 to 43.0 | H+H <sub>component</sub> < H <sub>1</sub><br>35.0 to 45.0           |
| Pin spacing at upper edge of carrier tape        | F              | 2.5 ±0.5                                                 | 5.0 <sup>+0.8</sup> <sub>-0.2</sub>                      | 7.5 ±0.8                                                  | 10.0 ±0.8                                                 | 15 ±0.8                                                   | 22.5 ±0.8                                                 | 27.5 ±0.8                                                           |
| Pin diameter                                     | d              | 0.4 ±0.05                                                | 0.5 ±0.05                                                | 0.5 ±0.05 or 0.6 <sup>+0.06</sup> <sub>-0.05</sub>        | 0.5 ±0.05 or 0.6 <sup>+0.06</sup> <sub>-0.05</sub>        | 0.8 <sup>+0.08</sup> <sub>-0.05</sub>                     | 0.8 <sup>+0.08</sup> <sub>-0.05</sub>                     | 0.8 <sup>+0.08</sup> <sub>-0.05</sub>                               |
| Component alignment                              | Δh             | ± 2.0 max.                                               | ± 2.0 max.                                               | ± 3.0 max.                                                | ± 3.0 max.                                                | ± 3.0 max.                                                | ± 3.0 max.                                                | ± 3.0 max.                                                          |
| Total tape thickness                             | t              | 0.6 ±0.2                                                 | 0.6 ±0.2                                                 | 0.6 ±0.2                                                  | 0.6 ±0.2                                                  | 0.6 ±0.2                                                  | 0.6 ±0.2                                                  | 0.6 ±0.2                                                            |
| Package<br>(see also page 150)                   |                | ROLL/AMMO                                                |                                                          |                                                           | AMMO                                                      |                                                           |                                                           |                                                                     |
|                                                  |                | REEL Ø 360 max.<br>Ø 30 ±1                               | B 52 ±2<br>58 ±2 } depending on comp. dimensions         |                                                           | REEL Ø 360 max.<br>Ø 30 ±1                                | 52 ±2<br>58 ±2 or 66 ±2                                   | REEL Ø 500 max.<br>Ø 25 ±1                                | 54 ±2<br>60 ±2 or 68 ±2 } depending on PCM and component dimensions |
| Unit                                             |                | see details page 151.                                    |                                                          |                                                           |                                                           |                                                           |                                                           |                                                                     |

Dims in mm.

\* Diameter of pins see General Data.


\* PCM 10 and PCM 15 can be crimped to PCM 7.5.

Position of components according to PCM 7.5 (sketch 11). P<sub>0</sub> = 12.7 or 15.0 is possible


Please clarify customer-specific deviations with the manufacturer.

## Types of Tape Packaging of Capacitors for Automatic Radial Insertion


### ■ ROLL Packaging



### ■ AMMO Packaging



### ■ REEL Packaging



## BAR CODE (Labelling)

Labelling of package units in plain text and with alphanumerical Bar Code

Scanner decoding of

- WIMA supplier number
- Customer's P/O number
- Customer's part number
- WIMA confirmation number
- WIMA part number
- Lot number
- Date code
- Quantity

In addition part description of

- article
- capacitance value
- rated voltage
- dimensions
- capacitance tolerance
- packing

as well as gross weight and customer's name are indicated in plain text.

|                                             |                                      |                                   |              |
|---------------------------------------------|--------------------------------------|-----------------------------------|--------------|
| <b>WIMA</b> Best Capacitors Made In Germany |                                      | Werk Unna                         |              |
| Supplier-ID: 123456789                      | <b>RoHS</b><br>2011/65/EU            | Date Code: 08.10.10               |              |
| Purchase Order No. (P/O): Bestellung xyz    |                                      | Quantity: 5.000                   |              |
| Customer Part No.: KUNDETEILENUMMER         |                                      | Customer No.: 0000100002          |              |
|                                             |                                      | Gross Weight [g]: 1870            |              |
| WIMA Confirmation No.: 0001004053000100     |                                      | WIMA Part No.: MKS2C034701C00K88D |              |
| Handling Unit:                              | MKS 2                                | QTY: 5.000                        | COO: DE      |
|                                             | MKS 2 0.47 µF 63 VDC 3.5x8.5x7.2 RM5 |                                   |              |
|                                             | Standard 10% Loss - Standard         |                                   | Drühte 6-2   |
| 1000067326                                  | Vorlage Debitor Inland               |                                   | Week 03/2011 |

BARCODE „Code 39“

## Packing Quantities for Capacitors with Radial Pins in PCM 2.5 mm to 22.5 mm



| PCM     | Size  |       |                |                | bulk | pcs. per packing unit |                    |      |      |      |   |      |   |   |  |
|---------|-------|-------|----------------|----------------|------|-----------------------|--------------------|------|------|------|---|------|---|---|--|
|         |       |       |                |                |      | ROLL                  |                    | REEL |      |      |   | AMMO |   |   |  |
|         | H16.5 | H18.5 | ø 360<br>H16.5 | ø 500<br>H18.5 |      | 340 × 340<br>H16.5    | 490 × 370<br>H18.5 |      |      |      |   |      |   |   |  |
| W       | H     | L     | Codes          | S              | N    | O                     | F                  | I    | H    | J    | A | C    | B | D |  |
| 2.5 mm  | 2.5   | 7     | 4.6            | 0B             | 5000 | 2200                  | 2500               | —    | 2800 | —    |   |      |   |   |  |
|         | 3     | 7.5   | 4.6            | 0C             | 5000 | 2000                  | 2300               | —    | 2300 | —    |   |      |   |   |  |
|         | 3.8   | 8.5   | 4.6            | 0D             | 5000 | 1500                  | 1800               | —    | 1800 | —    |   |      |   |   |  |
|         | 4.6   | 9     | 4.6            | 0E             | 5000 | 1200                  | 1500               | —    | 1500 | —    |   |      |   |   |  |
|         | 5.5   | 10    | 4.6            | 0F             | 5000 | 900                   | 1200               | —    | 1200 | —    |   |      |   |   |  |
| 5 mm    | 2.5   | 6.5   | 7.2            | 1A             | 5000 | 2200                  | 2500               | —    | 2800 | —    |   |      |   |   |  |
|         | 3     | 7.5   | 7.2            | 1B             | 5000 | 2000                  | 2300               | —    | 2300 | —    |   |      |   |   |  |
|         | 3.5   | 8.5   | 7.2            | 1C             | 5000 | 1600                  | 2000               | —    | 2000 | —    |   |      |   |   |  |
|         | 4.5   | 6     | 7.2            | 1D             | 6000 | 1300                  | 1500               | —    | 1500 | —    |   |      |   |   |  |
|         | 4.5   | 9.5   | 7.2            | 1E             | 4000 | 1300                  | 1500               | —    | 1500 | —    |   |      |   |   |  |
|         | 5     | 10    | 7.2            | 1F             | 3500 | 1100                  | 1400               | —    | 1400 | —    |   |      |   |   |  |
|         | 5.5   | 7     | 7.2            | 1G             | 4000 | 1000                  | 1200               | —    | 1200 | —    |   |      |   |   |  |
|         | 5.5   | 11.5  | 7.2            | 1H             | 2500 | 1000                  | 1200               | —    | 1200 | —    |   |      |   |   |  |
|         | 6.5   | 8     | 7.2            | 1I             | 2500 | 800                   | 1000               | —    | 1000 | —    |   |      |   |   |  |
|         | 7.2   | 8.5   | 7.2            | 1J             | 2500 | 700                   | 1000               | —    | 1000 | —    |   |      |   |   |  |
|         | 7.2   | 13    | 7.2            | 1K             | 2000 | 700                   | 950                | —    | 1000 | —    |   |      |   |   |  |
|         | 8.5   | 10    | 7.2            | 1L             | 2000 | 600                   | 800                | —    | 800  | —    |   |      |   |   |  |
|         | 8.5   | 14    | 7.2            | 1M             | 1500 | 600                   | 800                | —    | 800  | —    |   |      |   |   |  |
|         | 11    | 16    | 7.2            | 1N             | 1000 | 500                   | 600                | —    | 640  | —    |   |      |   |   |  |
| 7.5 mm  | 2.5   | 7     | 10             | 2A             | 5000 | —                     | 2500               | 4400 | 2500 | —    |   |      |   |   |  |
|         | 3     | 8.5   | 10             | 2B             | 5000 | —                     | 2200               | 4300 | 2300 | 4150 |   |      |   |   |  |
|         | 4     | 9     | 10             | 2C             | 4000 | —                     | 1700               | 3200 | 1700 | 3100 |   |      |   |   |  |
|         | 4.5   | 9.5   | 10.3           | 2D             | 3500 | —                     | 1500               | 2900 | 1400 | 2700 |   |      |   |   |  |
|         | 5     | 10.5  | 10.3           | 2E             | 3000 | —                     | 1300               | 2500 | 1300 | —    |   |      |   |   |  |
|         | 5.7   | 12.5  | 10.3           | 2F             | 2000 | —                     | 1000               | 2200 | 1100 | —    |   |      |   |   |  |
|         | 7.2   | 12.5  | 10.3           | 2G             | 1500 | —                     | 900                | 1800 | 1000 | —    |   |      |   |   |  |
| 10 mm   | 3     | 9     | 13             | 3A             | 3000 | —                     | 1100               | 2200 | —    | 1900 |   |      |   |   |  |
|         | 4     | 8.5   | 13.5           | FA             | 3000 | —                     | 900                | 1600 | —    | 1450 |   |      |   |   |  |
|         | 4     | 9     | 13             | 3C             | 3000 | —                     | 900                | 1600 | —    | 1450 |   |      |   |   |  |
|         | 4     | 9.5   | 13             | 3D             | 3000 | —                     | 900                | 1600 | —    | 1400 |   |      |   |   |  |
|         | 5     | 10    | 13.5           | FB             | 2000 | —                     | 700                | 1300 | —    | 1200 |   |      |   |   |  |
|         | 5     | 11    | 13             | 3F             | 3000 | —                     | 700                | 1300 | —    | 1200 |   |      |   |   |  |
|         | 6     | 12    | 13             | 3G             | 2400 | —                     | 550                | 1100 | —    | 1000 |   |      |   |   |  |
|         | 6     | 12.5  | 13             | 3H             | 2400 | —                     | 550                | 1100 | —    | 1000 |   |      |   |   |  |
| 15 mm   | 8     | 12    | 13             | 3I             | 2000 | —                     | 400                | 800  | —    | 740  |   |      |   |   |  |
|         | 5     | 11    | 18             | 4B             | 2400 | —                     | 600                | 1200 | —    | 1150 |   |      |   |   |  |
|         | 5     | 13    | 19             | FC             | 1000 | —                     | 600                | 1200 | —    | 1200 |   |      |   |   |  |
|         | 6     | 12.5  | 18             | 4C             | 2000 | —                     | 500                | 1000 | —    | 1000 |   |      |   |   |  |
|         | 6     | 14    | 19             | FD             | 1000 | —                     | 500                | 1000 | —    | 1000 |   |      |   |   |  |
|         | 7     | 14    | 18             | 4D             | 1600 | —                     | 450                | 900  | —    | 850  |   |      |   |   |  |
|         | 7     | 15    | 19             | FE             | 1000 | —                     | 450                | 900  | —    | 850  |   |      |   |   |  |
|         | 8     | 15    | 18             | 4F             | 1200 | —                     | 400                | 800  | —    | 740  |   |      |   |   |  |
|         | 8     | 17    | 19             | FF             | 500  | —                     | 400                | 800  | —    | 740  |   |      |   |   |  |
|         | 9     | 14    | 18             | 4H             | 1200 | —                     | 350                | 700  | —    | 650  |   |      |   |   |  |
|         | 9     | 16    | 18             | 4J             | 900  | —                     | 350                | 700  | —    | 650  |   |      |   |   |  |
| 22.5 mm | 10    | 18    | 19             | FG             | 500  | —                     | 300                | 650  | —    | 590  |   |      |   |   |  |
|         | 11    | 14    | 18             | 4M             | 1000 | —                     | 300                | 600  | —    | 540  |   |      |   |   |  |
|         | 5     | 14    | 26.5           | 5A             | 1200 | —                     | —                  | 800  | —    | 770  |   |      |   |   |  |
|         | 6     | 15    | 26.5           | 5B             | 1000 | —                     | —                  | 700  | —    | 640  |   |      |   |   |  |
|         | 7     | 16.5  | 26.5           | 5D             | 760  | —                     | —                  | 600  | —    | 550  |   |      |   |   |  |
|         | 8     | 20    | 28             | FH             | 500  | —                     | —                  | 500  | —    | 480  |   |      |   |   |  |
|         | 8.5   | 18.5  | 26.5           | 5F             | 500  | —                     | —                  | 480  | —    | 450  |   |      |   |   |  |
|         | 10    | 22    | 28             | FI             | 570* | —                     | —                  | 420  | —    | 380  |   |      |   |   |  |
|         | 10.5  | 19    | 26.5           | 5G             | 594* | —                     | —                  | 400  | —    | 360  |   |      |   |   |  |
|         | 10.5  | 20.5  | 26.5           | 5H             | 594* | —                     | —                  | 400  | —    | 360  |   |      |   |   |  |
| 11      | 21    | 26.5  | 5I             | 561*           | —    | —                     | 380                | —    | 350  |      |   |      |   |   |  |
| 12      | 24    | 28    | FJ             | 480*           | —    | —                     | 350                | —    | 310  |      |   |      |   |   |  |

\* TPS (Tray-Packing-System). Plate versions may have different packing units.  
Samples and pre-production needs on request.

■ Moulded versions.

Rights reserved to amend design data without prior notification.

## Packing Quantities for Capacitors with Radial Pins in PCM 27.5 mm to 52.5 mm

| PCM     | Size |      |      |       | bulk | pcs. per packing unit |       |       |   |          |   |           |   |           |   |
|---------|------|------|------|-------|------|-----------------------|-------|-------|---|----------|---|-----------|---|-----------|---|
|         |      |      |      |       |      | ROLL                  |       | REEL  |   |          |   | AMMO      |   |           |   |
|         |      |      |      |       |      | H16.5                 | H18.5 | ø 360 |   | ø 500    |   | 340 x 340 |   | 490 x 370 |   |
|         | W    | H    | L    | Codes | S    | N                     | O     | F     | I | H        | J | A         | C | B         | D |
| 27.5 mm | 9    | 19   | 31.5 | 6A    | 567* | –                     | –     | –     | – | 460/340* | – | –         | – | 420       | – |
|         | 11   | 21   | 31.5 | 6B    | 459* | –                     | –     | –     | – | 380/280* | – | –         | – | 350       | – |
|         | 13   | 24   | 31.5 | 6D    | 378* | –                     | –     | –     | – | 300      | – | –         | – | 290       | – |
|         | 13   | 25   | 33   | FK    | 405* | –                     | –     | –     | – | –        | – | –         | – | –         | – |
|         | 15   | 26   | 31.5 | 6F    | 324* | –                     | –     | –     | – | 270      | – | –         | – | 250       | – |
|         | 15   | 26   | 33   | FL    | 324* | –                     | –     | –     | – | –        | – | –         | – | –         | – |
|         | 17   | 29   | 31.5 | 6G    | 198* | –                     | –     | –     | – | –        | – | –         | – | –         | – |
|         | 17   | 34.5 | 31.5 | 6I    | 198* | –                     | –     | –     | – | –        | – | –         | – | –         | – |
|         | 20   | 32   | 33   | FM    | 162* | –                     | –     | –     | – | –        | – | –         | – | –         | – |
|         | 20   | 39.5 | 31.5 | 6J    | 162* | –                     | –     | –     | – | –        | – | –         | – | –         | – |
| 37.5 mm | 9    | 19   | 41.5 | 7A    | 441* | –                     | –     | –     | – | –        | – | –         | – | –         | – |
|         | 11   | 22   | 41.5 | 7B    | 357* | –                     | –     | –     | – | –        | – | –         | – | –         | – |
|         | 13   | 24   | 41.5 | 7C    | 294* | –                     | –     | –     | – | –        | – | –         | – | –         | – |
|         | 15   | 26   | 41.5 | 7D    | 252* | –                     | –     | –     | – | –        | – | –         | – | –         | – |
|         | 17   | 29   | 41.5 | 7E    | 154* | –                     | –     | –     | – | –        | – | –         | – | –         | – |
|         | 19   | 32   | 41.5 | 7F    | 140* | –                     | –     | –     | – | –        | – | –         | – | –         | – |
|         | 20   | 39.5 | 41.5 | 7G    | 126* | –                     | –     | –     | – | –        | – | –         | – | –         | – |
|         | 24   | 45.5 | 41.5 | 7H    | 112* | –                     | –     | –     | – | –        | – | –         | – | –         | – |
|         | 31   | 46   | 41.5 | 7I    | 84*  | –                     | –     | –     | – | –        | – | –         | – | –         | – |
|         | 35   | 50   | 41.5 | 7J    | 35*  | –                     | –     | –     | – | –        | – | –         | – | –         | – |
|         | 40   | 55   | 41.5 | 7K    | 28*  | –                     | –     | –     | – | –        | – | –         | – | –         | – |
| 48.5 mm | 19   | 31   | 56   | 8D    | 120* | –                     | –     | –     | – | –        | – | –         | – | –         | – |
|         | 23   | 34   | 56   | 8E    | 80*  | –                     | –     | –     | – | –        | – | –         | – | –         | – |
|         | 27   | 37.5 | 56   | 8H    | 84*  | –                     | –     | –     | – | –        | – | –         | – | –         | – |
|         | 33   | 48   | 56   | 8J    | 25*  | –                     | –     | –     | – | –        | – | –         | – | –         | – |
|         | 37   | 54   | 56   | 8L    | 25*  | –                     | –     | –     | – | –        | – | –         | – | –         | – |
| 52.5 mm | 25   | 45   | 57   | 9D    | 70*  | –                     | –     | –     | – | –        | – | –         | – | –         | – |
|         | 30   | 45   | 57   | 9E    | 60*  | –                     | –     | –     | – | –        | – | –         | – | –         | – |
|         | 35   | 50   | 57   | 9F    | 25*  | –                     | –     | –     | – | –        | – | –         | – | –         | – |
|         | 45   | 55   | 57   | 9H    | 20*  | –                     | –     | –     | – | –        | – | –         | – | –         | – |
|         | 45   | 65   | 57   | 9J    | 20*  | –                     | –     | –     | – | –        | – | –         | – | –         | – |

\* for 2-inch transport pitches.

\* TPS (Tray-Packing-System). Plate versions may have different packing units.  
Samples and pre-production needs on request.

■ Moulded versions.

Rights reserved to amend design data without prior notification.

Updated data on [www.wima.com](http://www.wima.com)

A WIMA part number consists of 18 digits and is composed as follows:

Field 1 - 4: Type description  
 Field 5 - 6: Rated voltage  
 Field 7 - 10: Capacitance  
 Field 11 - 12: Size and PCM  
 Field 13 - 14: Version code (e.g. Snubber versions)  
 Field 15: Capacitance tolerance  
 Field 16: Packing  
 Field 17 - 18: Pin length (untaped)

| 1                        | 2 | 3 | 4 | 5                     | 6 | 7                   | 8 | 9 | 10 | 11                         | 12 | 13                | 14 | 15                     | 16   | 17   | 18 |
|--------------------------|---|---|---|-----------------------|---|---------------------|---|---|----|----------------------------|----|-------------------|----|------------------------|------|------|----|
| M                        | K | S | 2 | C                     | 0 | 2                   | 1 | 0 | 0  | 1                          | A  | 0                 | 0  | M                      | S    | S    | D  |
| MKS 2                    |   |   |   | 63 VDC                |   | 0.01 μF             |   |   |    | 2.5x6.5x7.2                |    | -                 |    | 20%                    | bulk | 6 -2 |    |
| <b>Type description:</b> |   |   |   | <b>Rated voltage:</b> |   | <b>Capacitance:</b> |   |   |    | <b>Size:</b>               |    | <b>Tolerance:</b> |    | <b>Packing:</b>        |      |      |    |
| SMD-PET = SMDT           |   |   |   | 50 VDC = B0           |   | 22 pF = 0022        |   |   |    | 4.8x3.3x3 Size 1812 = KA   |    | ±20% = M          |    | AMMO H16.5 340x340 = A |      |      |    |
| SMD-PEN = SMDN           |   |   |   | 63 VDC = C0           |   | 47 pF = 0047        |   |   |    | 4.8x3.3x4 Size 1812 = KB   |    | ±10% = K          |    | AMMO H16.5 490x370 = B |      |      |    |
| SMD-PPS = SMDI           |   |   |   | 100 VDC = D0          |   | 100 pF = 0100       |   |   |    | 5.7x5.1x3.5 Size 2220 = QA |    | ±5% = J           |    | AMMO H18.5 340x340 = C |      |      |    |
| FKP 02 = FKPO            |   |   |   | 250 VDC = F0          |   | 150 pF = 0150       |   |   |    | 5.7x5.1x4.5 Size 2220 = QB |    | ±2.5% = H         |    | AMMO H18.5 490x370 = D |      |      |    |
| MKS 02 = MKS0            |   |   |   | 400 VDC = G0          |   | 220 pF = 0220       |   |   |    | 7.2x6.1x3 Size 2824 = TA   |    | ±1% = E           |    | REEL H16.5 360 = F     |      |      |    |
| FKS 2 = FKS2             |   |   |   | 450 VDC = H0          |   | 330 pF = 0330       |   |   |    | 7.2x6.1x5 Size 2824 = TB   |    | ...               |    | REEL H16.5 500 = H     |      |      |    |
| FKP 2 = FKP2             |   |   |   | 520 VDC = H2          |   | 470 pF = 0470       |   |   |    | 10.2x7.6x5 Size 4030 = VA  |    |                   |    | REEL H18.5 360 = I     |      |      |    |
| FKS 3 = FKS3             |   |   |   | 600 VDC = I0          |   | 680 pF = 0680       |   |   |    | 12.7x10.2x6 Size 5040 = XA |    |                   |    | REEL H18.5 500 = J     |      |      |    |
| FKP 3 = FKP 3            |   |   |   | 630 VDC = J0          |   | 1000 pF = 1100      |   |   |    | 15.3x13.7x7 Size 6054 = YA |    |                   |    | ROLL H16.5 = N         |      |      |    |
| MKS 2 = MKS2             |   |   |   | 700 VDC = K0          |   | 1500 pF = 1150      |   |   |    | 2.5x7x4.6 PCM 2.5 = 0B     |    |                   |    | ROLL H18.5 = O         |      |      |    |
| MKP 2 = MKP2             |   |   |   | 800 VDC = L0          |   | 2200 pF = 1220      |   |   |    | 3x7.5x4.6 PCM 2.5 = 0C     |    |                   |    | BLISTER W12 180 = P    |      |      |    |
| MKS 4 = MKS4             |   |   |   | 850 VDC = M0          |   | 3300 pF = 1330      |   |   |    | 2.5x6.5x7.2 PCM 5 = 1A     |    |                   |    | BLISTER W12 330 = Q    |      |      |    |
| MKP 4C = MKPC            |   |   |   | 900 VDC = N0          |   | 4700 pF = 1470      |   |   |    | 3x7.5x7.2 PCM 5 = 1B       |    |                   |    | BLISTER W16 330 = R    |      |      |    |
| MKP 4 = MKP4             |   |   |   | 1000 VDC = O1         |   | 6800 pF = 1680      |   |   |    | 2.5x7x10 PCM 7.5 = 2A      |    |                   |    | BLISTER W24 330 = T    |      |      |    |
| MKP 10 = MKP1            |   |   |   | 1100 VDC = P0         |   | 0.01 μF = 2100      |   |   |    | 3x8.5x10 PCM 7.5 = 2B      |    |                   |    | Bulk/TPS Standard = S  |      |      |    |
| FKP 1 = FKP1             |   |   |   | 1200 VDC = Q0         |   | 0.022 μF = 2220     |   |   |    | 3x9x13 PCM 10 = 3A         |    |                   |    | ...                    |      |      |    |
| MKP-X2 = MKX2            |   |   |   | 1250 VDC = R0         |   | 0.047 μF = 2470     |   |   |    | 4x9x13 PCM 10 = 3C         |    |                   |    |                        |      |      |    |
| MKP-X1 R = MKX1          |   |   |   | 1500 VDC = S0         |   | 0.1 μF = 3100       |   |   |    | 5x11x18 PCM 15 = 4B        |    |                   |    |                        |      |      |    |
| MKP-Y2 = MKY2            |   |   |   | 1600 VDC = T0         |   | 0.22 μF = 3220      |   |   |    | 6x12.5x18 PCM 15 = 4C      |    |                   |    |                        |      |      |    |
| MP 3-X2 = MPX2           |   |   |   | 2000 VDC = U0         |   | 0.47 μF = 3470      |   |   |    | 5x14x26.5 PCM 22.5 = 5A    |    |                   |    |                        |      |      |    |
| MP 3-X1 = MPX1           |   |   |   | 2500 VDC = V0         |   | 1 μF = 4100         |   |   |    | 6x15x26.5 PCM 22.5 = 5B    |    |                   |    |                        |      |      |    |
| MP 3-Y2 = MPY2           |   |   |   | 3000 VDC = W0         |   | 2.2 μF = 4220       |   |   |    | 9x19x31.5 PCM 27.5 = 6A    |    |                   |    |                        |      |      |    |
| MP 3R-Y2 = MPRY          |   |   |   | 4000 VDC = X0         |   | 4.7 μF = 4470       |   |   |    | 11x21x31.5 PCM 27.5 = 6B   |    |                   |    |                        |      |      |    |
| MKP 4F = MKPF            |   |   |   | 6000 VDC = Y0         |   | 10 μF = 5100        |   |   |    | 9x19x41.5 PCM 37.5 = 7A    |    |                   |    |                        |      |      |    |
| Snubber MKP = SNMP       |   |   |   | 250 VAC = 0V          |   | 22 μF = 5220        |   |   |    | 11x22x41.5 PCM 37.5 = 7B   |    |                   |    |                        |      |      |    |
| Snubber FKP = SNFP       |   |   |   | 275 VAC = 1W          |   | 47 μF = 5470        |   |   |    | 19x31x56 PCM 48.5 = 8D     |    |                   |    |                        |      |      |    |
| GTO MKP = GTOM           |   |   |   | 300 VAC = 2W          |   | 100 μF = 6100       |   |   |    | 25x45x57 PCM 52.5 = 9D     |    |                   |    |                        |      |      |    |
| DC-LINK MKP 3 = DCP3     |   |   |   | 305 VAC = AV          |   | 220 μF = 6220       |   |   |    | ...                        |    |                   |    |                        |      |      |    |
| DC-LINK MKP 4 = DCP4     |   |   |   | 350 VAC = BV          |   | 1000 μF = 7100      |   |   |    |                            |    |                   |    |                        |      |      |    |
| DC-LINK MKP 4S = DCP5    |   |   |   | 440 VAC = 4W          |   | 1500 μF = 7150      |   |   |    |                            |    |                   |    |                        |      |      |    |
| DC-LINK MKP 5 = DCP5     |   |   |   | 500 VAC = 5W          |   | ...                 |   |   |    |                            |    |                   |    |                        |      |      |    |
| DC-LINK MKP 6 = DCP6     |   |   |   | ...                   |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
| DC-LINK HC = DCHC        |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
| DC-LINK HY = DCHY        |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |
|                          |   |   |   |                       |   |                     |   |   |    |                            |    |                   |    |                        |      |      |    |

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,  
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А