

EPDM**High-Temperature****UL AWM Style 3340 and 3374
600V, 125°C Flex/150°C No Flex
(CSA Type CL1254)****Product Description**

The insulation used for this High-Temperature lead wire is a chemically cross-linked ethylene-propylene diene elastomer. Never before could you find many of the characteristics that are found in Silicone and Hypalon® combined into one insulation. This 150°C EPDM wire offers more abrasion resistance than Hypalon... has the temperature rating of Silicone... at a price less than Silicone. EPDM has exceptional qualities that help you achieve new levels of economy and quality. 150°C EPDM wire is recommended for Class 130(B), 155(F) and also in some 180(H) systems. It's UL Recognized under Style 3374 as a 150°C—600V Appliance Wiring Material. The CSA Listing, as a coil lead, is 125°C, 600V. For additional technical information, see Technical Information pages at the end of this section.

Recommended maximum baking cycles:

24 hours @ 350°F (177°C) • 4 hours @ 375°F (190°C)

Stranded Conductor

Stranded tinned
copper conductor

Separator Over Conductor

Separator

Part No.	AWG (stranding) (sq. mm) (stranding in mm)	Insulation Thickness		Nominal OD		Standard Lengths		Standard Unit Weight		Stock Colors (See Color Codes Chart on Page 3.29)
		Inch	mm	Inch	mm	Ft.	m	Lbs.	kg	
600V, 125°C Flex/150°C No Flex (UL) • 600V, 125°C (CSA)										
UL AWM Style 3340 and 3374 • CSA Type CL1254										
37118	18 (16x30) [.82 (16x.25)]	.045	1.14	.142	3.61	500 [†]	152.4	7.5	3.4	2, 4, 5, 9, 10, 13
						5000 ^{††}	1524.0	70.0	31.8	2, 9, 10, 13
37116	16 (26x30) [1.32 (26x.25)]	.045	1.14	.154	3.91	500 [†]	152.4	9.5	4.3	2, 4, 5, 9, 10, 13
						4000 ^{††}	1219.2	72.0	32.7	10
						5000 ^{††}	1524.0	90.0	40.9	10
37114	14 (41x30) [2.08 (41x.25)]	.045	1.14	.169	4.29	500 [†]	152.4	12.5	5.7	2, 10
						4000 ^{††}	1219.2	96.0	43.6	2, 10
						5000 ^{††}	1524.0	125.0	56.8	10
37112	12 (65x30) [3.29 (65x.25)]	.045	1.14	.190	4.83	500 [†]	152.4	16.5	7.5	2, 10
						3000 ^{††}	914.4	105.0	47.7	10
						5000 ^{††}	1524.0	175.0	79.5	10
37110	10 (65x28) [5.23 (65x.32)]	.060	1.52	.240	6.10	500 [†]	152.4	26.0	11.8	10
						2000 ^{††}	609.6	108.0	49.2	10
						5000 ^{††}	1524.0	275.0	125.0	10
37108 [▼]	8 (84x27) [8.60 (84x.36)]	.080	2.03	.327	8.31	250 ^{**}	76.2	22.5	10.2	10
						500 [†]	152.4	48.0	21.8	10
						2500	762.0	235.0	106.8	10
37106 [▼]	6 (84x25) [13.66 (84x.46)]	.080	2.03	.383	9.73	100 [*]	30.5	14.2	6.5	10
						250 ^{**}	76.2	33.0	15.0	10
						500 [†]	152.4	69.0	31.3	10
						2500	762.0	345.0	156.8	10
37104 [▼]	4 (105x24) [21.53 (105x.51)]	.080	2.03	.432	10.97	100 [*]	30.5	18.7	8.5	10
						250 ^{**}	76.2	50.0	22.7	10
						500 [†]	152.4	98.5	44.8	10
						1000	304.8	196.0	89.1	10
37103 [▼]	3 (133x24) [27.28 (133x.51)]	.080	2.03	.453	11.51	100 [*]	30.5	22.7	10.3	10
						250 ^{**}	76.2	61.8	28.1	10
37102 [▼]	2 (163x24) [33.43 (163x.51)]	.080	2.03	.494	12.55	100 [*]	30.5	31.1	14.1	10
						250 ^{**}	76.2	72.3	32.8	10
						1000	304.8	286.0	130.0	10
37101 [▼]	1 (210x24) [43.07 (210x.51)]	.095	2.41	.583	14.81	100 [*]	30.5	41.0	18.6	10
						250 ^{**}	76.2	95.0	43.2	10
						1000	304.8	376.0	170.9	10
37190 [▼]	1/0 (262x24) [53.73 (262x.51)]	.095	2.41	.633	16.08	50	15.2	24.7	11.2	10
						100 [*]	30.5	48.3	22.0	10
						250 ^{**}	76.2	115.5	52.5	10
						500	152.4	223.5	101.6	10
37100 [▼]	2/0 (504x26) [67.85 (504x.41)]	.095	2.41	.698	17.73	50	15.2	30.9	14.0	10
						100 [*]	30.5	58.8	26.7	10
						250 ^{**}	76.2	141.8	64.4	10
						500	152.4	279.5	127.0	10
37130 [▼]	3/0 (630x26) [84.81 (630x.41)]	.095	2.41	.758	19.25	50	15.2	38.5	17.5	10
						250 ^{**}	76.2	174.0	79.1	10
						500	152.4	346.0	157.3	10
37140 [▼]	4/0 (805x26) [108.37 (805x.41)]	.095	2.41	.849	21.57	50	15.2	44.6	20.2	10
						250 ^{**}	76.2	215.8	98.1	10
						500	152.4	449.0	203.7	10

*Separator over conductor.

[†]May contain more than one piece. Length may vary ±10% from length shown.

^{††}May contain more than one piece. Minimum length of any one piece is 200 ft.

*100 ft. put-ups are exact, one piece.

**200 ft. put-ups are exact, but may contain 2 pieces max. Minimum length of any one piece is 50 ft.

Hypalon is a DuPont trademark.

BELDEN

For more information, contact **Belden Technical Support: 1-800-BELDEN-1 • www.belden.com**

EPDM

High-Temperature

UL AWM Style 3484

600V, 125°C

(CSA Type AWM)

Product Description

This series of EPDM (ethylene-propylene diene elastomer) will provide you with a lead wire which possesses excellent characteristics. The reduced wall thickness results in a UL and CSA Rating of 600V, 125°C. For additional technical information, see Technical Information pages at the end of this section.



Stranded tinned
copper conductor

UL AWM Style 3499

7500V, 150°C

High-Voltage EPDM

Product Description

The insulation used for this High-Voltage wire is a chemically cross-linked ethylene-propylene diene elastomer with a separator for improved strippability. EPDM is naturally corona resistant and more heat resistant than many other rubber compounds and is able to take the longer bake cycles frequently needed for the big jobs. EPDM has superior weather resistance and low temperature pliability. EPDM is used in many high voltage applications. For additional technical information, see Technical Information pages at the end of this section.

Recommended maximum baking cycles:
24 hours @ 350°F (177°C) • 4 hours @ 375°F (190°C)



Separator
Stranded tinned
copper conductor

Part No.	AWG (stranding) [sq. mm] (stranding in mm)	Insulation Thickness		Nominal OD		Standard Lengths		Standard Unit Weight		Stock Colors (See Color Codes Chart on Page 3.29)
		Inch	mm	Inch	mm	Ft.	m	Lbs.	kg	

600V, 125°C (UL & CSA)

UL AWM Style 3484 • CSA Type AWM

37222	22 (7x30) [.36 (7x.25)]	.030	.76	.093	2.36	*	*	*	*	Special Order*
37220	20 (10x30) [.51 (10x.25)]	.030	.76	.102	2.59	*	*	*	*	Special Order*
37218	18 (16x30) [.81 (16x.25)]	.030	.76	.109	2.77	*	*	*	*	Special Order*
37216	16 (26x30) [1.32 (26x.25)]	.030	.76	.123	3.12	*	*	*	*	Special Order*
37214	14 (41x30) [2.08 (41x.25)]	.030	.76	.138	3.51	*	*	*	*	Special Order*
37212	12 (65x30) [3.29 (65x.25)]	.030	.76	.158	4.01	*	*	*	*	Special Order*

*Contact Belden's Customer Service Department for order requirements. **1-800-BELDEN-1**.

7500V, 150°C (UL)

UL AWM Style 3499

37508	8 (84x27) [8.60 (84x.36)]	.125	3.18	.423	10.74	50 *	15.2	9.6	4.4	10
						500 ††	152.4	66.0	30.0	10
						1000 ††	304.8	130.0	59.1	10
37506	6 (84x25) [13.66 (84x.46)]	.125	3.18	.470	11.94	50 *	15.2	11.8	5.3	10
						500 ††	152.4	90.0	40.9	10
						1000 ††	304.8	176.0	80.0	10
37504	4 (105x24) [21.53 (105x.51)]	.125	3.18	.526	13.36	50 *	15.2	15.0	6.8	10
						500 ††	152.4	122.0	55.5	10
						1000 ††	304.8	240.0	109.1	10
37502	2 (163x24) [33.43 (163x.51)]	.125	3.18	.581	14.76	50 *	15.2	19.4	8.8	10
						500 ††	152.4	167.5	76.0	10
						1000 ††	304.8	333.0	151.4	10
37501	1 (210x24) [43.07 (210x.51)]	.125	3.18	.638	16.21	50 *	15.2	23.1	10.5	10
						500 ††	152.4	206.0	93.6	10
37590	1/0 (262x24) [53.73 (262x.51)]	.125	3.18	.688	17.48	50 *	15.2	27.3	12.4	10
						250 †	76.2	123.5	56.1	10
						500 ††	152.4	243.0	110.5	10
37500	2/0 (504x26) [67.85 (504x.41)]	.125	3.18	.753	19.13	50 *	15.2	34.2	15.5	10
						250 †	76.2	150.5	68.4	10
						500 ††	152.4	302.5	137.5	10
37530	3/0 (630x26) [84.81 (630x.41)]	.125	3.18	.813	20.65	50 *	15.2	40.5	18.4	10
						250 †	76.2	184.0	83.6	10
37540	4/0 (805x26) [108.37 (805x.41)]	.125	3.18	.909	23.09	50 *	15.2	48.7	22.1	10
						250 †	76.2	228.8	104.0	10
						500 ††	152.4	472.0	214.5	10

*50 ft. put-ups are one piece, exact.

†250 ft. put-ups are exact, but may contain 2 pieces max. Minimum length of any one piece is 50 ft.

††May contain more than one piece. Length may vary ±10% from length shown.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А