


## 3 V to 24 V Input, 24 A microBUCK® DC/DC Converter



### DESCRIPTION

The SiC431 is a synchronous buck regulator with integrated high side and low side power MOSFETs. Its power stage is capable of supplying 24 A continuous current at up to 1 MHz switching frequency. This regulator produces an adjustable output voltage down to 0.6 V from 3 V to 24 V input rail to accommodate a variety of applications, including computing, consumer electronics, telecom, and industrial.

SiC431's architecture supports ultrafast transient response with minimum output capacitance and tight ripple regulation at very light load. The device is internally compensated and no external ESR network is required for loop stability purposes. The device also incorporates a power saving scheme that significantly increases light load efficiency.

The regulator integrates a full protection feature set, including output over voltage protection (OVP), cycle by cycle over current protection (OCP) short circuit protection (SCP) and thermal shutdown (OTP). It also has UVLO and a user programmable soft start.

The SiC431 is available in lead (Pb)-free power enhanced MLP44-24L package in 4 mm x 4 mm dimension.

### APPLICATIONS

- 5 V, 12 V, and 24 V input rail POLs
- Desktop, notebooks, server, and industrial computing
- Industrial and automation
- consumer electronics

### TYPICAL APPLICATION CIRCUIT AND PACKAGE OPTIONS




Fig. 1 - Typical Application Circuit for SiC431

### FEATURES

- Versatile
  - Operation from 3 V to 24 V input voltage
  - Adjustable output voltage down to 0.6 V
  - Scalable solution 8 A (SiC438), 12 A (SiC437), and 24 A (SiC431)
  - Output voltage tracking and sequencing with pre-bias start up
  - $\pm 1\%$  output voltage accuracy from  $-40\text{ }^\circ\text{C}$  to  $+125\text{ }^\circ\text{C}$
- Highly efficient
  - 97 % peak efficiency
  - 1  $\mu\text{A}$  supply current at shutdown
  - 50  $\mu\text{A}$  operating current, not switching
- Highly configurable
  - Four programmable switching frequencies available: 300 kHz, 500 kHz, 750 kHz, and 1 MHz
  - Adjustable soft start and adjustable current limit
  - Three modes of operation: forced continuous conduction, power save (SiC431B, SiC431D), or ultrasonic (SiC431A, SiC431C)
- Robust and reliable
  - Cycle-by-cycle current limit
  - Output overvoltage protection
  - Output undervoltage / short circuit protection with auto retry
  - Power good flag and over temperature protection
- Design tools
  - Supported by Vishay PowerCAD Online Design Simulation ([www.vishay.com/power-ics/powercad-list/](http://www.vishay.com/power-ics/powercad-list/))
  - Design Support Kit ([www.vishay.com/ppg?74589](http://www.vishay.com/ppg?74589))
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)



**RoHS**  
COMPLIANT  
HALOGEN  
**FREE**





Fig. 2 - Efficiency vs. Output Current  
( $V_{IN} = 12\text{ V}$ ,  $f_{sw} = 500\text{ kHz}$ , Full Load)

**PIN CONFIGURATION**

**Fig. 3 - SiC431 Pin Configuration**

| PIN DESCRIPTION |            |   |
|-----------------|------------|---|
| PIN NUMBER      | SYMBOL     | DESCRIPTION   |
| 1, 2, 22, 26    | $V_{IN}$   | Input voltage   |
| 3, 4, 13, 27    | $P_{GND}$  | Power signal return ground  |
| 5 to 9          | SW         | Switching node signal; output inductor connection point   |
| 10, 11, 28      | GL         | Low side power MOSFET gate signal   |
| 12              | $V_{DRV}$  | Supply voltage for internal gate driver. Connect a 2.2 $\mu$ F decoupling capacitor to $P_{GND}$          |
| 14              | $P_{GOOD}$ | Power good signal output; open drain  |
| 15              | $V_{DD}$   | Supply voltage for internal logic. Connect a 1 $\mu$ F decoupling capacitor to $A_{GND}$                  |
| 16, 25          | $A_{GND}$  | Analog signal return ground   |
| 17              | FB         | Output voltage feedback pin; connect to $V_{OUT}$ through a resistor divider network.                     |
| 18              | $V_{OUT}$  | Output voltage sense pin  |
| 19              | EN         | Enable pin  |
| 20              | MODE2      | Soft start and current limit selection; connect a resistor to $V_{DD}$ or $A_{GND}$ per Table 2           |
| 21              | MODE1      | Operating mode and switching frequency selection; connect a resistor to $V_{DD}$ or $A_{GND}$ per Table 1 |
| 23              | BOOT       | Bootstrap pin; connect a capacitor to PHASE pin for HS power MOSFET gate voltage supply                   |
| 24              | PHASE      | Switching node signal for bootstrap return path   |

| ORDERING INFORMATION |              |                 |                      |                 |                                |                     |
|----------------------|--------------|-----------------|----------------------|-----------------|--------------------------------|---------------------|
| PART NUMBER          | PART MARKING | MAXIMUM CURRENT | $V_{DD}$ , $V_{DRV}$ | LIGHT LOAD MODE | OPERATING JUNCTION TEMPERATURE | PACKAGE             |
| SiC431AED-T1-GE3     | SiC431A      | 24 A            | Internal             | Ultrasonic      | -40 °C to +125 °C              | PowerPAK® MLP44-24L |
| SiC431BED-T1-GE3     | SiC431B      |                 |                      | Power saving    |                                |                     |
| SiC431CED-T1-GE3     | SiC431C      |                 | External             | Ultrasonic      |                                |                     |
| SiC431DED-T1-GE3     | SiC431D      |                 |                      | Power saving    |                                |                     |



| <b>ABSOLUTE MAXIMUM RATINGS</b> ( $T_A = 25\text{ }^\circ\text{C}$ , unless otherwise noted) |                                |              |      |
|--|--------------------------------|--------------|------|
| ELECTRICAL PARAMETER   | CONDITIONS                     | LIMITS       | UNIT |
| $V_{IN}$   | Reference to $P_{GND}$         | -0.3 to +25  | V    |
| $V_{OUT}$  | Reference to $P_{GND}$         | -0.3 to +22  |      |
| $V_{DD} / V_{DRV}$   | Reference to $P_{GND}$         | -0.3 to +6   |      |
| SW / PHASE   | Reference to $P_{GND}$         | -0.3 to +25  |      |
| SW / PHASE (AC)  | 100 ns; reference to $P_{GND}$ | -8 to +30    |      |
| BOOT   | Reference to $P_{GND}$         | -0.3 to +31  |      |
| BOOT to SW   |                                | -0.3 to +6   |      |
| $A_{GND}$ to $P_{GND}$   |                                | -0.3 to +0.3 |      |
| EN   | Reference to $A_{GND}$         | -0.3 to +25  |      |
| All other pins   | Reference to $A_{GND}$         | -0.3 to +6   |      |
| <b>Temperature</b>   |                                |              |      |
| Junction temperature   | $T_J$                          | -40 to +150  | °C   |
| Storage temperature  | $T_{STG}$                      | -65 to +150  |      |
| <b>Power Dissipation</b>   |                                |              |      |
| Junction-to-ambient thermal impedance ( $R_{\theta JA}$ )                                    |                                | 16           | °C/W |
| Junction-to-case thermal impedance ( $R_{\theta JC}$ )                                       |                                | 2            |      |
| Maximum power dissipation  | Ambient temperature = 25 °C    | 7.75         | W    |
| <b>ESD Protection</b>  |                                |              |      |
| Electrostatic discharge protection   | Human body model               | 4000         | V    |
|  | Charged device model           | 1000         |      |

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating/conditions for extended periods may affect device reliability.


| <b>RECOMMENDED OPERATING CONDITIONS</b> (all voltages referenced to $A_{GND}$ , $P_{GND} = 0\text{ V}$ ) |      |             |                                   |      |
|--|------|-------------|-----------------------------------|------|
| PARAMETER  | MIN. | TYP.        | MAX.                              | UNIT |
| Input voltage ( $V_{IN}$ ) (SiC431A, SiC431B)  | 4.5  | -           | 24                                | V    |
| Input voltage ( $V_{IN}$ ) (SiC431C, SiC431D)  | 3    | -           | 24                                |      |
| Logic supply voltage, gate driver supply voltage ( $V_{DD}$ , $V_{DRV}$ ) (SiC431C, SiC431D)             | 4.5  | 5           | 5.5                               |      |
| Enable (EN)  | 0    | -           | 24                                |      |
| Output voltage ( $V_{OUT}$ )   | 0.6  | -           | $0.9 \times V_{IN}$<br>and < 20 V |      |
| <b>Temperature</b>   |      |             |                                   |      |
| Recommended ambient temperature  |      | -40 to +105 |                                   | °C   |
| Operating junction temperature   |      | -40 to +125 |                                   |      |



| <b>ELECTRICAL SPECIFICATIONS</b> ( $V_{IN} = 12\text{ V}$ , $V_{EN} = 5\text{ V}$ , $T_J = -40\text{ }^\circ\text{C}$ to $+125\text{ }^\circ\text{C}$ , unless otherwise stated) |                            |   |      |      |      |                  |
|--|----------------------------|---|------|------|------|------------------|
| PARAMETER  | SYMBOL                     | TEST CONDITIONS   | MIN. | TYP. | MAX. | UNIT             |
| <b>Power Supplies</b>  |                            |   |      |      |      |                  |
| $V_{DD}$ supply  | $V_{DD}$                   | $V_{IN} = 6\text{ V}$ to $24\text{ V}$ (SiC431A, SiC431B)             | 4.75 | 5    | 5.25 | V                |
| $V_{DD}$ UVLO threshold, rising  | $V_{DD\_UVLO}$             |   | 3.3  | 3.6  | 3.9  |                  |
| $V_{DD}$ UVLO hysteresis   | $V_{DD\_UVLO\_HYST}$       |   | -    | 300  | -    | mV               |
| Maximum $V_{DD}$ current   | $I_{DD}$                   | $V_{IN} = 6\text{ V}$ to $24\text{ V}$                                | 3    | -    | -    | mA               |
| $V_{DRV}$ supply   | $V_{DRV}$                  | $V_{IN} = 6\text{ V}$ to $24\text{ V}$ (SiC431A, SiC431B)             | 4.75 | 5    | 5.25 | V                |
| Maximum $V_{DRV}$ current  | $I_{DRV}$                  | $V_{IN} = 6\text{ V}$ to $24\text{ V}$                                | 50   | -    | -    | mA               |
| Input current  | $I_{IN}$                   | Non-switching, $V_{FB} > 0.6\text{ V}$                                | -    | 50   | 120  | $\mu\text{A}$    |
| Shutdown current   | $I_{IN\_SHDN}$             | $V_{EN} = 0\text{ V}$   | -    | 0.5  | 3    |                  |
| <b>Controller and Timing</b>   |                            |   |      |      |      |                  |
| Feedback voltage   | $V_{FB}$                   | $T_J = 25\text{ }^\circ\text{C}$                                      | 597  | 600  | 603  | mV               |
|  |                            | $T_J = -40\text{ }^\circ\text{C}$ to $+125\text{ }^\circ\text{C}$ (1) | 594  | 600  | 606  |                  |
| $V_{FB}$ input bias current  | $I_{FB}$                   |   | -    | 2    | -    | nA               |
| Minimum on-time  | $t_{ON\_MIN.}$             |   | -    | 50   | 65   | ns               |
| $t_{ON}$ accuracy  | $t_{ON\_ACCURACY}$         |   | -10  | -    | 10   | %                |
| On-time range  | $t_{ON\_RANGE}$            |   | 65   | -    | 2250 | ns               |
| Minimum frequency, skip mode   | $f_{SW\_MIN.}$             | Ultrasonic version (SiC431A, SiC431C)                                 | 20   | -    | 30   | kHz              |
|  |                            | Power save version (SiC431B, SiC431D)                                 | 0    | -    | -    |                  |
| Minimum off-time   | $t_{OFF\_MIN.}$            |   | 205  | 250  | 305  | ns               |
| <b>Power MOSFETs</b>   |                            |   |      |      |      |                  |
| High side on resistance  | $R_{ON\_HS}$               | $V_{DRV} = 5\text{ V}$ , $T_A = 25\text{ }^\circ\text{C}$             | -    | 6    | -    | m $\Omega$       |
| Low side on resistance   | $R_{ON\_LS}$               |   | -    | 2    | -    |                  |
| <b>Fault Protections</b>   |                            |   |      |      |      |                  |
| Over current protection (inductor valley current)  | $I_{OCP}$                  | $T_J = -10\text{ }^\circ\text{C}$ to $+125\text{ }^\circ\text{C}$     | -20  | -    | 20   | %                |
| Output OVP threshold   | $V_{OVP}$                  | $V_{FB}$ with respect to 0.6 V reference                              | -    | 20   | -    |                  |
| Output UVP threshold   | $V_{UVP}$                  |   | -    | -80  | -    |                  |
| Over temperature protection  | $T_{OTP\_RISING}$          | Rising temperature  | -    | 150  | -    | $^\circ\text{C}$ |
|  | $T_{OTP\_HYST}$            | Hysteresis  | -    | 25   | -    |                  |
| <b>Power Good</b>  |                            |   |      |      |      |                  |
| Power good output threshold  | $V_{FB\_RISING\_VTH\_OV}$  | $V_{FB}$ rising above 0.6 V reference                                 | -    | 20   | -    | %                |
|  | $V_{FB\_FALLING\_VTH\_UV}$ | $V_{FB}$ falling below 0.6 V reference                                | -    | -10  | -    |                  |
| Power good hysteresis  | $V_{FB\_HYST}$             |   | -    | 40   | -    | mV               |
| Power good on resistance   | $R_{ON\_PGOOD}$            |   | -    | 7.5  | 15   | $\Omega$         |
| Power good delay time  | $t_{DLY\_PGOOD}$           |   | 15   | 25   | 35   | $\mu\text{s}$    |
| <b>EN / MODE / Ultrasonic Threshold</b>  |                            |   |      |      |      |                  |
| EN logic high level  | $V_{EN\_H}$                |   | 1.6  | -    | -    | V                |
| EN logic low level   | $V_{EN\_L}$                |   | -    | -    | 0.4  |                  |
| EN pull down resistance  | $R_{EN}$                   |   | -    | 5    | -    | M $\Omega$       |
| <b>Switching Frequency</b>   |                            |   |      |      |      |                  |
| MODE1 (switching frequency)  | $R_{MODE1}$                | $f_{SW} = 300\text{ kHz}$   | -    | 51   | 55   | k $\Omega$       |
|  |                            | $f_{SW} = 500\text{ kHz}$   | 90   | 100  | 110  |                  |
|  |                            | $f_{SW} = 750\text{ kHz}$   | 180  | 200  | 220  |                  |
|  |                            | $f_{SW} = 1000\text{ kHz}$  | 450  | 499  | -    |                  |
| <b>Soft Start</b>  |                            |   |      |      |      |                  |
| Soft start time  | $t_{ss}$                   | Connect $R_{MODE2}$ between MODE2 and $A_{GND}$                       | 1.8  | 3    | 4.2  | ms               |
|  |                            | Connect $R_{MODE2}$ between MODE2 and $V_{DD}$                        | 3.6  | 6    | 8.4  |                  |
| <b>Over Current Protection</b>   |                            |   |      |      |      |                  |
| MODE2 (over current protection)  | $R_{MODE2}$                | $I_{OCP} = 32\text{ A}$   | 450  | 499  | -    | k $\Omega$       |
|  |                            | $I_{OCP} = 24.8\text{ A}$   | 180  | 200  | 220  |                  |
|  |                            | $I_{OCP} = 17.3\text{ A}$   | 90   | 100  | 110  |                  |
|  |                            | $I_{OCP} = 9.6\text{ A}$  | -    | 51   | 55   |                  |

**Note**

(1) Guaranteed by design

**FUNCTIONAL BLOCK DIAGRAM**

**Fig. 4 - SiC431 Functional Block Diagram**

**OPERATIONAL DESCRIPTION**

**Device Overview**

SiC431 is a high efficiency synchronous buck regulator capable of delivering up to 24 A continuous current. The device has user programmable switching frequency of 300 kHz, 500 kHz, 750 kHz, and 1 MHz. The control scheme delivers fast transient response and minimizes the number of external components. Thanks to the internal ramp information, no high ESR output bulk or virtual ESR network is required for the loop stability. This device also incorporates a power saving feature that enables diode emulation mode and frequency fold back as the load decreases.

SiC431 has a full set of protection and monitoring features:

- Over current protection in pulse-by-pulse mode
- Output over voltage protection
- Output under voltage protection with device latch
- Over temperature protection with hysteresis
- Dedicated enable pin for easy power sequencing
- Power good open drain output

This device is available in MLP44-24L package to deliver high power density and minimize PCB area.

**Power Stage**

SiC431 integrates a high performance power stage with a 2 mΩ n-channel low side MOSFET and a 6 mΩ n-channel high side MOSFET. The MOSFETs are optimized to achieve up to 97 % efficiency.


The input voltage ( $V_{IN}$ ) can go up to 24 V and down to as low as 3 V for power conversion. For input voltages ( $V_{IN}$ ) below 4.5 V an external  $V_{DD}$  and  $V_{DRV}$  supply is required (SiC431C, SiC431D). For input voltages ( $V_{IN}$ ) above 4.5 V only a single input supply is required (SiC431A, SiC431B).

**Control Mechanism**

SiC431 employs an advanced voltage - mode COT control mechanism. During steady-state operation, feedback voltage ( $V_{FB}$ ) is compared with internal reference (0.6 V typ.) and the amplified error signal ( $V_{COMP}$ ) is generated at the internal comp node. An internally generated ramp signal and  $V_{COMP}$  feed into a comparator. Once  $V_{RAMP}$  crosses  $V_{COMP}$ , an on-time pulse is generated for a fixed time. During the on-time pulse, the high side MOSFET will be turned on. Once the on-time pulse expires, the low side MOSFET will be turned on after a dead time period. The low side MOSFET will stay on for a minimum duration equal to the minimum off-time ( $t_{OFF\_MIN.}$ ) and remains on until  $V_{RAMP}$  crosses  $V_{COMP}$ . The cycle is then repeated.

Fig. 5 illustrates the basic block diagram for VM-COT architecture. In this architecture the following is achieved:


- The reference of a basic ripple control regulator is replaced with a high gain error amplifier loop
- This establishes two parallel voltage regulating feedback paths, a fast and slow path
- Fast path is the ripple injection which ensures rapid correction of the transient perturbation
- Slow path is the error amplifier loop which ensures the DC component of the output voltage follows the internal accurate reference voltage



**Fig. 5 - VM-COT Block Diagram**

All components for RAMP signal generation and error amplifier compensation required for the control loop are internal to the IC, see Fig. 5. In order for the device to cover a wide range of  $V_{OUT}$  operation, the internal RAMP signal components ( $R_X$ ,  $C_X$ ,  $C_Y$ ) are automatically selected depending on the  $V_{OUT}$  voltage and switching frequency. This method allows the RAMP amplitude to remain constant throughout the  $V_{OUT}$  voltage range, achieving low jitter and fast transient Response. The error amplifier internal compensation consists of a resistor in series with a capacitor ( $R_{COMP}$ ,  $C_{COMP}$ ).

Fig. 6 demonstrates the basic operational waveforms:



**Fig. 6 - VM-COT Operational Principle**

**Light Load Condition**

To improve efficiency at light-load condition, SiC431 provides a set of innovative implementations to eliminate LS recirculating current and switching losses. The internal zero crossing detector monitors SW node voltage to determine when inductor current starts to flow negatively. In power saving mode, as soon as inductor valley current crosses zero, the device deploys diode emulation mode by turning off low side MOSFET. If load further decreases, switching frequency is reduced proportional to load condition to save switching losses while keeping output ripple within tolerance. The switching frequency is set by the controller to maintain regulation. In the standard power save mode, there is no minimum switching frequency (SiC431B, SiC431D).

For SiC431A, SiC431C, the minimum switching frequency that the regulator will reduce to is < 20 kHz as the part avoids switching frequencies in the audible range. This light load mode implementation is called ultrasonic mode.

**Mode Setting, Over Current Protection, Switching Frequency, and Soft Start Selection**

The SiC431 has a low pin count, minimal external components, and offers the user flexibility to choose soft start times, current limit settings, switching frequencies and

to enable or disable the light load mode. Two MODE pins, MODE1 and MODE2, are user programmable by connecting a resistor from MODEx to V<sub>DD</sub> or A<sub>GND</sub>, allowing the user to choose various operating modes. This is best explained in the tables below.


| TABLE 1 - MODE1 CONFIGURATION SETTINGS |                     |                           |                         |
|--|---------------------|---------------------------|-------------------------|
| OPERATION                              | CONNECTION          | f <sub>SWITCH</sub> (kHz) | R <sub>MODE1</sub> (kΩ) |
| Skip                                   | To A <sub>GND</sub> | 300                       | 51                      |
|  |                     | 500                       | 100                     |
|  |                     | 750                       | 200                     |
|  |                     | 1000                      | 499                     |
| Forced CCM                             | To V <sub>DD</sub>  | 300                       | 51                      |
|  |                     | 500                       | 100                     |
|  |                     | 750                       | 200                     |
|  |                     | 1000                      | 499                     |

| TABLE 2 - MODE2 CONFIGURATION SETTINGS |                     |                        |                         |
|--|---------------------|------------------------|-------------------------|
| SOFT-START TIME                        | CONNECTION          | I <sub>LIMIT</sub> (%) | R <sub>MODE2</sub> (kΩ) |
| 3 ms                                   | To A <sub>GND</sub> | 30                     | 51                      |
|  |                     | 54                     | 100                     |
|  |                     | 78                     | 200                     |
|  |                     | 100 (32 A)             | 499                     |
| 6 ms                                   | To V <sub>DD</sub>  | 30                     | 51                      |
|  |                     | 54                     | 100                     |
|  |                     | 78                     | 200                     |
|  |                     | 100 (32 A)             | 499                     |

**OUTPUT MONITORING AND PROTECTION FEATURES**
**Output Over Current Protection (OCP)**

SiC431 has pulse-by-pulse over current limit control. The inductor current is monitored during low side MOSFET conduction time through R<sub>DS(on)</sub> sensing. After a pre-defined blanking time, the inductor current is compared with an internal OCP threshold. If inductor current is higher than OCP threshold, high side MOSFET is kept off until the inductor current falls below OCP threshold.

OCP is enabled immediately after V<sub>DD</sub> passes UVLO rising threshold.


**Fig. 7 - Over-Current Protection Illustration**



### Output Undervoltage Protection (UVP)

UVP is implemented by monitoring the FB pin. If the voltage level at FB drops below 0.12 V for more than 25  $\mu$ s, a UVP event is recognized and both high side and low side MOSFETs are turned off. After a duration equivalent to 20 soft start periods, the IC attempts to re-start. If the fault condition still exists, the above cycle will be repeated.

UVP is active after the completion of soft start sequence.

### Output Overvoltage Protection (OVP)

OVP is implemented by monitoring the FB pin. If the voltage level at FB rising above 0.72 V, a OVP event is recognized and both high side and low side MOSFETs are turned off. Normal operation is resumed once FB voltage drop below 0.68 V.

OVP is active after  $V_{DD}$  passes UVLO rising threshold.

### Over-Temperature Protection (OTP)

OTP is implemented by monitoring the junction temperature. If the junction temperature rises above 150  $^{\circ}$ C, a OTP event is recognized and both high side and low MOSFETs are turned off. After the junction temperature falls below 115  $^{\circ}$ C (35  $^{\circ}$ C hysteresis), the device restarts by initiating a soft start sequence.

### Sequencing of Input / Output Supplies

SiC431 has no sequencing requirements on its supplies or enables ( $V_{IN}$ ,  $V_{DD}$ ,  $V_{DRV}$ , EN).


### Enable

The SiC431 has an enable pin to turn the part on and off. Driving the pin high enables the device, while driving the pin low disables the device.

The EN pin is internally pulled to  $A_{GND}$  by a 5 M $\Omega$  resistor to prevent unwanted turn on due to a floating GPIO.

### Pre-Bias Start-Up


In case of pre-bias startup, output is monitored through FB pin. If the sensed voltage on FB is higher than the internal reference ramp value, control logic prevents high side and low side MOSFETs from switching to avoid negative output voltage spike and excessive current sinking through low side MOSFET.



**Fig. 8 - Pre-Bias Start-Up**

### Power Good

SiC431's power good is an open-drain output. Pull  $P_{GOOD}$  pin high through a > 10K resistor to use this signal. Power good window is shown in the below diagram. If voltage on FB pin is out of this window,  $P_{GOOD}$  signal is de-asserted by pulling down to  $A_{GND}$ . To prevent false triggering during transient events,  $P_{GOOD}$  has a 25  $\mu$ s blanking time.




**Fig. 9 -  $P_{GOOD}$  Window Diagram**




**ELECTRICAL CHARACTERISTICS**


( $V_{IN} = 12\text{ V}$ ,  $V_{OUT} = 1.2\text{ V}$ ,  $f_{sw} = 500\text{ kHz}$ ,  $C_{OUT} = 47\text{ }\mu\text{F} \times 13$ ,  $C_{IN} = 10\text{ }\mu\text{F} \times 6$ , unless otherwise noted)




**Fig. 10 - Efficiency vs. Output Current**  
( $V_{IN} = 12\text{ V}$ ,  $f_{sw} = 500\text{ kHz}$ , Full Load)




**Fig. 13 - Efficiency vs. Output Current**  
( $V_{IN} = 12\text{ V}$ ,  $f_{sw} = 500\text{ kHz}$ , Light Load)




**Fig. 11 - Efficiency vs. Output Current**  
( $V_{IN} = 12\text{ V}$ ,  $f_{sw} = 1000\text{ kHz}$ , Full Load)



**Fig. 14 - Efficiency vs. Output Current**  
( $V_{IN} = 12\text{ V}$ ,  $f_{sw} = 1000\text{ kHz}$ , Light Load)




**Fig. 12 - Voltage Reference vs. Junction Temperature**




**Fig. 15 - EN Current vs. Junction Temperature**

**ELECTRICAL CHARACTERISTICS**


( $V_{IN} = 12\text{ V}$ ,  $V_{OUT} = 1.2\text{ V}$ ,  $f_{sw} = 500\text{ kHz}$ ,  $C_{OUT} = 47\text{ }\mu\text{F} \times 13$ ,  $C_{IN} = 10\text{ }\mu\text{F} \times 6$ , unless otherwise noted)




**Fig. 16 - EN Logic Threshold vs. Junction Temperature**




**Fig. 19 - Shutdown Current vs. Input Voltage**




**Fig. 17 - Input Current vs. Input Voltage**



**Fig. 20 - Shutdown Current vs. Junction Temperature**



**Fig. 18 - Input Current vs. Junction Temperature**




**Fig. 21 - Line Regulation vs. Input Voltage**




**ELECTRICAL CHARACTERISTICS**

( $V_{IN} = 12\text{ V}$ ,  $V_{OUT} = 1.2\text{ V}$ ,  $f_{sw} = 500\text{ kHz}$ ,  $C_{OUT} = 47\text{ }\mu\text{F} \times 13$ ,  $C_{IN} = 10\text{ }\mu\text{F} \times 6$ , unless otherwise noted)



**Fig. 22 - Load Regulation vs. Output Current**



**Fig. 23 - On Resistance vs. Junction Temperature**

**ELECTRICAL CHARACTERISTICS**

( $V_{IN} = 12\text{ V}$ ,  $V_{OUT} = 1.2\text{ V}$ ,  $f_{sw} = 500\text{ kHz}$ ,  $C_{OUT} = 47\text{ }\mu\text{F} \times 13$ ,  $C_{IN} = 10\text{ }\mu\text{F} \times 6$ , unless otherwise noted)




Fig. 24 - Startup with  $V_{IN}$ ,  $t = 2\text{ ms/div}$




Fig. 27 - Startup with EN,  $t = 1\text{ ms/div}$




Fig. 25 - Shut down with  $V_{IN}$ ,  $t = 100\text{ ms/div}$




Fig. 28 - Shut down with EN,  $t = 200\text{ ms/div}$




Fig. 26 - Overcurrent Protection Behavior,  $t = 5\text{ }\mu\text{s/div}$






Fig. 29 - Output Undervoltage Protection Behavior,  $t = 50\text{ ms/div}$

**ELECTRICAL CHARACTERISTICS**


( $V_{IN} = 12\text{ V}$ ,  $V_{OUT} = 1.2\text{ V}$ ,  $f_{sw} = 500\text{ kHz}$ ,  $C_{OUT} = 47\text{ }\mu\text{F} \times 13$ ,  $C_{IN} = 10\text{ }\mu\text{F} \times 6$ , unless otherwise noted)




**Fig. 30 - Load Step, 12 A to 24 A, 1 A/ $\mu$ s,  $t = 10\text{ }\mu$ s/div**




**Fig. 33 - Load Release, 24 A to 12 A, 1 A/ $\mu$ s,  $t = 10\text{ }\mu$ s/div**




**Fig. 31 - Load Step, 0.1 A to 12 A, 1 A/ $\mu$ s,  $t = 10\text{ }\mu$ s/div  
Skip Mode Enabled**



**Fig. 34 - Load Release, 12 A to 0.1 A, 1 A/ $\mu$ s,  $t = 50\text{ }\mu$ s/div  
Skip Mode Enabled**




**Fig. 32 - Load Step, 0.1 A to 12 A, 1 A/ $\mu$ s,  $t = 10\text{ }\mu$ s/div  
Forced Continuous Conduction Mode**




**Fig. 35 - Load Release, 12 A to 0.1 A, 1 A/ $\mu$ s,  $t = 20\text{ }\mu$ s/div  
Forced Continuous Conduction Mode**

**ELECTRICAL CHARACTERISTICS**


( $V_{IN} = 12\text{ V}$ ,  $V_{OUT} = 1.2\text{ V}$ ,  $f_{sw} = 500\text{ kHz}$ ,  $C_{OUT} = 47\text{ }\mu\text{F} \times 13$ ,  $C_{IN} = 10\text{ }\mu\text{F} \times 6$ , unless otherwise noted)




**Fig. 36 - Output Ripple, 0.1 A,  $t = 2\text{ }\mu\text{s/div}$   
Forced Continuous Conduction Mode**



**Fig. 38 - Output Ripple, 12 A,  $t = 1\text{ }\mu\text{s/div}$   
Forced Continuous Conduction Mode**



**Fig. 37 - Output Ripple, 0.1 A,  $t = 20\text{ }\mu\text{s/div}$   
Skip Mode Enabled**

**EXAMPLE SCHEMATIC FOR SiC431**

**Fig. 39 - Schematic**



## EXTERNAL COMPONENT SELECTION FOR THE SiC43X

This section explains external component selection for the SiC43x family of regulators. Component reference designators in any equation refer to the schematic shown in Fig. 36.

See PowerCAD online design center to simplify external component calculations.

### Output Voltage Adjustment

If a different output voltage is needed, simply change the value of  $V_{OUT}$  and solve for  $R_{FB\_H}$  based on the following formula:

$$R_{FB\_H} = \frac{R_{FB\_L}(V_{OUT} - V_{FB})}{V_{FB}}$$

Where  $V_{FB}$  is 0.6 V for the SiC43X.  $R_{FB\_L}$  should be a maximum of 10 k $\Omega$  to prevent  $V_{OUT}$  from drifting at no load.

### Inductor Selection

In order to determine the inductance, the ripple current must first be defined. Low inductor values allow for the use of smaller package sizes but create higher ripple current which can reduce efficiency. Higher inductor values will reduce the ripple current and, for a given DC resistance, are more efficient. However, larger inductance translates directly into larger packages and higher cost. Cost, size, output ripple, and efficiency are all used in the selection process.

The ripple current will also set the boundary for power save operation. The SiC431 will typically enter power save mode when the load current decreases to 1/2 of the ripple current. For example, if ripple current is 4 A, power save operation will be active for loads less than 2 A. If ripple current is set at 40 % of maximum load current, power save will typically start at a load which is 20 % of maximum current.

The inductor value is typically selected to provide ripple current of 25 % to 50 % of the maximum load current. This provides an optimal trade-off between cost, efficiency, and transient performance. During the on-time, voltage across the inductor is  $(V_{IN} - V_{OUT})$ . The equation for determining inductance is shown below.

$$L_O = \frac{(V_{IN} - V_{OUT}) \times D}{K \times I_{OUT\_MAX} \times f_{SW}}$$

where, K is the maximum percentage of ripple current, D is the duty cycle,  $I_{OUT\_MAX}$  is the maximum load current and  $f_{SW}$  is the switching frequency.

### Capacitor Selection

The output capacitors are chosen based upon required ESR and capacitance. The maximum ESR requirement is controlled by the output ripple requirement and the DC tolerance. The output voltage has a DC value that is equal to the valley of the output ripple plus 1/2 of the peak-to-peak ripple. A change in the output ripple voltage will lead to a change in DC voltage at the output.

For instance, the design goal for output voltage ripple is 3 % (45 mV for  $V_{OUT} = 1.5$  V) with ripple current of 4.43 A. The maximum ESR value allowed is shown by the following equation.

$$ESR_{MAX} = \frac{V_{RIPPLE}}{I_{RIPPLE}} = \frac{45 \text{ mV}}{4.43 \text{ A}}$$

$$ESR_{MAX} = 10.2 \text{ m}\Omega$$

The output capacitance is usually chosen to meet transient requirements. A worst-case load release (from maximum load to no load) at the moment of peak inductor current, determines the required capacitance. If the load release is instantaneous (maximum load to no load in less than 1  $\mu$ s) the output capacitor must absorb all the inductor's stored energy. The output capacitor can be calculated according to the following equation.

$$C_{OUT\_MIN} = \frac{L_O(I_{OUT} + 0.5 \times I_{RIPPLE\_MAX})^2}{V_{PK}^2 - V_{OUT}^2}$$

Where  $I_{OUT}$  is the output current,  $I_{RIPPLE\_MAX}$  is the maximum ripple current,  $V_{PK}$  is the peak  $V_{OUT}$  during load release,  $V_{OUT}$  is the output voltage.

The duration of the load release is determined by  $V_{OUT}$  and the inductor. During load release, the voltage across the inductor is approximately  $-V_{OUT}$ , causing a down-slope or falling di/dt in the inductor. If the di/dt of the load is not much larger than di/dt of the inductor, then the inductor current will tend to track the falling load current. This will reduce the excess inductive energy that must be absorbed by the output capacitor; therefore a smaller capacitance can be used.

Under this circumstance, the following equation can be used to calculate the needed capacitance for a given rate of load release ( $di_{LOAD}/dt$ ).

$$C_{OUT} = \frac{\frac{L \times I_{PK}^2}{V_{OUT}} - (I_{PK} \times I_{RELEASE}) \times \frac{dT}{di_{LOAD}}}{2(V_{PK} - V_{OUT})}$$

$$I_{PK} = I_{RELEASE} + \left(\frac{1}{2} \times I_{RIPPLE\_MAX}\right)$$



Where  $I_{PK}$  is the peak inductor current,  $I_{RIPPLE\_MAX}$  is the maximum peak to peak inductor current,  $I_{RELEASE}$  is the maximum load release current,  $V_{PK}$  is the peak  $V_{OUT}$  during load release,  $dI_{LOAD}/dt$  is the rate of load release.

If the load step does not meet the requirement, increasing the crossover frequency can help by adding feed forward capacitor ( $C_{FF}$ ) in parallel to the upper feedback resistor to generate another zero and pole. Placing the geometrical mean of this pole and zero around the crossover frequency will result in faster transient response.  $f_z$  and  $f_p$  are the generated zero and pole, see equations below.

$$f_z = \frac{1}{2\pi \times R_{FB1} \times C_{FF}}$$

$$f_p = \frac{1}{2\pi \times (R_{FB1} // R_{FB2}) \times C_{FF}}$$

Where  $R_{FB1}$  is the upper feedback resistor,  $R_{FB2}$  is the lower feedback resistor  $C_{FF}$  is the feed forward capacitor,  $f_z$  is the zero from feed forward capacitor,  $f_p$  is the pole frequency generated from the feed forward capacitor.

A calculator is available to assist user to obtain the value of the feed forward capacitance value.

From the calculator, obtain the crossover frequency ( $f_c$ ). Use the equation below for the calculation of the feed forward capacitance value.

$$f_c = \sqrt{f_z \times f_p}$$

$$C_{FF} = \frac{1}{2\pi \times (f_c \times \sqrt{(R_{FB1} \times (R_{FB1} // R_{FB2}))})}$$

As the internal RC compensation of the SiC431 works with a wide range of output LC filters, the SiC431 offers stable operation for a wide range of output capacitance, making the product versatile and usable in a wide range of applications.

### Input Capacitance

In order to determine the minimum capacitance the input voltage ripple needs to be specified;  $V_{CINPKPK} \leq 500$  mV is a suitable starting point. This magnitude is determined by the final application specification. The input current needs to be determined for the lowest operating input voltage,

$$I_{CIN(RMS)} = I_O \times \sqrt{D \times (1 - D) + \frac{1}{12} \times \left( \frac{V_{OUT}}{L \times f_{sw} \times I_{OUT}} \right)^2 \times (1 - D)^2 \times D}$$

The minimum input capacitance can then be found,


$$C_{IN\_min.} = I_{OUT} \times \frac{D \times (1 - D)}{V_{CINPKPK} \times f_{sw}}$$

If high ESR capacitors are used, it is good practice to also add low ESR ceramic capacitance. A 4.7  $\mu$ F ceramic input capacitance is a suitable starting point.

Care must be taken to account for voltage derating of the capacitance when choosing an all ceramic input capacitance.


**PCB LAYOUT RECOMMENDATIONS**

**Step 1:  $V_{IN}$ /GND Planes and Decoupling**




1. Layout  $V_{IN}$  and  $P_{GND}$  planes as shown above
2. Ceramic capacitors should be placed between  $V_{IN}$  and  $P_{GND}$ , and very close to the device for best decoupling effect
3. Various ceramic capacitor values and package sizes should be used to cover entire decoupling spectrum e.g. 1210 and 0603
4. Smaller capacitance values, closer to  $V_{IN}$  pin(s), provide better high frequency response

**Step 2: SW Plane**



1. Connect output inductor to device with large plane to lower resistance
2. If a snubber network is required, place the components on the bottom layer as shown above

**Step 3:  $V_{DD}/V_{DRV}$  Input Filter**




1.  $C_{VDD}$  cap should be placed between  $V_{DD}$  and  $A_{GND}$  to achieve best noise filtering
2.  $C_{VDRV}$  cap should be placed close to  $V_{DRV}$  and  $P_{GND}$  pins to reduce effects of trace impedance and provide maximum instantaneous driver current for low side MOSFET during switching cycle


**Step 4: BOOT Resistor and Capacitor Placement**



1.  $C_{BOOT}$  and  $R_{BOOT}$  need to be placed very close to the device, between PHASE and BOOT pins
2. In order to reduce parasitic inductance, it is recommended to use 0402 chip size for the resistor and the capacitor


**Step 5: Signal Routing**


1. Separate the small analog signal from high current path. As shown above, the high paths with high  $dv/dt$ ,  $di/dt$  are placed on the left side of the IC, while the small control signals are placed on the right side of the IC. All the components for small analog signal should be placed closer to IC with minimum trace length
2. IC analog ground ( $A_{GND}$ ), pin 16, should have a single connection to  $P_{GND}$ . The  $A_{GND}$  ground plane connected to pin16 helps to keep  $A_{GND}$  quiet and improves noise immunity
3. The output signal can be routed through inner layers. Make sure this signal is far away from SW node and shielded by an inner ground layer

**Step 6: Thermal Management**


1. Thermal relief vias can be added to the  $V_{IN}$  and  $P_{GND}$  pads to utilize inner layers for high current and thermal dissipation
2. To achieve better thermal performance, additional vias can be placed on  $V_{IN}$  and  $P_{GND}$  planes. It is also necessary to duplicate the  $V_{IN}$  and ground plane at bottom layer to maximize the power dissipation capability of the PCB

3. SW pad is a noise source and it is not recommended to place vias on this pad
4. 8 mil vias on pads and 10 mil vias on planes are ideal via sizes. The vias on pad may drain solder during assembly and cause assembly issues. Please consult with the assembly house for guideline

**Step 7: Ground Connection**


1. In order to minimize the ground voltage drop due to high current, it is recommended to place vias on the  $P_{GND}$  planes. Make use of the inner ground layers to lower the impedance

**Step 7: Ground Layer**


1. It is recommended to make the whole inner 1 layer (next to top layer) ground plane
2. This ground plane provides shielding between noise source on top layer and signal trace within inner layer
3. The ground plane can be broken into two section,  $P_{GND}$  and  $A_{GND}$




| PRODUCT SUMMARY               |  |  |  |  |
|-------------------------------|--|--|--|--|
| Part number                   | SiC431A  | SiC431B  | SiC431C  | SiC431D  |
| Description                   | 24 A, 4.5 V to 24 V input, 300 kHz, 500 kHz, 750 kHz, 1 MHz, synchronous buck regulator with ultrasonic mode and internal 5 V bias | 24 A, 4.5 V to 24 V input, 300 kHz, 500 kHz, 750 kHz, 1 MHz, synchronous buck regulator with power save mode and internal 5 V bias | 24 A, 3 V to 24 V input, 300 kHz, 500 kHz, 750 kHz, 1 MHz, synchronous buck regulator with ultrasonic mode (external 5 V bias) | 24 A, 3 V to 24 V input, 300 kHz, 500 kHz, 750 kHz, 1 MHz, synchronous buck regulator with power save mode (external 5 V bias) |
| Input voltage min. (V)        | 4.5  | 4.5  | 3.0  | 3.0  |
| Input voltage max. (V)        | 24   | 24   | 24   | 24   |
| Output voltage min. (V)       | 0.6  | 0.6  | 0.6  | 0.6  |
| Output voltage max. (V)       | $0.90 \times V_{IN}$   | $0.90 \times V_{IN}$   | $0.90 \times V_{IN}$   | $0.90 \times V_{IN}$   |
| Continuous current (A)        | 24   | 24   | 24   | 24   |
| Switch frequency min. (kHz)   | 300  | 300  | 300  | 300  |
| Switch frequency max. (kHz)   | 1000   | 1000   | 1000   | 1000   |
| Pre-bias operation (yes / no) | Y  | Y  | Y  | Y  |
| Internal bias reg. (yes / no) | Y  | Y  | N  | N  |
| Compensation                  | Internal   | Internal   | Internal   | Internal   |
| Enable (yes / no)             | Y  | Y  | Y  | Y  |
| P <sub>GOOD</sub> (yes / no)  | Y  | Y  | Y  | Y  |
| Over current protection       | Y  | Y  | Y  | Y  |
| Protection                    | OVP, OCP, UVP/SCP, OTP, UVLO   | OVP, OCP, UVP/SCP, OTP, UVLO   | OVP, OCP, UVP/SCP, OTP, UVLO   | OVP, OCP, UVP/SCP, OTP, UVLO   |
| Light load mode               | Selectable ultrasonic  | Selectable powersave   | Selectable ultrasonic  | Selectable powersave   |
| Peak efficiency (%)           | 97   | 97   | 97   | 97   |
| Package type                  | PowerPAK MLP 44-24L  | PowerPAK MLP 44-24L  | PowerPAK MLP 44-24L  | PowerPAK MLP 44-24L  |
| Package size (W, L, H) (mm)   | 4 x 4 x 0.75   | 4 x 4 x 0.75   | 4 x 4 x 0.75   | 4 x 4 x 0.75   |
| Status code                   | 1  | 1  | 1  | 1  |
| Product type                  | microBUCK (step down regulator)  | microBUCK (step down regulator)  | microBUCK (step down regulator)  | microBUCK (step down regulator)  |
| Applications                  | Computers, consumer, industrial, healthcare, networking  | Computers, consumer, industrial, healthcare, networking  | Computers, consumer, industrial, healthcare, networking  | Computers, consumer, industrial, healthcare, networking  |

Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package / tape drawings, part marking, and reliability data, see [www.vishay.com/ppg?74589](http://www.vishay.com/ppg?74589).



### PowerPAK<sup>®</sup> MLP44-24L Case Outline




| DIM.             | MILLIMETERS |      |      | INCHES     |       |       |
|------------------|-------------|------|------|------------|-------|-------|
|                  | MIN.        | NOM. | MAX. | MIN.       | NOM.  | MAX.  |
| A <sup>(8)</sup> | 0.70        | 0.75 | 0.80 | 0.027      | 0.029 | 0.031 |
| A1               | 0.00        | -    | 0.05 | 0.000      | -     | 0.002 |
| A2               | 0.20 ref.   |      |      | 0.008 ref. |       |       |
| b <sup>(4)</sup> | 0.20        | 0.25 | 0.30 | 0.078      | 0.098 | 0.110 |
| D                | 3.90        | 4.00 | 4.10 | 0.155      | 0.157 | 0.159 |
| e                | 0.45 BSC    |      |      | 0.018 BSC  |       |       |
| e1               | 0.70 BSC    |      |      | 0.028 BSC  |       |       |
| e2               | 0.90 BSC    |      |      | 0.035 BSC  |       |       |
| E                | 3.90        | 4.00 | 4.10 | 0.155      | 0.157 | 0.159 |
| L                | 0.35        | 0.40 | 0.45 | 0.014      | 0.016 | 0.018 |
| L1               | 0.25        | 0.30 | 0.35 | 0.010      | 0.012 | 0.014 |
| L2               | 0.83        | 0.88 | 0.93 | 0.033      | 0.035 | 0.037 |
| N <sup>(3)</sup> | 24          |      |      | 24         |       |       |
| D2-1             | 1.00        | 1.05 | 1.10 | 0.039      | 0.041 | 0.043 |
| D2-2             | 1.45        | 1.50 | 1.55 | 0.057      | 0.059 | 0.061 |
| D2-3             | 2.68        | 2.73 | 2.78 | 0.106      | 0.108 | 0.110 |
| D2-4             | 2.05        | 2.10 | 2.15 | 0.081      | 0.083 | 0.085 |
| E2-1             | 0.95        | 1.00 | 1.05 | 0.037      | 0.039 | 0.041 |
| E2-2             | 1.10        | 1.15 | 1.20 | 0.043      | 0.045 | 0.047 |
| E2-3             | 0.52        | 0.57 | 0.62 | 0.020      | 0.022 | 0.024 |
| E2-4             | 0.95        | 1.00 | 1.05 | 0.037      | 0.039 | 0.041 |
| K                | 0.40 ref.   |      |      | 0.016 ref. |       |       |
| K1               | 0.57 ref.   |      |      | 0.022 ref. |       |       |
| K2               | 0.45 ref.   |      |      | 0.018 ref. |       |       |
| K3               | 0.50 ref.   |      |      | 0.020 ref. |       |       |
| K4               | 0.35 ref.   |      |      | 0.014 ref. |       |       |

ECN: T16-0945-Rev. A, 19-Dec-16  
DWG: 6055

#### Notes

- (1) Use millimeters as the primary measurement
- (2) Dimensioning and tolerances conform to ASME Y14.5M. - 1994
- (3) N is the number of terminals
- (4) Dimension b applies to plated terminal and is measured between 0.20 mm and 0.25 mm from terminal tip
- (5) The pin #1 identifier must be existed on the top surface of the package by using indentation mark or other feature of package body
- (6) Exact shape and size of this feature is optional
- (7) Package warpage max. 0.08 mm
- (8) Applied only for terminals

# Recommended Land Pattern PowerPAK® MLP44-24L



All dimensions are in millimeters





## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А