

# NVMFS5830NL

## Power MOSFET

40 V, 2.3 mΩ, 185 A, Single N-Channel

### Features

- Small Footprint (5x6 mm) for Compact Design
- Low  $R_{DS(on)}$  to Minimize Conduction Losses
- Low  $Q_G$  and Capacitance to Minimize Driver Losses
- AEC-Q101 Qualified and PPAP Capable
- These are Pb-Free Devices\*

### MAXIMUM RATINGS ( $T_J = 25^\circ\text{C}$ unless otherwise noted)

| Parameter                                                                                                                                                                          |                                                            |                                | Symbol            | Value        | Unit               |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------|--------------------------------|-------------------|--------------|--------------------|
| Drain-to-Source Voltage                                                                                                                                                            |                                                            |                                | $V_{DSS}$         | 40           | V                  |
| Gate-to-Source Voltage                                                                                                                                                             |                                                            |                                | $V_{GS}$          | $\pm 20$     | V                  |
| Continuous Drain Current $R_{\Psi J-mb}$ (Notes 1, 2, 3, 4)                                                                                                                        | Steady State                                               | $T_{mb} = 25^{\circ}\text{C}$  | $I_D$             | 185          | A                  |
|                                                                                                                                                                                    |                                                            | $T_{mb} = 100^{\circ}\text{C}$ |                   | 131          |                    |
| Power Dissipation $R_{\Psi J-mb}$ (Notes 1, 2, 3)                                                                                                                                  |                                                            | $T_{mb} = 25^{\circ}\text{C}$  | $P_D$             | 158          | W                  |
|                                                                                                                                                                                    |                                                            | $T_{mb} = 100^{\circ}\text{C}$ |                   | 79           |                    |
| Continuous Drain Current $R_{\theta JA}$ (Notes 1, 3, 4)                                                                                                                           | Steady State                                               | $T_A = 25^{\circ}\text{C}$     | $I_D$             | 29           | A                  |
|                                                                                                                                                                                    |                                                            | $T_A = 100^{\circ}\text{C}$    |                   | 20           |                    |
| Power Dissipation $R_{\theta JA}$ (Notes 1 & 3)                                                                                                                                    |                                                            | $T_A = 25^{\circ}\text{C}$     | $P_D$             | 3.8          | W                  |
|                                                                                                                                                                                    |                                                            | $T_A = 100^{\circ}\text{C}$    |                   | 1.9          |                    |
| Pulsed Drain Current                                                                                                                                                               | $T_A = 25^{\circ}\text{C}$ , $t_p = 10\text{ }\mu\text{s}$ |                                | $I_{DM}$          | 1012         | A                  |
| Operating Junction and Storage Temperature                                                                                                                                         |                                                            |                                | $T_J$ , $T_{stg}$ | -55 to + 175 | $^{\circ}\text{C}$ |
| Source Current (Body Diode)                                                                                                                                                        |                                                            |                                | $I_S$             | 185          | A                  |
| Single Pulse Drain-to-Source Avalanche Energy ( $T_J = 25^{\circ}\text{C}$ , $V_{GS} = 10\text{ V}$ , $I_{L(pk)} = 85\text{ A}$ , $L = 0.1\text{ mH}$ , $R_G = 25\text{ }\Omega$ ) |                                                            |                                | $E_{AS}$          | 361          | mJ                 |
| Lead Temperature for Soldering Purposes (1/8" from case for 10 s)                                                                                                                  |                                                            |                                | $T_L$             | 260          | $^{\circ}\text{C}$ |

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

### THERMAL RESISTANCE MAXIMUM RATINGS

| Parameter                                                    | Symbol          | Value | Unit               |
|--------------------------------------------------------------|-----------------|-------|--------------------|
| Junction-to-Mounting Board (top) – Steady State (Notes 2, 3) | $R_{\psi J-mb}$ | 1.0   | $^\circ\text{C/W}$ |
| Junction-to-Ambient – Steady State (Note 3)                  | $R_{\theta JA}$ | 39    |                    |



1. The entire application environment impacts the thermal resistance values shown, they are not constants and are only valid for the particular conditions noted.
2. Psi ( $\Psi$ ) is used as required per JESD51-12 for packages in which substantially less than 100% of the heat flows to single case surface.
3. Surface-mounted on FR4 board using a 650 mm<sup>2</sup>, 2 oz. Cu pad.
4. Maximum current for pulses as long as 1 second is higher but is dependent on pulse duration and duty cycle.



ON Semiconductor®


<http://onsemi.com>

| $V_{(BR)DSS}$ | $R_{DS(ON)} \text{ MAX}$ | $I_D \text{ MAX}$ |
|---------------|--------------------------|-------------------|
| 40 V          | 2.3 mΩ @ 10 V            | 185 A             |
|               | 3.6 mΩ @ 4.5 V           |                   |



SO-8 FLAT LEAD  
CASE 488AA  
STYLE 1

### MARKING DIAGRAM



- A = Assembly Location
- Y = Year
- W = Work Week
- ZZ = Lot Traceability

### ORDERING INFORMATION

| Device         | Package          | Shipping†          |
|----------------|------------------|--------------------|
| NVMFS5830NLT1G | SO-8FL (Pb-Free) | 1500 / Tape & Reel |
| NVMFS5830NLT3G | SO-8FL (Pb-Free) | 5000 / Tape & Reel |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

# NVMFS5830NL

## ELECTRICAL CHARACTERISTICS ( $T_J = 25^\circ\text{C}$ unless otherwise specified)

| Parameter | Symbol | Test Condition | Min | Typ | Max | Unit |
|-----------|--------|----------------|-----|-----|-----|------|
|-----------|--------|----------------|-----|-----|-----|------|

### OFF CHARACTERISTICS

|                                                           |                   |                                                     |                           |    |           |                      |
|-----------------------------------------------------------|-------------------|-----------------------------------------------------|---------------------------|----|-----------|----------------------|
| Drain-to-Source Breakdown Voltage                         | $V_{(BR)DSS}$     | $V_{GS} = 0\text{ V}, I_D = 250\text{ }\mu\text{A}$ | 40                        |    |           | V                    |
| Drain-to-Source Breakdown Voltage Temperature Coefficient | $V_{(BR)DSS}/T_J$ |                                                     |                           | 32 |           | mV/ $^\circ\text{C}$ |
| Zero Gate Voltage Drain Current                           | $I_{DSS}$         | $V_{GS} = 0\text{ V}, V_{DS} = 40\text{ V}$         | $T_J = 25^\circ\text{C}$  |    | 1         | $\mu\text{A}$        |
|                                                           |                   |                                                     | $T_J = 125^\circ\text{C}$ |    | 100       |                      |
| Gate-to-Source Leakage Current                            | $I_{GSS}$         | $V_{DS} = 0\text{ V}, V_{GS} = \pm 20\text{ V}$     |                           |    | $\pm 100$ | nA                   |

### ON CHARACTERISTICS (Note 5)

|                                            |                  |                                                 |     |     |     |                      |
|--------------------------------------------|------------------|-------------------------------------------------|-----|-----|-----|----------------------|
| Gate Threshold Voltage                     | $V_{GS(TH)}$     | $V_{GS} = V_{DS}, I_D = 250\text{ }\mu\text{A}$ | 1.4 |     | 2.4 | V                    |
| Negative Threshold Temperature Coefficient | $V_{GS(TH)}/T_J$ |                                                 |     | 7.2 |     | mV/ $^\circ\text{C}$ |
| Drain-to-Source On Resistance              | $R_{DS(on)}$     | $V_{GS} = 10\text{ V}, I_D = 20\text{ A}$       |     | 1.7 | 2.3 | $\text{m}\Omega$     |
|                                            |                  | $V_{GS} = 4.5\text{ V}, I_D = 20\text{ A}$      |     | 2.6 | 3.6 |                      |
| Forward Transconductance                   | $g_{FS}$         | $V_{DS} = 5\text{ V}, I_D = 10\text{ A}$        |     | 38  |     | S                    |

### CHARGES, CAPACITANCES & GATE RESISTANCE

|                              |              |                                                                  |  |      |  |    |
|------------------------------|--------------|------------------------------------------------------------------|--|------|--|----|
| Input Capacitance            | $C_{ISS}$    | $V_{GS} = 0\text{ V}, f = 1\text{ MHz}, V_{DS} = 25\text{ V}$    |  | 5880 |  | pF |
| Output Capacitance           | $C_{OSS}$    |                                                                  |  | 750  |  |    |
| Reverse Transfer Capacitance | $C_{RSS}$    |                                                                  |  | 500  |  |    |
| Total Gate Charge            | $Q_{G(TOT)}$ | $V_{GS} = 4.5\text{ V}, V_{DS} = 32\text{ V}, I_D = 60\text{ A}$ |  | 58   |  | nC |
| Total Gate Charge            | $Q_{G(TOT)}$ | $V_{GS} = 10\text{ V}, V_{DS} = 32\text{ V}, I_D = 60\text{ A}$  |  | 113  |  | nC |
| Threshold Gate Charge        | $Q_{G(TH)}$  | $V_{GS} = 4.5\text{ V}, V_{DS} = 32\text{ V}, I_D = 60\text{ A}$ |  | 5.5  |  | nC |
| Gate-to-Source Charge        | $Q_{GS}$     |                                                                  |  | 19.5 |  |    |
| Gate-to-Drain Charge         | $Q_{GD}$     |                                                                  |  | 32   |  |    |
| Plateau Voltage              | $V_{GP}$     |                                                                  |  | 3.6  |  |    |

### SWITCHING CHARACTERISTICS (Note 6)

|                     |              |                                                                                           |  |    |  |    |
|---------------------|--------------|-------------------------------------------------------------------------------------------|--|----|--|----|
| Turn-On Delay Time  | $t_{d(ON)}$  | $V_{GS} = 4.5\text{ V}, V_{DS} = 20\text{ V}, I_D = 10\text{ A}, R_G = 2.5\text{ }\Omega$ |  | 22 |  | ns |
| Rise Time           | $t_r$        |                                                                                           |  | 32 |  |    |
| Turn-Off Delay Time | $t_{d(OFF)}$ |                                                                                           |  | 40 |  |    |
| Fall Time           | $t_f$        |                                                                                           |  | 27 |  |    |

### DRAIN-SOURCE DIODE CHARACTERISTICS

|                         |          |                                                                                   |                             |  |      |     |    |
|-------------------------|----------|-----------------------------------------------------------------------------------|-----------------------------|--|------|-----|----|
| Forward Diode Voltage   | $V_{SD}$ | $V_{GS} = 0\text{ V},$<br>$I_S = 10\text{ A}$                                     | $T_J = 25^{\circ}\text{C}$  |  | 0.74 | 1.0 | V  |
|                         |          |                                                                                   | $T_J = 125^{\circ}\text{C}$ |  | 0.58 |     |    |
| Reverse Recovery Time   | $t_{RR}$ | $V_{GS} = 0\text{ V}, dI_S/dt = 100\text{ A}/\mu\text{s},$<br>$I_S = 60\text{ A}$ |                             |  | 41   |     | ns |
| Charge Time             | $t_a$    |                                                                                   |                             |  | 19   |     |    |
| Discharge Time          | $t_b$    |                                                                                   |                             |  | 19   |     |    |
| Reverse Recovery Charge | $Q_{RR}$ |                                                                                   |                             |  | 33   |     | nC |

5. Pulse Test: pulse width  $\leq 300\text{ }\mu\text{s}$ , duty cycle  $\leq 2\%$ .

6. Switching characteristics are independent of operating junction temperatures.

TYPICAL CHARACTERISTICS




Figure 1. On-Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Gate-to-Source Voltage




Figure 4. On-Resistance vs. Drain Current and Gate Voltage




Figure 5. On-Resistance Variation with Temperature




Figure 6. Drain-to-Source Leakage Current vs. Voltage

TYPICAL CHARACTERISTICS




Figure 7. Capacitance Variation




Figure 8. Gate-to-Source Voltage vs. Total Charge




Figure 9. Resistive Switching Time Variation vs. Gate Resistance




Figure 10. Diode Forward Voltage vs. Current




Figure 11. Maximum Rated Forward Biased Safe Operating Area

TYPICAL CHARACTERISTICS





Figure 12. Thermal Response

# NVMFS5830NL

## PACKAGE DIMENSIONS

DFN5 5x6, 1.27P  
(SO-8FL)  
CASE 488AA  
ISSUE H



### NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSION D1 AND E1 DO NOT INCLUDE MOLD FLASH PROTRUSIONS OR GATE BURRS.

| MILLIMETERS |          |      |      |
|-------------|----------|------|------|
| DIM         | MIN      | NOM  | MAX  |
| A           | 0.90     | 1.00 | 1.10 |
| A1          | 0.00     | ---  | 0.05 |
| b           | 0.33     | 0.41 | 0.51 |
| c           | 0.23     | 0.28 | 0.33 |
| D           | 5.15 BSC |      |      |
| D1          | 4.70     | 4.90 | 5.10 |
| D2          | 3.80     | 4.00 | 4.20 |
| E           | 6.15 BSC |      |      |
| E1          | 5.70     | 5.90 | 6.10 |
| E2          | 3.45     | 3.65 | 3.85 |
| e           | 1.27 BSC |      |      |
| G           | 0.51     | 0.61 | 0.71 |
| K           | 1.20     | 1.35 | 1.50 |
| L           | 0.51     | 0.61 | 0.71 |
| L1          | 0.05     | 0.17 | 0.20 |
| M           | 3.00     | 3.40 | 3.80 |
| θ           | 0°       | ---  | 12°  |

### STYLE 1:

1. SOURCE
2. SOURCE
3. SOURCE
4. GATE
5. DRAIN
6. DRAIN

\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free  
USA/Canada  
Europe, Middle East and Africa Technical Support:  
Phone: 421 33 790 2910  
Japan Customer Focus Center  
Phone: 81-3-5817-1050

ON Semiconductor Website: [www.onsemi.com](http://www.onsemi.com)

Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative

NVMFS5830NL/D

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,  
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А