


G3VM-601G

MOS FET Relays SOP 4-pin, High-load-voltage Type

MOS FET Relays in SOP 4-pin packages for high load voltages

- Load voltage: 600 V



Note: The actual product is marked differently from the image shown here.

RoHS Compliant


Application Examples

- Semiconductor test equipment
- Various battery-driven devices
- Power circuit
- Test & Measurement equipment
- Security equipment
- Amusement equipment
- Communication equipment
- Industrial equipment

Package

(Unit : mm, Average)

SOP 4-pin



Note: The actual product is marked differently from the image shown here.

Model Number Legend

G3VM-□□□□
1 2 3 4

- Load Voltage**
60 : 600 V
- Contact form**
1 : 1a (SPST-NO)
- Package**
G : SOP 4-pin

4. Other informations
When specifications overlap, serial code is added in the recorded order.

Ordering Information

Package	Contact form	Terminals	Load voltage (peak value) *	Continuous load current (peak value) *	Stick packaging		Tape packaging	
					Model	Minimum package quantity	Model	Minimum package quantity
SOP4	1a (SPST-NO)	Surface-mounting Terminals	600 V	70 mA	G3VM-601G1	100 pcs.	G3VM-601G1(TR)	2,500 pcs.
				90 mA	G3VM-601G		G3VM-601G(TR)	

* The AC peak and DC value are given for the load voltage and continuous load current.
Note: To order tape packaging for Relays with surface-mounting terminals, add "(TR)" to the end of the model number.

Absolute Maximum Ratings (Ta = 25°C)


	Item	Symbol	G3VM-601G1	G3VM-601G	Unit	Measurement conditions
Input	LED forward current	IF	30	50	mA	
	Repetitive peak LED forward current	IFP		1	A	100 μs pulses, 100 pps
	LED forward current reduction rate	ΔIf/°C	-0.3	-0.5	mA/°C	Ta ≥ 25°C
	LED reverse voltage	VR		5	V	
	Connection temperature	TJ		125	°C	
Output	Load voltage (AC peak/DC)	VOFF		600	V	
	Continuous load current (AC peak/DC)	Io	70	90	mA	
	ON current reduction rate	ΔIo/°C	-0.7	-0.9	mA/°C	Ta ≥ 25°C
	Pulse ON current	Iop	210	270	mA	t=100 ms, Duty=1/10
	Connection temperature	TJ		125	°C	
	Dielectric strength between I/O (See note 1.)	V-i		1500	Vrms	AC for 1 min
	Ambient operating temperature	Ta		-40 to +85	°C	With no icing or condensation
	Ambient storage temperature	Tstg		-55 to +125	°C	
Soldering temperature	-		260	°C	10 s	

Note: 1. The dielectric strength between the input and output was checked by applying voltage between all pins as a group on the LED side and all pins as a group on the light-receiving side.

■Electrical Characteristics (Ta = 25°C)

Item	Symbol	G3VM-601G1		G3VM-601G		Unit	Measurement conditions
		Minimum	Typical	Maximum	Typical		
LED forward voltage	V _F	Minimum	1.1		1.0	V	I _F =10 mA
		Typical	1.27		1.15		
		Maximum	1.4		1.3		
Reverse current	I _R	Maximum		10		μA	V _R =5 V
Capacitance between terminals	C _T	Typical		30		pF	V=0, f=1 MHz
Trigger LED forward current	I _{FT}	Typical	–		0.4	mA	G3VM-601G1 : I _o =70 mA G3VM-601G : I _o =90 mA
		Maximum	0.2		1		
Release LED forward current	I _{FC}	Minimum	–		0.1	mA	I _{OFF} =100 μA
		Typical	0.001		–		
Maximum resistance with output ON	R _{ON}	Typical	35		45	Ω	G3VM-601G1 : I _F =0.5 mA, I _o =70 mA, t < 1 s G3VM-601G : I _F =2 mA, I _o =90 mA
		Maximum		60			
Current leakage when the relay is open	I _{LEAK}	Typical	1		–	nA	V _{OFF} =600 V
		Maximum		1,000			
Capacitance between terminals	C _{OFF}	Typical		75		pF	V=0, f=1 MHz
Capacitance between I/O terminals	C _{I-O}	Typical		0.8		pF	f=1 MHz, V _s =0 V
Insulation resistance between I/O terminals	R _{I-O}	Minimum		1000		MΩ	V _{I-O} =500 VDC, RoH±60%
		Typical		10 ⁸			
Turn-ON time	t _{ON}	Typical		2		ms	G3VM-601G1 : I _F =0.5 mA, R _L =200 Ω, V _{DD} =10 V (See note 2.) G3VM-601G : I _F =2 mA, R _L =200 Ω, V _{DD} =10 V (See note 2.)
		Maximum	10		8		
Turn-OFF time	t _{OFF}	Typical	1		0.5	ms	G3VM-601G1 : I _F =0.5 mA, R _L =200 Ω, V _{DD} =10 V (See note 2.) G3VM-601G : I _F =2 mA, R _L =200 Ω, V _{DD} =10 V (See note 2.)
		Maximum	5		3		

Note: 2. Turn-ON and Turn-OFF Times



■Recommended Operating Conditions

For usage with high reliability, Recommended Operation Conditions is a measure that takes into account the derating of Absolute Maximum Ratings and Electrical Characteristics.

Each item on this list is an independent condition, so it is not simultaneously satisfy several conditions.


Item	Symbol		G3VM-601G1	G3VM-601G	Unit
Load voltage (AC peak/DC)	V _{DD}	Maximum	480		V
Operating LED forward current	I _F	Typical	0.5	2	mA
		Maximum	25		
Continuous load current (AC peak/DC)	I _o	Maximum	60	70	
Ambient operating temperature	T _a	Minimum	-20		°C
		Maximum	65		

■Spacing and Insulation


Item	Minimum	Unit
Creepage distances	4.0	mm
Clearance distances	4.0	
Internal isolation thickness	0.1	

Engineering Data


LED forward current vs. Ambient temperature




Continuous load current vs. On-state voltage




Turn ON, Turn OFF time vs. LED forward current




Current leakage vs. Load voltage G3VM-601G1




Continuous load current vs. Ambient temperature




On-state resistance vs. Ambient temperature




Turn ON, Turn OFF time vs. Ambient temperature




LED forward current vs. LED forward voltage



Trigger LED forward current vs. Ambient temperature



Current leakage vs. Ambient temperature




Introduction
General-purpose
High-voltage
Multi-contact pair
High-current and
Low-V_{ON} resistance
Small and high-
dielectric-
strength
High-dielectric-
strength
Current-limiting
Low-voltage-resistance
and Low-V_{ON} resistance
Small and High-
voltage
Certified Models with
Statistical Derivation
DIP
SOP
SSOP
USOP
VSON
G3VM-601G□

■ Appearance / Terminal Arrangement / Internal Connections

● Appearance

SOP (Small Outline Package)

SOP 4-pin




Note 1. The actual product is marked differently from the image shown here.

Note 2. "G3VM" does not appear in the model number on the Relay.

Note 3. The indentation in the corner diagonally opposite from the pin 1 mark is from a pin on the mold.

● Terminal Arrangement/Internal Connections (Top View)




■ Dimensions (Unit: mm)




Surface-mounting Terminals

Weight: 0.1 g



Actual Mounting Pad Dimensions

(Recommended Value, Top View)



Note: The actual product is marked differently from the image shown here.

■ Approved Standards

UL recognized 

Approved Standards	Contact form	File No.
UL (recognized)	1a (SPST-NO)	E80555

■ Safety Precautions

- Refer to the *Common Precautions for All MOS FET Relays* for precautions that apply to all MOS FET Relays.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «**JONHON**», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «**FORSTAR**».



JONHON

«**JONHON**» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«**FORSTAR**» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А