PIHER

# PC-16 16 mm Carbon Potentiometer





Bushless version

## FEATURES

- Carbon resistive element.
- IP54 protection according to IEC 60529.
- Polyester substrate.
- Modular gang type (up to 4).
- Self extinguishable material UL 94-V0.
- Upon request:
  - Metalic support.
  - Stereo matching.
  - Switch.
  - Nut & washer.
  - Bushless & shaftless models.
  - Assemblies with wires and connectors.

## MECHANICAL SPECIFICATIONS

| | |
|---|---|
| – Mechanical rotation angle: | 300° ± 5° |
| – Electrical rotation angle: | 280° ± 20° |
| – Torque: | 0.5 to 1.5 Ncm.<br>(0.7 to 2.1 in-oz) |
| – Stop torque: | > 40 Ncm. ( >56 in-oz) |
| – Max. torque nut (binding out): | < 80 Ncm. (112 in-oz) |
| – Thrust and pull in the shaft: | > 25 N |

* Others check availability.

** Up to 85°C depending on application.

## ELECTRICAL SPECIFICATIONS

– Range of values*
100Ω ≤ Rn ≤ 5 M (Decad. 1.0 - 2.0 - 2.2 - 2.5 - 4.7 - 5.0)

– Standard tolerance*: 100Ω ≤ Rn ≤ 1M Ω ------ ± 20%
1MΩ < Rn ≤ 5M Ω ------ ± 30%

– Max. Voltage: 250 VDC (lin) 125 VDC (no lin)

– Nominal Power 50°C (122°F) (see power rating curve)
0.2 W (lin) 0.1 W (no lin)

– Taper* Lin ; Log; Alog (Log. & Alog. only Rn ≥ 1K).

– Residual resistance*: ≤ 0.5% Rn (5 Ω min.)

– Equivalent Noise Resistance: ≤ 3% Rn (3 Ω min.)

– Operating temperature**: –25°C + 70°C (–13°F + 158°F)

## HOW TO ORDER

| PC-16 | D | H | 10 | I | M06 | 203 | A | 2020 | OPTIONAL EXTRAS 0 | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|

**Serie**
PC-16

**Model**
S =Single
D =Tandem
T =Triple
C =Quad.

**Mounting style**
H= Horizontal
V = Vertical
(See note 1)

**Bushing diameter**
07 = M7
10 = M10
SC = Bushless
(See note 2)

**Terminals**
I = PCB
C = Solder Lugs

**Shafts**
M04
M06
M07
M11
M17
P01
P22
---
(See note 3)

**Value**
101 = 100 Ω
203 = 20 K
504 = 500 K
505 = 5M
(See note 4)

**Taper**
A = Linear
B = Log.
C = Alog.
(See note 10)
Others tapers on request

**Tolerance**
0505 = ± 5%
1010 = ± 10%
2020 = ± 20%
3030 = ± 30%
(See note 5)

**Shafts spec. leng.**
XX.X
(See notes 6,9)

**Mounting brackets**
M1
M2
(See note 7)

**Stereo matching**
3D = 3dB
4D = 4dB
6D = 6dB
(See note 8)

**Switch**
I = PCB
C = Solder lugs
(See note 9)

**Nuts & Washers**
-TA = loose nut & washer
MTA=assembled nut & washer
-T- = loose nut
MT- = assembled nut
(See note 9)

NOTES:

(1) Mounting style: Type "V" is only available in model "S" potentiometer and with printed circuit terminals.

(2) Bushings: Type "10" has two paralell flat surfaces for avoiding rotation. Bushless option only available for single model.

(3) M07 shaft is only available with M10 bushing. --- = no shaft

(4) Value: • Code: 10 1 100 Ω
10 → 2 first digits of the value.
1 → Number of zeros
• In models "D", "T", "C", with different values, they will be asked by drawings.

(5) Tolerance (non standard), upon request. Example: +7% -5% Code: 07 05
07 → negative tolerance
05 → positive tolerance

(6) Shaft special length:
• Only for special length and plain shafts (not knurled). Example: Shaft Ø6.35 L= 24.5 M07 ..... 24.5
• NOTE: Maximun length recommended: L = 45
24.5 → special length shafts

(7) Mounting brackets: Only applicable for model "S", mounting "H" and without switch.

(8) Stereo matching: not available for single models. Maximun will be: •3dB for model "D" •4dB for model "T" •6dB for model "C"

(9) Not available for Bushless version.

(10) Switch option not available with antilog taper.

## HOW TO ORDER CUSTOM DRAWING

PC-16 S V + DRAWING NUMBER (Max. 16 digits)

This way of ordering should be used for options which are not included in the "How to order" standard and optional extras.

## STANDARD OPTIONS

Shaft length ..... 0 Standard Length
Mounting brackets ..... Without mounting brackets
Stereo matching ..... Only on request (see note 8)
Switch ..... No switch
Nut & washer ..... Without nut and washer

## MODELS




PC-16 S/D/T/C..H...

PC-16 SV .....

## METALLIC SUPPORT




PC-16 SH.....M1

PC-16 SH....M2

## BUSHINGS




07

10

## EXAMPLES OF BUSHLESS VERSION




Download STEP files here:
https://piher.net/piher/?p=938

## TERMINALS







C







I

## TAPERS

Standard

A = Linear
B = Log.
C = Alog.




## POWER RATING CURVE




## NUTS & WASHERS

Bushing 10




Bushing 07




NOTE = Please note relative terminal positions when ordering non linear tapers.

## TESTS

| | | TYPICAL VARIATIONS |
|---|---|---|
| ELECTRICAL LIFE | 1.000 h. @ 50°C; 0.2 W | ±5 % |
| MECHANICAL LIFE : POT.*<br>SWITCH | 25.000 (10-15 CPM)<br>10.000 (1 A, 50 VAC) | ±3 % (Rn < 1 MΩ) |
| TEMPERATURE COEFFICIENT | –25°C; +70°C | ±300 ppm/°C (Rn < 100 KΩ) |
| THERMAL CYCLING | 16 h. @ 85°C; 2h. @ –25°C | ±2.5 % |
| DAMP HEAT | 500 h. @ 40°C @ 95% HR | ±5 % |
| VIBRATION (for each plane X,Y,Z) | 2 h. @ 10 Hz. ... 55 Hz. | ±2 % |

(*) only applicable to values ≥1K. For lower values please consult.

## SWITCH



















PC-16S . . . H . . . . . . I / C







PC-16SV . . . I

## SWITCH SPECIFICATIONS

| | |
|---|---|
| NOMINAL CURRENT | 1A, 250 VAC |
| CONTACT RESISTANCE (initial) | 10 m Ω |
| OPERATING TORQUE | 1 to 3 Ncm (1.4 to 4.2 in oz) |
| OPERATING ANGLE | 30° ± 5° |
| TEST VOLTAGE | 500 V |

## PACKAGING

Boxes of 100 pieces (single body model): Inner dimensions 250 x 160 x 95 mm

## METALIC SHAFTS

STANDARD




| A | L | CODE |
|---|---|---|
| 4 | 45 | M04 |
| 6 | 45 | M06 |
| 6.35 | 45 | M07 |




| A | B | C | L | CODE |
|---|---|---|---|---|
| 2 | 5 | 7 | 15 | M11 |
| 2 | 10 | 11 | 20 | M12 |
| 4 | 12 | 14 | 25 | M13 |
| 4 | 12 | 14 | 30 | M14 |
| 4 | 12 | 14 | 35 | M15 |
| 4 | 12 | 14 | 40 | M16 |
| 4 | 12 | 14 | 45 | M17 |

SPECIAL




| A |
|---|
| ∅4 |
| ∅6 |
| ∅6.35 |

## PLASTIC SHAFTS Ø3.1




**P09**

## PLASTIC SHAFTS Ø4




**P01**




**P02**

## PLASTIC SHAFTS Ø4




P04







P07







P08




P10




P21

## PLASTIC SHAFTS Ø6

Shaft position shown full CCW. Any other position for plastic shafts has to be shiftted n times 24°. Other positions upon request.




P05




P06







P11




P12




P13







P14




P15




P16




P17




P18







P19




P20




P22

Special shaft example (18 teeth knurl & arrow. Check availability.).



## OPEN CIRCUIT FEATURE (CUT TRACK)




CCW on-off (A)

**PCI**
Cut track at the beginning of the travel.




**PCF**
Cut track at the end of the travel







CW on-off (E)

A = Initial S = Wiper E = Final.
PCI, PCF and other configurations available upon request. Check the ordering code with Piher.

## RECOMMENDED CONNECTIONS

Piher potentiometer's recommended connection circuit for a position sensor or control application.
(voltage divider circuit electronic design).




$R_L \geq 100 \times R$

Disclaimer

The product information in this catalogue is for reference purposes. Please consult for the most up to date and accurate design information.

Piher Sensors & Controls S.A., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Piher"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product described herein.

Piher disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Piher's terms and conditions of sale, including but not limited to the warranty expressed therein, which apply to these products.

No licence, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Piher.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Piher products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Piher for any damages arising or resulting from such use or sale. Please contact authorised Piher personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Information contained in and/or attached to this catalogue may be subject to export control regulations of the European Community, USA, or other countries. Each recipient of this document is responsible to ensure that usage and/or transfer of any information contained in this document complies with all relevant export control regulations. If you are in any doubt about the export control restrictions that apply to this information, please contact the sender immediately. For any Piher International Corp. Exports, Note: All products / technologies are EAR99 Classified commodities. Exports from the United States are in accordance with the Export Administration Regulations. Diversion contrary to US law is prohibited.

Piher is an Amphenol™ company.

Note: Piher products can be adapted to meet customer's requirements.
Due to continuous process improvement, specifications are subject to change without notice.

v180220

## Contact

Piher Sensors & Controls SA
Polígono Industrial Municipal
Vial T2, 22,
31500 Tudela - Spain.
t. +34-948-820450
f. +34-948-824050

sales@piher.net

www.piher.net

# OCEAN CHIPS
## Океан Электроники
## Поставка электронных компонентов

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «**JONHON**», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «**FORSTAR**».

AVIC JONHON

**«JONHON»** (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

**«FORSTAR»** (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).

FORSTAR®

Телефон: 8 (812) 309-75-97 (многоканальный)
Факс: 8 (812) 320-03-32
Электронная почта: ocean@oceanchips.ru
Web: http://oceanchips.ru/
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А