



**CXP optical cable assemblies from Molex offer improved fiber management for connecting CXP transceivers and complete Molex's iPass+ High-Speed Channel (HSC) CXP Copper and Optical System**

Molex's low-profile CXP optical 4.50mm round cable assemblies offer improved fiber management over traditional flat cables for connecting CXP transceivers. The CXP optical cable assemblies utilize 24 fibers using industry-standard MTP/MPO connectors, 12 transmit (TX) and 12 receive (RX), and 10 Gbps high-bandwidth (OM3) fiber. This design meets the InfiniBand bandwidth requirements for CXP modules spaced up to 300.00m (984.25').

Molex provides a complete optical CXP solution with cable assemblies and loopbacks. Products include MTP/MPO-to-LC cable assemblies for connections to Small Form-factor Pluggable (SFP) or LC patch panels. Loopbacks feature a compact housing that loop optical TX to RX ports for testing, burn-in and field troubleshooting.

**Features and Benefits**

- MTP/MPO CXP connector interface meets CXP interface specifications
- Low-profile, round cable design for improved cable management over flat cable, with 360° cable-routing capability
- Up to 10 Gbps data rate capability provides optimized bandwidth by application
- RoHS compliant to meet environmental requirements for electronic equipment and accessories

Molex's CXP optical cable assemblies are part of the iPass+ HSC CXP system, which is the latest addition to the existing iPass product family. The iPass Interconnect System offers connectors and cables that enable flexible-speed compatibility for applications ranging from 1 to 10 Gbps and is an ideal solution for the growing server-storage market. For additional information, visit: [www.molex.com/link/cxp.html](http://www.molex.com/link/cxp.html).

**106284 Cable Assemblies**



**SPECIFICATIONS**

**Reference Information**

Packaging: Individual pack in a bag  
Mates With: CXP Optical Transceivers

**Optical**

Fiber Specifications:  
Fiber Count: 24 fibers (12 TX / 12 RX)  
Multi Mode: 50/125µm  
Insertion Loss at Test:  
Multi Mode: 0.22dB Typical; ≤0.75dB max.  
Connector to Connector: MTP to MTP  
Bandwidth: See table on page 2 of datasheet

**Mechanical**

Bend Radius: 50.8mm (2.00") min. long-term

**Physical**

Jacket Dimensions:  
Interconnect Cables – 1 to 20 meters: 4.50mm (.177")  
Distribution Cables – 21 to 300 meters: 5.40mm (.213")  
Fire Rating:  
OFNR (Riser): Lengths less than or equal to 20 meters  
OFNP (Plenum): Lengths over 20 meters  
Operating Temperature: 0 to +70°C  
Storage Temperature: -40 to +70°C

- **High-Performance Computing**
  - Controller cards and servers
  - Switches
  - Direct Attached Storage (DAS)
- **Data Centers**
  - Controller cards and servers
  - Switches
  - Blades
  - Storage Attached Networks (SAN)
- **Networking**
  - NIC cards and servers
  - Switches
  - Routers
  - Network Attached Storage (NAS)



**BANDWIDTH SPEEDS**

Fiber Type	Overfilled Launch Bandwidth, Min. (MHz-km)		1 Gigabit Ethernet Link Distance, Min. (m)		10 Gigabit Ethernet Link Distance, Min. (m)	
	850nm	1300nm	850nm	1300nm	850nm	1300nm
Standard Bandwidth	500	500	600	600	86	-
High Bandwidth	1500	500	900	550	300	-

**ORDERING INFORMATION**

Order No.	Bandwidth	Fire Rating	Cable Diameter	Length
106284-0001	Standard	OFNR (Riser)	4.50mm (.177")	1.00m (3.28')
106284-0005				5.00m (16.40')
106284-0010				10.00m (32.81')
106284-0015				15.00m (49.21')
106284-0020				20.00m (65.62')
106284-0025		OFNP (Plenum)	5.40mm (.213")	25.00m (82.02')
106284-0030				30.00m (98.43')
106284-0050				50.00m (164.04')
106284-0100				100.00m (328.08')
106284-1001				High (10 Gbps)
106284-1005	5.00m (16.40')			
106284-1010	10.00m (32.81')			
106284-1015	15.00m (49.21')			
106284-1020	20.00m (65.62')			
106284-1025	OFNP (Plenum)	5.40mm (.213")	25.00m (82.02')	
106284-1030			30.00m (98.43')	
106284-1050			50.00m (164.04')	
106284-1100			100.00m (328.08')	

[www.molex.com/link/cxp.html](http://www.molex.com/link/cxp.html)

**Americas Headquarters**  
 Lisle, Illinois 60532 U.S.A.  
 1-800-78MOLEX  
 amerinfo@molex.com

**Asia Pacific North Headquarters**  
 Yamato, Kanagawa, Japan  
 81-46-265-2325  
 apninfo@molex.com

**Asia Pacific South Headquarters**  
 Jurong, Singapore  
 65-6268-6868  
 apsinfo@molex.com

**European Headquarters**  
 Munich, Germany  
 49-89-413092-0  
 eurinfo@molex.com

**Corporate Headquarters**  
 2222 Wellington Ct.  
 Lisle, IL 60532 U.S.A.  
 P: 630-969-4550 F: 630-969-1352

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,  
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А