Honeywell

THE POWER OF **CONNECTED**

# Heavy Duty Pressure Transducers

PX3 Series, 1 bar to 50 bar | 15 psi to 700 psi

***32313757***

*Issue E*

**Datasheet**



## DESCRIPTION

Honeywell's PX3 Series Heavy Duty Pressure Transducers use piezoresistive sensing technology with ASIC (Application Specific Integrated Circuit) signal conditioning in a brass housing and Metri-Pack 150, DIN, or cable harness electrical connections. The PX3 Series is calibrated and temperature compensated from -40°C to 125°C [-40°F to 257°F].

## VALUE TO CUSTOMERS

- Total Error Band (TEB) ±1.0 %FSS from -20°C to 85°C: Provides indication of the sensor's true measurement performance over a specified temperature range; small error promotes system uptime and efficiency. (See Figure 1.)

**Figure 1. TEB Definition and Temperature Performance**




- Higher insulation resistance and dielectric strength: Protects the user and sensor in high over-voltage situations, and ensures that the device is compliant with industry standards.
- Higher EMC performance: Operates more reliably in the presence of electro-magnetic fields, such as near wireless signals, RF communication, and electrical devices.
- Higher external freeze/thaw resistance: Survives exposure to frost, commonly found in refrigeration systems. (See Figure 2.)

**Figure 2. PX3 Series External Freeze/Thaw Resistance**

(Shown with mating connector, see Figure 5.)

- Reduced current consumption: Helps to reduce energy costs, and enhances product life if used in battery driven systems.
- Media compatibility: Common HFC (hydrofluorocarbon) refrigerants (R410A and R134A), next generation low global warming potential (GWP) refrigerants (R448A/ Solstice® N40, R32 and R1234ZE), engine oil, petroleum-based hydraulic fluids, brake fluids (DOT3), and dry air. For ammonia and other corrosive media, see Honeywell's SPT Series.

## DIFFERENTIATION

- Optional diagnostics mode: Beneficial in applications where the sensor functionality and the need to know internal or external failure modes is critical.
- Great customer value: Multiple configuration possibilities provide flexibility of use in the application with no upfront NRE or tooling charges.
- Durable: Provides the tough environmental specifications needed, including insulation resistance and dielectric strength, external freeze-thaw resistance (see Figure 2), and EMC performance.
- 4 mA to 20 mA output is temperature compensated up to 125°C.

## FEATURES

- Pressure range: 1 bar to 50 bar | 15 psi to 700 psi (absolute and sealed gage)
- Ratiometric output: 0.5 Vdc to 4.5 Vdc or 0.33 Vdc to 2.97 Vdc
- 4 mA to 20 mA output supports transmission of output signals over longer distances
- Calibrated and temperature compensated
- Total Error Band: ±1.0 %FSS from -20°C to 85°C [-4°F to 185°F]
- External freeze/thaw resistance: 6 cycles from -30°C to 50°C [-22°F to 122°F]
- Insulation resistance: >100 MOhm, 1500 Vdc (in dry, non-ionized air)
- Dielectric strength: AC1500V, 1 min. or AC1800V, 1 s (in dry, non-ionized air)
- Current consumption: 3.5 mA max.
- EMC (radiated immunity): 200 V/m (ratiometric voltage output), 140 V/m (current output) per ISO 11452-2
- Ingress protection IP67 (Metri-Pack connector), IP69K (cable harness), IP65 (DIN connector)
- RoHS, REACH, and CE compliant
- Six industry-standard pressure port types, including a tube port which provides for hermetically-sealed process connection

## POTENTIAL APPLICATIONS

- Industrial: Refrigerant pressure monitoring in HVAC/R systems; dry air system pressure, process controls and automation
- Transportation: Dry air system monitoring; hydraulic, brake, and engine oil fluid pressure monitoring; air brake pressure monitoring

The PX3 Series is not recommended for use with media involving water, saturated air such as steam and vapor, and ammonia.

## PORTFOLIO

Honeywell's PX3 Series joins the PX2 Series, MLH Series, and SPT Series heavy duty pressure transducers.

**Table 1. Electrical Specifications**

| Characteristic | Parameter |
|---|---|
| Supply voltage:<br>ratiometric voltage output:<br>5 Vdc<br>3.3 Vdc<br>current output:<br>-40°C to 100°C<br>>100°C to 125°C | <br><br>5 Vdc ±0.25 Vdc<br>3 Vdc ±0.25 Vdc<br><br>8 Vdc to 30 Vdc<br>8 Vdc to 25 Vdc |
| Over voltage and reverse voltage:<br>ratiometric voltage output<br>current output | <br>±16 Vdc<br>±35 Vdc |
| Current consumption:<br>5 Vdc supply<br>3.3 Vdc supply | <br>3.0 mA max.<br>1.6 mA to 2.1 mA |
| Short circuit protection | yes |
| Nominal output transfer function:<br>5 Vdc supply<br>3.3 Vdc supply<br>8 Vdc to 30 Vdc supply | <br>0.5 Vdc to 4.5 Vdc (ratiometric to supply)<br>0.33 Vdc to 2.97 Vdc (ratiometric to supply)<br>4 mA to 20 mA |

**Table 2. Performance Specifications (At 25°C [77°F] and under unless otherwise noted.)**

| Characteristic | Parameter |
|---|---|
| Operating temperature range[1] | -40°C to 125°C [-40°F to 257°F] |
| Storage temperature range[1] | -40°C to 125°C [-40°F to 257°F] |
| Compensated temperature range | -40°C to 125°C [-40°F to 257°F] |
| Total Error Band[2]:<br>-20°C to 85°C [-4°F to 185°F]<br><-20°C, >85°C [<-4°F, >185°F] | <br>±1.0 %FSS<br>±2.0 %FSS |
| Accuracy BFSL[3] | ±0.25 %FSS |
| Response time | <2 ms (10% to 90% step change in pressure) |
| Turn on time[4] | <7 ms |
| EMC rating[5]:<br>surge immunity (all leads)<br>electrostatic discharge<br>radiated immunity<br>fast transient burst<br>immunity to conducted disturbances<br>radiated emissions<br>radiated immunity:<br>ratiometric (voltage) output<br>4 mA to 20 mA (current) output | <br>±1000 V line to ground per IEC 61000-4-5<br>±4 kV contact, ±8 kV air per IEC 61000-4-2<br>10 V/m (80 MHz to 1000 MHz) per IEC 61000-4-3<br>±1 kV per IEC 61000-4-4<br>3 V per IEC 61000-4-6<br>40 dBµV (30 MHz to 230 MHz), 47 dBµV (230 MHz to 1000 MHz) per CISPR 11<br><br>200 V/m per ISO 11452-2<br>140 V/m per ISO 11452-2 |
| Insulation resistance[6]:<br>ratiometric voltage output<br>current output | <br>>100 MOhm at 1500 Vdc<br>>100 MOhm at 1000 Vdc |
| Dielectric strength | <1 mA at 1500 Vac (1 min) or 1800 Vac (1 s) |
| Load resistance[6]:<br>ratiometric voltage output<br>current output | <br>>5 kOhm<br>($V_{in}$ - 8) x 50 Ohm |
| Life | >10 million full scale pressure cycles over the calibrated pressure range |

[1] Dependent on seal material. See Figure 5.

[2] Total Error Band: The maximum deviation from the ideal transfer function over the entire compensated temperature and pressure range. Includes all errors due to offset, full scale span, pressure non-linearity, pressure hysteresis, pressure non-repeatability, thermal effect on offset, thermal effect on span, and thermal hysteresis.

[3] Accuracy: The maximum deviation in output from a Best Fit Straight Line (BFSL) fitted to the output measured over the pressure range at 25°C [77°F]. Includes all errors due to pressure non-linearity, pressure hysteresis, and pressure non-repeatability.

[4] Turn on time: Duration from power applied until first valid output for voltage output. Typical value for 4 mA to 20 mA output.

[5] Tested using 1,5 m [59.1 in] long cable.

[6] Tested in dry, non-ionized air.

**Table 3. Pressure Reference Definitions**

| Pressure Reference | Definition |
|---|---|
| Absolute | Output is calibrated to be proportional to the difference between applied pressure and a fixed reference to perfect vacuum (absolute zero pressure). |
| Sealed gage[1] | Sensor construction is identical to the absolute version with a built in reference at zero pressure in order to minimize measurement error over temperature. The output is calibrated to be proportional to the difference between applied pressure and a reference of 1 standard atmosphere (1.013 barA \| 14.7 psiA). Example: 100 psi sealed gage has a calibrated pressure range from 14.7 psi absolute to 114.7 psi absolute. (See Figure 3.) |

[1] Sealed gage option only available in pressure ranges at or above 8 bar | 100 psi.

**Figure 3. Ratiometric Output Option AA for 100 psi, Absolute vs Sealed Gage**




**Table 4. Pressure Ratings**

| bar | | | psi | | |
|---|---|---|---|---|---|
| Operating Pressure | Over-pressure | Burst Pressure | Operating Pressure | Over-pressure | Burst Pressure |
| 1 | 5 | 8 | 15 | 70 | 115 |
| 1.6 | 5 | 8 | 30 | 150 | 250 |
| 2 | 10 | 17 | 50 | 250 | 400 |
| 2.5 | 10 | 17 | 100 | 450 | 750 |
| 4 | 17 | 27 | 150 | 450 | 750 |
| 6 | 31 | 51 | 174 | 450 | 750 |
| 8 | 31 | 51 | 200 | 450 | 1150 |
| 10 | 31 | 51 | 250 | 450 | 1150 |
| 12 | 31 | 51 | 300 | 1000 | 1500 |
| 16 | 32 | 80 | 500 | 1000 | 1500 |
| 20 | 69 | 103 | 600 | 1000 | 1500 |
| 25 | 69 | 103 | 667 | 1000 | 1500 |
| 30 | 69 | 103 | 700 | 1000 | 1500 |
| 35 | 69 | 103 | - | - | - |
| 40 | 69 | 103 | - | - | - |
| 46 | 69 | 103 | - | - | - |
| 50 | 69 | 103 | - | - | - |

**Diagnostics Mode (For Ratiometric Voltage Output Only)**

The PX3 Series diagnostics mode allows the device to indicate when internal or external faults occur. If an internal fault occurs, the output will rail to the preset lower or upper limit values shown in Figure 4 and Table 5.

External faults will result in the sensor's output exceeding those preset limits (lower or upper). (For example, if the external sensor ground (signal) were lost, the sensor output would exceed the upper rail of 97.5%.)

**Figure 4. Analog Output with Diagnostics**




**Table 5. Output Transfer Function Codes**

| Fault Condition | Analog Diagnostic Rail |
|---|---|
| EEPROM Corrupt | below lower rail |
| Sensor Bridge Open (any element) | above upper rail |
| Sensor Bridge Short (any element) | above upper rail |
| Low supply voltage | below lower rail |
| Loss of ground connection | above upper rail |

**Table 6. Environmental and Mechanical Specifications**

| Characteristic | Parameter |
|---|---|
| Shock:<br>threaded ports<br>tube port | <br>100 G per MIL-STD-202G, Method 213B, Cond. F (at 25°C [77°F])<br>100 G per MIL-STD-202F, Method 213B, and Condition C |
| Vibration:<br>threaded ports<br>tube port | <br>20 G sweep, 10 Hz to 2000 Hz (at 25°C [77°F])<br>10 Hz to 55 Hz, 2 mm displacement, tested as per IEC 60068-2-6; Test FC. (at 25°C [77°F]) |
| Ingress protection:<br>Metri-Pack 150 electrical connector<br>DIN electrical connector<br>Cable harness electrical connector | <br>IP67<br>IP65<br>IP65, IP67, IP69K |
| Ambient humidity | 0 %RH to 95 %RH, non-condensing |
| External freeze/thaw resistance | >6 cycles from -30°C to 50°C [-22°F to 122°F] |
| Wetted materials:<br>threaded ports<br>external seals for ports<br>tube port<br>braze filler<br>internal O-ring media seal<br>sensing element and substrate<br>adhesives | <br>brass C36000; lead (Pb) content: 3.7% max.<br>nitrile<br>copper UNS C12200; lead (Pb) free<br>silver and copper alloy<br>seal material based on application (see seal material media compatibility options below)<br>alumina, glass, silicon<br>epoxy |
| Internal O-ring material media compatibility[1]:<br>HNBR (option H)<br>silicone (option S) | <br>refrigerants, engine oil, petroleum-based hydraulic fluid<br>dry air |
| Electrical connector material | PBT 30% GF |

[1] Honeywell can assist with selecting suitable O-ring seal material for the media based on the seal manufacturer's recommendation. The customer should test the compatibility with the media to ensure that it is correct for the application.

## CAUTION
### PRODUCT DAMAGE TO TUBE PRESSURE PORT TYPE DURING BRAZING
Ensure that the temperature of the brass port and plastic connector is maintained below 125°C during flame brazing. Exposure to temperatures higher than 125°C can cause permanent product damage and can compromise ingress protection leading to short circuits.
**Failure to comply with these instructions may result in product damage.**

## CAUTION
### PRODUCT DAMAGE DUE TO MECHANICAL ISSUES
- Ensure torque specifications are determined for the specific application. Values provided are for reference only. (Mating materials and thread sealants can result in significantly different torque values from one application to the next.)
- When using mating parts made of stainless steel, use a thread sealant with anti-seize properties to prevent thread galling. Ensure the sealant is rated for the application.
- Use appropriate tools (such as an open ended wrench or deep well socket) to install transducers.
- Always hand-start transducers into the hole to prevent cross threading and damage.
- Ensure that torque is not applied to the electrical connector.
- Ensure that the proper mating electrical connector with a seal is used to connect the transducer. Improper or damaged seals can compromise ingress protection, leading to short circuits.

**Failure to comply with these instructions may result in product damage.**

## CAUTION
### PRODUCT DAMAGE DUE TO PARTICULATES AND SATURATED AIR
Ensure that filters and dehumidifiers are used upstream of the transducers to keep media flow free of large particulates and condensed moisture. PX3 Series transducers are dead-end devices. Particulate accumulation may clog the port or damage the diaphragm. Condensing moisture may affect sensor output and lower insulation resistance.
**Failure to comply with these instructions may result in product damage.**

## CAUTION
### PRODUCT DAMAGE DUE TO CONDUCTIVE MEDIA
Ensure sensor is not used with conductive or ionic media. These media can affect sensor output and lower insulation resistance.
**Failure to comply with these instructions may result in product damage.**

# Heavy Duty Pressure Transducers
PX3 Series, 1 bar to 50 bar | 15 psi to 700 psi

**Figure 5. Nomenclature and Order Guide**

For example, **PX3AN1BS150PAAAX** defines a PX3 Series Heavy Duty Pressure Transducer, Metri-Pack 150, standard (UL V-0) electrical connector type, 1/4-18 NPT pressure port type, brass housing body, silicone: -40°C to 125°C [-40°F to 257°F] seal material and temperature range, 150 psi pressure range, absolute pressure reference, ratiometric: 0.5 Vdc to 4.5 Vdc output transfer function, no special

**PX3 A N1 B S 150P A AA X**

**Series**

| | |
|---|---|
| **PX3** | Heavy Duty Pressure Transducer[1] |

**Electrical Connector Type**

| | | |
|---|---|---|
| **A** | Metri-Pack 150, Standard (UL V-0)[2] | |
| **C** | DIN (Male, EN 175301-803C) | |

| | PVC Cable[3] -40°C to 105°C [-40°F to 221°F] two or three 22 AWG wires | XLPE Cable[3] -40°C to 125°C [-40°F to 257°F] two or three 22 AWG wires |
|---|---|---|
| 0.5 m [1.3ft] | **K** | **L** |
| 1.0 m [3.2 ft] | **E** | **M** |
| 2.0 m [6.6 ft] | **F** | **N** |
| 3.0 m [9.8 ft] | **G** | **P** |
| 5.0 m [16.4 ft] | **H** | **Q** |


three-wire

two-wire

Three-wire cable is required for ratiometric Output Transfer Functions **AA**, **DA**, **AC** and **DC**; two-wire cable is required for Output Transfer Function **CH**.

Three meter and five meter cables are only available with Output Transfer Function **CH.**

**Pressure Port Type[4]**

| | | |
|---|---|---|
| **F1** | 7/16-20 UNF 1/4 inch 45° Flare Female Schrader (SAE J512) | |
| **G1** | G1/4 A-G (ISO 1179-3) | |
| **G2** | G1/4 A-L (ISO 1179-2) | |
| **M1** | M12 x 1.5 (ISO 6149-3) | |
| **N1** | 1/4-18 NPT (ANSI/ASME B1.20.1) | |
| **N2** | 1/8-27 NPT (ANSI/ASME B1.20.1) | |
| **T1** | Tube[5] | |

**Special**

| | |
|---|---|
| **X** | |

**Output Transfer Function**

| | |
|---|---|
| **AA** | Ratiometric: 5.0 V, 10% to 90% Vs |
| **DA** | Ratiometric: 5.0 V, 10% to 90% Vs (diagnostics on)[6] |
| **AC** | Ratiometric: 3.3 V, 10% to 90% Vs |
| **DC** | Ratiometric: 3.3 V, 10% to 90% Vs (diagnostics on)[6] |
| **CH** | Current: 4 mA to 20 mA |

**Pressure Reference**

| | |
|---|---|
| **A** | Absolute |
| **S** | Sealed gage[7] |

**Pressure Range**

| bar | | bar | | psi | | psi | |
|---|---|---|---|---|---|---|---|
| **001B** | 1 bar | **016B** | 16 bar | **015P** | 15 psi | **250P** | 250 psi |
| **1.6B** | 1.6 bar | **020B** | 20 bar | **030P** | 30 psi | **300P** | 300 psi |
| **002B** | 2 bar | **025B** | 25 bar | **050P** | 50 psi | **500P** | 500 psi |
| **2.5B** | 2.5 bar | **030B** | 30 bar | **100P** | 100 psi | **600P** | 600 psi |
| **004B** | 4 bar | **035B** | 35 bar | **150P** | 150 psi | **667P** | 667 psi |
| **006B** | 6 bar | **040B** | 40 bar | **174P** | 174 psi | **700P** | 700 psi |
| **008B** | 8 bar | **046B** | 46 bar | **200P** | 200 psi | | |
| **010B** | 10 bar | **050B** | 50 bar | | | | |
| **012B** | 12 bar | | | | | | |

**Internal O-ring Material and Temperature Range[1, 8]**

| | |
|---|---|
| **H** | HNBR (Hydrogenated Nitrile Butadiene Rubber): -30°C to 125°C [-22°F to 257°F] |
| **S** | Silicone: -40°C to 125°C [-40°F to 257°F] |

**Housing Body Material**

| | |
|---|---|
| **B** | Brass (C36000) |

[1] Not all catalog listing combinations are shown. Custom configurations, such as varied cable lengths, end mating connectors, different O-ring materials, and different pressure ranges are available. Please contact Honeywell.

[2] Metri-Pack 150 mating connectors with shielded cable and three 22 AWG wires are available from Honeywell. Order part no. 3685301 for 1 m [3.2 ft] cable length and part no. 3685302 for 3 m [9.8 ft] cable length.

[3] PVC Flame Retardant (FR) type cable is FT1 rated per IEC60332-1; XLPE non-flame retardant cable is FT2 rated per IEC60332-1.

[4] See Table for pressure port materials.

[5] Tube port is not available with DIN connector option.

[6] See page 3 for Diagnostics Mode information.

[7] Sealed gage option only available in pressure ranges at or above 8 bar | 100 psi.

[8] See Table 6 for O-ring seal material media compatibility.

Mating Connector[2]

**Figure 6. Metri-Pack Mounting Dimensions (For reference only. mm/[in].)**

**Pinout**




**Ratiometric Voltage Output**
Pin A = Ground
Pin B = V+
Pin C = Vout

**Current Output**
Pin A = Return
Pin B = Supply
Pin C = Not connected

**General product marking**




### F1: 7/16-20 UNF 1/4 inch 45° Flare Female Schrader (SAE J512)

**Seal:** 45° cone
**Mating geometry:** SAE J512
**Installation torque:** 17 N m [12.5 ft-lb]
**Weight:** 41 g to 46 g [1.4 oz to 1.6 oz]




### G1: G1/4 A-G (ISO 1179-3)

**Seal:** O-ring (included)
**Mating geometry:** ISO 1179-1
**Installation torque:** 50 N m [36.9 ft-lb]
**Weight:** 35,1 g to 40,1 g [1.2 oz to 1.4 oz]




### G2: G1/4 A-L (ISO 1179-2)

**Seal:** ISO 9974-2/DIN 3869 profile ring (included)
**Mating geometry:** ISO 1179-1
**Installation torque:** 50 N m [36.9 ft-lb]
**Weight:** 35,1 g to 40.1 g [1.2 oz to 1.4 oz]




### M1: M12 x 1.5 (ISO 6149-3)

**Seal:** O-ring (included)
**Mating geometry:** ISO 6149-1
**Installation torque:** 25 N m [18.4 ft-lb]
**Weight:** 33,9 g to 38,9 g [1.2 oz to 1.4 oz]




### N1: 1/4-18 NPT

**Seal:** Pipe thread
**Mating geometry:** ANSI B1.20.1
**Installation torque:** Two to three turns from finger tight
**Weight:** 35,1 g to 40,1 g [1.2 oz to 1.4 oz]




### N2: 1/8-27 NPT

**Seal:** Pipe thread
**Mating geometry:** ANSI B1.20.1
**Installation torque:** Two to three turns from finger tight
**Weight:** 31,2 g to 36.2 g [1.1 oz to 1.3 oz]




### T1: Tube

**Seal:** Brazing
**Weight:** 32 g [1.1 oz]



**Figure 7. DIN Mounting Dimensions (For reference only. mm/[in].)**

## Pinout




**Ratiometric Voltage Output**
Pin 1 = Ground
Pin 2 = V+
Pin 3 = Vout
Pin 4 (PE) = Not connected

**Current Output**
Pin 1 = Return
Pin 2 = Supply
Pin 3 = Not connected
Pin 4 (PE) = Not connected

## General product marking




### F1: 7/16-20 UNF 1/4 inch 45° Flare Female Schrader (SAE J512)

**Seal:** 45° cone
**Mating geometry:** SAE J512
**Installation torque:** 17 N m [12.5 ft-lb]
**Weight:** 42 g to 47 g [1.5 oz to 1.7 oz]




### G1: G1/4 A-G (ISO 1179-3)

**Seal:** O-ring (included)
**Mating geometry:** ISO 1179-1
**Installation torque:** 50 N m [36.9 ft-lb]
**Weight:** 36,1 g to 41,1 g [1.3 oz to 1.4 oz]




### G2: G1/4 A-L (ISO 1179-2)

**Seal:** ISO 9974-2/DIN 3869 profile ring (included)
**Mating geometry:** ISO 1179-1
**Installation torque:** 50 N m [36.9 ft-lb]
**Weight:** 36,1 g to 41,1 g [1.3 oz to 1.4 oz]




### M1: M12 x 1.5 (ISO 6149-3)

**Seal:** O-ring (included)
**Mating geometry:** ISO 6149-1
**Installation torque:** 25 N m [18.4 ft-lb]
**Weight:** 34,9 g to 39,9 g [1.2 oz to 1.4 oz]




### N1: 1/4-18 NPT

**Seal:** Pipe thread
**Mating geometry:** ANSI B1.20.1
**Installation torque:** Two to three turns from finger tight
**Weight:** 36,1 g to 41,1 g [1.3 oz to 1.4 oz]




### N2: 1/8-27 NPT

**Seal:** Pipe thread
**Mating geometry:** ANSI B1.20.1
**Installation torque:** Two to three turns from finger tight
**Weight:** 32,2 g to 37,2 g [1.1 oz to 1.3 oz]



**Figure 8. Cable Harness Mounting Dimensions (For reference only. mm/[in].)**

**Wire colors**




**Voltage Output**
Black = Ground
Red = V+
White = Vout

**Current Output**
Black = Return
Red = Supply

**General product marking**




### F1: 7/16-20 UNF 1/4 inch 45° Flare Female Schrader (SAE J512)

**Seal:** 45° cone
**Mating geometry:** SAE J512
**Installation torque**: 17 N m [12.5 ft-lb]
**Weight:** 90 g to 88 g [3.2 oz to 3.1 oz]




### G1: G1/4 A-G (ISO 1179-3)

**Seal:** O-ring (included)
**Mating geometry:** ISO 1179-1
**Installation torque**: 50 N m [36.9 ft-lb]
**Weight:** 70 g to 68 g [2.5 to 2.4 oz]




### G2: G1/4 A-L (ISO 1179-2)

**Seal:** ISO 9974-2/DIN 3869 profile ring (included)
**Mating geometry:** ISO 1179-1
**Installation torque:** 50 N m [36.9 ft-lb]
**Weight:** 70 g to 68 g [2.5 oz to 2.4 oz]




### M1: M12 x 1.5 (ISO 6149-3)

**Seal:** O-ring (included)
**Mating geometry:** ISO 6149-1
**Installation torque**: 25 N m [18.4 ft-lb]
**Weight:** 69 g to 67 g [2.4 oz]



**Figure 8. Cable Harness Mounting Dimensions (For reference only. mm/[in].)**

**N1: 1/4-18 NPT**
**Seal:** Pipe thread
**Mating geometry:** ANSI B1.20.1
**Installation torque**: Two to three turns from finger tight
**Weight:** 70 g to 68 g [2.5 oz to 2.4 oz]




**N2: 1/8-27 NPT**
**Seal:** Pipe thread
**Mating geometry:** ANSI B1.20.1
**Installation torque:** Two to three turns from finger tight
**Weight:** 66 g to 64 g [2.3 oz]




**T1: Tube**
**Seal:** Brazing
**Weight:** 67 g [2.4 oz]



**ADDITIONAL INFORMATION**

The following associated literature is available on the Honeywell web site at sensing.honeywell.com:

- Product line guide
- Product range guide
- Product installation instructions
- Application notes:
  - Heavy Duty Pressure Transducers, PX2 Series and PX3 Series
  - PX2 Series and PX3 Series Heavy Duty Pressure Transducers for Potential Use in Industrial Refrigeration
  - PX2 Series and PX3 Series Heavy Duty Pressure Transducers for Potential Use in Industrial HVAC/R Applications
- Technical notes:
  - Total Error Band Specification for Honeywell Heavy Duty Pressure Transducers, PX2 Series and PX3 Series
  - Media Compatibility for Honeywell Heavy Duty Pressure Transducers, PX2 Series and PX3 Series
- CAD models

**⚠ WARNING**

**PERSONAL INJURY**

DO NOT USE these products as safety or emergency stop devices or in any other application where failure of the product could result in personal injury.

**Failure to comply with these instructions could result in death or serious injury.**

**⚠ WARNING**

**MISUSE OF DOCUMENTATION**

- The information presented in this datasheet is for reference only. Do not use this document as a product installation guide.
- Complete installation, operation, and maintenance information is provided in the instructions supplied with each product.

**Failure to comply with these instructions could result in death or serious injury.**

**Warranty/Remedy**

Honeywell warrants goods of its manufacture as being free of defective materials and faulty workmanship during the applicable warranty period. Honeywell's standard product warranty applies unless agreed to otherwise by Honeywell in writing; please refer to your order acknowledgement or consult your local sales office for specific warranty details. If warranted goods are returned to Honeywell during the period of coverage, Honeywell will repair or replace, at its option, without charge those items that Honeywell, in its sole discretion, finds defective. **The foregoing is buyer's sole remedy and is in lieu of all other warranties, expressed or implied, including those of merchantability and fitness for a particular purpose. In no event shall Honeywell be liable for consequential, special, or indirect damages.**

While Honeywell may provide application assistance personally, through our literature and the Honeywell web site, it is buyer's sole responsibility to determine the suitability of the product in the application.

Specifications may change without notice. The information we supply is believed to be accurate and reliable as of this writing. However, Honeywell assumes no responsibility for its use.

**For more information**

Honeywell Sensing and Internet of Things services its customers through a worldwide network of sales offices and distributors. For application assistance, current specifications, pricing or the nearest Authorized Distributor, visit sensing.honeywell.com or call:

Asia Pacific +65 6355-2828
Europe +44 (0) 1698 481481
USA/Canada +1-800-537-6945

Solstice® N40 is a registered trademark of Honeywell International Inc.

**Honeywell Sensing and Internet of Things**
9680 Old Bailes Road
Fort Mill, SC 29707
www.honeywell.com

32313757-E-EN | E | 01/18
© 2018 Honeywell International Inc.

# OCEAN CHIPS
## Океан Электроники
## Поставка электронных компонентов

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «**JONHON**», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «**FORSTAR**».

AVIC JONHON

**«JONHON»** (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

**«FORSTAR»** (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).

FORSTAR®

Телефон: 8 (812) 309-75-97 (многоканальный)
Факс: 8 (812) 320-03-32
Электронная почта: ocean@oceanchips.ru
Web: http://oceanchips.ru/
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А