



FEATURES

- Efficiency up to 81%
- Overload Protection
- Fully Regulated Output Voltage
- Operating Temperature Range -40°C to +85°C
- Wide 4:1 Input Range
- Isolation Voltage 1600 VDC
- Remote On/Off Control
- Lead free, RoHs compliant
- UL/cUL/IEC/EN 60950-1 Safety Approval(pending)
- 3 Years Product Warranty



The PJ03S/D series are miniature, SIP-8 package, isolated 3W DC/DC converters with 1,600VDC isolation. The PJ03S/D series features fully regulated output and wide 4:1 input voltage ranges. It offers over load protection and allows a wide operating temperature range of -40°C to +85°C. These isolated DC/DC converters are the latest offering from a world leader in power systems technology and manufacturing — Delta Electronics, Inc

Model Selection Guide

| Model Number | Input Voltage (Range) | Output Voltage | Output Current | | Input Current | | Max. capacitive Load | Efficiency (typ.) |
|--------------|-----------------------|----------------|----------------|------|---------------|----------|----------------------|-------------------|
| | | | Max. | Min. | @Max. Load | @No Load | | @Max. Load |
| | VDC | VDC | mA | mA | mA(typ.) | mA(typ.) | μF | % |
| PJ03S1203A | 12 (4.5 ~ 18) | 3.3 | 700 | 175 | 260 | 60 | 1760 | 74 |
| PJ03S1205A | | 5 | 600 | 150 | 320 | | 1000 | 78 |
| PJ03S1212A | | 12 | 250 | 63 | 313 | | 170 | 80 |
| PJ03S1215A | | 15 | 200 | 50 | 313 | | 110 | 80 |
| PJ03D1205A | | ±5 | ±300 | ±75 | 313 | | 470* | 80 |
| PJ03D1212A | | ±12 | ±125 | ±31 | 313 | | 1008* | 80 |
| PJ03D1215A | | ±15 | ±100 | ±25 | 313 | | 47 * | 80 |
| PJ03S2403A | 24 (9 ~ 36) | 3.3 | 700 | 175 | 128 | 25 | 1760 | 75 |
| PJ03S2405A | | 5 | 600 | 150 | 156 | | 1000 | 80 |
| PJ03S2412A | | 12 | 250 | 63 | 154 | | 170 | 81 |
| PJ03S2415A | | 15 | 200 | 50 | 154 | | 110 | 81 |
| PJ03D2405A | | ±5 | ±300 | ±75 | 158 | | 470 * | 79 |
| PJ03D2412A | | ±12 | ±125 | ±31 | 156 | | 100 * | 80 |
| PJ03D2415A | | ±15 | ±100 | ±25 | 154 | | 47 * | 81 |
| PJ03S4803A | 48 (18 ~ 75) | 3.3 | 700 | 175 | 65 | 15 | 1760 | 74 |
| PJ03S4805A | | 5 | 600 | 150 | 79 | | 1000 | 79 |
| PJ03S4812A | | 12 | 250 | 63 | 79 | | 170 | 79 |
| PJ03S4815A | | 15 | 200 | 50 | 79 | | 110 | 79 |
| PJ03D4805A | | ±5 | ±300 | ±75 | 79 | | 470* | 79 |
| PJ03D4812A | | ±12 | ±125 | ±31 | 79 | | 100 * | 79 |
| PJ03D4815A | | ±15 | ±100 | ±25 | 78 | | 47 * | 80 |

* For each output



Input Characteristics

| Parameter | Model | Min. | Typ. | Max. | Unit |
|-----------------------------------|------------------|----------------|------|------|------|
| Input Surge Voltage (1 sec. max.) | 12V Input Models | -0.7 | --- | 25 | VDC |
| | 24V Input Models | -0.7 | --- | 50 | |
| | 48V Input Models | -0.7 | --- | 100 | |
| Start-Up Threshold Voltage | 12V Input Models | 3 | 4 | 4.5 | |
| | 24V Input Models | 4.5 | 6 | 9 | |
| | 48V Input Models | 8.5 | 12 | 18 | |
| Under Voltage Shutdown | 12V Input Models | --- | 3.5 | 4 | |
| | 24V Input Models | --- | --- | 8 | |
| | 48V Input Models | --- | --- | 16 | |
| Reverse Polarity Input Current | All Models | --- | --- | 1 | A |
| Short Circuit Input Power | | --- | --- | 2500 | mW |
| Internal Filter Type | | Capacitor type | | | |
| Internal Power Dissipation | | --- | --- | 2600 | mW |

Output Characteristics

| Parameter | Conditions | Min. | Typ. | Max. | Unit |
|---------------------------------|-----------------------------|------|------|-------|-------------------|
| Output Voltage Setting Accuracy | At 50% Load and Nominal Vin | --- | --- | ±1.0 | %Vom. |
| Output Voltage Balance | Dual Output, Balanced Loads | --- | ±0.5 | ±2.0 | % |
| Line Regulation | Vin=Min. to Max. | --- | ±0.3 | ±0.5 | % |
| Load Regulation | Io=25% to 100% | --- | ±0.5 | ±1.0 | % |
| Ripple & Noise (20MHz) | 0-20 MHz Bandwidth | --- | 50 | 75 | mV _{p-p} |
| Transient Recovery Time | 25% Load Step Change | --- | 300 | 500 | µsec |
| Transient Response Deviation | | --- | ±3 | ±5 | % |
| Temperature Coefficient | | --- | --- | ±0.02 | %/°C |
| Short Circuit Protection | Continuous | | | | |

General Characteristics

| Parameter | Conditions | Min. | Typ. | Max. | Unit |
|-------------------------------|---|---------|------|------|-------|
| I/O Isolation Voltage (rated) | 60 Seconds | 1600 | --- | --- | VDC |
| I/O Isolation Resistance | 500 VDC | 1000 | --- | --- | MΩ |
| I/O Isolation Capacitance | 100KHz, 1V | --- | 200 | --- | pF |
| Switching Frequency | | --- | 350 | --- | KHz |
| MTBF (calculated) | MIL-HDBK-217F@25°C, Ground Benign | 800,000 | --- | --- | Hours |
| Safety Approvals(pending) | UL/cUL 60950-1 recognition (CSA certificate), IEC/EN 60950-1(CB-scheme) | | | | |

Recommended Input Fuse

| 12V Input Models | 24V Input Models | 48V Input Models |
|-----------------------|----------------------|----------------------|
| 1500mA Slow-Blow Type | 700mA Slow-Blow Type | 350mA Slow-Blow Type |


Remote On/Off Control

| Parameter | Conditions | Min. | Typ. | Max. | Unit |
|-------------------------------|---|------|------|------|------|
| Converter On | Under 0.6 VDC or Open Circuit, drops down to 0VDC by 2mV/°C | | | | |
| Converter Off | | 2.7 | --- | 15 | VDC |
| Device Standby Input Current | | --- | 1 | 2.5 | mA |
| Control Input Current (on) | Vin = 0V | --- | --- | 1 | mA |
| Control Input Current (off) | Vin = 5.0V | --- | --- | 1 | mA |
| Control Common | Referenced to Negative Input | | | | |

Environmental Characteristics

| Parameter | Conditions | Min. | Max. | Unit |
|--|---------------------|------|------|----------|
| Operating Ambient Temperature Range (See Power Derating Curve) | Natural Convection | -40 | +85 | °C |
| Case Temperature | | --- | 105 | °C |
| Storage Temperature Range | | -55 | +125 | °C |
| Humidity (non condensing) | | --- | 95 | % rel. H |
| Cooling | Free-Air convection | | | |
| Lead Temperature (1.5mm from case for 10Sec.) | | --- | 260 | °C |


Power Derating Curve



Notes

- 1 Specifications typical at $T_a=+25^{\circ}\text{C}$, resistive load, nominal input voltage and rated output current unless otherwise noted.
- 2 Transient recovery time is measured to within 1% error band for a step change in output load of 75% to 100%.
- 3 Ripple & Noise measurement bandwidth is 0-20 MHz measured with a $1\mu\text{F}$ M/C.
- 4 These power converters require a minimum output loading to maintain specified regulation, operation under no-load conditions will modules; however, they may not meet all specifications listed.
- 5 All DC/DC converters should be externally fused at the front end for protection.
- 6 We recommend to protect the converter by a slow blow fuse in the input supply line.
- 7 That "natural convection" is about 20LFM but is not equal to still air (0 LFM).
- 8 Specifications are subject to change without notice.

Mechanical Drawing



Physical Outline

| | |
|---------------|---|
| Case Size | : 21.8x9.3x11.2 mm (0.86x0.37x0.44 inches) |
| Case Material | : Non-Conductive Black Plastic (flammability to UL 94V-0 rated) |
| Pin Material | : Alloy 42 |
| Weight | : 4.8g |



| Part Numbering System | | | | | | |
|-----------------------|---------------|-------|-------------------|---------------|----------------|--------------------|
| P | J | 03 | S | 48 | 05 | A |
| Form factor | Family series | Watt | Number of Outputs | Input Voltage | Output Voltage | Option Code |
| D-DIP | A~Z | 01:1W | S - Single | 03:3.3V | 03:3.3V | A - Std. Functions |
| P-SIP | | 02:2W | D - Dual | 05: 5V | 05: 5V | |
| S-SMD | | 03:3W | | 12:12V | 12:12V | |
| | | 04:4W | | 24: 24V | 15: 15V | |
| | | 06:6W | | 48:48V | 24: 24V | |

WARRANTY

Delta offers a three(3) years limited warranty. Complete warranty information is listed on our web site or is available upon request from Delta.

Information furnished by Delta is believed to be accurate and reliable. However, no responsibility is assumed by Delta for its use, nor for any infringements of patents or other rights of third parties, which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Delta. Delta reserves the right to revise these specifications at any time, without notice.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А