

www.vishay.com

Vishay Siliconix

Automotive P-Channel 40 V (D-S) 175 °C MOSFET


PRODUCT SUMMARY				
V _{DS} (V)	-40			
$R_{DS(on)}(\Omega)$ at $V_{GS} = -10 \text{ V}$	0.061			
$R_{DS(on)}(\Omega)$ at $V_{GS} = -4.5 \text{ V}$	0.093			
I _D (A)	-6.9			
Configuration	Single			
Package	TSOP-6			

FEATURES

- TrenchFET® power MOSFET
- AEC-Q101 qualified c
- 100 % R_q and UIS tested
- Typical ESD protection 800 V
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912







Marking Code: 8W

D 4 3 G G	(3) G O	
D Top View		(4) S
V		

ABSOLUTE MAXIMUM RATINGS (T _C = 25 °C, unless otherwise noted)					
PARAMETER	SYMBOL	LIMIT	UNIT		
Drain-Source Voltage		V _{DS}	-40	V	
Gate-Source Voltage	V _{GS}	± 12	V		
Continuous Drain Current	T _C = 25 °C	1	-6.9		
Continuous Drain Current	T _C = 125 °C	I _D	-4		
Continuous Source Current (Diode Conduct	I _S	-6.3	Α		
Pulsed Drain Current		I _{DM}	-27		
Single Pulse Avalanche Current	L = 0.1 mH	I _{AS}	-18		
Single Pulse Avalanche Energy	L=0.11IIII	E _{AS}	16.7	mJ	
Maximum Bower Discipation 8	T _C = 25 °C	D	5	W	
Maximum Power Dissipation ^a	T _C = 125 °C	P_{D}	1.6	VV	
Operating Junction and Storage Temperatu	re Range	T _J , T _{stq}	-55 to +175	°C	

THERMAL RESISTANCE RATINGS						
PARAMETER		SYMBOL	LIMIT	UNIT		
Junction-to-Ambient	PCB Mount b	R_{thJA}	110	°C/W		
Junction-to-Foot (Drain)		R_{thJF}	30	G/VV		

- a. Pulse test; pulse width $\leq 300 \,\mu\text{s}$, duty cycle $\leq 2 \,\%$.
- b. When mounted on 1" square PCB (FR4 material).
- c. Parametric verification ongoing.

Vishay Siliconix

PARAMETER	SYMBOL	TEST CONDITIONS		MIN.	TYP.	MAX.	UNIT
Static							
Drain-Source Breakdown Voltage	V _{DS}	$V_{GS} = 0 \text{ V}, I_{D} = -250 \mu\text{A}$		-40	-	-	V
Gate-Source Threshold Voltage	V _{GS(th)}	V _{DS} =	V _{GS} , I _D = -250 μA	-1.5	-2.0	-2.5	V
Gate-Source Leakage	lana	V _{DS} =	$0 \text{ V}, \text{ V}_{GS} = \pm 12 \text{ V}$	1	-	± 2	μΑ
Gate-Source Leakage	I _{GSS}		$0 \text{ V}, \text{ V}_{GS} = \pm 20 \text{ V}$	-	-	± 30	mA
		V _{GS} = 0 V	V _{DS} = -40 V	-	-	-1	
Zero Gate Voltage Drain Current	I _{DSS}	V _{GS} = 0 V	$V_{DS} = -40 \text{ V}, T_{J} = 125 ^{\circ}\text{C}$	-	-	-50	μΑ
		V _{GS} = 0 V	V _{DS} = -40 V, T _J = 175 °C	-	-	-150	
On-State Drain Current a	I _{D(on)}	V _{GS} = -10 V	$V_{DS} = -5 V$	-10	-	-	Α
		V _{GS} = -10 V	I _D = -2.5 A	-	0.048	0.061	Ω
Drain-Source On-State Resistance a	R _{DS(on)}	V _{GS} = -10 V	I _D = -2.5 A, T _J = 125 °C	-	0.070	-	
	= = (=::)	V _{GS} = -10 V	I _D = -2.5 A, T _J = 175 °C	-	0.081	-	
Forward Transconductance b		$V_{GS} = -4.5 \text{ V}$ $I_D = -2 \text{ A}$		-	0.077	0.093	S
Dynamic b	9fs	V _{DS} =	= -15 V, I _D = -4 A	-	10	-	3
		1			700	075	
Input Capacitance	C _{iss}	-	V 00 V (4 MU)	-	733	975	
Output Capacitance	C _{oss}	$V_{GS} = 0 V$	$V_{GS} = 0 \text{ V}$ $V_{DS} = -20 \text{ V}, f = 1 \text{ MHz}$		130	175	pF
Reverse Transfer Capacitance	C _{rss}			-	84	115	
Total Gate Charge ^c	Q_g			-	8.4	12.5	
Gate-Source Charge c	Q_{gs}	$V_{GS} = -4.5 \text{ V}$	$V_{GS} = -4.5 \text{ V}$ $V_{DS} = -20 \text{ V}, I_D = -4 \text{ A}$		2.4	-	nC
Gate-Drain Charge ^c	Q_{gd}			ı	4.1	-	
Gate Resistance	R_g	f = 1 MHz		2.6	5.3	7.9	Ω
Turn-On Delay Time ^c	t _{d(on)}			-	9	12	
Rise Time ^c	t _r	$V_{DD} = -20 \text{ V}, \text{ R}_{L} = 5 \Omega$ $I_{D} \cong -4 \text{ A}, \text{ V}_{GEN} = -10 \text{ V}, \text{ R}_{g} = 1 \Omega$		-	24	32	
Turn-Off Delay Time ^c	t _{d(off)}			-	26	34	ns
Fall Time ^c	t _f			-	31	41	
	1	1		1			
Source-Drain Diode Ratings and Chara	acteristics ^b						
	I _{SM}			-	-	-27	А


Notes

- a. Pulse test; pulse width \leq 300 μ s, duty cycle \leq 2 %.
- b. Guaranteed by design, not subject to production testing.
- c. Independent of operating temperature.


Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.




TYPICAL CHARACTERISTICS (T_A = 25 °C, unless otherwise noted)




Output Characteristics




Transfer Characteristics




On-Resistance vs. Drain Current



Transfer Characteristics




Transconductance




Capacitance




TYPICAL CHARACTERISTICS (T_A = 25 °C, unless otherwise noted)




Gate Charge




On-Resistance vs. Junction Temperature




On-Resistance vs. Gate-to-Source Voltage



Threshold Voltage




Source Drain Diode Forward Voltage




Drain Source Breakdown vs. Junction Temperature



THERMAL RATINGS (T_A = 25 °C, unless otherwise noted)




Safe Operating Area



Normalized Thermal Transient Impedance, Junction-to-Ambient

Vishay Siliconix

THERMAL RATINGS (T_A = 25 °C, unless otherwise noted)



Normalized Thermal Transient Impedance, Junction-to-Foot

Note

- The characteristics shown in the two graphs
 - Normalized Transient Thermal Impedance Junction-to-Ambient (25 °C)
 - Normalized Transient Thermal Impedance Junction-to-Case (25 °C)

are given for general guidelines only to enable the user to get a "ball park" indication of part capabilities. The data are extracted from single pulse transient thermal impedance characteristics which are developed from empirical measurements. The latter is valid for the part mounted on printed circuit board - FR4, size 1" x 1" x 0.062", double sided with 2 oz. copper, 100 % on both sides. The part capabilities can widely vary depending on actual application parameters and operating conditions.


Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see www.vishay.com/ppg?65332.







TSOP: 5/6-LEAD

JEDEC Part Number: MO-193C





D A₂ A
Seating Plane



	MILLIMETERS			ı	NCHES		
Dim	Min	Nom	Max	Min	Nom	Max	
Α	0.91	-	1.10	0.036	-	0.043	
A ₁	0.01	-	0.10	0.0004	-	0.004	
A ₂	0.90	-	1.00	0.035	0.038	0.039	
b	0.30	0.32	0.45	0.012	0.013	0.018	
С	0.10	0.15	0.20	0.004	0.006	0.008	
D	2.95	3.05	3.10	0.116	0.120	0.122	
Е	2.70	2.85	2.98	0.106	0.112	0.117	
E ₁	1.55	1.65	1.70	0.061	0.065	0.067	
е		0.95 BSC		(0.0374 BSC	;	
e ₁	1.80	1.90	2.00	0.071	0.075	0.079	
L	0.32	-	0.50	0.012	-	0.020	
L ₁	0.60 Ref			0.024 Ref			
L ₂		0.25 BSC				0.010 BSC	
R	0.10	-	-	0.004	-	-	
θ	0°	4°	8°	0°	4°	8°	
θ_1	7° Nom				7° Nom		
ECN: C-06593-Rev. I, 18-Dec-06 DWG: 5540							

Document Number: 71200 www.vishay.com 18-Dec-06 uww.vishay.com



Mounting LITTLE FOOT® TSOP-6 Power MOSFETs

Surface mounted power MOSFET packaging has been based on integrated circuit and small signal packages. Those packages have been modified to provide the improvements in heat transfer required by power MOSFETs. Leadframe materials and design, molding compounds, and die attach materials have been changed. What has remained the same is the footprint of the packages.

The basis of the pad design for surface mounted power MOSFET is the basic footprint for the package. For the TSOP-6 package outline drawing see http://www.vishay.com/doc?71200 and see http://www.vishay.com/doc?72610 for the minimum pad footprint. In converting the footprint to the pad set for a power MOSFET, you must remember that not only do you want to make electrical connection to the package, but you must made thermal connection and provide a means to draw heat from the package, and move it away from the package.

In the case of the TSOP-6 package, the electrical connections are very simple. Pins 1, 2, 5, and 6 are the drain of the MOSFET and are connected together. For a small signal device or integrated circuit, typical connections would be made with traces that are 0.020 inches wide. Since the drain pins serve the additional function of providing the thermal connection to the package, this level of connection is inadequate. The total cross section of the copper may be adequate to carry the current required for the application, but it presents a large thermal impedance. Also, heat spreads in a circular fashion from the heat source. In this case the drain pins are the heat sources when looking at heat spread on the PC board.

Figure 1 shows the copper spreading recommended footprint for the TSOP-6 package. This pattern shows the starting point for utilizing the board area available for the heat spreading copper. To create this pattern, a plane of copper overlays the basic pattern on pins 1,2,5, and 6. The copper plane connects the drain pins electrically, but more importantly provides planar copper to draw heat from the drain leads and start the process of spreading the heat so it can be dissipated into the ambient air. Notice that the planar copper is shaped like a "T" to move heat away from the drain leads in all directions. This pattern uses all the available area underneath the body for this purpose.



FIGURE 1. Recommended Copper Spreading Footprint

Since surface mounted packages are small, and reflow soldering is the most common form of soldering for surface mount components, "thermal" connections from the planar copper to the pads have not been used. Even if additional planar copper area is used, there should be no problems in the soldering process. The actual solder connections are defined by the solder mask openings. By combining the basic footprint with the copper plane on the drain pins, the solder mask generation occurs automatically.

A final item to keep in mind is the width of the power traces. The absolute minimum power trace width must be determined by the amount of current it has to carry. For thermal reasons, this minimum width should be at least 0.020 inches. The use of wide traces connected to the drain plane provides a low impedance path for heat to move away from the device.

REFLOW SOLDERING

Vishay Siliconix surface-mount packages meet solder reflow reliability requirements. Devices are subjected to solder reflow as a test preconditioning and are then reliability-tested using temperature cycle, bias humidity, HAST, or pressure pot. The solder reflow temperature profile used, and the temperatures and time duration, are shown in Figures 2 and 3.



Ramp-Up Rate	+6°C/Second Maximum
Temperature @ 155 ± 15°C	120 Seconds Maximum
Temperature Above 180°C	70 – 180 Seconds
Maximum Temperature	240 +5/-0°C
Time at Maximum Temperature	20 - 40 Seconds
Ramp-Down Rate	+6°C/Second Maximum

FIGURE 2. Solder Reflow Temperature Profile

Document Number: 71743 www.vishay.com 27-Feb-04

Vishay Siliconix





FIGURE 3. Solder Reflow Temperature and Time Durations

THERMAL PERFORMANCE

A basic measure of a device's thermal performance is the junction-to-case thermal resistance, $R\theta_{jc},$ or the junction-to-foot thermal resistance, $R\theta_{\mbox{\scriptsize if}}.$ This parameter is measured for the device mounted to an infinite heat sink and is therefore a characterization of the device only, in other words, independent of the properties of the object to which the device is mounted. Table 1 shows the thermal performance of the TSOP-6.

TABLE 1.				
Equivalent Steady State Performance—TSOP-6				
Thermal Resistance Rθ _{jf}	30°C/W			

SYSTEM AND ELECTRICAL IMPACT OF TSOP-6

In any design, one must take into account the change in MOSFET $r_{DS(on)}$ with temperature (Figure 4).



FIGURE 4. Si3434DV

www.vishay.com Document Number: 71743 27-Feb-04



RECOMMENDED MINIMUM PADS FOR TSOP-6



Recommended Minimum Pads Dimensions in Inches/(mm)

Return to Index



Legal Disclaimer Notice

Vishay

Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.



Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«**FORSTAR**» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: http://oceanchips.ru/

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А