TLE8110EE

Smart Multichannel Low Side Switch with Parallel Control and SPI Interface coreFLEX

Automotive Power





1	Overview	. 4
2 2.1	Block Diagram	
3 3.1 3.2 3.3	Pin Configuration Pin Assignment Pin Definitions and Functions Terms	. 8 . 8
4 4.1 4.2 4.3	General Product Characteristics Absolute Maximum Ratings Functional Range Thermal Resistance	11 12
5 5.1 5.2	Power Supply Description Power Supply Electrical Characteristics Power Supply	15
6 6.1 6.2	Reset and Enable Inputs Description Reset and Enable Inputs Electrical Characteristics Reset Inputs	18
7 7.1 7.2 7.3 7.4	Power Outputs Description Power Outputs Description of the Clamping Structure Electrical Characteristics Power Outputs Parallel Connection of the Power Stages	20 21 22
8 8.1 8.2	Diagnosis Description Diagnosis Electrical Characteristics Diagnosis	31
9 9.1 9.2	Parallel Inputs Description Parallel Inputs Electrical Characteristics Parallel Inputs	34
10 10.1	Protection Functions	
11 11.1 11.2 11.3	16 bit SPI Interface Description 16 bit SPI Interface Timing Diagrams Electrical Characteristics 16 bit SPI Interface	41 41
12 12.1 12.2 12.2.1	Control of the device Internal Clock SPI Interface. Signals and Protocol Description 16 bit SPI Interface Signals	44 44 44
12.2.2 12.2.3 12.2.3.1 12.2.3.2	Daisy Chain Capability	45 45
12.2.3.3 12.2.4 12.2.4.1	16- and 2x8-bit protocol mixed. safeCOMMUNICATION	49 49
12.2.4.2 12.2.4.3	Modulo-8 Counter	





12.3	Register and Command - Overview	50
12.3.1	CMD - Commands	53
12.3.1.1	CMD_RSD - Command: Return Short Diagnosis	54
12.3.1.2	CMD_RSDS - Command: Return Short Diagnosis and Device Status	55
12.3.1.3	CMD_RPC - Command: Return Pattern Check	58
12.3.1.4	CMD_RINx - Command: Return Input Pin (INx) -Status	58
12.3.2	DCC - Diagnosis Registers and compactCONTROL	60
12.3.2.1	DRx - Diagnosis Registers Contents	63
12.3.2.2	DRx - Return on DRx Commands	63
12.3.2.3	DMSx/OPSx - Diagnosis Mode Set / Output Pin Set Commands	64
12.3.3	OUTx - Output Control Register CHx	66
12.3.4	ISx - INPUT or Serial Mode Control Register, Bank A and Bank B	66
12.3.5	PMx - Parallel Mode Register CHx	67
12.3.6	DEVS - Device Settings	67
13	Package Outlines	70
14	Revision History (Book)	71



Smart Multichannel Low Side Switch with Parallel Control and SPI Interface coreFLEX

TLE8110EE





1 Overview

Features

- · Overvoltage, Overtemperature, ESD -Protection
- Direct Parallel PWM Control of all Channels
- safeCOMMUNICATION (SPI and Parallel)
- Efficient Communication Mode: compactCONTROL
- Compatible with 3.3V- and 5V- Micro Controllers I/O ports
- clampSAFE for highly efficient parallel use of the channels
- Green Product (RoHS compliant)
- AEC Qualified



PG-DSO-36-41

Application

Power Switch Automotive and Industrial Systems switching Solenoids, Relays and Resistive Loads

Description

10 - channel Low-Side Switch in Smart Power Technology [SPT] with **S**erial **P**eripheral Interface [SPI] and 10 open drain DMOS output stages. The TLE8110EE is protected by embedded protection functions and designed for automotive and industrial applications. The output stages are controlled via Parallel Input Pins for PWM use or SPI Interface. The TLE8110EE is particularly suitable for Engine Management and Powertrain Systems.

Туре	Package	Marking
TLE8110EE	PG-DSO-36-41	TLE8110EE

Data Sheet 4 Rev. 1.0, 2009-06-15



Overview

Table 1 Product Summary

Parameter	Symbol	Value	Unit
Analogue Supply voltage	V_{DD}	4.50 5.50	V
Digital Supply Voltage	$V_{\sf CC}$	3.00 5.50	V
clamping voltage (CH 1-10)	$V_{\mathrm{DS}(\mathrm{AZ})\mathrm{typ}}$	55	V
On resistance	R _{ON1-4}	0.30	Ω
typical at Tj=25°C and $I_{\rm Dnom}$	R _{ON5-6}	0.25	Ω
	R _{ON7-10}	0.60	Ω
On resistance	R _{ON1-4}	0.60	Ω
maximum at Tj=150°C and $I_{\rm Dnom}$	R _{ON5-6}	0.50	Ω
	R _{ON7-10}	1.20	Ω
Nominal Output current (CH 1-4)	I_{Dnom}	1.50	Α
Nominal Output current (CH 5-6)	I_{Dnom}	1.70	Α
Nominal Output current (CH 7-10)	I_{Dnom}	0.75	Α
Output Current Shut-down Threshold (CH 1-4) min.	$I_{DSD(low)}$	2.60	Α
Output Current Shut-down Threshold (CH 5-6) min.	$I_{DSD(low)}$	3.70	Α
Output Current Shut-down Threshold (CH 7-10) min.	$I_{DSD(low)}$	1.70	Α




Figure 1 Block Diagram TLE8110EE



Block Diagram

2 Block Diagram




Figure 2 Block Diagram

2.1 Description

Communication

The TLE8110EE is a 10-channel low-side switch in PG-DSO-36-41 package providing embedded protective functions. The 16 bit serial peripheral interface (SPI) can be utilized for control and diagnosis of the device and the loads. The SPI interface provides daisy-chain capability in order to assemble multiple devices in one SPI chain by using the same number of micro-controller pins.

The analogue and the digital part of the device is supplied by 5V. Logic Input and Output Signals are then compatible to 5V logic level [TTL - level]. Optionally, the logic part can be supplied with lower voltages to achieve signal compatibility with e.g. 3.3V logic level [CMOS - level].

The TLE8110EE is equipped with 10 parallel input pins that are routed to each output channel. This allows control of the channels for loads driven by Pulse Width Modulation (PWM). The output channels can also be controlled by SPI.

Reset

The device is equipped with one Reset Pin and one Enable. Reset [RST] serves the whole device, Enable [EN] serves only the Output Control Unit and the Power Stages.

Diagnosis

The device provides diagnosis of the load, including open load, short to GND as well as short circuit to V_{Batt} detection and over-load / over-temperature indication. The SPI diagnosis flags indicates if latched fault conditions may have occurred.





Block Diagram

Protection

Each output stage is protected against short circuit. In case of over load, the affected channel is switched off. The switching off reaction time is dependent on two switching thresholds. Restart of the channel is done by clearing the Diagnosis Register. This feature protects the device against uncontrolled repetitive short circuits. The reaction to a short-circuit and over-temperature can alternatively changed to further modes, such as semi- or auto - restart of the affected channel.

There is a temperature sensor available for each channel to protect the device in case of over temperature. In case of over temperature the affected channel is switched off and the Over-Temperature Flag is set. Restart of the channel is done by deleting the Flag. This feature protects the device against uncontrolled temperature toggling.

Parallel Connection of Channels

The device is featured with a central clamping structure, so-called *CLAMP*safe. This feature ensures a balanced clamping between the channels and allows in case of parallel connection of channels a high efficient usage of the channel capabilities. This parallel mode is additionally featured by best possible parameter- and thermal matching of the channels and by controlling the channels accordingly.

Data Sheet 7 Rev. 1.0, 2009-06-15



Pin Configuration

3 Pin Configuration

3.1 Pin Assignment




Figure 3 Pin Configuration

3.2 Pin Definitions and Functions

Pin	Symbol	Function
1	GND	Ground
2	P_IN1	Parallel Input Pin 1. Default assignment to Output Channel 1.
3	P_IN2	Parallel Input Pin 2. Default assignment to Output Channel 2.
4	EN	Enable Input Pin. If not needed, connect with Pull-up resistor to VCC.
5	RST	Reset Input Pin. (low active). If not needed, connect with Pull-up resistor to VCC.
6	P_IN3	Parallel Input Pin 3. Default assignment to Output Channel 3.
7	P_IN4	Parallel Input Pin 4. Default assignment to Output Channel 4.
8	VDD	Analogue Supply Voltage
9	P_IN5	Parallel Input Pin 5. Default assignment to Output Channel 5.
10	VCC	Digital Supply Voltage
11	S_SO	Serial Peripheral Interface [SPI], Serial Output
12	S_CLK	Serial Peripheral Interface [SPI], Clock Input
13	S_CS	Serial Peripheral Interface [SPI], Chip Select (active Low)
14	S_SI	Serial Peripheral Interface [SPI], Serial Input
15	P_IN6	Parallel Input Pin 6. Default assignment to Output Channel 6.
16	P_IN7	Parallel Input Pin 7. Default assignment to Output Channel 7.
17	P_IN8	Parallel Input Pin 8. Default assignment to Output Channel 8.
18	GND	Ground

Data Sheet 8 Rev. 1.0, 2009-06-15



FLEX Smart Multi-Channel Switch

Pin Configuration

Pin	Symbol	Function
19	GND	Ground
20	OUT9	Drain of Power Transistor Channel 9
21	OUT10	Drain of Power Transistor Channel 10
22	N.C.	internally not connected, connect to Ground
23	GND	Ground
24	OUT6	Drain of Power Transistor Channel 6
25	OUT4	Drain of Power Transistor Channel 4
26	OUT3	Drain of Power Transistor Channel 3
27	P_IN9	Parallel Input Pin 9. Default assignment to Output Channel 9.
28	P_IN10	Parallel Input Pin 10. Default assignment to Output Channel 10.
29	OUT2	Drain of Power Transistor Channel 2
30	OUT1	Drain of Power Transistor Channel 1
31	OUT5	Drain of Power Transistor Channel 5
32	GND	Ground
33	N.C.	internally not connected, connect to Ground
34	OUT8	Drain of Power Transistor Channel 8
35	OUT7	Drain of Power Transistor Channel 7
36	GND	Ground
Cooling Tab	GND	Cooling Tab; internally connected to GND



Pin Configuration

3.3 Terms




Figure 4 Terms



4 General Product Characteristics

4.1 Absolute Maximum Ratings¹⁾

Absolute Maximum Ratings

 $T_{\rm j}$ = -40 °C to +150 °C; all voltages with respect to ground, positive current flowing into pin (unless otherwise specified)

Pos.	Parameter	Symbol	Limit Values		Unit	Conditions	
			Min.	Max.			
Supply	Voltages		'	<u> </u>	-		
4.1.1	Digital Supply voltage	$V_{\sf CC}$	-0.3	5.5	V	permanent	
4.1.2	Digital Supply voltage	$V_{\sf CC}$	-0.3	6.2	V	t < 10s	
4.1.3	Analogue Supply voltage	V_{DD}	-0.3	5.5	V	permanent	
4.1.4	Analogue Supply voltage	V_{DD}	-0.3	6.2	V	t < 10s	
Power S	Stages				l .		
4.1.5	Load Current (CH 1 to 10)	I _{Dn}	-	I _{DSD(low)}	Α	_	
4.1.6	Reverse Current Output (CH 1-10)	I _{Dn}	-I _{DSD(low)}	-	Α	_	
4.1.7	Total Ground Current	I_{GND}	-20	20	Α	_	
4.1.8	Continous Drain Source Voltage (Channel 1 to 10)	V_{DSn}	-0.3	45	V	_	
4.1.9	maximum Voltage for short circuit protection on Output	V_{DSn}	-	24	V	one event on one single channel.	
Single 0	Clamping Energies ^{1) 2)}						
4.1.10	Maximum Energy Dissipation per Channel. Single Pulse. Channel 1-4.	E_{AS}	-	28	mJ	I _D = 3.8A Tj = 150°C	
4.1.11	Maximum Energy Dissipation per Channel. Single Pulse. Channel 1-4.	E_{AS}	-	43	mJ	I _D = 1.5A Tj = 150°C	
4.1.12	Maximum Energy Dissipation per Channel. Single Pulse. Channel 5-6.	E_{AS}	-	37	mJ	I _D = 4.8A Tj = 150°C	
4.1.13	Maximum Energy Dissipation per Channel. Single Pulse. Channel 5-6.	E_{AS}	-	54	mJ	I _D = 1,7A Tj = 150°C	
4.1.14	Maximum Energy Dissipation per Channel. Single Pulse. Channel 7-10.	E_{AS}	-	10	mJ	I _D = 2.3A Tj = 150°C	
4.1.15	Maximum Energy Dissipation per Channel. Single Pulse. Channel 7-10.	E_{AS}	-	32	mJ	I _D = 0.75A Tj = 150°C	
Logic P	ins (SPI, INn, EN, RST)	·			•		
4.1.16	Input Voltage at all Logic Pin	V_{x}	-0.3	5.5	V	permanent	

¹⁾ Not subject to production test, specified by design.

Data Sheet 11 Rev. 1.0, 2009-06-15



Absolute Maximum Ratings (cont'd)

 $T_{\rm j}$ = -40 °C to +150 °C; all voltages with respect to ground, positive current flowing into pin (unless otherwise specified)

Pos.	Parameter	Symbol	Limit Values		Unit	Conditions
			Min.	Max.		
4.1.17	Input Voltage at all Logic Pin	V_{x}	-0.3	6.2	V	t < 10s
4.1.18	Input Voltage at Pin 27, 28 (IN9, 10,)	V_{x}	-0.3	45	V	permanent
Temper	atures	-	'	<u>'</u>		
4.1.19	Junction Temperature	T_{j}	-40	150	°C	_
4.1.20	Junction Temperature	T_{j}	-40	175	°C	max. 100hrs cumulative
4.1.21	Storage Temperature	$T_{\rm stg}$	-55	150	°C	_
ESD Ro	bustness				1	
4.1.22	Electro Static Discharge Voltage "Human Body Model - HBM"	V_{ESD}	-4	4	kV	All Pins HBM ³⁾ 1.5KOhm, 100pF
4.1.23	Electro Static Discharge Voltage "Charged Device Model - CDM"	V_{ESD}	-500	500	V	All Pins CDM ⁴⁾
4.1.24	Electro Static Discharge Voltage "Charged Device Model - CDM"	V_{ESD}	-750	750	V	Pin 1, 18, 19, 36 (corner pins) CDM ⁴⁾

- 1) Only one single channel at one time.
- 2) triangular test pulse
- 3) ESD susceptibility, HBM according to EIA/JESD 22-A114-B
- 4) ESD susceptibility, Charged Device Model "CDM" EIA/JESD22-C101-C

Note: Stresses above the ones listed here may cause permanent damage to the device. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

Note: Integrated protection functions are designed to prevent IC destruction under fault conditions described in the data sheet. Fault conditions are considered as "outside" normal operating range. Protection functions are not designed for continuous repetitive operation.

4.2 Functional Range

Pos.	Parameter	Symbol	Limit Values		Unit	Conditions
			Min.	Max.		
Supply	y Voltages		- 11		l l	1
4.2.1	Analogue Supply Voltage	V_{DD}	4.5	5.5	V	_
4.2.2	Digital Supply Voltage	$V_{\sf CC}$	3	V_{DD}	V	_
4.2.3	Digital Supply Voltage	$V_{\sf CC}$	V_{DD}	5.5	V	leakage Currents (I_{CC}) might increase if $V_{CC} > V_{DD}$.
Power	Stages			•	*	•
4.2.4	Ground Current	I_{GND_typ}	9		Α	resistive loads ¹⁾



Pos.	Parameter	Symbol	Lir	nit Values	Unit	Conditions
			Min.	Max.		
Tempe	eratures					
4.2.5	Junction Temperature	$T_{\rm j}$	-40	150	°C	-
4.2.6	Junction Temperature	$T_{\rm j}$	-40	175	°C	1) for 100hrs
		-				

¹⁾ Not subject to production test, specified by design.

Note: Within the functional range the IC operates as described in the circuit description. The electrical characteristics are specified within the conditions given in the related electrical characteristics table.

4.3 Thermal Resistance

Pos.	Parameter	Symbol	Limit Values			Unit	Conditions
			Min.	Тур.	Max.		
4.3.1	Junction to Soldering Point	R_{thJSP}	-	1.75	3.60	K/W	$P_{\text{vtot}} = 3W^{1)2)3)$
4.3.2	Junction to Ambient	R_{thJA}	-	25.00	-	K/W	$P_{\text{vtot}} = 3W^{1)2)3}$

¹⁾ Not subject to production test, specified by design.

²⁾ Homogenous power distrubution over all channels (All Power stages equally heated), dependent on cooling set-up

³⁾ refer to Figure 5






Figure 5 PG-DSO-36-41 PCB set-up

Data Sheet 14 Rev. 1.0, 2009-06-15



Power Supply

5 Power Supply

5.1 Description Power Supply

The TLE8110EE is supplied by analogue power supply line V_{DD} which is used for the analogue functions of the device, such as the gate control of the power stages. The digital power supply line V_{CC} is used to supply the digital part and offers the possibility to adapt the logic level of the serial output pins to lower logic levels.




Figure 6 Block Diagram Supply and Reset

Description Supply

The Supply Voltage Pins are monitored during the power-on phase and under normal operating conditions for under voltage.

If during Power-on the increasing supply voltage exceeds the Supply Power-on Switching Threshold, the internal Reset is released after an internal delay has expired.

In case of under voltage, a device internal reset is performed. The Switching Threshold for this case is the Poweron Switching threshold minus the Switching Hysteresis.

In case of under voltage on the analogue supply line V_{DD} the outputs are turned off but the content of the registers and the functionality of the logic part is kept alive. In case of under voltage on the digital supply V_{CC} line, a complete reset including the registers is performed.

After returning back to normal supply voltage and an internal delay, the related functional blocks are turned on again. For more details, refer to the chapter "Reset"

The device internal under-voltage set will set the TOR bit and the related bits in SDS (Short Diagnosis and Device Status) to allow the micro controller to detect this reset. For more information, refer to the chapter "Control of the Device".

Figure 7 removed



Power Supply

5.2 Electrical Characteristics Power Supply

Electrical Characteristics: Power Supply

Pos.	Parameter	Symbol	Limit Values		ues	Unit	Conditions	
			Min.	Тур.	Max.			
Digital	Supply and Power-on Reset	1	•	•				
5.2.1	Digital Supply Voltage	$V_{\sf CC}$	3	-	5.5	V		
5.2.2 a)	Digital Supply Current during Reset (V _{CC} < V _{CCpo})	$I_{ m CCstb}$	-	15	20	μΑ	$\begin{aligned} &\mathbf{f_{SCLK}} = \mathbf{0Hz}, \\ &\mathbf{S_CS} = V_{CC}, \\ &\mathbf{Tj} = \mathbf{85^{\circ}C}^{1)} \\ &V_{CC} = 2.0V \\ &V_{DD} > V_{CC} \end{aligned}$	
b)			-	20	40	μΑ	$\begin{aligned} &\mathbf{f_{SCLK}} = \mathbf{0Hz}, \\ &\mathbf{S_CS} = V_{CC}, \\ &\mathbf{Tj} = 150^{\circ}\mathbf{C} \\ &V_{CC} = 2.0\mathbf{V} \\ &V_{DD} > V_{CC} \end{aligned}$	
5.2.3 a)	Digital Supply Current during Reset (V _{RST} < V _{RSTI})	$I_{ m CCstb}$	-	2	5	μΑ	$\begin{aligned} &\mathbf{f_{SCLK}} = \mathbf{0Hz}, \\ &\mathbf{S_CS} = V_{\mathbf{CC}}, \\ &\mathbf{Tj} = \mathbf{85^{\circ}C^{1)}} \\ &V_{\mathbf{DD}} > V_{\mathbf{CC}} \end{aligned}$	
b)			-	5	15	μΑ	$\begin{aligned} &\mathbf{f_{SCLK}} = \mathbf{0Hz}, \\ &\mathbf{S_CS} = V_{\mathbf{CC}}, \\ &\mathbf{Tj} = 150^{\circ}\mathbf{C} \\ &V_{\mathbf{DD}} > V_{\mathbf{CC}} \end{aligned}$	
5.2.4 a)	Digital Supply Operating Current $V_{\rm CC}$ = 3.3V		I_{CC}	-	0.15	2	mA	f _{SCLK} = 0Hz, Tj=150°C. all Channels ON
b)			-	0.5	5	mA	f _{SCLK} = 5MHz, Tj=150°C. all Channels ON	
5.2.5 a)	Digital Supply Operating Current $V_{\rm CC}$ = 5.5V	I_{CC}	-	0.25	2	mA	f _{SCLK} = 0Hz, Tj=150°C. all Channels ON	
b)			-	0.8	10	mA	f _{SCLK} = 5MHz, Tj=150°C. all Channels ON	
5.2.6	Digital Supply Power-on Switching Threshold	V_{CCpo}	1.9	2.8	3	V	V _{CC} increasing	
5.2.7	Digital Supply Switching Hysteresis	V_{CChy}	100	300	500	mV	1)	
5.2.8	removed							



Power Supply

Electrical Characteristics: Power Supply

Pos.	Parameter	Symbol		Limit Val	ues	Unit	Conditions
			Min.	Тур.	Max.		
5.2.9	removed						
Analog	ue Supply and Power-on Reset	1		"	l.		1
5.2.10	Analogue Supply Voltage	V_{DD}	4.5	-	5.5	V	-
5.2.11 a)	Analogue Supply Current during Reset (V _{DD} < V _{DDpo})	I_{DDstb}	-	10	20	μА	$f_{SCLK} = 0Hz,$ $Tj=85^{\circ}C^{1)}$ $V_{DD} = 2V$
b)			-	15	40	μA	f_{SCLK} = 0Hz, Tj=150°C V_{DD} = 2V
5.2.12 a)	Analogue Supply Current during Reset	I_{DDstb}	-	1	5	μΑ	f _{SCLK} = 0Hz, Tj=85°C ¹⁾
b)	(V _{EN} < V _{ENI})		-	2	15	μΑ	f _{SCLK} = 0Hz, Tj=150°C
5.2.13	Analogue Supply Operating Current	I_{DD}	-	8	25	mA	f _{SCLK} = 05MHz ¹⁾ Tj=150°C all Channels ON
5.2.14	Analogue Supply Power-on Switching Threshold	V_{DDpo}	3	4.2	4.5	V	V_{DD} increasing
5.2.15	Analogue Supply Switching Hysteresis	V_{DDhy}	100	200	400	mV	1)
5.2.16	Analogue Supply Power-on Delay Time	$t_{ m VDDpo}$	-	100	200	μs	$V_{\rm DD}$ increasing ¹⁾
5.2.17	removed						

¹⁾ Parameter not subject to production test. Specified by design.

²⁾ C = 50pF connected to S_SO



Reset and Enable Inputs

6 Reset and Enable Inputs

6.1 Description Reset and Enable Inputs

The TLE8110EE contains one Reset- and one Enable Input Pin as can be seen in Figure 6.

Description:

Reset Pin [RST] is the main reset and acts as the internal under voltage reset monitoring of the digital supply voltage V_{CC} : As soon as \overline{RST} is pulled low, the whole device including the control registers is reset.

The Enable Pin [EN] resets only the Output channels and the control circuits. The content of the all registers is kept. This functions offers the possibility of a "soft" reset turning off only the Output lines but keeping alive the SPI communication and the contents of the control registers. This allows the read out of the diagnosis and setting up the device during or directly after Reset.

6.2 Electrical Characteristics Reset Inputs

Electrical Characteristics: Reset Inputs

 $3V < V_{CC} < 5.5V$; $4.5V < V_{DD} < 5.5V$; $V_{batt} = 13.5V$, $T_{j} = -40 \, ^{\circ}\text{C}$ to +150 $^{\circ}\text{C}$, all voltages with respect to ground, positive current flowing into pin (unless otherwise specified)

Pos.	Parameter	Symbol	L	imit Va	lues	Unit	Conditions
			Min.	Тур.	Max.		
Reset I	nput Pin [RST]	1	-	-	·		
6.2.1	Low Level of RST	V_{RSTI}	-0.3	-	V _{CC} *0.2	V	-
6.2.2	High Level of RST	V_{RSTh}	V _{CC} *0.4	-	V _{CC}	V	-
6.2.3	RST Switching Hysteresis	V_{RSThy}	20	100	300	mV	1)
6.2.4	Reset Pin pull-down Current	$I_{RSTresh}$	20	40	85	μΑ	V _{RST} =5V
		$I_{RSTresl}$	2.4	-	-	μΑ	V _{RST} =0.6V ¹
6.2.5	removed						
6.2.6	Minimum Reset Duration time RST	t_{RSTmin}	1	-	-	μs	1)
Enable	Input Pin [EN]						
6.2.7	Low Level of EN	V_{ENI}	-0.3	-	V _{CC} *0.2	V	-
6.2.8	High Level of EN	V_{ENh}	V _{CC} *0.4	-	V _{CC}	V	-
6.2.9	EN Switching Hysteresis	V_{ENhy}	20	60	300	mV	1)
6.2.10	Enable Pin pull-down Current	I_{ENresh}	5	35	85	μΑ	V _{EN} =5V
		I_{ENresl}	2.4	-	-	μΑ	V _{EN} =0.6V ¹⁾
6.2.11	Enable Reaction Time (reaction of OUTx)	t_{ENrr}	-	4	-	μs	1)
6.2.12	Minimum Enable Duration time EN	t_{ENmin}	1.2	-	-	μs	1)

¹⁾ Parameter not subject of production test. Specified by design.

Data Sheet 18 Rev. 1.0, 2009-06-15



Reset and Enable Inputs




Figure 8 Timing



7 Power Outputs

7.1 Description Power Outputs

The TLE8110EE is a 10 channel low-side powertrain switch. The power stages are built by N-channel power MOSFET transistors. The device is a universal multichannel switch but mostly suited for the use in Engine Management Systems [EMS]. Within an EMS, the best fit of the channels to the typical loads is:

- Channel 1 to 4 for Injector valves or mid-sized solenoids with a nominal current requirement of 1.5A.
- · Channel 5 to 6 for mid-sized solenoids or Injector valves with a nominal current requirement of 1.7A
- Channel 7 to 10 for small solenoids or relays with a nominal current requirement of 0.75A

Channel 1 to 10 provide enhanced clamping capabilities of typically 55V best suited for inductive loads such as injector valves. It is recommended in case of an inductive load, to connect an external free wheeling- or clamping diode, where-ever possible to reduce power dissipation.

All channels can be connected in parallel. Channels 1 to 4, 5 to 6 and 7 to 10 are prepared by matching for parallel connection with the possibility to use a high portion of the capability of each single channel also in parallel mode (refer to **Chapter 7.4**).

Channel 5 and 6 have a higher current shut down threshold to allow to connect in parallel mode a load with a high inrush-current, such as a lambda sensor heater.




Figure 9 Block Diagram of Control and Power Outputs



7.2 Description of the Clamping Structure

When switching off inductive loads, the potential at pin OUT rises to $V_{DS(CL)}$ potential, because the inductance intends to continue driving the current. The voltage clamping is necessary to prevent destruction of the device, see **Figure 10** for the principle clamping circuit. Nevertheless, the maximum allowed load inductance is limited.




Figure 10 Principle Clamping Structure

Maximum Load Inductance

During demagnetization of inductive loads, energy has to be dissipated in the device. This energy can be calculated with following equation:

$$E = V_{\text{DS(CL)}} \cdot \left[\frac{V_{\text{batt}} - V_{\text{DScl}}}{R_{\text{L}}} \cdot \ln \left(1 - \frac{R_{\text{L}} \cdot I_{\text{L}}}{V_{\text{batt}} - V_{\text{DScl}}} \right) + I_{\text{L}} \right] \cdot \frac{L}{R_{\text{L}}}$$
(1)

Following equation simplifies under the assumption of R_L = 0:

$$E = \frac{1}{2}LI_{L}^{2} \cdot \frac{V_{DScl}}{V_{DScl} - V_{Batt}}$$
 (2)

The maximum energy, which is converted into heat, is limited by the thermal design of the component.

The Repetitive Clamping Energies E_{AR} as defined in the following **Chapter 7.3**, **Item 7.3.4** (and following items) are representing cummulated operating scenarios for one channel group with:

- normal operating condition with a typical battery voltage of V_{Batt} = 16V and an ambient temperature of typically T_a = 125°C.
- cold operation with a typical battery voltage of typically V_{Batt} = 13.5V and an ambient temperature of typically T_a = -40°C.
- generator defect with a typical battery voltage of $V_{Batt} = 18V$ and an ambient temperature of typically $T_a = 135$ °C.

The Power Dissipation P_v is typically considered with P_v = 3W during normal operation. This power dissipation changes during the other operating conditions according the thermal behaviour of R_{DSon} and the load Resistance $R_{L.}$ The interaction of both, together with an assumed typical R_{thja} = 7.5K/W, the given average junction temperature T_i is considered as the start temperature for the clamping process.

Due to the fact, that the maximum possible Repetitive Clamping Energy $E_{\rm AR}$ varies with the Load Current $I_{\rm D}$, partially optional operating points are specified within the scenarios. Those optional operating points are not considered as cummulative clamping pulses to the scenario.

Data Sheet 21 Rev. 1.0, 2009-06-15



7.3 Electrical Characteristics Power Outputs

Electrical Characteristics: Diagnostics

Pos.	Parameter	Symbol		Limit Val	ues	Unit	Conditions
			Min.	Тур.	Max.		
Output	Channel Resistance					-	
7.3.1	On State Resistance CH1 to 4	R_{DSon}	-	0.3	-	Ohm	I_{Dnom} =1,5A; Tj=25°C ¹⁾
			-	0.45	0.6	Ohm	I _{Dnom} =1,5A; Tj=150°C
7.3.2	On State Resistance CH 5 to 6	R_{DSon}	-	0.25	-	Ohm	I_{Dnom} =1.7A; Tj=25°C ¹⁾
			-	0.35	0.5	Ohm	I _{Dnom} =1.7A; Tj=150°C
7.3.3	On State Resistance CH7 to 10	R_{DSon}	-	0.6	-	Ohm	I_{Dnom} =0.75A; Tj=25°C ¹⁾
			-	0.85	1.2	Ohm	I _{Dnom} =0.75A; Tj=150°C
Clamp	ing Energy			<u> </u>			
Chann	el 1-4						
7.3.4	Maximum Energy Dissipation per Channel. Repetitive Pulses. Operating Mode 600Mio. pulses over life time. Or Item 7.3.5	E_{AR}	-	-	15	mJ	I _D = 1.25A Tj=145°C
7.3.5	Maximum Energy Dissipation per Channel. Repetitive Pulses. Operating Mode 600Mio. pulses over life time.	E_{AR}	-	-	21	mJ	I _D = 0.87A Tj=145°C
7.3.6	Maximum Energy Dissipation per Channel. Repetitive Pulses. Cold Operation: 0.5Mio. pulses over life time cumulated. Or Item 7.3.7	E_{AR}	-	-	25	mJ	I _D = 1.73A Tj=-20°C
7.3.7	Maximum Energy Dissipation per Channel. Repetitive Pulses. Cold Operation 3Mio. pulses over life time cumulated.	E_{AR}	-	-	20	mJ	I _D = 0.87A Tj=-20°C
7.3.8	Maximum Energy Dissipation per Channel. Repetitive Pulses. Generator Defect 300k pulses over life time cumulated. Or Item 7.3.9	E_{AR}	-	-	18	mJ	I _D =1.45A Tj=150°C



Electrical Characteristics: Diagnostics (cont'd)

Pos.	Parameter	Symbol		Limit Val	ues	Unit	Conditions
			Min.	Typ.	Max.		
7.3.9	Maximum Energy Dissipation per Channel. Repetitive Pulses. Generator Defect 300k pulses over life time cumulated.	E_{AR}	-	-	27	mJ	I _D = 0.98A Tj=150°C
7.3.10	Maximum Energy Dissipation per Channel. Repetitive Pulses. Jump Start 20k pulses over life time cumulated, max 1 min per cycle. Or Item 7.3.11	E_{AR}	-	-	33	mJ	I _D = 1.82A Tj=95°C
7.3.11	Maximum Energy Dissipation per Channel. Repetitive Pulses. Jump Start 20k pulses over life time cumulated, max 1 min per cycle.	E_{AR}	-	-	50	mJ	I _D = 1.23A Tj=95°C
Channe	el 5-6						
7.3.12	Maximum Energy Dissipation per Channel. Repetitive Pulses. Operating Mode 600Mio. pulses over life time.	E_{AR}	-	-	24	mJ	I _D = 1.7A Tj=145°C
7.3.13	Maximum Energy Dissipation per Channel. Repetitive Pulses. Cold Operation 3Mio. pulses over life time cumulated.	E_{AR}	-	-	23	mJ	I _D = 1.72A Tj= -20°C
7.3.14	Maximum Energy Dissipation per Channel. Repetitive Pulses. Generator Defect 300k pulses over life time cumulated.	E_{AR}	-	-	31	mJ	IDS = 1.92A Tj=150°C
7.3.15	Maximum Energy Dissipation per Channel. Repetitive Pulses. Jump Start 20k pulses over life time cumulated, max 1 min per cycle.	E_{AR}	-	-	59	mJ	I _D = 2.43A Tj = 95°C



Electrical Characteristics: Diagnostics (cont'd)

Pos.	Parameter	Symbol	Limit Values			Unit	Conditions
			Min.	Тур.	Max.		
Channe	7-10	!		- !			
7.3.16	Maximum Energy Dissipation per Channel. Repetitive Pulses. Operating Mode 600Mio. pulses over life time.	E_{AR}	-	-	13	mJ	I _D = 0.49A Tj =145°C
7.3.17	Maximum Energy Dissipation per Channel. Repetitive Pulses. Cold Operation 0.5Mio pulses over life time cumulated. Or Item 7.3.18	E_{AR}	-	-	15	mJ	I _D = 0,54A Tj = -20°C
7.3.18	Maximum Energy Dissipation per Channel. Repetitive Pulses. Cold Operation 3Mio. pulses over life time cumulated.	E_{AR}	-	-	12	mJ	I _D = 0.49A Tj = -20°C
7.3.19	Maximum Energy Dissipation per Channel. Repetitive Pulses. Generator Defect 300k pulses over life time cumulated.	E_{AR}	-	-	17	mJ	I _D = 0.55A Tj = 150°C
7.3.20	Maximum Energy Dissipation per Channel. Repetitive Pulses. Jump Start 20k pulses over life time cumulated, max 1 min per cycle.	E_{AR}	-	-	31		I _D = 0.69A Tj = 95°C
Leakag	e Current		•			•	
7.3.21	Output Leakage Current in standby mode, Channel 1 to 4	I_{Doff}	-	-	3	μA	V_{DS} =13.5V; V_{DD} =5V, Tj=85°C ¹⁾
			-	-	8	μA	V _{DS} =13.5V; V _{DD} =5V, Tj=150°C
7.3.22	Output Leakage Current in standby mode, Channel 5 to 6	I_{Doff}	-	-	6	μА	V_{DS} =13.5V; V_{DD} =5V, Tj=85°C ¹⁾
			-	-	12	μA	V _{DS} =13.5V; V _{DD} =5V, Tj=150°C



Electrical Characteristics: Diagnostics (cont'd)

Pos.	Parameter	Symbol		Limit Val	ues	Unit	Conditions
			Min.	Тур.	Max.		
7.3.23	Output Leakage Current in standby mode, Channel 7 to 10	I_{Doff}	-	-	2	μΑ	V _{DS} =13.5V; V _{DD} =5V, Tj=85°C ¹⁾
			-	-	5	μΑ	V _{DS} =13.5V; V _{DD} =5V, Tj=150°C
Clampi	ng Voltage						
7.3.24	Output Clamping Voltage, Channel 1 to 10	V_{DScl}	45	55	60	V	
Timing							
7.3.25	Output Switching Frequency	f_{OUTx}	-	-	20	kHz	resistive load duty cyle > 25%.
7.3.26	Turn-on Time	t _{dON}	-	5	10	μs	V_{DS} =20% of V_{batt} V_{batt} = 13.5V, I_{DS1} to I_{DS6} = 1A, I_{DS7} to I_{DS10} = 0.5A, resistive load
7.3.27	Turn-off Time	t _{dOFF}	-	5	10	μs	V_{DS} =80% of V_{batt} V_{batt} = 13.5V, I_{DS1} to I_{DS6} = 1A, I_{DS7} to I_{DS10} = 0.5A resistive load

¹⁾ Parameter is not subject to production test, specified by design.




Figure 11 CH 1-4: typical behaviour of RDS_ON versus the junction temperaure Tj






Figure 12 CH 5-6: typical behaviour of RDS_ON versus the junction temperaure Tj




Figure 13 CH7-10: typical behaviour of RDS_ON versus the junction temperaure Tj






Figure 14 All Channels: typical behaviour of the clamping voltage versus the junction temperature




Figure 15 Timing of Output Channel switching (resistive load)

7.4 Parallel Connection of the Power Stages

The TLE8110EE is equipped with a structure which improves the capability of parallel-connected channels. The device can be "informed" via the PMx.PMx - bits (see chapter control of the device) which of the channels are connected in parallel. The input channels can be mapped to the parallel connected output channels in order to apply the PWM signals. This feature allows a flexible adaptation to different load situations within the same hardware setup.

In case of overload the ground current and the power dissipation is increasing. The application has to take into account that all maximum ratings are observed (e.g. operating temperature $T_{\rm J}$ and total ground current $I_{\rm GND}$, see Maximum Ratings). In case of parallel connection of channels with or w/o PM-bit set, the maximum clamping energy defined by the derating factor must not be exceeded.

All stages are switched on and off simultaneously. The μ C has to ensure that the stages which are connected in parallel have always the same state (on or off). The PM-bit should be set according to the parallel connected power stages in order to achieve the best possible de-rating factors.



The performance during parallel connection of channels is specified by design and not subject to the production test. The given factors are maximum values.

All channels at the same junction temperature level.

I_FACTOR

The maximum operating current I_{DSD,OUTxy(sum)} is the minimum "Current Shut-down Threshold Low" I_{DSD,(low),n(min)}.

• $I_{DSD,OUTxy(sum)} = I_FACTOR * SUM[I_{DSD(low),n(min)}]$ with $I_FACTOR = 1$.

The typical maximum operating current I_{DSD,OUTxy(sum)} is the "Current Shut-down Threshold Typ" I_{DSD(typ),n(min)}.

• $I_{D,OUTxy(sum)} = I_FACTOR * SUM[I_{D(typ),n}]$

E_FACTOR

The Maximum Clamping Energy $E_{\mathsf{ARxy}(\mathsf{sum})}$ of parallel connected channels is defined as follows:

• $E_{AR,xy(sum)} = E_FACTOR * SUM[E_{AR},n]$ at Tj = 150°C and $I_D = I_{Dnom}$

ON-Resistance

The typical ON-Resistance $R_{\mathrm{DSon,xy(sum)}}$ of parallel connected channels is sum of the typical RDSon $R_{\mathrm{DSon,n(typ)}}$ defined as follows

• $R_{\text{DSon,xy(sum)}} = 1/[1/R_{\text{DSon,n(typ)}} + 1/R_{\text{DSon,n+1(typ)}}]$

	Derating Factors ¹⁾	²⁾ in case of Parallel C	onnection of Chann	els: related PM-Bit	set
-	Channel Group	Parameter	2 CH parallel	3 CH parallel	4 CH parallel
7.4.1	CH 1-4	typical shut down current before reaching I _{DSD(typ),n} I _{D,OUTxy(sum)}	I_FACTOR = 0.95	I_FACTOR = 0.90	I_FACTOR = 0.85
7.4.2		Maximum Clamping Energy E _{ARxy(sum)}	E_FACTOR = 0.8	E_FACTOR = 0.7	E_FACTOR = 0.6
7.4.3		typical ON- Resistance $R_{\mathrm{DSon,xy(sum)}}$	$R_{\mathrm{DSon,xy(sum)}}$	$R_{DSon,xy(sum)}$	$R_{DSon,xy(sum)}$
7.4.4	CH 5-6	typical shut down current before reaching I _{DSD(typ),n} I _{D,OUTxy(sum)}	I_FACTOR = 0.95	-	-
7.4.5		Maximum Clamping Energy E _{ARxy(sum)}	E_FACTOR = 0.8	-	-
7.4.6		typical ON-Resistance $R_{\mathrm{DSon,xy(sum)}}$	$R_{\mathrm{DSon,xy(sum)}}$	-	-

Data Sheet 28 Rev. 1.0, 2009-06-15



-	Derating Factors ¹⁾	2) in case of Parallel C	onnection of Chann	els: related PM-Bit	t set
	Channel Group	Parameter	2 CH parallel	3 CH parallel	4 CH parallel
7.4.7	CH 7-10	typical shut down current before reaching I _{DSD(typ),n}	I_FACTOR = 0.95	I_FACTOR = 0.90	I_FACTOR = 0.85
7.4.8		I _{D,OUTxy(sum)} Maximum Clamping Energy E _{ARxy(sum)}	E_FACTOR = 0.8	E_FACTOR 0.7	E_FACTOR 0.6
7.4.9		typical ON- Resistance R _{DSon,xy(sum)}	$R_{DSon,xy(sum)}$	$R_{DSon,xy(sum)}$	$R_{DSon,xy(sum)}$

¹⁾ The performance during parallel connection of channels is specified by design and not subject to the production test.

²⁾ All channels at the same junction temperature level.

	Derating Factors ¹	²⁾ in case of Parallel C	Connection of Chan	nels: related PM-	Bit not set
	Channel Group	Parameter	2 CH parallel	3 CH parallel	4 CH parallel
7.4.10	CH 1-4	typical shut down current before reaching I _{DSD(typ),n} I _{D,OUTxy(sum)}	I_FACTOR = 0.95	I_FACTOR = 0.90	I_FACTOR = 0.85
7.4.11		Maximum Clamping Energy E _{ARxy(sum)}	E_FACTOR = 0.5	E_FACTOR = 0.33	E_FACTOR = 0.25
7.4.12		typical ON- Resistance $R_{\mathrm{DSon,xy(sum)}}$	$R_{\mathrm{DSon,xy(sum)}}$	$R_{DSon,xy(sum)}$	$R_{DSon,xy(sum)}$
7.4.13	CH 5-6	typical shut down current before reaching I _{DSD(typ),n} I _{D,OUTxy(sum)}	I_FACTOR = 0.95	-	-
7.4.14		Maximum Clamping Energy E _{ARxy(sum)}	E_FACTOR = 0.5	-	-
7.4.15		typical ON- Resistance $R_{DSon,xy(sum)}$	$R_{\mathrm{DSon,xy(sum)}}$	-	-

FLEX Smart Multi-Channel Switch

Power Outputs

	Derating Factors ¹	⁾²⁾ in case of Parallel C	Connection of Chan	nels: related PM-	Bit not set
	Channel Group	Parameter	2 CH parallel	3 CH parallel	4 CH parallel
7.4.16	CH 7-10	typical shut down current before reaching I _{DSD(typ),n}	I_FACTOR = 0.95	I_FACTOR = 0.90	I_FACTOR = 0.85
7.4.17	_	I _{D,OUTxy(sum)} Maximum Clamping Energy E _{ARxy(sum)}	E_FACTOR = 0.5	E_FACTOR = 0.33	E_FACTOR = 0.25
7.4.18		typical ON- Resistance $R_{DSon,xy(sum)}$	$R_{DSon,xy(sum)}$	$R_{\mathrm{DSon,xy(sum)}}$	$R_{DSon,xy(sum)}$

¹⁾ The performance during parallel connection of channels is specified by design and not subject to the production test.

²⁾ All channels at the same junction temperature level.



Diagnosis

8 Diagnosis

8.1 Description Diagnosis

The TLE8110EE provides diagnosis information about the device and about the load. Following diagnosis flags have been implemented for each channel:

- The diagnosis information of the protective functions, such as "over current" and "over temperature"
- · The open load diagnosis
- The short to ground information.

Updating the Diagnosis is based on a filter-dependent standard delay time of typ. 150µs. This value is set as a default.

Refer to Figure 16 for details.

Application Hint:

In specific application cases - such as driving Uni-Polar Stepper Motor - it might be possible, that reverse currents flow for a short time, which possibly can disturb the diagnosis circuit at neighboring channels and cause wrong diagnosis results of those channels. To reduce the possibility, that this effect appears in a certain timing range, the filter time of Channels 7 to 10 can be extended to typ. 2.5ms or typ. 5ms by setting the "Diagnosis Blind Time" - Bits (DBTx). If Channels 7 to 10 are used for driving loads causing reverse currents, they influence each other and additionally might affect Channels 5 and 6. It is recommended to use the channels 7 + 8 and 9 + 10 as pairs for anti-parallel control signals, such as for the stepper motors. For logic setting details, see chapter "Control of the Device"




Figure 16 Block Diagram of Diagnosis

Data Sheet 31 Rev. 1.0, 2009-06-15



Diagnosis

8.2 Electrical Characteristics Diagnosis

Electrical Characteristics: OFF State Diagnosis

Pos.	Parameter	Symbol	Limit Values			Unit	Conditions
			Min.	Тур.	Max.		
Open L	oad Diagnosis	1	U		<u> </u>	<u> </u>	
8.2.1	Open load detection threshold voltage	V_{DSol}	2.00	2.60	3.20	V	-
8.2.2	Output pull-down diagnosis current per channel (low level)	I_{Dpd}	50	90	150	μΑ	V _{DS} = 13.5 V
8.2.3	Open Load Diagnosis Delay Time (all channels)	$t_{\sf d}$	100	-	220	μs	DEVS.DBT1=0 DEVS.DBT2=1 or 0
8.2.4 a)	Channel 7-10: Open Load Diagnosis Delay Time	t_{d}	1.65	2.5	3.45	ms	DEVS.DBT1=1 DEVS.DBT2=0
b)	"Diagnosis Blind Time" see chapter "Control of the device"		3.3	5	7.3	ms	DEVS.DBT1=1 DEVS.DBT2=1
Short t	Figure 17, Figure 18 o GND Diagnosis						
8.2.5	Short to ground detection threshold voltage	V_{DSsg}	1.00	1.50	2.00	V	-
8.2.6	Output diagnosis current for short to ground per channel (low level)	I_{Dsg}	-150	-100	-50	μΑ	$V_{\rm DS} = 0 \text{V}$
8.2.7	Short to GND Diagnosis Delay Time	$t_{\sf d}$	100	-	220	μs	DEVS.DBT1=0 DEVS.DBT2=1 or 0
8.2.8 a)	Channel 7-10: Short to GND Diagnosis Delay	t_{d}	1.65	2.5	3.45	ms	DEVS.DBT1=1 DEVS.DBT2=0
b)	Time. "Diagnosis Blind Time" see chapter "Control of the device", Figure 17, Figure 18		3.3	5	7.3	ms	DEVS.DBT1=1 DEVS.DBT2=1



Diagnosis




Figure 17 Diagnosis Blind Time




Figure 18 Diagnosis Blind Time - Logic Flow



Parallel Inputs

9 Parallel Inputs

9.1 Description Parallel Inputs

There are 10 input pins available are on TLE8110EE to control the output stages.

Each input signal controls the output stages of its assigned channel. For example, IN1 controls OUT1, IN2 controls OUT2, etc.

A "Low"-Signal at INx switches the related Output Channel off. The zener diode protects the input circuit against ESD pulses.

For details about the Boolean operation, refer to the chapter "Control of the device", for details about timing refer to Figure 11.

9.2 Electrical Characteristics Parallel Inputs

Electrical Characteristics: Diagnostics

 $3V < V_{CC} < 5.5V$; $4.5V < V_{DD} < 5.5V$; $V_{batt} = 13.5V$, $T_{j} = -40 \, ^{\circ}\text{C}$ to +150 $^{\circ}\text{C}$, all voltages with respect to ground, positive current flowing into pin (unless otherwise specified)

Pos.	Parameter	Symbol		Limit Val	ues	Unit	Conditions
			Min.	Тур.	Max.		
Paralle	I Inputs	<u> </u>				<u> </u>	'
9.2.1	Low Level of parallel Input pin	V_{INxI}	-0.3	-	V _{CC} * 0.2	V	-
9.2.2	High Level of Parallel Input pin	V_{INxh}	V _{CC} * 0.4	-	V _{CC}	V	-
9.2.3	Parallel Input Pin Switching Hysteresis	V_{INxhy}	15	60	300	mV	1)
9.2.4 a)	Input Pin pull-down Current	I_{INxh}	20	40	85	μΑ	V _{INx} =5V
b)		I_{INxI}	2.4	-	-	μΑ	V _{INx} =0.6V ¹⁾

¹⁾ Parameter not subject to production test. Specified by design.

Data Sheet 34 Rev. 1.0, 2009-06-15



Protection Functions

10 Protection Functions

The device provides embedded protective functions. Integrated protection functions are designed to prevent IC destruction under fault conditions described in this Document. Fault conditions are considered "outside" the normal operating range. Protection functions are not designed for continuous repetitive operation.

There is an over load and over temperature protection implemented in the TLE8110EE.

If a protection function becomes active during the write cycle of Diagnosis Information into the Diagnosis Register, the information is latched and stored into the diagnosis register after the write process.

In order to achieve a maximum protection, the affected channel with over current or over temperature is switched off. The device can be configured via serial communication interface in three ways in order to react on this fault condition:

- after switching off, turning on again after a delay time: In case of over temperature, when the temperature has
 decreased below the temperature shut down threshold. In case of over-current, the affected channel is turning
 on after a delay time until the over temperature protection is activated.
- after switching off, turning on again the affected channel with the next parallel or serial control command.
- Default Setting: after switching off latching the condition and remain off until the Diagnosis Register is cleared via serial control. In this case, the internal Diagnosis Bits for Over Temperature and Over Current are cleared with the rising edge of S_CS

For the failure condition of Reverse Currents, the device contains a "Reverse Current Protection Comparator" [RCP]. This RCP can optionally be activated by setting the DEVS.RCP Bit.

In case the comparator is activated, it detects a reverse current and switches ON the related output channel. The channel is kept ON up to a reverse current channel dependent threshold $I_{\rm RCP_off}$. This threshold is defined by regulators target value to keep the output voltage at $>/\sim$ -0.3V. If the current exceeds a defined value, the comparator switches OFF and other protection functions are protecting the circuit against reverse current. That means that at higher currents / or in case RCP is de-activated / not activated, the reverse current is flowing through the body diode of the DMOS. In that case, the voltage drops to typically -0.6V according the voltage of the body diode. In case the comparator threshold has been exceeded and the RCP has been switched OFF, the functions remains OFF until the reverse current arrives back to zero reverse current. Only then, the comparator can be activated again after a delay time $t_{\rm RCP\ on\ delay}$.

This function reduces the un-wanted influence of a reverse current to the analogue part of the circuit (such as the diagnosis). For more details about the functionality, see **Figure 21** and **Figure 22** and concerning the settings and the related registers, refer to Chapter "Control of the Device".

Figure 19 gives an overview about the protective functions.




Figure 19 Block Diagram Protection Functions

Data Sheet 35 Rev. 1.0, 2009-06-15



Protection Functions

10.1 Electrical Characteristics Overload Protection Function

Electrical Characteristics: Overload Protection Function

Pos.	Parameter	Symbol	Limit Values			Unit	Conditions
			Min.	Тур.	Max.		
Over Cu	irrent Protection		U		<u> </u>		
10.1.1	Output Current Shut-down Threshold Low (Channel 1 to 4)	$I_{\mathrm{DSD(low)}}$	2.6	3.8	5	А	-
10.1.2	Output Current Shut-down Threshold Low (Channel 5 to 6)	$I_{\mathrm{DSD(low)}}$	3.70	4.85	6.00	А	-
10.1.3	Output Current Shut-down Threshold Low (Channel 7 to 10)	$I_{\mathrm{DSD(low)}}$	1.7	2.3	2.9	А	-
10.1.4	Output Current Shut-down Threshold High (Channel 1 to 4)	$I_{\mathrm{DSD(high)}}$	-	1.5 * I _{DSD} (low)	-	A	1)
10.1.5	Output Current Shut-down Threshold High (Channel 5 to 6)	$I_{\mathrm{DSD(high)}}$	-	1.5 * I _{DSD}	-	A	1)
10.1.6	Output Current Shut-down Threshold High (Channel 7 to 10)	$I_{\mathrm{DSD(high)}}$	-	1.5 * I _{DSD} (low)	-	A	1)
10.1.7	Short Overload shutdown Delay Time (all Channels)	t _{OFFcl_h}	5	21	40	μs	valid for "Output Current Threshold High" ¹⁾
10.1.8	Long Overload shutdown Delay Time (all Channels)	t _{OFFcl_I}	10	40	70	μs	valid for "Output Current Threshold Low"
10.1.9	Automatic Restart Delay Time ²⁾ in case of over current	t_{aONd}	70	-	200	μs	1)
Over Te	mperature Protection						
10.1.10	Thermal Shut Down Temperature	T_{jSD}	175	190	205	°C	1)
10.1.11	Thermal Shut Down Hysteresis	T_{jSDh}	10	-	20	K	1)
10.1.12	Automatic Restart Delay Time ²⁾ in case of over temperature	t_{aONd}	70	-	200	μs	1)



Electrical Characteristics: Overload Protection Function (cont'd)

 $3V < V_{CC} < 5.5V$; $4.5V < V_{DD} < 5.5V$; $V_{batt} = 13.5V$, $T_{j} = -40$ °C to +150 °C, all voltages with respect to ground, positive current flowing into pin (unless otherwise specified)

Pos.	Parameter	Symbol		Limit Val	ues	Unit	Conditions	
			Min.	Тур.	Max.			
Revers	e Current Protection	+	+	-	+			
10.1.13	Reverse Current Comparator Switch-off Current level CH 1 - 4	I_{RCP_off}	-	-0.9	-	А	DEVS.RCP = 1 ¹⁾ Tj = 25°C	
10.1.14	Reverse Current Comparator Switch-off Current level CH 5 - 6	I_{RCP_off}	-	-0.6	-	А	DEVS.RCP = 1^1 Tj = 25° C	
10.1.15	Reverse Current Comparator Switch-off Current level CH 7 - 10	I_{RCP_off}	-	-0.45	-	А	DEVS.RCP = 1^1 Tj = 25° C	
10.1.16	Reverse Current Comparator switch on delay time	$t_{ m RCP_on_}$	-	24	-	μs	DEVS.RCP = 1 ¹ Tj = 25°C	

¹⁾ Parameter not subject to production test. Specified by design.

Data Sheet 37 Rev. 1.0, 2009-06-15

²⁾ Only active when LOTCx[1:0] = 10 and as long as no overload or overtemperature condition present. In case the channel is switched off the delay time is cleared. The application must avoid to exceed the I_{DSD}- and maximum ratings specification. Otherwise a damage or reduction of the lifetime can be expected.






Figure 20 Timing (CLn: Over Current Latch; OT: Over Temperature Flag; x_CS: Chip-Select)






Figure 21 Reverse Current Protection Comparator






Figure 22 Reverse Current Protection Comparator (typical behaviour vs junction temperature)



16 bit SPI Interface

11 16 bit SPI Interface

11.1 Description 16 bit SPI Interface

The diagnosis and control interface is based on a serial peripheral interface (SPI).

The SPI is a full duplex synchronous serial slave interface, which uses four lines: S_SO , S_SI , S_CLK and $\overline{S_CS}$. Data is transferred by the lines S_SI and S_SO at the data rate given by S_CLK . The falling edge of $\overline{S_CS}$ indicates the beginning of a data access. Data is sampled in on line S_SI at the falling edge of S_CLK and shifted out on line S_I at the rising edge of S_I . A modulo 8 counter ensures that data is taken only, when a multiple of 8 bit has been transferred. If in one transfer cycle not a multiple of 8 bits have been counted, the data frame is ignored. The interface provides daisy chain capability.




Figure 23 16 bit SPI Interface

The SPI protocol is described in Chapter "Control of the device". Concerning Reset of the SPI, please refer to the chapter "Reset"

11.2 Timing Diagrams




Figure 24 Data Transfer in Daisy Chain Configuration

Data Sheet 41 Rev. 1.0, 2009-06-15



16 bit SPI Interface

11.3 Electrical Characteristics 16 bit SPI Interface

Electrical Characteristics: Diagnostics

 $3V < V_{\rm CC} < 5.5V$; $4.5V < V_{\rm DD} < 5.5V$; $V_{\rm batt} = 13.5V$, $T_{\rm j} = -40$ °C to +150 °C, all voltages with respect to ground, positive current flowing into pin (unless otherwise specified)

Pos.	Parameter	Symbol	L	imit Val	ues	Unit	Conditions	
			Min. Typ.		Max.			
Input Ch	naracteristics (CS, SCLK, SI)		1				1	
11.3.1	L level of pin S_C S_CI S_		-0.3	_	V _{CC} * 0.2	V	-	
11.3.2	H level of pin S_C S_CI S_	$V_{\text{S_CSh}}$	V _{CC} * 0.4	-	V _{cc}	V	-	
11.3.3	Hysteresis Input Pins	$V_{\text{S_CShy}} \\ V_{\text{S_CLKhy}} \\ V_{\text{S_SIhy}}$	20	100	300	mV	-	
11.3.4 a)	Input Pin pull-down Current	$I_{\mathrm{S_CLKh}}$ $I_{\mathrm{S_Slh}}$	20	40	85	μΑ	V _{IN} =5V	
b)	S_CI S_	$K I_{S,CLKL}$	2.4	-	-	μΑ	V _{IN} =0.6V ¹⁾	
11.3.5 a)	Input Pin pull-up Current	$I_{\mathrm{S_CSh}}$	-4	-	-	μА	$V_{\text{S_CS}} = 2 \text{ V}, \\ V_{\text{CC}} = 3.3 \text{ V}$	
b)	<u>\$_0</u>	$\overline{I_{\text{S_CSI}}}$	-20	-40	-85	μА	$V_{\text{S_CS}} = 0 \text{ V},$ $V_{\text{CC}} = 5 \text{V}$	
Output 0	Characteristics (SO)							
11.3.6	L level output voltage	$V_{\mathrm{S_SOI}}$	0	-	0.4	V	$I_{\rm S_SO}$ = -2 mA	
11.3.7	H level output voltage	$V_{\mathrm{S_SOh}}$	V _{cc} - 0.4 V	-	V_{cc}		$I_{\rm S_SO}$ = 1.5 mA	
11.3.8	Output tristate leakage current	$I_{\mathrm{S_SOoff}}$	-10	-	10	μΑ	$V_{\rm S_SO} = V_{\rm cc}$	
Timings								
11.3.9	Serial clock frequency	$f_{ t S_CLK}$	0	-	5	MHz	$-C_{L}$ = 50 pF ¹⁾	
11.3.10	Serial clock period	$t_{\text{S_CLK(P)}}$	200	-	-	ns	1)	
11.3.11	Serial clock high time	$t_{\rm SCLK(H)}$	50	-	-	ns	1)	
11.3.12	Serial clock low time	$t_{SCLK(L)}$	50	-	-	ns	1)	
11.3.13	Enable lead time (falling $\overline{\text{CS}}$ to rising SCLK)	$t_{\mathrm{CS(lead)}}$	250	-	-	ns	1)	
11.3.14	Enable lag time (falling SCLK to rising CS)	g $t_{\rm CS(lag)}$	250	-	-	ns	1)	
11.3.15	$\frac{\text{Transfer delay time (rising }\overline{\text{CS}}\text{ to falling}}{\overline{\text{CS}}}$	$t_{\rm CS(td)}$	250	-	-	ns	1)	
11.3.16	Data setup time (required time SI to falling SCLK)	$t_{\rm SI(su)}$	20	-	-	ns	1)	
11.3.17	Data hold time (falling SCLK to SI)	$t_{\rm SI(h)}$	20	-	-	ns	1)	
11.3.18	Output enable time (falling CS to SO valid)		-	-	200	ns	$C_{\rm L}$ = 50 pF ¹⁾	



16 bit SPI Interface

Electrical Characteristics: Diagnostics (cont'd)

 $3V < V_{CC} < 5.5V$; $4.5V < V_{DD} < 5.5V$; $V_{batt} = 13.5V$, $T_{j} = -40$ °C to +150 °C, all voltages with respect to ground, positive current flowing into pin (unless otherwise specified)

Pos.	Parameter	Symbol	L	imit Valı	ues	Unit	Conditions		
			Min.	Тур.	Max.				
11.3.19	Output disable time (rising $\overline{\text{CS}}$ to SO tristate)	$t_{\rm SO(dis)}$	-	-	200	ns	$C_{\rm L}$ = 50 pF ¹⁾		
11.3.20	Output data valid time with capacitive load	$t_{\rm SO(v)}$	-	-	100	ns	$C_{\rm L}$ = 50 pF ¹⁾		

¹⁾ Not subject to production test, specified by design.

Data Sheet 43 Rev. 1.0, 2009-06-15



12 Control of the device

This chapter describes the SPI-Interface signals, the protocol, registers and commands. Reading this chapter allows the Software Engineer to control the device. The chapter contains also some information about communication safety features of the protocol.

12.1 Internal Clock

The device contains an internal clock oscillator.

Electrical Characteristics: Diagnostics

 $3V < V_{CC} < 5.5V$; $4.5V < V_{DD} < 5.5V$; $V_{batt} = 13.5V$, $T_{j} = -40 \, ^{\circ}\text{C}$ to +150 $^{\circ}\text{C}$, all voltages with respect to ground, positive current flowing into pin (unless otherwise specified)

Pos.	Parameter	Symbol	I	_imit Val	ues	Unit	Conditions		
			Min.	Тур.	Max.				
Paralle	I Inputs						•		
12.1.1	internal clock oscillator frequency	f_{int_osc}	-	500	-	kHz	1)		

¹⁾ Parameter not subject to production test. Specified by design.

12.2 SPI Interface. Signals and Protocol

12.2.1 Description 16 bit SPI Interface Signals

S_CS - Chip Select:

The system micro controller selects the TLE8110EE by means of the $\overline{S_CS}$ pin. Whenever the pin is in low state, data transfer can take place. When $\overline{S_CS}$ is in high state, any signals at the S_CLK and S_SI pins are ignored and S_SI pins are ignored and S_SI pins are ignored and S_SI pins are ignored.

S_CS High to Low transition: —

- The information to be transferred loaded into the shift register (16-bit Protocol).
- S_SO changes from high impedance state to high or low state depending on the logic OR combination between the transmission or error flag [TOR] (see Chapter 12.2.4.3) and the signal level at pin S_SI. As a result, even in daisy chain configuration, a high signal indicates a faulty transmission or an existing error on one of the Output Channels. The transmission error flag is set after RST, so a reset between two SPI commands is indicated.

S CS Low to High transition:

 Command decoding is only done, when after the falling edge of CS exactly a multiple (1, 2, 3, ...) of eight S CLK signals have been detected. (See Modulo-8 Counter: Chapter 12.2.4.2)

Data Sheet 44 Rev. 1.0, 2009-06-15



S_CLK - Serial Clock:

This input pin clocks the internal shift register. The serial input (S_SI) transfers data is shifted into the register on the falling edge of S_CLK while the serial output (S_SO) shifts the information out on the rising edge of the serial clock. It is essential that the S_CLK pin is in low state whenever chip select CS makes any transition.

S_SI - Serial Input:

Serial input data bits are shifted in at this pin, the most significant bit first. The bit at the S_SI Pin is read on the falling edge of S_CLK.

S_SO Serial Output:

Data is shifted out serially at this pin, the most significant bit first. S_SO is in high impedance state until the $\overline{S_SO}$ pin goes to low state. The next bits will appear at the S_SO pin following the rising edge of S_CLK .

12.2.2 Daisy Chain Capability

The SPI-Interface of TLE8110EE provides daisy chain capability. In this configuration several devices are activated by the same $\overline{S_CS}$ signal. The S_SI line of one device is connected with the S_SO line of another device (see Figure 25), which builds a chain. The ends of the chain are connected with the output and input of the master device, S_SO and S_SI respectively. The master device provides the master clock CLK, which is connected to the S_CLK line of each device in the chain. By each clock edge on S_CLK , one bit is shifted into the S_SI . The bit shifted out can be seen at SO. After 16 S_CLK cycles, the data transfer for one device has been finished. In single chip configuration, the $\overline{S_CS}$ line must go high to make the device accept the transferred data. In daisy chain configuration the data shifted out at device 1 has been shifted in to device 2. Example: When using three devices in daisy chain, three times 16 bits have to be shifted through the devices. After that, the $\overline{S_CS}$ line must go high (see Figure 25).




Figure 25 Principle example for Data Transfer in Daisy Chain Configuration

Note: Due to the integrated modulo 8 counter, 8 bit and 16 bit devices can be used in one daisy chain.

12.2.3 SPI Protocol

The device contains two protocol styles which are applied dependent of the used commands. There is the standard 16-bit protocol and the 2x8-bit protocol. Both protocols can appear also be mixed.

12.2.3.1 16-bit protocol

Each Cycle where a serial data or command frame is sent to the S_SI of the SPI interface, a data frame is returned at the same time by the S_SO The content of the S_SO frame is dependent on the previous command which has been sent to S_SI. Read Command (R/W = R) returns one cycle later the content of the addresses register. (see Figure 26).

Data Sheet 45 Rev. 1.0, 2009-06-15







Figure 26 16-bit protocol

S_SI Serial Input

Reset Value: N.A.



Field	Bits	Description						
W/R	15	 W/R - Write / Read Write register: The register content of the addressed register will be updated after CS low → high transition. After sending a WRITE command, the device returns data according the addressed register Read register: The register content of the addressed register will be sent in the next frame. 						
ADDR	14:12	ADDR - Address Pointer to register for read and write command						
DATA/CMD 11:0 DATA_CMD - Data / Command Data written to or read from register selected b		DATA_CMD - Data / Command Data written to or read from register selected by address ADDR						

S_SO Serial Output

Reset Value: xxxx xxxx xxxx xxxx_B¹⁾

CS	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
TOD	DAD		ADDD					T		D.A.	T A		T	T	T	
TOR	PAR		ADDR							DA [*]	IA					

1) after reset is send a Short Diagnosis and Device Status CMD_CSDS, see Chapter 12.3.1.2.

Field	Bits	Description					
TOR	CS	Transmission or Output Error (see Chapter 12.2.4.2) O Previous transmission was successful, no error, no reset. Previous transmission failed, Error on one of the Output Channels, under voltage reset* or first transmission after reset. * OR operated diagnosis information of all Output Channels. (To read out details perform CMD RSDS, see Chapter 12.3.1.2)					



Field	Bits	Description
PAR	15	PAR - Parity Bit 1: odd number of '1' in data and address field 0: even number of '1' in data and address field
ADDR	14:12	Address Address which has bin addressed
DATA	11:0	Data Content of Address or feedback Data

Note: Reading a register needs two SPI frames. In the first frame the RD command is sent. In the second frame the output at SPI signal SO will contain the requested information. A new command can be executed in the second frame.

12.2.3.2 2x8-bit protocol

Each Cycle where a serial data or command frame is sent to the S_SI of the SPI interface, a data frame is returned at the same time by the S_SO. The content of the S_SO frame is dependent of the previous command which has been sent to S_SI and the content of the actual content of S_SI: The first Upper Byte send to S_SI controls the content of the Lower Byte actual returned by S_SO. The Lower Byte send to S_SI controls the Lower Byte in S_SO of the next frame. (see Figure 27).





Figure 27 2x8-bit protocol

Data Sheet 47 Rev. 1.0, 2009-06-15





Reset Value: N.A.



Field	Bits	Description
Upper Byte	15:8	Upper Byte contains the command, which is performed after sending 8 bit to S_SI. The action out of this command is affecting the Lower Byte of S_SO of the actual communication frame.
Lower Byte	7:0	Lower Byte contains the command and data, which is performed at the end of the actual communication frame. The action out of this command is affection the Upper Byte of S_SO of next communication frame.

S_SO Serial Output

Reset Value: xxxx xxxx xxxx xxxx xxxx_B¹⁾

CS	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0	
TOR				Uppe	r Byte							Low	er Byte				
						i		ů.		i				i.			

1) after reset is send a Short Diagnosis and Device Status CMD_CSDS, see Chapter 12.3.1.2.

Field	Bits	Description						
TOR CS		Transmission or Output Error (see Chapter 12.2.4.2) O Previous transmission was successful, no error, no reset. Previous transmission failed, Error on one of the Output Channels, under voltage reset* or first transmission after reset. * OR operated diagnosis information of all Output Channels. (To read out details perform CMD_SDS, see Chapter 12.3.1)						
Upper Byte	15:8	Upper Byte contains the data according the command and data in the Lower Byte of the previous communication Frame.						
Lower Byte	7:0	Lower Byte contains the data according the command in the Upper Byte of the actual communication frame						

Note: Reading a register needs two SPI frames. In the first frame the RD command is sent. In the second frame the output at SPI signal SO will contain the requested information. A new command can be executed in the second frame.

12.2.3.3 16- and 2x8-bit protocol mixed.

The 16-bit and 2x8-bit protocols are mixed according the used commands (see **Chapter 12.3.1**). Specially care should be taken, changing from the 16-bit protocol to the 2x8-bit protocol. In this case, it is important to send a NOP command to S_SI. Otherwise, by sending instead a Command, a collision between the S_SO data in the following frame and the Lower Byte of the 2x8-bit protocol will happen (see **Chapter 12.2.3.2**).






Figure 28 16-bit protocol

12.2.4 safeCOMMUNICATION

The devise contains some safety features, which are improving the protecting of the application against malfunction in case of disturbance of the communication between the Micro Controller and the Device:

12.2.4.1 Encoding of the commands

The Commands are encoded. In case other bit-patterns, then the defined once are received, the commands are ignored and the communication error is indicated in the TOR-Bit (see Chapter 12.2.4.3) and can be read out in detail with the command CMD_RSDS (seeChapter 12.3.1.2).

12.2.4.2 Modulo-8 Counter

The modulo is the integral remainder in integral division. In data communications, a modulo based approach is used to ensure that user information in SPI protocols is in the correct order. The device has a receiver-side counter, and a defined counter size. The modulo counter specifies the number of subsequent numbers available. In case of TLE8110EE Modulo 8 counter specifies 8 serial numbers. The modulo 8 counter ensures that data is taken only, when a multiple of 8 bit has been transferred. If in one transfer cycle not a multiple of 8 bits have been counted, the data frame is ignored and a Communication Error is indicated in the TOR-Bit (see Chapter 12.2.4.3) and in the CMD RSDS - Feedback (see Chapter 12.3.1.2).



12.2.4.3 TOR - Transmission or Diagnosis Error Bit

As described in Chapter 12.2.3.1 and Chapter 12.2.3.2 the Transmission or Diagnosis Error bit [TOR] appears on S_SO, as soon as CS makes a High-to-LOW transition until the first rising edge of the clock signal. The TOR contains ONLY error information which has appeared in and since last frame. TOR does not contain any latched information.

- Command Ignored and Modulo 8: In the next frame after the error, the TOR bit will be set once.
- Under voltage: After digital- or analogue under voltage, the TOR of the first transmission contains the error
 information. In the following transmissions, the information is not shown anymore. But the under voltage
 information is latched in the CMD_CSDS bit until it is cleared (see Chapter 12.3.1).
- OR operated Diagnosis or protection error information: If one of those errors has appeared since the last frame, the information change is shown in the TOR bit. (The error is latched in the related Diagnosis and Error register and remains there until it is cleared). But the TOR bit will show the information-change only once. In the next frame, the TOR bit is cleared again

The information about the data transmission, TOR contains, is always from the previous transmission. The Diagnosis information, the Bit contains is the status of the diagnosis until the CS high-to-low transition. Changes in the diagnosis during the transmission are latched and stored until the next read-out cycle. By read-out of the TOR-bit, no stored information is cleared. The Error information can be read out in detail, by sending the command CMD_SDS and can be cleared (NOT Diagnosis Error) by the command CMD_CSDS (see Chapter 12.3.1)

In order to reduce the Micro Controller work load, it is possible to read out the TOR bit also without constructively data transfer. That means, by just toggling CS, the status can be read out.

To allow using the TOR Bit also in SPI-Daisy-Chain configuration, the TOR-Bit is OR operated with S_SI which contains the TOR information of the previous device in the Daisy-Chain.

12.3 Register and Command - Overview

This Chapter describes the Registers and Commands. The commands allow to carry through some actions, such as reading out or clearing the diagnosis or reading out the Input Pins.

Specially highlighted here should be the encoded CMD_DMSx/OPSx commands - compactCONTROL -, a highly efficient command-set to set a part of the output pins and read out the diagnosis at the same time. Included in this command set is the possibility to check, if the communication works well as also the possibility to read-out some of the parallel Input Pins INx. Using this compact command set can reduce the workload of the micro-controller during run-time significantly.

CMD_RSD is preformed and short diagnostics [SD] is returned after each Write Cycle to any of the writable registers.

After start-up of the device, the registers are loaded with the default settings as described below in the register $\frac{\text{descriptions}}{\text{RST}}$ or an under-voltage condition appears at the supply pin V_{CC} what causes an under-voltage reset. If a low signal at pin EN is applied or an under-voltage condition appears at pin V_{DD} , the Registers are not cleared.

Data Sheet 50 Rev. 1.0, 2009-06-15



Table 1								
Name	Type	Addr	Short Description	see:				
CMD	W ¹⁾	000 _B	Commands	Chapter 12.3.1				
DCC	W ¹⁾	001 _B	Diagnosis Registers and Compact Control	Chapter 12.3.2				
OUTx	W/R	010 _B	Output Control Register CHx.	Chapter 12.3.3				
DEVS	W/R	011 _B	Device Settings	Chapter 12.3.6				
MSCS	W/R	100 _B	reserved					
ISAx	W/R	101 _B	Input or Serial Mode Register CHx Bank A	Chapter 12.3.4				
ISBx	W/R	110 _B	Input or Serial Mode Register CHx Bank B	Chapter 12.3.4				
PMx	W/R	111 _B	Parallel Mode Control of CHx with CHy	Chapter 12.3.5				

¹⁾ if a read command is send, the command is ignored and S_SO returns a frame with '0'.

Table 2	2														
Registe	er Over	view													
Name		Addr	11	10	9	8	7	6	5	4	3	2	1	0	def.1)
CMD	W ²⁾	000 _B	0	1	1	1		-		Com	mand	-		-	
DCC	W ²⁾	001 _B						Com	mand						
OUTx	W/R	010 _B	1	1	OUT 10	OUT9	OUT8	OUT7	OUT6	OUT5	OUT4	OUT3	OUT2	OUT1	C00h
DEVS	W/R	011 _B	RCP	DBT2	DBT1	LOTC 70 [1]	LOTC 70 [0]	LOTC 16 [1]	LOTC 16 [0]	0	0	DCC 10	DCC9	DCC 18	007h
MSCS	W/R	100 _B		1			1	rese	rved				1		000h
ISAx	W/R	101 _B	15	S6	15	S5	15	64	IS	33	IS	62	15	S1	AAAh
ISBx	W/R	110 _B	0	0	0	0	IS	10	IS	S9	IS	88	15	67	0AAh
PMx	W/R	111 _B	0	0	0	0	PM91 0	PM89	PM78	PM56	0	PM34	PM23	PM12	000h

¹⁾ Default Values after Reset

²⁾ if a read command is send, the command is ignored and S_SO returns a frame with '0'.






Figure 29 Logic Output Control Block Diagram TLE8110EE



12.3.1 CMD - Commands

By using the Address Range CMD[14:12]='000' commands can be send to the device. The Feedback of the commands is provided in the next SPI SO Frame. Details about the Feedback on each command is described in the **Chapter 12.3.1.1**ff.

It is possible to perform per each Communication Frame ONE Command out of Group-A (see following description of the Commands) and ONE Command out of Group-B at the same time. Performing more then one Command of one Group is not possible. For the case, this happens, the commands are ignored.

CMD	
Command Register	Reset Value: N.A.

Overview Commands

S_SI SPI_Serial Input

CMD	11	10	9	8	7	6	5	4	3	2	1	0
RSD	0	1	1	1	0	0	0	0	0	0	0	1
RSDS	0	1	1	1	0	0	0	0	0	0	1	0
RPC	0	1	1	1	0	0	0	0	0	1	0	0
RINx	0	1	1	1	0	0	0	0	1	0	0	0
CSDS	0	1	1	1	0	0	0	1	0	0	0	0
NOP	0	1	1	1	0	0	0	0	0	0	0	0

Field	Command	Туре	Description
	s Group-B (Bitombinations ar		ommand will be ignored then.
NOP	0000	W	NOP - no operation. A frame with '0000h' will be returned
CMD_CSDS	0001	W	CMD_CSDS - Command: Clear Short Diagnosis and Device Status Clear the Device Status information. Performing this Clear Command clears the Information in the Reset and Communication Error Information as long as the incident is not present anymore. If the incident is still present, the related Bits remain setted. Performing this command does NOT clear the Diagnosis Registers. The Diagnosis Information is cleared by the Clear Diagnosis Commands. (see Chapter 12.3.2) SO returns a Frame with '0000h' after performing CMD_CSDS or in case this command is carried out together with a command out of Group-A, the feedback is according the Group-A command

Command Bits Group-A (Bits [3:0])

All other bit combinations are not valid. Command will be ignored then.



Field	Command	Туре	Description
CMD_NOP	0000	W	NOP - no operation. A frame with '0000h' will be returned
CMD_RINx	1000	W	CMD_RINx - Command: Return Input Pin INx -Status (Chapter 12.3.1.4)
CMD_RPC	0100	W	CMD_RPC - Command: Return Pattern Check (Chapter 12.3.1.3)
CMD_RSDS	0010	W	CMD_RSDS - Command: Return Short Diagnosis and Device Status (Chapter 12.3.1.2)
CMD_RSD	0001	W	CMD_RSD - Command: Return Short Diagnosis (Chapter 12.3.1.1)

12.3.1.1 CMD_RSD - Command: Return Short Diagnosis

The Command CMD_RSD offers the possibility to read out the OR-operated "short"-Diagnosis within one SO Feedback Frame. The data to be send is latched at the end of the command frame .




Figure 30 SPI Feedback on CMD_RSD

S_SO SPI_Serial Output

CS	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
TOR	PAR	0	0	0	0	0	SD10	SD9	SD8	SD7	SD6	SD5	SD4	SD3	SD2	SD1

Data Sheet 54 Rev. 1.0, 2009-06-15



Field	Bits	Туре	Description
-	-	-	SD1-10 Short Diagnosis
			0 Normal Operation
			1 Each SD-Bit contains the NAND-operated Diagnosis Error of each
			related Channel. Details can be read in diagnosis registers
			SD is returned after each Write Cycle to any of the writable registers.

12.3.1.2 CMD_RSDS - Command: Return Short Diagnosis and Device Status

The Command CMD_RSD offers the possibility to read out the OR-operated "short"-Diagnosis and the device Status - such as Reset-Information and Communication Error - within one SO Feedback Frame. The data to be send is latched at the end of the command frame .




Figure 31 SPI Feedback on CMD_RSDS



S_SO SPI_Serial Output

_		•														
CS	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
TOR	PAR	0	0	0	0	0	0	0	SDS8	SDS7	SDS6	SDS5	SDS4	SDS3	SDS2	SDS1

Field	Bits	Туре	Description
-	7:0	-	SDS - Short Diagnosis and Device Status
-	0	-	SDS1 - Diagnosis Error in Channel 1 to 6 0 normal operation 1 diagnosis failure
-	1	-	SDS2 - Diagnosis Error in Channel 7 to 10 0 normal operation 1 diagnosis failure
-	2	-	SDS3 - Under Voltage on VCC (Digital Supply Voltage) see Figure 32
-	3	-	SDS4 - Under Voltage on VDD (Analogue Supply Voltage) see Figure 32
-	4	-	SDS5 - Modulo Counter Error 0 normal operation 1 Previous Modulo Counter Error
-	5	-	SDS6 - Previous Communication Error - Encoded Command Ignored 0 normal operation 1 Previous Communication Error - Encoded Command Ignored
-	6	-	SDS7 - not used = '0' always '0'
-	7	-	SDS8 - not used = '0' always '0'






Figure 32 Behaviour of SDS3, 4



12.3.1.3 CMD_RPC - Command: Return Pattern Check

The Command CMD_RPC offers the possibility to get returned the previous Command to check if the communication works well. The data to be send is latched at the end of the command frame .




Figure 33 SPI Feedback on CMD_RPC

S_SO SPI_Serial Output

CS	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
TOR	PAR= 0	0	0	0	0	1	1	1	0	0	0	0	0	1	0	0

Field	Bits	Туре	Description
-	-	-	CMD_RPC is returned

12.3.1.4 CMD RINx - Command: Return Input Pin (INx) -Status

The Command CMD_RINx offers the possibility to read out the actual status of the Input Pins. This command allows to check the correct communication on the INx Pins. The data to be send is latched at the end of the command frame .






Figure 34 SPI Feedback on CMD_RINx

S_SO SPI_Serial Output

CS	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
TOR F	PAR	0	0	0	0	0	IN10	IN9	IN8	IN7	IN6	IN5	IN4	IN3	IN2	IN1

Field	Bits	Type	Description
_	-	-	INx Input Pin Status
			The Status of the INx Pins is read out at the moment of CS High-to-Low
			transition. Details see Figure 35.
			0 INx = Low corresponding OFF
			1 INx = High corresponding ON






Figure 35 Read-out of INx Pins

12.3.2 DCC - Diagnosis Registers and compactCONTROL

The DCC - Diagnosis and Compact Control Set allows to read out and clear the Diagnosis Registers. Additionally this Command set offers the possibility to proceed with a compactCONTROL Mode using DMS - Diagnosis Mode Set and OPS - Output Pin Set Commands. This compactCONTROL Mode offers the possibility to Control the device with lowest work load on the micro controller side.

If any other pattern then the defined commands is received on S_SI, the command is ignored and rated as a Communication Error. In this case, this incident is reported in SDS (Chapter 12.3.1.2) and TOR (Chapter 12.2.4.3).

If an Error in the Output Channels is detected by the diagnosis circuit, the result is latched in the diagnosis registers related to each channel.

The Diagnosis Register is not deleted, when it is just read out. The Diagnosis Register byte can only be cleared by using the appropriated command. In this case, the complete Register Bank is cleared. The separation in two diagnosis register banks allows together with the Device Control Bits "Latch on Over Current or Over Temperature" [LOTC] a separated handling of the channel groups. The groups of Channel 1 to 6 and 7 to 10 can be treated separately in this case. For details, see also chapter **Chapter 12.3.6**.

DCC	
Diagnosis Registers and Compact Control	Reset Value: N.A.



S_SI SPI_Serial Input

DCC	11	10	9	8	7	6	5	4	3	2	1	0
DRA	0	1	0	1	0	0	0	0	0	0	0	0
DRB	0	1	1	0	0	0	0	0	0	0	0	0
DRACL	0	0	0	1	0	0	0	0	0	0	0	0
DRBCL	0	0	1	0	0	0	0	0	0	0	0	0
DMSCL/OPSx	1	0	0	0				OF	Sx			
DMS1/OPSx	1	0	1	1				OF	'Sx			
DMS2/OPSx	1	1	0	1				OF	'Sx			
DMS3/OPSx	1	1	1	0	OPSx							
DMSx/OPS1	1		DMSx		0	0	0	0	0	0	0	1
DMSx/OPS2	1		DMSx		0	0	0	0	0	0	1	0
DMSx/OPS3	1		DMSx		0	0	0	0	0	1	0	0
DMSx/OPS4	1		DMSx		0	0	0	0	1	0	0	0
DMSx/OPS5	1		DMSx		0	0	0	1	0	0	0	0
DMSx/OPS6	1		DMSx		0	0	1	0	0	0	0	0
DMSx/OPS7	1		DMSx		0	1	0	0	0	0	0	0
DMSx/OPS8	1		DMSx		1	0	0	0	0	0	0	0

Field	Bits	Туре	Description
DCC_DRA	11:0	W	DRA - Diagnosis Register A (see Chapter 12.3.2.1) Read out Diagnosis Register A. Return the contents in the next SPI Frame. (see Chapter 12.3.2.2)
DCC_DRB	11:0	W	DRB - Diagnosis Register B (see Chapter 12.3.2.1) Read out Diagnosis Register B. Return the contents in the next SPI Frame. (see Chapter 12.3.2.2)
DCC_ DRACL	11:0	W	DRACL - Diagnosis Register A Clear Clear the contents of the Diagnosis Register A. Return the cleared contents in the next SPI Frame. If the Diagnosis Error Remains, the Information remains.(see Chapter 12.3.2.2)
DCC_ DRBCL	11:0	W	DRBCL - Diagnosis Register B Clear Clear the contents of the Diagnosis Register B. Return the cleared contents in the next SPI Frame. If the Diagnosis Error Remains, the Information remains. (see Chapter 12.3.2.2)
DCC_ DMSCL	11:8	W	DMSCL/OPSx - Diagnosis Mode Set, Clear / Output Pins Set On sending this command, the diagnosis registers DRA, DRB as well as the "virtual" Diagnosis Output Registers DO[7:0] (see Chapter 12.3.2.3) are cleared. Output Pin Settings are done according the content of OPSx. Returns the contents of cleared DR2 on SO in the 2nd byte of the actual communication frame and the Output Pin Feedback in the 1st Byte of the next frame. (see Chapter 12.3.2.3)



Field	Bits	Туре	Description
DCC_ DMS1	11:8	W	DMS1/OPSx - Diagnosis Mode Set, Register1 / Output Pins Set On sending this command, the diagnosis registers DR1 is selected. Output Pin Settings are done according the content of OPSx. Returns the contents of DR1 on SO in the 2nd byte of the actual communication frame and the Output Pin Feedback in the 1st Byte of the next frame. (see Chapter 12.3.2.3)
DCC_ DMS2	11:8	W	DMS2/OPSx - Diagnosis Mode Set, Register2 / Output Pins Set On sending this command, the diagnosis registers DR2 is selected. Output Pin Settings are done according the content of OPSx. Returns the contents of DR2 on SO in the 2nd byte of the actual communication frame and the Output Pin Feedback in the 1st Byte of the next frame. (see Chapter 12.3.2.3)
DCC_ DMS3	11:8	W	DMS3/OPSx - Diagnosis Mode Set, Register3 / Output Pins Set On sending this command, the diagnosis registers DR3 is selected. Output Pin Settings are done according the content of OPSx. Returns the contents of DR3 on SO in the 2nd byte of the actual communication frame and the Output Pin Feedback in the 1st Byte of the next frame. (see Chapter 12.3.2.3)
DCC_ DMSx/OPSx	7:0	W	DMSx/OPS1 - Diagnosis Mode Set x/ Output Pin Set Command 1 On sending this command, the diagnosis register is selected according DMSx. The Output Pins of Channel 7-10 are set according the following definitions. The OPSx are commands, no register. The commands are controlling the contents of ISA, ISB and OUTx. OPS[7:0] - Output Pin Set 0000 0001: CH7 input select, 1: parallel* / 0 : Serial 0000 0010: CH8 input select, 1: parallel* / 0 : Serial 0000 0100: CH9 input select, 1: parallel* / 0 : Serial 0000 1000: CH10 input select, 1: parallel* / 0 : Serial 0001 0000: CH7 output set, 1: ON / 0:OFF 0010 0000: CH8 output set, 1: ON / 0:OFF 0100 0000: CH9 output set, 1: ON / 0:OFF 1000 0000: CH9 output set, 1: ON / 0:OFF (*parallel controlled by INx) Sending OR operated combinations of above listed options (only OPSx) are possible in order to control more then one channel at the same time. If parallel mode Mode is selected (in "input select"), the serial settings (in "output select") are ignored. In parallel Mode, the selected Channels are controlled via INx Pins. The default setting of ISB corresponds the command OPS[7:0] = xxxx 1111b. (parallel mode, status of the Outputs according signal on INx) Returns the contents the selected DRx register on SO in the 2nd byte of the actual communication frame and the Output Pin Feedback [OPF] in the 1st Byte of the next frame. (see Chapter 12.3.2.3)



12.3.2.1 DRx - Diagnosis Registers Contents

DRA[1:0]x Diagnosis	-	-	k A and	Bank B			Res	set Value	: 0000 0	000 0000	_B = 000 _h
11	10	9	8	7	6	5	4	3	2	1	0
DRA[1]6	DRA[0]6	DRA[1]5	DRA[0]5	DRA[1]4	DRA[0]4	DRA[1]3	DRA[0]3	DRA[1]2	DRA[0]2	DRA[1]1	DRA[0]1
11	10	9	8	7	6	5	4	3	2	1	0
0	0	0	0	DRB[1]10	DRB[0]10	DRB[1]9	DRB[0]9	DRB[1]8	DRB[0]8	DRB[1]7	DRB[0]7

Field	Bits	Туре	Description
DRA[1:0]x / DRB[1:0]x	1:0	R	DRA[1:0]x / DRB[1:0]x DRn[1]x/DRn[0]x = 11 no Error DRn[1]x/DRn[0]x = 10 Over Load, Shorted Load, Over temperature in ON-Mode DRn[1]x/DRn[0]x = 01 Open Load in OFF-Mode DRn[1]x/DRn[0]x = 00 Short to GND in OFF-Mode default DRx[1:0] = 11 _B
			A new error on the same channel will overwrite older information. The diagnosis information which is returned by SO is latched when CS makes a High-to-Low transistion of the frame which sends out the register.

12.3.2.2 DRx - Return on DRx Commands




Figure 36 SPI Feedback on x_DRx commands



S_SO SPI_Serial Output

_		•														
CS	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
TOR	PAR	0	0	1	DRx [1]x	DRx [0]x										

Field	Bits	Туре	Description
-	-	-	DRx Contents 0 no Diagnosis Error 1 Diagnosis Error

12.3.2.3 DMSx/OPSx - Diagnosis Mode Set / Output Pin Set Commands

Protocol

Each Cycle where a serial data or command frame is sent to the Serial Input [SI] of the SPI interface, a data frame is returned immediately by the Serial Output [SO]. The content of the SO frame is dependent of the previous command which has been sent to SI and the content of the actual content of SI: The first Byte send by S_SI controls the content of the second byte actual returned by S_SO. The second Byte send by S_SI controls the first byte in S_SO of the next frame. (see Figure 37)




Figure 37 Data Transfer in Diagnosis and Compact Control

S_SI SPI_Serial Input

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
Diagno	sis Mo	de Set	DMS[4:	:0]	I.		Output Pin Set OPS[7:0]								
-								serial r	mode s	elected		paralle	l or ser	ial mod	de
0	0	0	1	-	-	-	-	CH10:	CH9:	CH8:	CH7:	CH10:	CH9:	CH8:	CH7:
								1:ON	1:ON	1:ON	1:ON	0 =	0 =	0 =	0 =
								0:OFF	0:OFF	0:OFF	0:OFF	serial	serial	serial	serial
												1 =	1 =	1 =	1 =
												par.	par.	par.	par.



s_so

SPI_Serial Output

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
Output P	in Set	Feedba	ack OP	F[7:0]				Diagno	sis Ou	tput DC	0[7:0]				

Diagnosis Register

Diagnosis Output Registers DO[7:0]

	7	6	5	4	3	2	1	0
Diag Register-1	DR4[1]	DR4[0]	DR3[1]	DR3[0]	DR2[1]	DR2[0]	DR1[1]	DR1[0]
Diag Register-2	DR1NA	DR3NA	1	1	DR6[1]	DR6[0]	DR5[1]	DR5[0]
Diag Register-3	DR10[1]	DR10[0]	DR9[1]	DR9[0]	DR8[1]	DR8[0]	DR7[1]	DR7[0]

Field	Bits	Туре	Description
DO[7:0]	7:0	R	DO[7:0] - Diagnosis Output Contents according settings of DMS[4:0] Returned within the same frame as the pointer is send. DRx[1:0] definitions: see Chapter 12.3.2.1
DO[7:6] Diag Register-2	7:6	R	DO1NA: NAND-operated diagnosis of Diag Register-1 DO3NA: NAND-operated diagnosis of Diag Register-3 1: at least one diagnosis error is stored in the related Diag Register 0: no diagnosis error is stored in the related Diag Register.

Output Pin Feedback

Output Pin Feedback OPF[7:0]

•							
15	14	13	12	11	10	9	8
OPF[7]	OPF[6]	OPF[5]	OPF[4]	OPF[3]	OPF[2]	OPF[1]	OPF[0]

Field	Bits	Туре	Description
OPF[7:0]	15:8	R	OPF[7:0] - Output Pin Feedback Principally, OPF can return the previously send OPS word and the IN 10:7 -pin settings, dependent serial/parallel-setting of OPS: - If Serial Mode is selected by one or more OPS[3:0]-bits, the related OPF[7:4]-bits are returning the settings of OPS[7:4], send at the previous frame. - if parallel Mode is selected by one or more OPS[3:0]-bits, the related OPF[7:4]-bits are returning the condition available at the related IN 1:7 Pins at the moment of S CS high-to-low transition.
			A mix of both modes is possible and depends on the channel related settings.



COMMAND

Reset Value: 1010 1010 1010_B = AAA_h

12.3.3 OUTx - Output Control Register CHx

The Output Control Register OUTx consists of 10 Bits to control the Output Channel. Each Bit switches ON/OFF the related Channel.

OUTx becomes only active when ISx[1:0] = 0x. For details refer to Chapter 12.3.4.

OUTx Output 0	Control F	Register				000 0000	DATA				
11	10	9	8	7	6	5	4	3	2	1	0
1	1	OUT10	OUT9	OUT8	OUT7	OUT6	OUT5	OUT4	OUT3]	OUT2	OUT1

Field	Bits	Type	Description
OUTx[9:0]	9:0	R/W	Data - OUTx[9:0] OUTx = 0 According Channel is switched OFF OUTx = 1 According Channel is switched ON default (all channels OFF) OUT[9:0] = 00 0000 0000 _B = 000 _h
OUT[11:10]	11:10	R/W	Data - OUTx[11:10] bits are set to OUT[11:10] = 1.

12.3.4 ISx - INPUT or Serial Mode Control Register, Bank A and Bank B

The INPUT or Serial Control Register [ISx[1:0]] allows to define the way of controlling the Output Channels. There are 4 setting options possible:

- Standard Serial Control: The related Output Channel is set according the content of the OUTx Register. (Chapter 12.3.3)
- A further possibility is the control by the Input Pins
- The settings of the Parallel Mode Register PMx[0]. (Chapter 12.3.5)
- Additionally possible is the AND operation between the setting of the OUTx register and the PWM signal at the INPUT Pin.

ISAx INPUT or Serial Mode Control Register Bank A

11 10 9 8 7 6 5	1 2 2 1 0
	4 3 2 1 0
IS6 IS5 IS4	IS3 IS2 IS1



ISBx INPUT or Serial Mode Control Register Bank B

	COMMAND
Reset Value: 0000 1010 1	$1010_{-} = 0\Delta\Delta$

11	10	9	8	7	6	5	4	3	2	1	0
0	0	0	0	IS	10	IS		IS	88	IS	67

Field	Bits	Туре	Description
ISx[1:0]	11:0 ISAx 7:0 ISBx	R/W	Command - IS[1:0] ISx[1:0]= 0x: Serial Mode - The Channel is set ON/OFF by OUTx. 10: INPUT Mode - CHx ON/OFF according INx 11: AND operate Mode INx with OUTx -> CHx ON if OUTx & INx = 1 default all Channels ISx[1:0] = 10 _B

12.3.5 PMx - Parallel Mode Register CHx

The Parallel Mode Register PMx[1] allows to "inform" the device about externally parallel connected output channels. If a PMx bit is set, the "lower" related Input Channel controls the indicated Output Channels to achieve best possible matching and according to that highest efficiency of both channels. Additionally to that, the CLAMPsafe feature allows high matching during clamping.

PMx COMMAND Parallel Mode Register CHx Reset Value: $0000\ 00000\ 00000_{\rm B} = 000_{\rm h}$

	_										
11	10	9	8	7	6	5	4	3	2	1	0
0	0	0	0	PM910	PM89	PM78	PM56	0	PM34	PM23	PM12

Field	Bits	Туре	Description
PMx	11:8	R/W	0
PMx	7:0	R/W	PMx - Parallel Mode Bit 0 Direct Mode 1 Parallel Mode of Channel 1 with x+1 default PMx[0] = 0 Controlling Parallel Mode is possible between Channel 1 to 4, 5 to 6, 7 to 10. In between the groups, no parallel mode is supported but possible. In case Parallel Mode is chosen and a diagnosis error at only one of the channels is detected, the according diagnosis bit is set. This information mismatch can be caused by tolerance related inbalance of the channels connected together in parallel mode. The diagnosis bits should be or-operated by the Micro Controller side.

12.3.6 DEVS - Device Settings

This Register allows additional Device settings. For details refer also to the Chapter "Electrical Characteristics". The Diagnosis Current Control register allow to select between different Diagnosis Modes. The Diagnosis Currents can be switched off to avoid glowing of any connected LEDs.



The Register Latch on Over Current or Over Temperature LOTC[1:0] defines the reaction of the protection functions on exceeding the operating ranges.

DEVS Device Se			Res	set Value	: 0000 00		MMAND _B = 007 _h				
11	10	9	8	7	6	5	4	3	2	1	0
RCP	DBT2	DBT1	LOTC70 [1]	LOTC70 [0]	LOTC16 [1]	LOTC16 [0]	0	0	DCC10	DCC9	DCC18

Field	Bits	Type	Description
RCP	11	R/W	RCP - Reverse Current Protection
			1: reverse current comp is enabled (valid for all Channels)
			0: disabled
			default: RCP = 0
DBT2	10	R/W	DBT2,1 - Diagnosis Blind Time Channel 7 to 10
DBT1	9		0,0 standard Filter Time of typ. 150μs
			1,0 standard Filter Time of typ. 150μs
			0,1 OFF-state diagnosis Blind Time of typ. 2.5ms
			1,1 OFF-state diagnosis Blind Time of typ. 5ms
LOTC16[1:0] LOTC70[1:0]		R/W	LOTCx[1:0] - Latch on Over Temperature or Over Current
			LOTC16[1:0] - Settings for Ch 1 to 6
			LOTC70[1:0] - Settings for Ch 7 to 10
			00 Default: shut down and latch when over current or over
			temperature was detected. The related channel can only be
			turned on again, when the Diagnosis Byte is deleted by a clear command.
			Changing to other modes might cause severe damage to
			the device over longer operating periods.
			01 shut down and restart with next turn-on command /or DATA of
			the channel. No clearance of the Diagnosis Register required.
			10 shut down and restart automatically after delay time
			11 not used, is a command with =11 is received, frame is ignored.
			default LOTCxx[1:0] = 00.
DEVS[4:3]	4:3	R/W	not used. set to '0'



FLEX Smart Multi-Channel Switch

Control of the device

Field	Bits	Туре	Description
DCCx	2:0	R/W	DCCx - Diagnosis Current Control DCC18 switching ON/OFF diagnosis current of CH1-8 DCC9 switching ON/OFF diagnosis current of CH9 DCC10 switching ON/OFF diagnosis current of CH10 O OFF-State Diagnosis (Detection of open load and short to GND) of CHx is switched OFF. ON state diagnosis (over current and over temperature detection) is still active. Diagnosis Current is switched OFF. OFF-State (Detection of open load and short to GND) and ON- State (over current and over temperature detection) Diagnosis of CHx switched ON, Diagnosis Current is switched ON default DCC = 1



Package Outlines

13 Package Outlines




Figure 38 PG-DSO-36-41 Exposed Pad

Green Product (RoHS compliant)

To meet the world-wide customer requirements for environmentally friendly products and to be compliant with government regulations the device is available as a green product. Green products are RoHS-Compliant (i.e Pb-free finish on leads and suitable for Pb-free soldering according to IPC/JEDEC J-STD-020).

You can find all of our packages, sorts of packing and others in our Infineon Internet Page "Products": http://www.infineon.com/products.

Dimensions in mm





Revision History (Book)

14 Revision History (Book)

TLE8110EE

Revision History: 2009-06-15 Rev. 1.0

Ver 1.0 2009-06-15: datasheet released

Data Sheet 71 Rev. 1.0, 2009-06-15

Edition 2009-06-15

Published by Infineon Technologies AG 81726 Munich, Germany © 2009 Infineon Technologies AG All Rights Reserved.

Legal Disclaimer

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

Information

For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office (www.infineon.com).

Warnings

Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office.

Infineon Technologies components may be used in life-support devices or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.



Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«**FORSTAR**» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: http://oceanchips.ru/

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А