



Western Digital® PC SN720 NVMe™ SSD

Performance Reimagined

Cutting-edge NVMe Architecture

With future-ready, scalable NVMe architecture, the Western Digital PC SN720 NVMe SSD is breaking through performance limits of commercial and embedded applications, and supporting higher storage uses in today's IoT market, while providing a compact storage device with high capacity points from 256GB to 2TB.

Powerful Construction Suited for IoT

The Western Digital PC SN720 NVMe SSD, supporting PCIe Gen3 x4, is designed for applications that require both high performance and low power. Partners that could benefit from NVMe technology include:

- **Edge Equipment and IoT Gateway:** Such as network equipment, industrial machinery, medical equipment, or embedded PC that need the high capacities to capture the floor's and sensors' data and the high IOPS to support the system's data analytics
- **Media Content Delivery and Streaming:** In-flight entertainment systems, train control and monitoring systems, data recorder and video surveillance that require high capacity and reliability
- **Commercial:** Interactive kiosks, ATMs and Point-of-Sales (POS), Multi-Functional Printers (MFP) and industries that require high-volume transaction processing

Pushing the Performance for IoT

Equipped with a fully integrated solution which includes in-house controller, 64-layer 3D NAND, firmware, and testing, Western Digital provides longevity of supply in a robust and reliable design.

Designed with Western Digital's in-house tiered-caching NVMe architecture, the Western Digital PC SN720 NVMe SSD delivers extreme performance with sequential read and write speeds up to 3,400MB/s and 2,800MB/s respectively and high endurance up to 500 TBW, all of which is available in a M.2 2280 form factor.

Summary

The Western Digital PC SN720 NVMe SSD packs a powerful punch in a compact design, which enables outstanding performance for the most demanding IoT and embedded applications that seek a reliable storage device with capacity points from 256GB to 2TB.



WESTERN DIGITAL PC SN720 NVMe SSD KEY BENEFITS & FEATURES

**READ SPEEDS UP TO 3,400MB/S SATURATES THE
PCIe GEN3 x4 INTERFACE SUPPORTING NVMe
ARCHITECTURE**

**256GB-2TB CAPACITIES AVAILABLE IN M.2 2280
FORM FACTOR**

ENDURANCE OF UP TO 500 TBW

5 YEAR LIMITED WARRANTY

Western Digital PC SN720 NVMe SSD

Specifications are subject to change

Form Factors					M.2 2280
Interface					PCIe Gen3 x4 NVMe v1.3
Formatted Capacities¹					256GB, 512GB, 1TB, (2TB version for later release)
Performance²	256GB	512GB	1TB	2TB	
Sequential Read up to (MB/s)	3,000	3,400	3,400		
Sequential Write up to (MB/s)	1,600	2,400	2,800		
Random Read up to (IOPS)	225K	400K	500K		Coming Soon
Random Write up to (IOPS)	185K	330K	400K		
Endurance ³ (TBW)	200	300	400		
Power	256GB	512GB	1TB	2TB	
Peak Power (10µs) (A)	2.8	2.8	2.8		
Avg. Active Power ^{4,5} (mW)	110	110	140		
Low Power (PS3) ⁵ (mW)	70	70	100		Coming Soon
Sleep (PS4) ⁵ (mW)	2.5	2.5	2.5		
Supply Voltage (V / ±5%)	3.3	3.3	3.3		
Reliability					
MTTF ⁶					Up to 1.752M hours
Environmental					
Operating Temperature ⁷					32°F to 158°F (0°C to 70°C)
Non-operating Temperature ⁸					-67°F to 185°F (-55°C to 85°C)
Operating Vibration					5 gRMS, 10-2000 Hz, 3 axes
Non-operating Vibration					4.9 gRMS, 7-800 Hz, 3 axes
Shock					1,500G @0.5 ms half sine, 3 pulses per face
Certifications					FCC, UL, TUV, KCC, BSMI, VCCI, C-Tick
Limited Warranty ⁹					5 years
Physical Dimensions					
Width					22mm ±0.15mm
Length					2280: 80mm ±0.15mm
Thickness (max)					2.38mm
Weight					7.5g ±1g
SKU	Form Factor	Capacity			
SDAPNTW-256G	M.2 2280 S3-M	256GB			
SDAPNTW-512G	M.2 2280 S3-M	512GB			
SDAPNTW-1T00	M.2 2280 S3-M	1TB			
SDAPNTW-2T00	M.2 2280 S3-M	2TB			



Western Digital

Western Digital
5601 Great Oaks Parkway
San Jose, CA 95119, USA
www.wdc.com

Western Digital and the Western Digital logo are the registered trademarks of Western Digital Corporation or its affiliates in the U.S. and/or other countries. All marks are the property of their respective owners. Pictures shown may vary from actual products. The NVMe™ word mark is a trademark of NVM Express, Inc.

¹ As used for storage capacity, one gigabyte (GB) = one billion bytes and one terabyte (TB) = one trillion bytes. Total accessible capacity varies depending on operating environment.

² Test Conditions: Performance is based on the CrystalDiskMark 5.2.2 benchmark using a 1000MB LBA range ASUS Z170A desktop with Intel® i7-6700K 4.0GHz, 8GB 2133MHz DDR4. Windows 10 Pro 64-bit using Microsoft StorNVMe driver, secondary drive. Performance may vary based on host device. 1 MB = 1,000,000 bytes. IOPS = input/output operations per second.

³ TBW (terabytes written) values calculated using JEDEC client workload (JESD219) and vary by product capacity.

⁴ Measured using MobileMark™ 2014 on HP EliteBook X360 1030 G2 with i7-7600U, 8GB RAM. Windows 10 Pro, 64-bit RS3 using Microsoft StorNVMe driver, primary drive.

⁵ Power measurements at 25°C.

⁶ MTTF = Mean Time To Failure based on internal testing using Telcordia stress part testing. MTTF is based on a sample population and is estimated by statistical measurements and acceleration algorithms. MTTF does not predict an individual drive's reliability and does not constitute a warranty. (Telcordia SR-332, GB, 40°C)

⁷ Operational temperature as reported by device (composite temperature.)

⁸ Non-operational storage temperature does not guarantee data retention.

⁹ 5 years or Max Endurance (TBW) limit, whichever occurs first. 5 year warranty in regions not recognizing "limited." See <http://support.wdc.com> for more details.

Product specifications subject to change without notice. Not all products are available in all regions of the world.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А