


3M™ HIGH FLEX LIFE FLAT CABLE, HF319 SERIES
 .050", 28 AWG STRANDED, HIGH FLEX LIFE, HALOGEN FREE PO



Note: Available in standard 100 ft and 300 ft rolls, please specify when ordering.
 Contact 3M for availability of additional conductor counts and/or custom roll lengths.

- NOTES**
- MATERIAL:**
 A) PRIMARY INSULATION: HALOGEN FREE POLYOLEFIN (PO).
 B) CONDUCTORS: 28 AWG, 19 X 40 AWG SILVER PLATED STRANDED COPPER ALLOY
 - REGULATORY INFORMATION:**
 VISIT 3M.com/regs OR CONTACT YOUR 3M REPRESENTATIVE TO FIND THE RoHS COMPLIANCE STATUS OF THE 3M PART YOU ARE INTERESTED IN.

 UL FILE NO: E42769.
 UL STYLE NO: 21682.
 - MARKINGS:**
 STANDARD: NONE
 CANADIAN: SEE "PRINTING ILLUSTRATION" VIEW
 PRIMARY CABLE: BLUE MARK ON EDGES DESIGNATES WIRE NUMBER 1.
 - ENVIRONMENTAL:**
 TEMP RATING: -40°C TO +105°C (EIA-364-32G, METHOD A, TEST CONDITION 2).

 -10°C TO +105°C (UL TEMPERATURE RATING)
 FLAMABILITY RATING: HORIZONTAL.
 - HALOGEN FREE IS DEFINED AS BOTH:**
 1) NO HALOGEN COMPOUNDS THAT ARE INTENTIONALLY ADDED TO THE PRODUCT OR USED IN THE MANUFACTURING PROCESS FOR THE PRODUCT.
 2) ANY IMPURITIES PRESENT ARE LESS THAN 900 ppm BROMINE, LESS THAN 900 ppm CHLORINE AND/OR LESS THAN 1500 ppm TOTAL BROMINE AND CHLORINE. THE LATTER ARE THE LEVELS SET FORTH IN CERTAIN INDUSTRY STANDARDS FOR PRINTED CIRCUIT BOARDS, SUCH AS THE INTERNATIONAL ELECTROTECHNICAL COMMISSION (IEC) 61249-2-21 STANDARD. THIS INFORMATION REPRESENTS 3M'S KNOWLEDGE AND BELIEF WHICH MAY BE BASED IN WHOLE OR IN PART ON INFORMATION PROVIDED BY 3RD PARTY SUPPLIERS TO 3M.

ORDERING INFORMATION

X HF319/XX XX

BLANK = STANDARD
 C = CANADIAN

NUMBER OF CONDUCTORS
 (SEE TABLE 1)

BLANK = STANDARD
 SF = SPLICE FREE

ROLLING FLEX CYCLES PER
 EIA-364-41

RADIUS	MINIMUM CYCLES
1/2"	18 MILLION
3/4"	113 MILLION

ALL CYCLES WERE PERFORMED AT AMBIENT CONDITIONS.

TABLE 1
 DIMENSION CHART

NUMBER OF CONDUCTORS	3M PART NUMBER	DIMENSION 'A' ± AS NOTED	DIMENSION 'B' (SEE NOTE 2)
6	HF319/06	0.300"±0.010"	0.250"±0.007"
9	HF319/09	0.450"±0.010"	0.400"±0.007"
10	HF319/10	0.500"±0.010"	0.450"±0.007"
14	HF319/14	0.700"±0.010"	0.650"±0.007"
15	HF319/15	0.750"±0.010"	0.700"±0.007"
16	HF319/16	0.800"±0.015"	0.750"±0.011"
20	HF319/20	1.000"±0.015"	0.950"±0.011"
24	HF319/24	1.200"±0.015"	1.150"±0.011"
25	HF319/25	1.250"±0.015"	1.200"±0.011"
26	HF319/26	1.300"±0.015"	1.250"±0.011"
30	HF319/30	1.500"±0.020"	1.450"±0.015"
34	HF319/34	1.700"±0.020"	1.650"±0.015"
36	HF319/36	1.800"±0.020"	1.750"±0.015"
37	HF319/37	1.850"±0.020"	1.800"±0.015"
40	HF319/40	2.000"±0.020"	1.950"±0.015"
50	HF319/50	2.500"±0.020"	2.450"±0.015"
60	HF319/60	3.000"±0.020"	2.950"±0.015"
64	HF319/64	3.200"±0.020"	3.150"±0.015"

TABLE 2
 ELECTRICAL CHARACTERISTICS

VOLTAGE RATING	USA: 300V, CANADA: 150V, EU: 50V	
INSULATION RESISTANCE	PRIMARY CABLE >1 X 10 ¹⁰ Ω/10 FT (3 m)	
	UNBALANCED	BALANCED
CHARACTERISTIC IMPEDANCE	100 Ω	169 Ω
CAPACITANCE	15.0 pF/ft [49.2 pF/m]	8.4 pF/ft [27.7 pF/m]
INDUCTANCE	0.15 μH/ft [0.49 μH/m]	0.24 μH/ft [0.79 μH/m]
PROPAGATION DELAY	1.48 ns/ft [4.86 ns/m]	1.42 ns/ft [4.66 ns/m]
VELOCITY OF PROPAGATION	68%	72%

NOTE: UNBALANCED IS MEASURED BETWEEN GROUND-SIGNAL-GROUND CONDUCTORS.
 BALANCED IS MEASURED WITHIN A PAIR.

"PRINTING ILLUSTRATION"

AWM 21682 105°C 300V HOR **AWM 1A 105°C 150V FT2 EU<50V**

3M ELECTRONICS MATERIALS SOLUTIONS DIVISION
 INTERCONNECT SOLUTIONS
<http://www.3mconnectors.com>

3M IS A TRADEMARK OF 3M COMPANY.
 FOR TECHNICAL, SALES OR ORDERING
 INFORMATION CALL 800-225-5373



DESIGN REFERENCE	NEXT ASSEMBLY	REV	ECO	ISSUE DATE AND DESCRIPTION	DRFT	CHKD
		C	80477	SEP 06, 2018 REVISED DATA AND NOTES	JNC	BPM
		B	40826	MAY 22, 2012 REVISED AND REDRAWN	JNC	SN
DESIGNER	SCALE	DATE	DATE	DATE	DATE	DATE
CASTIGLIONE		MAY 15, 2012		MAY 15, 2012		MAY 15, 2012
DIVISION	SCALE	DATE	DATE	DATE	DATE	DATE
	EMSD					
DO NOT SCALE DRAWING	TOLERANCES EXCEPT AS NOTED	© 3M COPYRIGHT 2018 This document and the information it contains are 3M property and may not be reproduced or further distributed without 3M permission, or used or disclosed other than for 3M authorized purposes. All rights reserved.				
THIRD ANGLE PROJECTION	INCHES	TITLE				
	0 ± .1 .00 ± .05 .000 ± .010 .0000 ±	HIGH FLEX LIFE, FLAT CABLE, 28 AWG STRANDED, HF319				
INTERPRET PER ASME Y14.5 - 2009	MILLIMETERS	CAGE NUMBER				
	0 ± 2.5 .0 ± 1.3 .00 ± .25 .000 ±	D 78-5100-2342-3				
MAX SURFACE ROUGHNESS	ANGLE	REV.				
0.8 SURFACES		C				
MARKED ONLY		MODEL				
		HF319				
		SHT 1 OF 2				

78-5100-2342-3
 DRAWING NUMBER
 Time 9/7/2018 -- UTC Offset (hrs) 6
 Imaged: Central Standard

3M™ HIGH FLEX LIFE FLAT CABLE, HF319 SERIES
 .050", 28 AWG STRANDED, HIGH FLEX LIFE, HALOGEN FREE PO

Regulatory: For regulatory information about this product, visit 3M.com/regs or contact your 3M representative.


Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use: Many factors beyond 3M's control and uniquely within user's control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy, and Disclaimer: Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OR TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

3M Electronics Materials Solutions Division
 6801 River Place Blvd.
 Austin, TX 78726-9000
 1-800-225-5373
 www.3M.com/interconnect

DESIGN REFERENCE	NEXT ASSEMBLY	REV	ECO	ISSUE DATE AND DESCRIPTION	DRFT	CHKD
ACROSS CODES		DRFT	DATE	MFG	DATE	
		CASTIGLIONE	MAY 15, 2012		MAY 15, 2012	
DIVISION	DIVISION CODE	CHKD	DATE	APPRV	DATE	
	EMSD			S. NEU	MAY 15, 2012	
DO NOT SCALE DRAWING	SCALE	TOLERANCES EXCEPT AS NOTED		 © 3M COPYRIGHT 2018 This document and the information it contains are 3M property and may not be reproduced or further distributed without 3M permission, or used or disclosed other than for 3M authorized purposes. All rights reserved.		
		INCHES		TITLE		
		.0 ± .1		HIGH FLEX LIFE, FLAT CABLE, 28 AWG STRANDED, HF319		
		.00 ± .05		CAGE NUMBER		
		.000 ± .010		D 78-5100-2342-3		
		.0000 ±		REV. C		
THIRD ANGLE PROJECTION		MILLIMETERS		MODEL		
		0 ± 2.5		HF319		
INTERPRET PER ASME Y14.5 - 2009		.0 ± 1.3		DET		
		.00 ± .25		LISTS <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO		
MAX SURFACE ROUGHNESS		.000 ±		SHT 2 OF 2		
DTX SURFACES		ANGLES				
<input checked="" type="checkbox"/> MARKED ONLY						

78-5100-2342-3
 DRAWING NUMBER
 1
 REVISION
 C
 6
 (hrs)
 Offset

 UTC
 9/7/2018
 Time
 Standard
 Central
 Imaged

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А