



**Product:** [32822](#)

Lead Wire, #22 Str TC UNISTRAND, PVC Ins, AWM 1007 CSA TYPE TR-64TEW

[Request Sample](#)

**Product Description**

Low Temp Plastic Lead Wire, 22AWG (7x30) Tinned Copper Unistrand, PVC Insulation, AWM 1007 CSA TYPE TR-64 300V 90C VW-1

**Technical Specifications**

**Physical Characteristics (Overall)**

**Conductor**

| AWG | Stranding | Material                         | No. of Conductors |
|-----|-----------|----------------------------------|-------------------|
| 22  | 7x30      | TC - Tinned Copper (Uni-Strand®) | 1                 |

Conductor Count: 1

**Insulation**

| Material                 | Nominal Diameter | Nominal Wall Thickness | Min. Average Wall Thickness |
|--------------------------|------------------|------------------------|-----------------------------|
| PVC - Polyvinyl Chloride | 0.062 in         | 0.016 in               | 0.015 in                    |

**Electrical Characteristics**

**Voltage**

| Non-UL Voltage Rating | UL Voltage Rating |
|-----------------------|-------------------|
| 300 V                 | 300 V             |

**Temperature Range**

|                     |      |
|---------------------|------|
| Non-UL Temp Rating: | 90°C |
| UL Temp Rating:     | 80°C |

**Mechanical Characteristics**

|                    |                |
|--------------------|----------------|
| Bulk Cable Weight: | 3.6 lbs/1000ft |
|--------------------|----------------|

**Standards**

|                         |                            |
|-------------------------|----------------------------|
| UL AWM Style:           | UL Style 1007 (300 V 80°C) |
| CSA Rating:             | 90°C                       |
| CSA AWM Specification:  | TR-64                      |
| CSA Type:               | TR-64                      |
| Military Specification: | N/A                        |

**Applicable Environmental and Other Programs**

|                                    |                               |
|------------------------------------|-------------------------------|
| EU Directive 2000/53/EC (ELV):     | Yes                           |
| EU Directive 2003/96/EC (BFR):     | Yes                           |
| EU Directive 2011/65/EU (ROHS II): | Yes                           |
| EU Directive 2012/19/EU (WEEE):    | Yes                           |
| EU Directive 2015/863/EU:          | Yes                           |
| EU Directive Compliance:           | EU Directive 2003/11/EC (BFR) |
| EU CE Mark:                        | Yes                           |

|                                       |            |
|---------------------------------------|------------|
| EU RoHS Compliance Date (yyyy-mm-dd): | 2005-07-01 |
| MII Order #39 (China RoHS):           | Yes        |

## Flammability, LSOH, Toxicity Testing

|                    |           |
|--------------------|-----------|
| UL Flammability:   | VW-1      |
| UL voltage rating: | 300 V RMS |

## Plenum/Non-Plenum

|               |    |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

## Part Number

### Variants

| Item #        | Color       | Putup Type | Length   | UPC          |
|---------------|-------------|------------|----------|--------------|
| 32822 0105000 | Black       | Reel       | 5,000 ft | 612825143307 |
| 32822 0055000 | Green, Dark | Reel       | 5,000 ft | 612825143284 |
| 32822 0035000 | Orange      | Reel       | 5,000 ft | 612825143277 |
| 32822 0025000 | Red         | Reel       | 5,000 ft | 612825143260 |
| 32822 0095000 | White       | Reel       | 5,000 ft | 612825143291 |

|           |  |
|-----------|--|
| Footnote: | I - MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 200'.                                      |
| Footnote: | U - TOPCOAT ADDERS ON STOCK SOLID COLORS. MINIMUM ORDER 10,000' PER COLOR COMBINATION. (SEE TOPCOAT ADDER TABLE) |
| Footnote: | Z - FINAL PUT-UP MAY VARY (= OR -) 10% FOR SPOOLS OR REELS AND (+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN. |
| Footnote: | C - CRATE REEL PUT-UP.   |

## History

|                      |  |
|----------------------|--|
| Update and Revision: | Revision Number: 0.277 Revision Date: 04-28-2020 |
|----------------------|--|

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А