



PNP Power Amplifier Silicon Transistor

Qualified per MIL-PRF-19500/580

Qualified Levels:
JAN, JANTX and
JANTXV


DESCRIPTION

This family of 2N4234, 2N4235, and 2N4236 silicon transistors are military qualified up to the JANTXV level for high-reliability applications.

Important: For the latest information, visit our website <http://www.microsemi.com>.

FEATURES

- JEDEC registered 2N4234 and 2N4236 number
- JAN, JANTX, and JANTXV qualifications available per MIL-PRF-19500/580
- RoHS compliant version available



TO-205AD
(formerly TO-39)
Package

APPLICATIONS / BENEFITS

- Short leaded TO-205AD package
- Lightweight package
- Military and other high-reliability applications

MAXIMUM RATINGS @ $T_A = +25^\circ\text{C}$ unless otherwise noted

Parameters / Test Conditions	Symbol	Value	Unit
Junction & Storage Temperature	T_J, T_{stg}	-65 to +200	$^\circ\text{C}$
Thermal Resistance Junction-to-Case	$R_{\theta JC}$	29	$^\circ\text{C/W}$
Thermal Resistance Junction-to-Ambient	$R_{\theta JA}$	175	$^\circ\text{C/W}$
Total Power Dissipation ⁽¹⁾ @ $T_A = 25^\circ\text{C}$ ⁽¹⁾ @ $T_C = 25^\circ\text{C}$ ⁽²⁾	P_T	1.0 6.0	W
Collector – Emitter Voltage 2N4234 2N4235 2N4236	V_{CEO}	-40 -60 -80	V
Collector – Base Voltage 2N4234 2N4235 2N4236	V_{CBO}	-40 -60 -80	V
Emitter - Base Voltage	V_{EBO}	-7.0	V
Base Current	I_B	-0.5	A
Collector Current	I_C	-1.0	A

Notes: 1. Derated linearly by 5.7 mW/ $^\circ\text{C}$ for $T_A > +25^\circ\text{C}$
2. Derated linearly by 34 mW/ $^\circ\text{C}$ for $T_C > +25^\circ\text{C}$

MSC – Lawrence

6 Lake Street,
Lawrence, MA 01841
Tel: 1-800-446-1158 or
(978) 620-2600
Fax: (978) 689-0803

MSC – Ireland

Gort Road Business Park,
Ennis, Co. Clare, Ireland
Tel: +353 (0) 65 6840044
Fax: +353 (0) 65 6822298


Website:

www.microsemi.com

MECHANICAL and PACKAGING

- CASE: Hermetically sealed, steel base, nickel cap
- TERMINALS: Steel Leads, nickel plated, then solder dipped or RoHS compliant matte-tin available on commercial grade only
- MARKING: Part number, date code, manufacturer's ID and serial number
- POLARITY: PNP
- WEIGHT: Approximately 1.064 grams
- See [Package Dimensions](#) on last page.

PART NOMENCLATURE



SYMBOLS & DEFINITIONS

Symbol	Definition
I_B	Base current: The value of the dc current into the base terminal.
I_C	Collector current: The value of the dc current into the collector terminal.
I_E	Emitter current: The value of the dc current into the emitter terminal.
T_C	Case temperature: The temperature measured at a specified location on the case of a device.
V_{CB}	Collector-base voltage: The dc voltage between the collector and the base.
V_{CBO}	Collector-base voltage, base open: The voltage between the collector and base terminals when the emitter terminal is open-circuited.
V_{CC}	Collector-supply voltage: The supply voltage applied to a circuit connected to the collector.
V_{CE}	Collector-emitter voltage: The dc voltage between the collector and the emitter.
V_{CEO}	Collector-emitter voltage, base open: The voltage between the collector and the emitter terminals when the base terminal is open-circuited.
V_{EB}	Emitter-base voltage: The dc voltage between the emitter and the base
V_{EBO}	Emitter-base voltage, collector open: The voltage between the emitter and base terminals with the collector terminal open-circuited.

ELECTRICAL CHARACTERISTICS @ $T_A = +25^\circ\text{C}$, unless otherwise noted

Characteristics	Symbol	Min	Max	Unit
-----------------	--------	-----	-----	------

OFF CHARACTERISTICS

Collector-Emitter Breakdown Voltage $I_C = -100\text{ mA}$	2N4234 2N4235 2N4236	$V_{(BR)CEO}$	-40 -60 -80	V
Collector-Emitter Cutoff Current $V_{CB} = -30\text{ V}$ $V_{CB} = -40\text{ V}$ $V_{CB} = -60\text{ V}$	2N4234 2N4235 2N4236	I_{CEO}	 -1.0 -1.0 -1.0	mA
Collector-Emitter Cutoff Current $V_{CB} = -40\text{ V}, V_{BE} = -1.5\text{ V}$ $V_{CB} = -60\text{ V}, V_{BE} = -1.5\text{ V}$ $V_{CB} = -80\text{ V}, V_{BE} = -1.5\text{ V}$	2N4234 2N4235 2N4236	I_{CEX}	 -100 -100 -100	nA
Collector-Base Cutoff Current $V_{CB} = -40\text{ V}$ $V_{CB} = -60\text{ V}$ $V_{CB} = -80\text{ V}$	2N4234 2N4235 2N4236	I_{CBO}	 -100 -100 -100	nA
Emitter-Base Cutoff Current $V_{BE} = -7.0\text{ V}$		I_{EBO}	-0.5	mA


ON CHARACTERISTICS ⁽³⁾

Forward-Current Transfer Ratio $I_C = -100\text{ mA}, V_{CE} = -1.0\text{ V}$ $I_C = -250\text{ mA}, V_{CE} = -1.0\text{ V}$ $I_C = -500\text{ mA}, V_{CE} = -1.0\text{ V}$	h_{FE}	40 30 20	150	
Collector-Emitter Saturation Voltage $I_C = -1.0\text{ A}, I_B = -100\text{ mA}$ $I_C = -500\text{ mA}, I_B = -50\text{ mA}$	$V_{CE(sat)}$		-0.6 -0.4	V
Base-Emitter Saturation Voltage $I_C = -500\text{ mA}, I_B = -50\text{ mA}$ $I_C = -1.0\text{ A}, I_B = -100\text{ mA}$	$V_{BE(sat)}$		-1.1 -1.5	V

DYNAMIC CHARACTERISTICS

Magnitude of Common Emitter Small-Signal Short-Circuit Forward Current Transfer Ratio $I_C = -100\text{ mA}, V_{CE} = -10\text{ V}, f = 1\text{ MHz}$	$ h_{FE} $	3.0		
Output Capacitance $V_{CB} = -10\text{ V}, I_E = 0, f = 100\text{ MHz}$	C_{obo}		100	pF

ELECTRICAL CHARACTERISTICS @ $T_A = +25\text{ }^{\circ}\text{C}$, unless otherwise noted (continued)**SAFE OPERATING AREA****DC Tests** $T_C = +25\text{ }^{\circ}\text{C}$, 1 cycle, $t \geq 0.5\text{ s}$ **Test 1** $V_{CE} = -6.0\text{ V}$, $I_C = -1.0\text{ A}$ **Test 2** $V_{CE} = -12\text{ V}$, $I_C = -500\text{ mA}$ **Test 3** $V_{CE} = -30\text{ V}$, $I_C = -166\text{ mA}$ (2N4234) $V_{CE} = -50\text{ V}$, $I_C = -100\text{ mA}$ (2N4235) $V_{CE} = -70\text{ V}$, $I_C = -71\text{ mA}$ (2N4236)(3) Pulse Test: Pulse Width = $300\text{ }\mu\text{s}$, duty cycle $\leq 2.0\%$

PACKAGE DIMENSIONS


Ltr	Dimensions				Notes
	Inch		Millimeters		
	Min	Max	Min	Max	
CD	0.305	0.335	7.75	8.51	
CH	0.240	0.260	6.10	6.60	
HD	0.335	0.370	8.51	9.40	
h	0.009	0.041	0.23	1.04	
j	0.028	0.034	0.71	0.86	3
k	0.029	0.045	0.74	1.14	3, 4
LD	0.016	0.021	0.41	0.53	8, 9
LL	0.500	0.750	12.7	19.05	
LC	0.200 TP		5.08 TP		7
LU	0.016	0.019	0.41	0.48	8, 9
L1	-	0.050	-	1.27	8, 9
L2	0.250	-	6.35	-	8, 9
P	0.100	-	2.54	-	7
Q	-	0.050	-	1.27	5
r	-	0.010	-	0.25	10
α	45° TP		45° TP		7

NOTES:

- Dimensions are in inches.
- Millimeters are given for information only.
- Beyond r (radius) maximum, TL shall be held for a minimum length of 0.011 inch (0.28 mm).
- Dimension TL measured from maximum HD.
- Body contour optional within zone defined by HD, CD, and Q.
- CD shall not vary more than .010 inch (0.25 mm) in zone P. This zone is controlled for automatic handling.
- Leads at gauge plane 0.054 +0.001 -0.000 inch (1.37 +0.03 -0.00 mm) below seating plane shall be within 0.007 inch (0.18 mm) radius of true position (TP) at maximum material condition (MMC) relative to tab at MMC.
- Dimension LU applies between L1 and L2. Dimension LD applies between L2 and LL minimum. Diameter is uncontrolled in L1 and beyond LL minimum.
- All three leads.
- The collector shall be internally connected to the case.
- Dimension r (radius) applies to both inside corners of tab.
- In accordance with ASME Y14.5M, diameters are equivalent to Φ x symbology.
- Lead 1 = emitter, lead 2 = base, lead 3 = collector.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А