

Dual-Band Wireless DPDT RF Switch

DESCRIPTION


- The CG2164X3 is a GaAs MMIC DPDT (Double Pole Double Throw) switch for 2.5 GHz and 6 GHz dual-band wireless LAN applications

FEATURES

- Control Voltage:
VC(H) = 1.8 to 5.0 V (3.0V TYP.)
VC(L) = -0.2 to 0.2 V (0V TYP.)
- Low Insertion Loss:
 $L_{ins} = 0.50$ dB TYP. @ $f = 2.5$ GHz
 $L_{ins} = 0.60$ dB TYP. @ $f = 6.0$ GHz
- High Isolation:
ISL = 23 dB TYP. @ $f = 2.5$ GHz
ISL = 15 dB TYP. @ $f = 6.0$ GHz
- Power Handling:
 $P_{in}(0.5dB) = +32$ dBm TYP. @ $f = 2.5$ GHz,
VC(H) = 3.0 V, VC(L) = 0 V
 $P_{in}(0.5dB) = +30$ dBm TYP. @ $f = 6.0$ GHz,
VC(H) = 3.0 V, VC(L) = 0 V

PACKAGE

- 6-pin TSON Package
(1.5mm x 1.5mm x 0.37mm)




APPLICATIONS

- Dual-band wireless LAN
(IEEE802.11a/b/g/n/ac)

ORDERING INFORMATION

Part Number	Order Number	Package	Marking	Description
CG2164X3	CG2164X3-C2	6-pin plastic TSON (Pb-Free)	C0N	<ul style="list-style-type: none"> • Embossed tape 8 mm wide • Pin 1, 6 face the perforation side of the tape • MOQ 10 kpcs/reel
CG2164X3-EVAL	CG2164X3-EVAL			<ul style="list-style-type: none"> • Evaluation Board with DC block capacitors, power supply bypass capacitors, and RF and DC connectors • MOQ 1

PIN CONFIGURATION AND INTERNAL BLOCK DIAGRAM



Pin No.	Pin Name
1	ANT2
2	VC2
3	RX
4	TX
5	VC1
6	ANT1

Remark Exposed pad : GND

TRUTH TABLE

VC1	VC2	ANT1-TX	ANT1-RX	ANT2-TX	ANT2-RX
High	Low	OFF	ON	ON	OFF
Low	High	ON	OFF	OFF	ON

ABSOLUTE MAXIMUM RATINGS

($T_A = +25^\circ\text{C}$, unless otherwise specified)

Parameter	Symbol	Rating	Unit
Control Voltage	VC	6.0 ^{Note 1}	V
Input Power	P_{in1}	+33 ^{Note 2}	dBm
	P_{in2}	+26 ^{Note 3}	dBm
Operating Ambient Temperature	T_A	-45~+85	$^\circ\text{C}$
Storage Temperature	T_{stg}	-55~+150	$^\circ\text{C}$

- Note**
- $|VC1 - VC2| \leq 6.0\text{V}$
 - $3.0\text{V} \leq |VC1 - VC2| \leq 5.0\text{V}$ $f \geq 0.5\text{GHz}$
 - $3.0\text{V} \leq |VC1 - VC2| \leq 5.0\text{V}$ $f \geq 0.05\text{GHz}$

RECOMMENDED OPERATING RANGE

($T_A = +25^\circ\text{C}$, unless otherwise specified)

Parameter	Symbol	MIN.	TYP.	MAX.	Unit
Operating Frequency	f	0.05	-	6.0	GHz
Switch Control Voltage (H)	VC(H)	+1.8	+3.0	+5.0	V
Switch Control Voltage (L)	VC(L)	-0.2	0	+0.2	V

ELECTRICAL CHARACTERISTICS 1

(TA=+25°C, VC(H)=3.0V, VC(L)=0V, Zo=50Ω, DC Block Capacitance=8pF, unless otherwise specified)

Parameter	Symbol	Test Conditions	MIN.	TYP.	MAX.	Unit
Insertion Loss	Lins1	f = 0.05 to 0.5 GHz ^{Note1}	-	0.40	0.65	dB
	Lins2	f = 0.5 to 1.0 GHz ^{Note1}	-	0.45	0.70	dB
	Lins3	f = 1.0 to 2.0 GHz ^{Note1}	-	0.50	0.75	dB
	Lins4	f = 2.0 to 2.5 GHz	-	0.50	0.75	dB
	Lins5	f = 2.5 to 4.9 GHz	-	0.55	0.90	dB
	Lins6	f = 4.9 to 6.0 GHz	-	0.60	1.00	dB
Isolation (ANT to TX, RX)	ISL1	f = 0.05 to 0.5 GHz ^{Note1}	32	35	-	dB
	ISL2	f = 0.5 to 1.0 GHz ^{Note1}	26	29	-	dB
	ISL3	f = 1.0 to 2.0 GHz ^{Note1}	21	24	-	dB
	ISL4	f = 2.0 to 2.5 GHz	20	23	-	dB
	ISL5	f = 2.5 to 4.9 GHz	13	16	-	dB
	ISL6	f = 4.9 to 6.0 GHz	12	15	-	dB
Isolation (ANT1 to ANT2, TX to RX)	ISL7	f = 0.05 to 0.5 GHz ^{Note1}	34	37	-	dB
	ISL8	f = 0.5 to 1.0 GHz ^{Note1}	27	30	-	dB
	ISL9	f = 1.0 to 2.0 GHz ^{Note1}	22	25	-	dB
	ISL10	f = 2.0 to 2.5 GHz	22	25	-	dB
	ISL11	f = 2.5 to 4.9 GHz	15	18	-	dB
	ISL12	f = 4.9 to 6.0 GHz	15	18	-	dB
Return Loss	RL1	f = 0.05 to 2.0 GHz ^{Note1}	-	20	-	dB
	RL2	f = 2.0 to 6.0 GHz	-	15	-	dB
0.5 dB Loss Compression Input Power ^{Note2}	P _{in(0.5dB)}	f = 0.05 GHz	-	+24.5	-	dBm
		f = 0.5 to 1.0 GHz	-	+31	-	dBm
		f = 2.4 to 2.5 GHz	-	+32	-	dBm
		f = 4.9 to 6.0 GHz	-	+30	-	dBm

Note1 DC block capacitance = 1,000pF at f=0.05 to 2.0GHz

Note2 P_{in(0.5dB)} is the measured input power level when the insertion loss increases 0.5dB more than that of the linear range.

ELECTRICAL CHARACTERISTICS 2


(TA=+25°C, VC(H)=3.0V, VC(L)=0V, Zo=50Ω, DC Block Capacitance=8pF, unless otherwise specified)

Parameter	Symbol	Test Conditions	MIN.	TYP.	MAX.	Unit
2nd Harmonics	2f0	f = 2.5 GHz, P _{in} =+20dBm	-	85	-	dBc
		f = 6.0 GHz, P _{in} =+20dBm	-	80	-	dBc
3rd Harmonics	3f0	f = 2.5 GHz, P _{in} =+20dBm	-	85	-	dBc
		f = 6.0 GHz, P _{in} =+20dBm	-	85	-	dBc
3rd Order Input Intercept Point	IIP3	f = 2.5GHz 2-tone 1MHz Spacing	-	+55	-	dBm
Error Vector Magnitude	EVM	802.11a, 64QAM, 54Mbps, P _{in} ≤+24.5dBm	-	2.5	-	%
		802.11g, 64QAM, 54Mbps, P _{in} ≤+25dBm	-	2.5	-	%
Switch Control Speed	tsw	50% CTL to 90/10%	-	30	-	ns
Switch Control Current	Icont	Non RF	-	2	-	μA


TYPICAL CHARACTERISTICS

(VC(H)=3V, VC(L)=0V, T_A = +25°C, DC Block Capacitance=8pF, through board loss is subtracted in insertion loss data)


Typical Insertion Loss vs. Frequency




Typical Isolation vs. Frequency




Typical Return Loss vs. Frequency



Typical Insertion Loss vs. Input Power



EVALUATION CIRCUIT




Note C0 : 0.05 to 2.0 GHz 1,000pF
2.0 to 6.0 GHz 8pF

The application circuits and their parameters are for reference only and are not intended for use in actual designs. DC Blocking Capacitors are required at all RF ports.


PACKAGE DIMENSIONS

6-pin Plastic TSON (Unit: mm)



PCB Layout Footprint

6-pin TSON (Unit: mm)



The PCB Layout Footprint In this document Is for reference only.

RECOMMENDED SOLDERING CONDITIONS

Recommended Soldering Conditions are available on CEL's [Part Summary page](#) under Associated Documents

REVISION HISTORY

Version	Change to current version	Page(s)
CDS-0033-01 (Issue A) September 14, 2016	Preliminary datasheet	N/A
CDS-0033-02 (Issue B) December 27, 2016	Revised Electrical Characteristics table Added "Recommended Soldering Conditions" section	3, 5
CDS-0033-03 (Issue C) March 20, 2017	Initial Datasheet. Revised Electrical Characteristics table	3
CDS-0033-05 (Issue D) August 28, 2017	Updated Characteristics tables and added Error Vector Magnitude Added "Typical Characteristics" graphs section Updated Evaluation Circuit diagram	3, 4, 5, 6
CDS-0033-06 (Issue E) October 25, 2017	Added PCB Layout Footprint	7

[CAUTION]

- All information included in this document is current as of the date this document is issued. Such information, however, is subject to change without any prior notice.
- You should not alter, modify, copy, or otherwise misappropriate any CEL product, whether in whole or in part.
- CEL does not assume any liability for infringement of patents, copyrights, or other intellectual property rights of third parties by or arising from the use of CEL products or technical information described in this document. No license, expressed, implied or otherwise, is granted hereby under any patents, copyrights or other intellectual property rights of CEL or others.
- Descriptions of circuits, software and other related information in this document are provided only to illustrate the operation of semiconductor products and application examples. You are fully responsible for the incorporation of these circuits, software, and information in the design of your equipment. CEL assumes no responsibility for any losses incurred by you or third parties arising from the use of these circuits, software, or information.
- CEL has used reasonable care in preparing the information included in this document, but CEL does not warrant that such information is error free. CEL assumes no liability whatsoever for any damages incurred by you resulting from errors in or omissions from the information included herein.
- Although CEL endeavors to improve the quality and reliability of its products, semiconductor products have specific characteristics such as the occurrence of failure at a certain rate and malfunctions under certain use conditions. Please be sure to implement safety measures to guard them against the possibility of physical injury, and injury or damage caused by fire in the event of the failure of a CEL product, such as safety design for hardware and software including but not limited to redundancy, fire control and malfunction prevention, appropriate treatment for aging degradation or any other appropriate measures
Because the evaluation of microcomputer software alone is very difficult, please evaluate the safety of the final products or system manufactured by you.
- Please use CEL products in compliance with all applicable laws and regulations that regulate the inclusion or use of controlled substances, including without limitation, the EU RoHS Directive.
CEL assumes no liability for damages or losses occurring as a result of your noncompliance with applicable laws and regulations.
- This document may not be reproduced or duplicated, in any form, in whole or in part, without prior written consent of CEL.
- Please contact CEL if you have any questions regarding the information contained in this document or CEL products, or if you have any other inquiries.

[CAUTION]

This product uses gallium arsenide (GaAs) of the toxic substance appointed in laws and ordinances. GaAs vapor and powder are hazardous to human health if inhaled or ingested.

- Do not dispose in fire or break up this product.
- Do not chemically make gas or powder with this product.
- When discarding this product, please obey the laws of your country.
- Do not lick the product or in any way allow it to enter the mouth.

[CAUTION]

Although this device is designed to be as robust as possible, ESD (Electrostatic Discharge) can damage this device. This device must be protected at all times from ESD. Static charges may easily produce potentials of several kilovolts on the human body or equipment, which can discharge without detection. Industry-standard ESD precautions should be used at all times.

CEL Headquarters • 4590 Patrick Henry Drive • Santa Clara, CA 95054 • Tel: (408) 919-2500 • www.cel.com

For a complete list of sales offices, representatives and distributors,

Please visit our website: www.cel.com/contactus

For inquiries email us at rfw@cel.com

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А