

Surface Mount Multilayer Ceramic Chip Capacitor Solutions for High Voltage Applications



FEATURES

- Excellent reliability and thermal shock performance
- High voltage breakdown compared to standard design
- High reliable serial electrode design
- Protective surface coating may be required to prevent surface arcing
- Wet build process
- Reliable Noble Metal Electrode (NME) system
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912



RoHS
COMPLIANT
HALOGEN
FREE
GREEN
(5-2008)

APPLICATIONS

- Input filter capacitors
- Output filter capacitors
- Snubber capacitors reduce MOSFET voltage spikes
- Filtering for switching power supplies
- For lighting and other AC applications please contact: mlcc@vishay.com

ELECTRICAL SPECIFICATIONS

| X7R |
|--|
| <p>GENERAL SPECIFICATION</p> <p>Note Electrical characteristics at +25 °C unless otherwise specified</p> <p>Operating Temperature: -55 °C to +125 °C</p> <p>Capacitance Range: 180 pF to 15 nF</p> <p>Voltage Range: 3000 V_{DC}, 4000 V_{DC}, 5000 V_{DC}</p> <p>Temperature Coefficient of Capacitance (TCC): ± 15 % from -55 °C to +125 °C, with 0 V_{DC} applied</p> <p>Dissipation Factor (DF): 2.5 % maximum at 1.0 V_{RMS} and 1 kHz</p> <p>Insulating Resistance: at +25 °C 100 000 MΩ min. or 1000 ΩF whichever is less at +125 °C 10 000 MΩ min. or 100 ΩF whichever is less</p> <p>Aging Rate: 1 % maximum per decade</p> <p>Dielectric Strength Test: performed per method 103 of EIA 198-2-E Applied test voltages 3000 V_{DC}- / 4000 V_{DC}- / 5000 V_{DC}-rated: min. 120 % of rated voltage</p> |

| QUICK REFERENCE DATA | | | | |
|----------------------|------|---------------------|-------------|---------|
| DIELECTRIC | CASE | MAXIMUM VOLTAGE (V) | CAPACITANCE | |
| | | | MINIMUM | MAXIMUM |
| X7R | 1812 | 5000 | 180 pF | 3.9 nF |
| | 1825 | 5000 | 330 pF | 10 nF |
| | 2220 | 5000 | 390 pF | 10 nF |
| | 2225 | 5000 | 470 pF | 15 nF |

Note

- Detail ratings see "Selection Chart"

| ORDERING INFORMATION | | | | | | | | |
|------------------------------|------------|--|---------------------------------------|--|--|--------------|---|-------------------|
| HV2220 | Y | 152 | K | X | M | A | T | HV ⁽²⁾ |
| CASE CODE | DIELECTRIC | CAPACITANCE NOMINAL CODE | CAPACITANCE TOLERANCE | TERMINATION | DC VOLTAGE RATING ⁽¹⁾ | MARKING | PACKAGING | PROCESS CODE |
| 1812 1825 2220 2225 | Y = X7R | Expressed in picofarads (pF). The first two digits are significant, the third is a multiplier. Examples 152 = 1500 pF | J = ± 5 % K = ± 10 % M = ± 20 % | X = Ni barrier 100 % tin plated matte finish | H = 3000 V V = 4000 V M = 5000 V | A = unmarked | T = 7" reel / plastic tape R = 11 1/4" / 13" reel / plastic tape | HV = high voltage |

Notes

- DC voltage rating should not be exceeded in application. Other application factors may affect the MLCC performance. Consult for questions: mlcc@vishay.com
- Process code with 2 digits has to be added.

| ENVIRONMENTAL STATUS | | | |
|----------------------|--|----------------|--------------|
| TERMINATION CODE | TERMINATION DESCRIPTION | RoHS COMPLIANT | VISHAY GREEN |
| X | Ni barrier 100 % tin plated matte finish | Yes | Yes |

| DIMENSIONS in inches (millimeters) | | | | | | |
|------------------------------------|--------|--------------------------------|--------------------------------|-----------------------|---------------------|--------------|
| | | | | | | |
| CASE CODE | STYLE | LENGTH (L) | WIDTH (W) | MAXIMUM THICKNESS (T) | TERMINATION PAD (P) | |
| | | | | | MINIMUM | MAXIMUM |
| 1812 | HV1812 | 0.177 ± 0.012 (4.50 ± 0.30) | 0.126 ± 0.008 (3.20 ± 0.20) | 0.106 (2.70) | 0.010 (0.25) | 0.030 (0.76) |
| 1825 | HV1825 | 0.177 ± 0.012 (4.50 ± 0.30) | 0.252 ± 0.010 (6.40 ± 0.25) | 0.106 (2.70) | 0.010 (0.25) | 0.030 (0.76) |
| 2220 | HV2220 | 0.220 ± 0.010 (5.59 ± 0.25) | 0.200 ± 0.010 (5.08 ± 0.25) | 0.106 (2.70) | 0.010 (0.25) | 0.030 (0.76) |
| 2225 | HV2225 | 0.220 ± 0.010 (5.59 ± 0.25) | 0.250 ± 0.010 (6.35 ± 0.25) | 0.106 (2.70) | 0.010 (0.25) | 0.030 (0.76) |



| SELECTION CHART | | | | | | | | | | | | | |
|----------------------------|--------|-----------------------|------|------|-----------------------|------|------|-----------------------|------|------|-----------------------|------|------|
| DIELECTRIC | | X7R | | | | | | | | | | | |
| STYLE | | HV1812 ⁽¹⁾ | | | HV1825 ⁽¹⁾ | | | HV2220 ⁽¹⁾ | | | HV2225 ⁽¹⁾ | | |
| EIA CODE | | 1812 | | | 1825 | | | 2220 | | | 2225 | | |
| VOLTAGE (V _{DC}) | | 3000 | 4000 | 5000 | 3000 | 4000 | 5000 | 3000 | 4000 | 5000 | 3000 | 4000 | 5000 |
| VOLTAGE CODE | | H | V | M | H | V | M | H | V | M | H | V | M |
| CAP. CODE | CAP. | | | | | | | | | | | | |
| 101 | 100 pF | | | | | | | | | | | | |
| 121 | 120 pF | | | | | | | | | | | | |
| 151 | 150 pF | | | | | | | | | | | | |
| 181 | 180 pF | | | • | | | | | | | | | |
| 221 | 220 pF | | • | • | | | | | | | | | |
| 271 | 270 pF | | • | • | | | | | | | | | |
| 331 | 330 pF | | • | • | | • | • | | | | | | |
| 391 | 390 pF | | • | • | | • | • | | | • | | | |
| 471 | 470 pF | | • | • | | • | • | | • | • | | | • |
| 561 | 560 pF | • | • | • | | • | • | | • | • | | | • |
| 681 | 680 pF | • | • | • | | • | • | | • | • | | • | • |
| 821 | 820 pF | • | • | • | | • | • | | • | • | | • | • |
| 102 | 1.0 nF | • | • | | | • | • | | • | • | | • | • |
| 122 | 1.2 nF | • | • | | • | • | • | • | • | • | | • | • |
| 152 | 1.5 nF | • | • | | • | • | • | • | • | • | | • | • |
| 182 | 1.8 nF | • | | | • | • | • | • | • | • | • | • | • |
| 222 | 2.2 nF | • | | | • | • | | • | • | | • | • | • |
| 272 | 2.7 nF | • | | | • | • | | • | • | | • | • | • |
| 332 | 3.3 nF | • | | | • | • | | • | • | | • | • | • |
| 392 | 3.9 nF | • | | | • | | | • | | | • | • | |
| 472 | 4.7 nF | | | | • | | | • | | | • | • | |
| 562 | 5.6 nF | | | | • | | | • | | | • | • | |
| 682 | 6.8 nF | | | | • | | | • | | | • | | |
| 822 | 8.2 nF | | | | • | | | • | | | • | | |
| 103 | 10 nF | | | | • | | | • | | | • | | |
| 123 | 12 nF | | | | | | | | | | • | | |
| 153 | 15 nF | | | | | | | | | | • | | |
| 183 | 18 nF | | | | | | | | | | | | |


Note

⁽¹⁾ See soldering recommendations within this data book, or visit: www.vishay.com/doc?45034




X7R DIELECTRIC - TYPICAL PARAMETERS


TEMPERATURE COEFFICIENT OF CAPACITANCE




AGING RATE




DISSIPATION FACTOR VS. TEMPERATURE




IMPEDANCE / ESR VS. FREQUENCY HV1812Y181KXMATHV



IMPEDANCE / ESR VS. FREQUENCY HV1812Y152KXVATHV




IMPEDANCE / ESR VS. FREQUENCY HV1825Y182KXMATHV





X7R DIELECTRIC - TYPICAL PARAMETERS



STANDARD PACKAGING QUANTITIES (1)

| CASE CODE | TAPE SIZE | 7" REEL QUANTITIES PACKAGING CODE "T" | 11 1/4" AND 13" REEL QUANTITIES PACKAGING CODE "R" |
|-----------|-----------|--|--|
| 1812 | 12 mm | 1000 | 4000 |
| 1825 | 12 mm | 1000 | 4000 |
| 2220 | 12 mm | 1000 | 4000 |
| 2225 | 12 mm | 500 | 4000 |

Note

(1) Reference: EIA standard RS 481 - "Taping of Surface Mount Components for Automatic Placement"

STORAGE AND HANDLING CONDITIONS

- (1) Store the components at 5 °C to 40 °C ambient temperature and ≤ 70 % relative humidity conditions.
- (2) The product is recommended to be used within a time-frame of 2 years after shipment.
Check solderability in case extended shelf life beyond the expiry date is needed.

Precautions:

- a. Do not store products in an environment containing corrosive elements, especially where chloride gas, sulfide gas, acid, alkali, salt or the like are present. This may cause corrosion or oxidation of the terminations, which can easily lead to poor soldering.
- b. Store products on the shelf and avoid exposure to moisture or dust.
- c. Do not expose products to excessive shock, vibration, direct sunlight and so on.



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Material Category Policy

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А