THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 20
© COPYRIGHT 20 BY - ALL RIGHTS RESERVED.

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	K	REV PER ECO 14-015092	10-6-14	CT	PD







1: WIRE INSULATION :12.7[.500]-14.0[.551]

2: WIRE CMA: 119500 to 150500

3 ;TONGUE RADIUS FEATURE IS NOT A TOOLING CONTROLLED DIMENSION AND MAY NOT BE A TRUE RADIUS

WEIGHT	DIM A	B	MATERIAL&FINISH	PART NUMBER	
80 gms	6.73+/-0.04 [.265+/-.002]	1/4 or M6	BODY: COPPER ASTM B187 ANNEALED TIN PLATE .00381[.000150] MIN THICK PER MIL-T-10727 INSERT&FUNNEL:BRASS ASTM B36 NICKEL PLATE SAE AMS QQ-N-290A, DATED JULY 2000,.00254 [.000100] MIN THICK	134594-4	OBSOLETE
79 gms	8.34±0.04 [.328±.002]	5/16 or M8		134594-3	
78 gms	10.04±0.04 [.395±.002]	3/8 or M10		134594-1	

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm[Inches]

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ±0.3
1 PLC ±0.3
2 PLC ±0.13
3 PLC ±.
4 PLC ±.
ANGLES ±5

MATERIAL -
FINISH -

DWN JJ. DESPRETZ 24JUN2004
CHK G-ROBERT -
APVD Y PETRONIN 24JUN2004
PRODUCT SPEC -
APPLICATION SPEC -
WEIGHT -

TE Connectivity

NAME SEALED COPALUM ASSEMBLY -

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A2	-	C-134594	-

CUSTOMER DRAWING | SCALE 2:1 | SHEET 1 OF 4 | REV K

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 20
© COPYRIGHT 20 BY - ALL RIGHTS RESERVED.

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	-	SEE SHEET 1	-	-	-





1: WIRE INSULATION :12.7[.500]-14.0[.551]

2: WIRE CMA: 119500 to 150500

3: TONGUE RADIUS FEATURE IS NOT A TOOLING CONTROLLED DIMENSION AND MAY NOT BE A TRUE RADIUS

WEIGHT	DIM A	B	MATERIAL&FINISH	PART NUMBER
77 grams	8.34+/-0.04 [.328+/-.002]	5/16 or M8	BODY: COPPER ASTM B187 ANNEALED TIN PLATE .00381[.000150] MIN THICK PER MIL-T-10727	134594-6
78 grams	6.73+/-0.04 [.265+/-.002]	1/4 or M6	INSERT&FUNNEL:BRASS ASTM B36 NICKEL PLATE SAE AMS QQ-N-290A, DATED JULY 2000,.00254 [.000100] MIN THICK	134594-2

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm[Inches]

MATERIAL: -

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	±0.3
1 PLC	±0.3
2 PLC	±0.13
3 PLC	±-
4 PLC	±-
ANGLES	±5

FINISH: -

DWN JJ. DESPRETZ 24JUN2004
CHK G-ROBERT -
APVD Y. PETRONIN 24JUN2004
PRODUCT SPEC -
APPLICATION SPEC -
WEIGHT -

TE Connectivity

NAME SEALED COPALUM ASSEMBLY -

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A2	-	C-134594	-

CUSTOMER DRAWING | SCALE 2:1 | SHEET 2 OF 4 | REV K

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 20
© COPYRIGHT 20 BY - ALL RIGHTS RESERVED.

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	-	SEE SHEET 1	-	-	-





1: WIRE INSULATION :12.7[.500]-14.0[.551]

2: WIRE CMA: 119500 to 150500

3: TONGUE RADIUS FEATURE IS NOT A TOOLING CONTROLLED DIMENSION AND MAY NOT BE A TRUE RADIUS

WEIGHT	DIM A	B	MATERIAL&FINISH	PART NUMBER
77 grams	8.34±0.04 [.328±.002]	5/6 or M8	BODY: COPPER ASTM B187 ANNEALED TIN PLATE .00381[.000150] MIN THICK PER MIL-T-10727 INSERT&FUNNEL:BRASS ASTM B36 NICKEL PLATE SAE AMS QQ-N-290A, DATED JULY 2000,.00254 [.000100] MIN THICK	134594-5

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm[Inches]

MATERIAL: - / -

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ±0.3
1 PLC ±0.3
2 PLC ±0.13
3 PLC ±-
4 PLC ±-
ANGLES ±5
FINISH: - / -

DWN JJ. DESPRETZ 24JUN2004
CHK G-ROBERT -
APVD Y. PETRONIN 24JUN2004
PRODUCT SPEC -
APPLICATION SPEC -
WEIGHT -

TE Connectivity

NAME SEALED COPALUM ASSEMBLY -

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A2	-	C-134594	-

CUSTOMER DRAWING | SCALE 2:1 | SHEET 3 OF 4 | REV K

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 20
© COPYRIGHT 20 BY - ALL RIGHTS RESERVED.

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	-	SEE SHEET 1	-	-	-





1: WIRE INSULATION : 12.7[.500]-14.0[.551]

2: WIRE CMA: 119500 to 150500

3: TONGUE RADIUS FEATURE IS NOT A TOOLING CONTROLLED DIMENSION AND MAY NOT BE A TRUE RADIUS

WEIGHT	DIM A	B	MATERIAL&FINISH	PART NUMBER
76 grams	8.34±0.04 [.328±.002]	5/6 or M8	BODY: COPPER ASTM B187 ANNEALED TIN PLATE .00381[.000150] MIN THICK PER MIL-T-10727 INSERT&FUNNEL:BRASS ASTM B36 NICKEL PLATE SAE AMS QQ-N-290A, DATED JULY 2000,.00254 [.000100] MIN THICK	1134594-7

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm[Inches]

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ±0.3
1 PLC ±0.3
2 PLC ±0.13
3 PLC ±-
4 PLC ±-
ANGLES ±5

MATERIAL -
FINISH -

DWN JJ. DESPRETZ 24JUN2004
CHK G-ROBERT -
APVD Y. PETRONIN 24JUN2004
PRODUCT SPEC -
APPLICATION SPEC -
WEIGHT -

TE Connectivity

NAME SEALED COPALUM ASSEMBLY -

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A2	-	C-1134594	-

CUSTOMER DRAWING | SCALE 2:1 | SHEET 4 OF 4 | REV K

OCEAN CHIPS
Океан Электроники
Поставка электронных компонентов

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «**JONHON**», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «**FORSTAR**».

AVIC JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).

FORSTAR®

Телефон: 8 (812) 309-75-97 (многоканальный)
Факс: 8 (812) 320-03-32
Электронная почта: ocean@oceanchips.ru
Web: http://oceanchips.ru/
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А