



SENSOR SOLUTIONS FOR AEROSPACE & DEFENSE FROM TE CONNECTIVITY

SENSOR SOLUTIONS FOR AEROSPACE & DEFENSE FROM TE CONNECTIVITY

TE Connectivity (TE) is one of the largest connectivity and sensor companies in the world. Our broad portfolio of sensor technologies is designed for a wide range of mission critical applications in Aerospace and Defense and other industries. By leveraging our core competencies in high reliability sensors for harsh environments such as Temperature, RFI, EMI, Vibration, and Lightning, we enable our customers to transform their concepts into creations — redefining what's possible using intelligent, efficient and high-performing TE products and solutions.



SENSOR SOLUTIONS

- FLOW
- FLUID PROPERTY
- FORCE/TORQUE
- HUMIDITY
- LIQUID LEVEL
- RATE/INERTIAL
- POSITION
- PRESSURE
- TEMPERATURE
- ULTRASONIC
- VIBRATION/SHOCK

QUALITY STATEMENTS

- AS/EN 9100
- ATEX
- ESA/ESCC QUALIFIED
- NADCAP
- ISO 14001
- ISO 9001
- MEASURING INSTRUMENTS
DIRECTIVE 2004/22/EC ANNEX D
- NASA/GSFC QUALIFIED
- PART21G
- TS 16949

DESIGN/DEVELOPMENT

- DO-160
- DO-254
- MIL-STD-810
- GRESS

APPLICATION SOLUTIONS FOR AEROSPACE & DEFENSE

Long development cycles and high qualification costs require aerospace companies to identify stable, reliable, cost-effective partners. TE Connectivity has design engineering groups, as well as AS9100 certified sensor manufacturing facilities, in North America, Europe and Asia Pacific which support Tier 1, 2 and 3 providers with a wide variety of critical sensor solutions for aerospace and defense applications. Regional design and manufacturing allows TE to furnish ITAR free designs and supply products close to our customers' assembly facilities.

Cockpit Controls

- Automatic autopilot disconnect force sensors
- Motorized potentiometers for position feedback
- Brake pedal position sensors
- Rotary panel switches and sensors
- Force sensors for flight data recording of pilot inputs
- Throttle quadrant position sensors
- Flap and spoiler lever position sensors

Flight Controls & Actuation

- High lift load sensors
- THSA secondary load path engagement sensors
- Aileron LVDT position sensors
- Resolvers for flap and slat position monitoring
- Force and position sensors for spoiler electro-mechanical actuation
- Brake actuator force sensors for rotorcraft

Landing Gear & Brakes

- Brake torque sensors
- Pressure sensors for Nose Wheel steering feedback
- Resolvers for steering position
- Load on wheels force sensors
- Centre of gravity force sensors

Cabin, Galley & Cargo

- Cabin pressure indicator
- Waste tank level sensors
- Environmental cabin control pressure sensors
- Cargo humidity sensors
- Galley temperature sensors
- Air quality temperature sensors
- Oxygen generation pressure transducers

Launch & Space

- Payload monitoring vibration sensors
- Thrust vectoring LVDT position sensors
- Electrical actuator position resolvers
- Booster separation potentiometers
- Cryogenic fuel pressure transducers
- Satellite temperature sensors
- Mirror/antenna position LVDT sensors

Engine, Turbine & APU

- Thermocouple harnesses for exhaust gas temperature
- LVDT for thrust reverser position monitoring
- Platinum 200 air temperature sensors
- Variable bleed valve LVDT position sensors
- Rotor track and Balance accelerometers
- Health and Usage Monitoring Systems(HUMS) accelerometers
- Thermistor heater fuel tank level and flow

Military (Missile, Ground Vehicle, Marine, UAV...)

- Missile fin actuation
- Fuel tank level & flow sensors
- Gun stabilization and shock measurement
- Tamper detection for missiles
- Electronic safe arm and fire
- Oil pressure and temperature sensors
- Airspeed and altitude sensors



PRESSURE SENSORS

Board Mounted
mV Output



MEAS 1230

Package	8 pin DIL
Type	Gage, absolute, differential
Pressure Range	0 - 5 & 10" H ₂ O 0 - 0.07, 0.14, 0.35, 1, 2, 3, 7 bar / 0 - 1, 2, 5, 15, 30, 50, 100 psi
Output/Span	50 mV and 100 mV typical
Unique Features	<ul style="list-style-type: none"> • Temperature compensated • High performance UltraStable die Current excitation
Accuracy	±0.1% Non-linearity
Operating Temp	-40°C to 125°C
Dimensions (mm)	15.2 x 20.3
Typical Apps	Air flow measurement, leak detection, cabin control, ventilation



MEAS MS52xx, MS54xx

Package	Surface mount
Type	Gage, absolute
Pressure Range	0 - 1, 12 bar / 0 - 15, 174 psi (MS52xx) 0 - 1, 7, 12 bar / 0 - 15, 102, 174 psi (MS54xx)
Output/Span	150 mV, 240 mV
Unique Features	<ul style="list-style-type: none"> • Small size (MS54xx) • High linearity or high sensitivity options • Plastic tube or metal ring options • With gel to protect against moisture • High endurance (Option HM)
Accuracy	±0.05% or ±0.2% Non-linearity
Operating Temp	-40°C to 125°C
Dimensions (mm)	7.6 x 7.6, height model dependent (MS52xx) 6.4 x 6.2 (MS54xx)
Typical Apps	Absolute pressure sensor systems, engine controls, high resolution altimeters, variometers, barometers

Media Isolated Modules
Analog Output



MEAS 89 Button, 89 with Fittings

Package	O-ring mount and threaded / weldable or process fitting
Type	Sealed gage, absolute
Pressure Range	0 - 69, 207, 345 bar / 0 - 1K, 3K, 5K psi
Output/Span	100 mV typical
Unique Features	<ul style="list-style-type: none"> • High pressure, modular design
Accuracy	±0.25% FSO Non-linearity
Operating Temp	-40°C to 125°C
Dimensions (mm)	89 Button: Ø 9.0 x 7.5 89 with Fittings: Ø 22.2 x 23.6
Typical Apps	Air tank pressure, hydraulics, process control, oxygen generation, inerting systems

Transducers and Transmitters



MEAS P900

Package	Threaded ports with stainless steel housing and various heavy duty electrical connections, various electrical outputs
Type	Gage, absolute
Pressure Range	0 - 5 bar to 0 - 689 bar / 0 - 75 psi to 0 - 10K psi
Output/Span	0 - 5 Vdc, 0 - 10 Vdc, 4 - 20 mA
Unique Features	<ul style="list-style-type: none"> • High overpressure (10X over pressure) • Shock & vibration resistant • Heavy Industrial grade transducer • Advanced digital compensation / calibration • Mechanical over pressure stops • High temperature operation
Accuracy	0.1% to 0.2% FSO
Operating Temp	-54°C to 120°C
Dimensions (mm)	Application dependent
Typical Apps	Hydraulic controls / steering, torpedo depth, vehicle braking systems, drones, weapon systems
Agency Approvals	CE, CENELEC (Intrinsically Safe)



MEAS M7100, U7100

Package	Automotive grade, stainless steel hermetic pressure ports and integral electrical connector, heavy duty
Type	Gage, no vent gage (M7100) Gage, sealed gage, absolute (U7100)
Pressure Range	0 - 10 thru 0 - 689 bar / 0 - 150 thru 0 - 10K psi (M7100) 0 - 1 thru 0 - 10 bar / 0 - 15 thru 0 - 150 psi (U7100)
Output/Span	0.5 - 4.5 Vdc [Ratiometric Output]; 1 - 5 Vdc [Regulated] (M7100) 0.5 - 4.5 Vdc [Ratiometric Output] (U7100)
Unique Features	<ul style="list-style-type: none"> • 1% total error band (-20°C to 85°C) • Solid state reliability • Survives high vibration and immersion • Microfused technology (M7100) • UltraStable technology (U7100)
Accuracy	0.25% FSO
Operating Temp	-40°C to 125°C
Dimensions (mm)	26.7 x 26.7 x 50.0
Typical Apps	Military vehicles engine control, compressors, hydraulic
Agency Approvals	CE (EMC), UL 508

PRESSURE SENSORS

Miniature Transducers and Transmitters



MEAS XP Series

Unique Features	<ul style="list-style-type: none"> • Titanium construction (XP5, XPM4) • Stainless steel housing (XPM6, XPM10) • Amplified output options (XP5, XPM6, XPM10) • Cable and connector options (XPM4) • For static and dynamic applications
Non Linearity	Up to $\pm 0.25\%$ FSO (XP5, XPM6, XPM10) Up to $\pm 0.35\%$ FSO (XPM4)
Output/Span	20, 30, 75, 100mV (XP5) 30mV, 60mV, 100mV (XPM4) 100mV (XPM6) 50, 100mV (XPM10)
Pressure Range	1 - 345 bar / 15 - 5K psi (XP5, XPM10) 5 - 207 bar / 75 - 3K psi (XPM4) 103 - 1K bar / 1.5K - 15K psi (XPM6)
Overpressure	2X
Operating Temp	-40°C to 120°C
Dimensions (mm)	XP5: Hex 10 XPM4: Hex 8 XPM6: Hex 12 XPM10: Hex 15
Typical Apps	Military and aerospace, explosive test benches, space



MEAS XPC10

Unique Features	<ul style="list-style-type: none"> • Amplified output available • For static and dynamic applications • Optional IP67 ingress protection • High temperature operation
Non Linearity	Up to $\pm 0.25\%$ F.S.
Output/Span	12mV FSO, 4V FSO (amplified)
Pressure Range	0 - 10, 21, 34, 52, 69, 103, 207, 345, 517 bar / 0 - 150, 300, 500, 750, 1K, 1.5K, 3K, 5K, 7.5K psi
Overpressure	1.5X
Operating Temp	-40°C to 220°C
Dimensions (mm)	Hex 15
Typical Apps	Aerospace, test benches, high frequency / high temperature pressure applications



MEAS EPIH

Unique Features	<ul style="list-style-type: none"> • Diffused silicon diaphragm with a large variety of sizes and shapes available as small as 0.05" outside diameter • High frequency response (to 1.7 MHz)
Non Linearity	$\pm 1.0\%$ FSO
Output/Span	12 mV to 75 mV
Pressure Range	0 - 0.35, 0.69, 1, 2, 3, 5, 7, 14, 21 bar / 0 - 5, 10, 15, 25, 50, 75, 100, 200, 300 psi
Overpressure	2X to 5X
Operating Temp	-40°C to 120°C
Dimensions (mm)	Application dependent
Typical Apps	Aerospace testing, wind tunnels, aircraft body and wing dynamics

FORCE / TORQUE SENSORS



MEAS FN HL Series

Package	Flange mount
Operating Mode	Tension/Compression
Unique Features	<ul style="list-style-type: none"> • Extremely robust design • Very high EMC/RFI immunity
Ranges N (Lbf)	Airframe dependent
Output	4/20 mA
Temperature Range	-70°C to +90°C
Dimensions	Airframe dependent
Typical Apps	Measurement of force between geared rotary actuator and slat on high lift systems



MEAS FN TH Series

Package	Load pin
Operating Mode	Tension
Unique Features	<ul style="list-style-type: none"> • Built in test feature • Dual redundant • Very high ultimate load
Ranges N (Lbf)	Airframe dependent
Output	0.5 to 5.5Vdc or 4/20mA
Temperature Range	-70°C to +90°C
Dimensions	Airframe dependent
Typical Apps	Detection of secondary load path engagement on trimmable horizontal stabilizer actuator



MEAS FN PC Series

Package	Tail stock/control rod
Operating Mode	Tension/Compression
Unique Features	<ul style="list-style-type: none"> • Compact • Extremely high performance design • Mono or dual channel
Ranges N (Lbf)	Airframe dependent
Output	0.5 to 10.5Vdc
Temperature Range	-55°C to +55°C
Dimensions	Airframe dependent
Typical Apps	Monitoring of pilot input forces for flight data recording

FORCE / TORQUE SENSORS



MEAS FN EM Series

Package	Pancake
Operating Mode	Compression
Unique Features	<ul style="list-style-type: none"> Ultra-flat for integration directly into electro-mechanical actuators
Ranges N (Lbf)	Airframe dependent
Output	0.5 to 10.5Vdc
Temperature Range	-55°C to 55°C
Dimensions	Airframe dependent
Typical Apps	Compression force measurement electro-mechanical actuators



MEAS VR BT Series

Pin	
Torque	
Unique Features	<ul style="list-style-type: none"> High temperature variable reluctance technology
Ranges N (Lbf)	Airframe dependent
Output	50mV rms (AC)
Temperature Range	-40°C to 150°C
Dimensions	Airframe dependent
Typical Apps	Monitoring of force brakes



MEAS FN AF Series

Load pin	
Compression	
Unique Features	<ul style="list-style-type: none"> Built in test feature, dual redundant Very high ultimate load
Ranges N (Lbf)	Airframe dependent
Output	0.5 to 5.5Vdc or 4/20mA
Temperature Range	-70°C to 90°C
Dimensions	Airframe dependent
Typical Apps	Monitoring of force between the electrical actuator and the ailerons

TEMPERATURE SENSORS

Sensing Elements



MEAS Platinum Thin Film Chips

RTD Package	Leadless chips
Type	<ul style="list-style-type: none"> Thin film platinum deposited on ceramic substrate Contact pads on top and bottom side for NTC chip like assembly Contact pads on both ends for SMT
Resistance Range	100Ω, 1000Ω (Other values on request)
Unique Features	<ul style="list-style-type: none"> Long term stability Interchangeability Assembly like NTC chips Very small dimensions Short response time
Accuracy	According to DIN EN 60751
Operating Temp	-50°C to +400°C
Dimensions (mm)	1.5 x 1.5 (top / bottom pads) 1.2 x 3.6 (SMT)
Typical Apps	Aerospace, test and measurement



MEAS Platinum Thin Film Sensors

Wired component	
Unique Features	<ul style="list-style-type: none"> Thin film platinum deposited on ceramic substrate, glass coated Tube outline available Connection via radial leads
Resistance Range	100Ω, 1000Ω (Other values on request)
Unique Features	<ul style="list-style-type: none"> Long term stability Interchangeability Small dimensions Short response time High electrical insulation
Accuracy	Class T (F0.1), A (F0.15), B (F0.3) according to DIN EN 60751
Operating Temp	-50°C to 600°C (standard) down to -200 °C or up to 1000 °C (on request)
Dimensions (mm)	2.0 x 2.3 x 1.1 (standard) 1.2 x 4.0 x 1.1 (standard) other dimensions (on request)
Typical Apps	Aerospace, test and measurement



MEAS Glass Wire Wound Sensors

GO, GX	
Unique Features	<ul style="list-style-type: none"> RTD Glass rod Radial leads
Resistance Range	100Ω (2x100Ω on few versions)
Unique Features	<ul style="list-style-type: none"> Aggressive environments (acid, oil, solvent) Small dimensions Stability No hysteresis Short response time Interchangeability
Accuracy	Class W0.3, W0.15, W0.1 according to IEC60751
Operating Temp	-200°C to 400°C
Dimensions (mm)	Ø 1.8 / Length 5mm to Ø 4.5 / Length 48mm
Typical Apps	Aviation and aeronautics

TEMPERATURE SENSORS

Sensing Elements



MEAS Space Qualified (Hi-Rel)

Package	Radial, bead, custom
Type	<ul style="list-style-type: none"> Epoxy Glass Probes ESCC 4006013 ESCC 4006014 GSFC 319-P18 449900 Series
Resistance Range	1kΩ to 100kΩ
Unique Features	<ul style="list-style-type: none"> ESA and NASA approved High reliability and accuracy
Accuracy	0.5% to 10%
Operating Temp	-55°C to 115°C
Dimensions (mm)	From 2.4
Typical Apps	Instrumentation and compensation



MEAS Nickel RTD

<ul style="list-style-type: none"> SOT 23, bare die on request Thin film nickel structure on silicon substrate, protected with a passivation layer SOT23 Package for SMT Good thermal connection of sensing element through leadframe-pin Bare die for COB assembly
1000Ω
<ul style="list-style-type: none"> Harsh environment compatible Automotive qualified Very small dimensions Very short response time Good linearity High temperature coefficient Low power consumption
Class B, according to former DIN 43760 standard
-55 °C to 160 °C
2.1 x 2.5 x 2.1 (SOT23), 0.7 x .7 x 0.4 (bare die)
Thermal compensation, thermal management



MEAS Radial Leaded Thermistors

<ul style="list-style-type: none"> NTC Epoxy or glass coated
Radial, axial, beads
100 to 1MΩ
<ul style="list-style-type: none"> Interchangeable Moisture resistant Stability
0.25% to 20%
-55°C to 280°C
0.4 to 4.9
Temperature sensing for OEM



MEAS Axial Thermistors

<ul style="list-style-type: none"> NTC Glass coated
DO-35
5kΩ to 100kΩ
<ul style="list-style-type: none"> Tight tolerance (±1%) Max stability using high density (HD) chip Hermetically sealed Tinned & Nickel plated leads
±1% to ±3%
-40°C to 300°C
2.0 x 4.0 body
Fire detection units, PCB temp sensing

Sensor Assemblies



MEAS Thermocouple Probes and Harnesses

Package	Screw-in or push-in design with cable extension, connector, or connecting head
Type	<ul style="list-style-type: none"> Collapsible Mineral Insulated (MI) with alloy sheath (radius≥5*OD) Flexible cable with plastic or composite insulation Rigid protection sheath: ceramic, quartz or alloy sheath
Sensor Range	Type T, J, K, N, R, S, B (According to TC type and insulation type)
Unique Features	<ul style="list-style-type: none"> High temperature and high vibration level (for MI) Available in small diameters for fast respond time Grounded or ungrounded or apparent hot junction Single or multiple measuring points
Accuracy	Class 1 according to IEC584
Operating Temp	-40°C to 1700°C (according to TC type and insulation type)
Dimensions (mm)	<ul style="list-style-type: none"> OD Ø0.3 mm to Ø8 mm for MI ø0.15mm for smallest flexible cable Custom dimensions, fittings and cable lengths (from few centimeters to many meters)
Typical Apps	Engine temperature



MEAS Surface Sensors

<ul style="list-style-type: none"> RTD: Pt, Ni, Cu Thermocouple: Type J, K, T, E
Silicone rubber or polyimide laminated element, SP683
<ul style="list-style-type: none"> Flat, flexible, rectangular sensor Variety of designs available
<ul style="list-style-type: none"> Surface sensing for curved or uneven surfaces Noninvasive, simple installation Adhesive backing option
RTD: Class A, B according to IEC60751
Varies: -50°C to 200°C Available up to 220°C
Custom dimensions available
Aerospace, motor end windings of stator coils, generators

POSITION SENSORS

Angular Position Sensors, Encoders Absolute



MEAS Resolver

Package	Hollow Shaft, Size 15
Range	360 degrees absolute
Output	Analog (sin, cos)
Input Voltage (VR1-R2), Typical	2V rms - 10Vrms
Input Frequency, Typical	4kHz - 20kHz
Operating Temperature	-55°C to 150°C
Angular Error Rang, Typical	±7 arcmin to ± 20 arcmin
Pairs of Pole	1 / 3
Maximum Rational Speed	20,000 rpm
Weight	Approx. 90g
Unique Feature	Robust, wear-free, EMI insensitive
Typical Apps	Angular position of rotary actuators, rotating shafts



MEAS Resolver

Package	Hollow Shaft, Size 21
Range	360 degrees absolute
Output	Analog (sin, cos)
Input Voltage (VR1-R2), Typical	2V rms - 12V rms
Input Frequency, Typical	2kHz - 15kHz
Operating Temperature	-55°C to 150°C
Angular Error Rang, Typical	±7 arcmin to ± 20 arcmin
Pairs of Pole	1 / 2 / 3 / 4
Maximum Rational Speed	20,000 rpm
Weight	Approx. 240g
Unique Feature	Robust, wear-free, EMI insensitive
Typical Apps	Angular position of e-motors (commutation) and permanent magnet generators



MEAS Resolver

Package	Input Shaft, Integrated Bearing, Size 11
Range	360 degrees absolute
Output	Analog (sin, cos)
Input Voltage (VR1-R2), Typical	2V rms
Input Frequency, Typical	2,5kHz
Operating Temperature	-55°C to 150°C
Angular Error Rang, Typical	±10 arcmin
Pairs of Pole	1
Maximum Rational Speed	10,000 rpm
Weight	Approx. 120g
Unique Feature	Robust, wear-free, EMI insensitive
Typical Apps	Measuring angular position of cockpit controls (lever, stick and pedal)



MEAS Synchro

Package	Input Shaft, Integrated Bearing, Size 11
Range	360 degrees absolute
Output	Analog (3 phase)
Input Voltage (VR1-R2), Typical	21V rms - 26V rms
Input Frequency, Typical	400Hz - 2500Hz
Operating Temperature	-55°C to 150°C
Angular Error Rang, Typical	±5 arcmin to ±10 arcmin
Pairs of Pole	1
Maximum Rational Speed	10,000 rpm
Weight	Approx. 150g
Unique Feature	Robust, wear-free, EMI insensitive
Typical Apps	Angular position of cockpit controls (lever, stick and pedal)



MEAS Multiturn Position Sensor Unit

Package	Input Shaft, Integrated Bearing, Customized [1]
Range	Multiturn (50.400 to 129.600) degree
Output	2 x Analog (3 phase), Redundant
Input Voltage (VR1-R2), Typical	21V rms - 26V rms
Input Frequency, Typical	400Hz - 2500Hz
Operating Temperature	-55°C to 90°C
Angular Error Rang, Typical	±80 arcmin (400Hz) / ±25 arcmin (2.500Hz)
Pairs of Pole	1
Maximum Rational Speed	600 rpm
Weight	Approx. 935g [1]
Unique Feature	Robust, DO160 qualified
Typical Apps	Multiturn position of primary and secondary flight control actuators

POSITION SENSORS

Potentiometers, Angular Position Sensors



MEAS 6000 Series
Servo Mount

Package

- 12.7 mm - 50.8 mm / .500 in - 2.00 in housing diameter
- 3.170mm - 6.34mm / .1248 in - .2498 in shaft diameter
- 12.7mm - 1.74mm / .500 in - .680 in housing length
- 11.1mm - 47.62mm / .438 in - 1.875 in mounting pilot diameter

Resistance

1K - 20K

Range

Up to 355 degrees

Linearity

± 0.5%

Output Smoothness

<0.1%

Resolution

Infinite

Operating Temp

-65°C to 125°C

Rotational Life

50 million cycles min.

Typical Apps

Flight control actuators, missile fin actuators



MEAS 6200 Series
Bushing Mount

- 12.7 mm - 50.8 mm / .500 in - 2.00 in housing diameter
- 3.170mm - 6.34mm / .1248 in - .2498 in shaft diameter
- 12.7mm - 1.74mm / .500 in - .680 in housing length
- 3/8 32 NEF thread / 10.31mm / .4062 in pilot diameter

Resistance

1K - 20K

Range

Up to 355 degrees

Linearity

± 0.5%

Output Smoothness

<0.1%

Resolution

Infinite

Operating Temp

-65°C to 125°C

Rotational Life

50 million cycles min.

Typical Apps

Rocket engine fuel valves, brake pedals



MEAS 6900 Series
Element/Wiper/Insul

- 17.81 mm - 45.85mm / .702 in - 1.805 in element outside diameter
- 4.724 mm - 11.05mm / .186 in - .435 in element inside diameter
- 3.175 mm - 6.35 mm / .125 in - .250 shaft insulator inside diameter
- 4.064 mm - 7.80mm / .160 in - .307 in mating wiper inside diameter
- 5.08 mm / .200 in assembled package height

Resistance

1K / 5K / 10K

Range

Up to 355 degrees

Linearity

± 0.5%

Output Smoothness

< 0.1%

Resolution

Infinite

Operating Temp

-65°C to 125°C

Rotational Life

50 million cycles min.

Typical Apps

Cargo handling systems, cockpit controls



MEAS 6100 Series
Hollow Shaft

- 27.94 mm - 66.5 mm / 1.100 in - 2.62 in housing diameter
- 3.175 mm - 19 mm / .125 in - .752 in hollow shaft diameter

Resistance

1K - 20 K

Range

Up to 355 degrees

Linearity

± 0.5%

Output Smoothness

< 0.1%

Resolution

Infinite

Operating Temp

-65°C to 125°C

Rotational Life

50 million cycles min.

Typical Apps

Targeting pod gimbals, missile thrust diverters

Linear Position Transducers Cable Extension Transducers



MEAS M150, MTA

Range

0 - 1.5 to 0 - 5 inches

Output

Voltage divider

**Environment/
IP Rating**

IP50

Enclosure

Aluminum

Accuracy

±0.4% to ±1%

Unique Features

- M150, one of the world's smallest stringpot
- Designed for space-critical and testing applications

Operating Temp

-40°C to 85°C (M150)
-55°C to 100°C (MTA)

Dimensions (mm)

19 x 19 x 10 (M150)

Typical Apps

Aerospace



MEAS MT2, MT3

Range

0 - 3 to 0 - 30 inches

Output

Voltage divider, incremental encoder

**Environment/
IP Rating**

IP50, IP67 (MT3A)

Enclosure

Aluminum and polycarbonate

Accuracy

±0.25% to ±1.1%

- Designed for test applications
- Dual-axis measuring cable alignment
- Tracks high-acceleration linear position up to 136g's
- High-frequency response
- GAM EG 13 certification

Operating Temp

-55°C to 125°C

Dimensions (mm)

55 x 45 x 55

Typical Apps

Aerospace and flight testing

Potentiometers, Linear Position Sensors



MEAS 5903 / 5905 Series
Linear Motion

Package

- 7.94 mm - 12.7 mm / .312 in - .500 in housing diameter
- 1.98 mm - 3.18 mm / .078 in - .125 in shaft diameter

Resistance

1K / 5K / 10K

Range

5903 series - up to 50.8 mm / 2 in stroke
5905 series - up to 101.6 mm / 4 in stroke

Linearity

±1%

Output Smoothness

<0.1%

Resolution

Infinite

Operating Temp.

-65°C to 125°C

Rotational Life

50 million cycles min

Typical Apps

Flight control actuators, targeting pod gimbals, nose wheel position

POSITION SENSORS

Linear Position Transducers,
Inductive Absolute



MEAS M12

Package	AISI-304 Series Stainless steel
Linearity	±0.25% of range
Excitation	AC operated
Output	AC voltage
Range	±10 to ±100 mm
Unique Features	<ul style="list-style-type: none"> • Metric series • High stroke to length ratio • Constant sum of secondaries • Excellent temperature coefficient
Operating Temp	-55°C to 150°C (220°C optional)
Diameter (mm)	12
Typical Apps	Hydraulic spool valve position feedback, flight simulators, engine thrust reversers

Angular Position Sensors,
Hall Effect Absolute



MEAS H005 / H009 Series

Package	<ul style="list-style-type: none"> • 12.7 mm - 22.19 mm / .500 in - .875 in housing diameter • 3.170 mm / .1248 in shaft diameter • 16.9 mm - 17.4 mm / .670 in - .680 in housing length
Range	Up to 359 degrees
Output Options	Analog / PWM / Serial
Resolution	12 Bit - Analog / PWM 14 Bit - Serial
Linearity	± 0.2%
Nominal Supply	5 volts
Operating Temp	-40°C to 150°C
Rotational Life	> 100 million cycles (bearing life)
Typical Apps	Missile fin actuation

MEAS H009-1200 Series Dual Output

Package	<ul style="list-style-type: none"> • 22.23 mm / .875 in housing diameter • 3.170 mm / .1248 in shaft diameter • 26.1 mm / 1.03 in housing length
Range	Up to 359 degrees (dual output)
Output Options	Analog / PWM / Serial
Resolution	12 Bit - Analog / PWM 14 Bit - Serial
Linearity	± 0.2% (dual output)
Nominal Supply	5 volts (dual output)
Operating Temp	-40°C to 150°C
Rotational Life	> 100 million cycles (bearing life)
Typical Apps	Missile fin actuation

VIBRATION SENSORS

DC Accelerometers



MEAS 3038

Package	SMD
Type	MEMS, Board level
F.S. Range (g)	±50, 100, 200, 500, 2000, 6000
Unique Features	<ul style="list-style-type: none"> • Hermetically sealed • High over-range protection • Gas damping
Accuracy	±0.5% Non-linearity
Excitation Voltage	—
Operating Temp	-54°C to 125°C
Dimensions (mm)	7.62 x 7.62 x 3.3
Typical Apps	Vibration / shock monitoring, embedded systems, shock testing, safe and arm



MEAS EGAXT

Package	Stainless steel
Type	Plug and Play, Unamplified, Adhesive / Screw mount
F.S. Range (g)	±5 through 2500
Unique Features	<ul style="list-style-type: none"> • Sub-miniature • Lightweight • 10,000 g over-range protection
Accuracy	±1.0% Non-linearity
Excitation Voltage	—
Operating Temp	-40°C to 120°C
Dimensions (mm)	7.2 x 4.6 x 4.6
Typical Apps	Flight test and control, launch, crash, impact testing, robotics



MEAS 4602/4604HT

Package	Anodized aluminum
Type	Plug and Play, Amplified, Screw mount
F.S. Range (g)	±2, 10, 30, 50, 100, 200, 500
Unique Features	<ul style="list-style-type: none"> • Exceptional temp compensation • HT version to 170°C • High over-range • Hermetically sealed
Accuracy	±1.0% Non-linearity
Excitation Voltage	8 - 36 Vdc / 8 - 18 Vdc (HT)
Operating Temp	-54°C to 170°C (HT)
Dimensions (mm)	21.08 x 21.59 x 7.62
Typical Apps	Flight testing on engines, flutter test, weapons development

VIBRATION SENSORS

DC Accelerometers
Plug and Play



MEAS 3420XA

Package	Anodized aluminum
Type	±1 to 500
F.S. Range (g)	Triaxial
Unique Features	<ul style="list-style-type: none"> • Analog output • Precision aligned • Performance over temperature
Accuracy	±0.2% Non-linearity
Excitation Voltage	8.5 to 36 VDC
Operating Temp	-40°C to 85°C
Dimensions (mm)	24 x 24 x 28.30
Typical Apps	Safety system, military research and development



MEAS 3520XA

Package	Anodized aluminum
Type	±1 to 500
F.S. Range (g)	1, 2, or 3
Unique Features	<ul style="list-style-type: none"> • Digital output • Direct to PC • User configurable settings
Accuracy	±0.2% Non-linearity
Excitation Voltage	8.5 to 36 VDC
Operating Temp	-40°C to 85°C
Dimensions (mm)	52 x 36.50 x 17.50
Typical Apps	Impact detection, stores separation

Piezoelectric Accelerometers
Plug and Play



MEAS 7202A/7204A


Package	Stainless steel
Type	Voltage mode plug, through hole mount
Sensitivity (mV/g)	100, 10
Unique Features	<ul style="list-style-type: none"> • Annular shear mode • Integral strain relief • Case isolated, internally shielded • 3-pin connector • +150°C option
Operating Temp	-55°C to 130°C
Dimensions (mm)	13.34 x 19.05
Typical Apps	HUMS applications, rotor track and balance

PIEZO FILM SENSORS



MEAS Piezo Cable

Package	Shielded coaxial 20 gage piezo cable
Type	Polymer jacketing; armored jacketing
Range	µPa sensitivity
Unique Features	<ul style="list-style-type: none"> • Continuous lengths to 1km • Shielded construction
Accuracy	±20% (typical)
Operating Temp	-40°C to 85°C (up to 100°C available)
Dimensions (mm)	3 mm diameter; continuous lengths
Typical Apps	Geophone, impact sensors, intrusion detection



MEAS Tamper Box

Package	Flat film or box mounted
Type	Tamper detection sensor
Range	Application dependent
Unique Features	<ul style="list-style-type: none"> • Low power • Custom shapes and sizes • High security
Accuracy	Application dependent
Operating Temp	-40°C to 85°C
Dimensions (mm)	Application dependent
Typical Apps	Encryption modules, POS card readers, PIN entry devices, tamper

ULTRASONIC SENSORS

Standard Contact Point Level



MEAS LL-01

Type	Gap
Unique Features	<ul style="list-style-type: none"> • All 316L SS • Integral electronics • Miniature threads • Single machined • No adjustment for viscosity, density
Input	6 - 24VDC
Output	1/2A contact
Pressure	250 psi
Temperature	100°C
Actuation point	0.25"
Process Connection	1/4"NPT & 1/2"NPT
Cable	12"
Approvals	CE
Typical Apps	Compressors, coolant reservoirs



MEAS LL-10

Type	Tip
Unique Features	<ul style="list-style-type: none"> • All 316L SS • Integral electronics • No adjustment for viscosity, density
Input	9 - 24VDC
Output	1A SPDT
Pressure	1000 psi
Temperature	100°C
Actuation point	2.25" standard
Process Connection	3/4"NPT
Cable	12"
Approvals	CE
Typical Apps	Hydraulic reservoirs, dark water

PRODUCT AND APPLICATION MATRIX	Flow	Fluid Property	Force/Torque	Humidity	Liquid Level	Rate/Inertial	Position	Pressure	Temperature	Ultrasonic	Vibration/Shock
Cockpit Controls			●				●				
Flight Controls and Actuation			●				●				
Landing Gear & Brakes			●				●	●			
Cabin, Galley & Cargo				●	●		●	●	●	●	
Launch & Space			●				●	●	●		●
Engine, Turbine & APU	●				●		●	●	●		●
Military (Missile, Ground Vehicle, Marine, UAV...)	●	●			●	●	●	●	●	●	●

te.com/aerospacedefense-sensorsolutions

© 2016 TE Connectivity. All Rights Reserved.

Microfused, UltraStable, Measurement Specialties, MEAS, TE Connectivity, TE, and the TE connectivity (logo) are trademarks of the TE Connectivity Ltd. family of companies. Other logos, product and company names mentioned herein may be trademarks of their respective owners.

While TE has made every reasonable effort to ensure the accuracy of the information in this brochure, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this brochure are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.

SS-TS-AD200 08/2016

TE CONNECTIVITY

For More Information Contact TE

te.com/sensorsolutions-contact

www.te.com



Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А