

30 V to 60 V PTC Thermistors For Overload Protection



FEATURES

- Wide range of trip and non-trip currents:
From 94 mA up to 2 A for the trip current
- Small ratio between trip and non-trip currents
($I_t/I_{nt} = 1.5$ at 25 °C)
- High maximum overload current (up to 23 A)
- Leaded parts withstand mechanical stresses and vibration
- UL file E148885 according to XGPU standard UL1434
- UL approved PTCs are guaranteed to withstand severe test programs
 - Long-life cycle tests (over 5000 trip cycles)
 - Long-life storage tests (3000 h at 250 °C)
 - Electrical cycle tests at low ambient temperatures (- 40 °C or 0 °C)
 - Damp-heat and water immersion tests
 - Overvoltage tests at up to 200 % of rated voltage
- Compliant to RoHS directive 2002/95/EC and in accordance to WEEE 2002/96/EC


RoHS
COMPLIANT

APPLICATIONS

Over-temperature/over-load protection:

- Telecommunications
- Automotive systems
- Industrial electronics
- Consumer electronics
- Electronic data processing

DESCRIPTION

These directly heated thermistors have a positive temperature coefficient and are primarily intended for overload protection. They consist of a naked disk with two tinned brass or copper clad steel leads and are coated with a high temperature silicone UL 94 V-0 coating. Leadless disks and leaded disks without coating are available on request.

MOUNTING

The PTC Thermistors are suitable for processing on automatic insertion equipment.

Typical soldering

235 °C; duration: 5 s (Pb-bearing)
245 °C, duration: 5 s (Lead (Pb)-free)

Resistance to soldering heat

260 °C, duration: 10 s max.

MARKING

Only the grey lacquered thermistors with a diameter of 8.5 mm to 20.5 mm are marked with BC, R_{25} value (example 1R9) on one side and I_{nt} , V_{max} . on the other side.

| QUICK REFERENCE DATA | | |
|---|--------------|----------|
| PARAMETER | VALUE | UNIT |
| Maximum voltage (DC or AC) | 30 to 60 | V |
| Holding current | 0.094 to 2 | A |
| Resistance at 25 °C (R_{25}) | 0.3 to 50 | Ω |
| I_{max} . | 0.8 to 23 | A |
| Switch temperature | 140 | °C |
| Operating temperature range at max. voltage | - 40 to + 85 | °C |
| Climatic category | 40/125/56 | |

| ELECTRICAL DATA AND ORDERING INFORMATION for 2381 66. 5...1; max. voltage = 30 V to 60 V (AC or DC) ⁽¹⁾ | | | | | | | | | |
|--|---|----------------------------------|------------------|---|---|-----------------------------|---------------------|-----------------|----------------|
| I _{nt} MAX. at 25 °C (mA) | I _t MIN. at 25 °C (mA) | R ₂₅ ± 20 % (Ω) | V MAX. (V) | I MAX. ⁽²⁾ at 25 °C (mA) | I _{res} MAX. at V _{max.} and 25 °C (mA) | DISSIP. FACTOR (mW/K) | Ø D MAX. (mm) | CATALOG NUMBERS | |
| | | | | | | | | BULK | TAPE ON REEL |
| 94 | 145 | 50 | 60 | 800 | 22 | 6.9 | 5 | 2381 660 59491 | 2381 660 69491 |
| 130 | 195 | 25 | 60 | 1200 | 25 | 6.9 | 5 | 2381 660 51311 | 2381 660 61311 |
| 180 | 270 | 13 | 30 | 1700 | 45 | 6.9 | 5 | 2381 660 51811 | 2381 660 61811 |
| 270 | 405 | 6 | 30 | 2500 | 60 | 6.9 | 5 | 2381 660 52711 | 2381 660 62711 |
| 320 | 480 | 5 | 30 | 3500 | 62 | 7.8 | 7 | 2381 661 53211 | 2381 661 63211 |
| 410 | 615 | 3 | 30 | 4500 | 65 | 7.8 | 7 | 2381 661 54111 | 2381 661 64111 |
| 470 | 705 | 2.5 | 30 | 5000 | 70 | 8.8 | 8.5 | 2381 661 54711 | 2322 661 64711 |
| 540 | 810 | 1.9 | 30 | 6000 | 75 | 8.8 | 8.5 | 2381 661 55411 | 2381 661 65411 |
| 610 | 915 | 1.7 | 30 | 7000 | 80 | 9.9 | 10.5 | 2381 662 56111 | 2381 662 66111 |
| 700 | 1050 | 1.3 | 30 | 8000 | 90 | 9.9 | 10.5 | 2381 662 57011 | 2381 662 67011 |
| 830 | 1245 | 1.1 | 30 | 10 000 | 100 | 11.5 | 12.5 | 2381 662 58311 | 2381 662 68311 |
| 920 | 1380 | 0.9 | 30 | 11 000 | 105 | 11.5 | 12.5 | 2381 662 59211 | 2381 662 69211 |
| 1170 | 1755 | 0.7 | 30 | 13 500 | 140 | 14.5 | 16.5 | 2381 663 51121 | - |
| 1390 | 2085 | 0.5 | 30 | 16 000 | 170 | 14.5 | 16.5 | 2381 663 51321 | - |
| 1770 | 2655 | 0.4 | 30 | 20 000 | 200 | 18.7 | 20.5 | 2381 664 51721 | - |
| 2050 | 3075 | 0.3 | 30 | 23 000 | 220 | 18.7 | 20.5 | 2381 664 52021 | - |

Notes

⁽¹⁾ The thermistors are clamped at the seating plane.

⁽²⁾ I_{max.} is the maximum overload current that may flow through the PTC when it passes from the low ohmic to the high ohmic state.


UL approval: I_{max.} x 0.85

| SAP AND 12NC PART NUMBERS | | | |
|---------------------------|----------------|----------------|----------------|
| 12NC | SAP CODING | 12NC | SAP CODING |
| 2381 660 x9491 | PTCCL05H940EyE | 2381 662 x6111 | PTCCL11H611DyE |
| 2381 660 x1311 | PTCCL05H131EyE | 2381 662 x7011 | PTCCL11H701DyE |
| 2381 660 x1811 | PTCCL05H181DyE | 2381 662 x8311 | PTCCL13H831DyE |
| 2381 660 x2711 | PTCCL05H271DyE | 2381 662 x9211 | PTCCL13H921DyE |
| 2381 661 x3211 | PTCCL07H321DyE | 2381 663 51121 | PTCCL17H112DBE |
| 2381 661 x4111 | PTCCL07H411DyE | 2381 663 51321 | PTCCL17H132DBE |
| 2381 661 x4711 | PTCCL09H471DyE | 2381 664 51721 | PTCCL21H172DBE |
| 2381 661 x5411 | PTCCL09H541DyE | 2381 664 52021 | PTCCL21H202DBE |

Notes

- For bulk parts replace x by "5" and y by "B"
- For taped on reel parts replace x by "6" and y by "T"

CURRENT DEVIATION AS A FUNCTION OF THE AMBIENT TEMPERATURE



VOLTAGE DERATING AS A FUNCTION OF AMBIENT TEMPERATURE

ELECTRICAL CHARACTERISTICS I_{max} . AS A FUNCTION OF VOLTAGE


I_{max} . as stated in the electrical data and ordering information tables, is the maximum overload current that may flow through the PTC when passing from the low ohmic to high ohmic state at rated voltage.

When other voltages are present after tripping, the I_{max} . value can be derived from the above I_{max} . as a function of voltage graph. Voltages below V_{rated} will allow higher overload currents to pass the PTC.

TYPICAL TRIP-TIME AS A FUNCTION OF TRIP CURRENT RATIO


Curve 1: $\varnothing D_{max} = 20.5$ mm
 Curve 2: $\varnothing D_{max} = 16.5$ mm
 Curve 3: $\varnothing D_{max} = 12.5$ mm
 Curve 4: $\varnothing D_{max} = 10.5$ mm
 Curve 5: $\varnothing D_{max} = 8.5$ mm
 Curve 6: $\varnothing D_{max} = 7.0$ mm
 Curve 7: $\varnothing D_{max} = 5.0$ mm
 Measured in accordance with "IEC 60738".

Trip-time or switching time (t_s)

To check the trip-time for a specific PTC, refer to the Electrical Data and Ordering Information tables for the value I_{nt} . Divide the overload or trip current by this I_{nt} and you realize the factor I_t/I_{nt} . This rule is valid for any ambient temperature between 0 °C and 70 °C. Adapt the correct non-trip current with the appropriate curve in the Current Deviation as a Function of the Ambient Temperature graph. The relationship between the I_t/I_{nt} factor and the switching time is a function of the PTC diameter; see the above graphs.

Example

What will be the trip-time at $I_{ol} = 3$ A and $T_{amb} = 0$ °C of a thermistor type 2381 661 54711; 2.5 Ω ; $\varnothing D_{max} = 8.5$ mm:

I_{nt} from the table: 470 mA at 25 °C

I_{nt} : 470 x 1.12 = 526 mA (at 0 °C).

Overload current = 3 A; factor I_t/I_{nt} : $3/0.526 = 5.70$. In the typical trip-time as a function of trip current ratio graph, at the 8.5 mm line and $I_t/I_{nt} = 5.70$, the typical trip-time is 1.7 s.

| COMPONENTS OUTLINE | | | |
|--------------------|----------------|------|---------|
| CODE NUMBER 2381 | | SPQ | OUTLINE |
| 660 | 5...1 | 500 | Fig. 1a |
| | 6...1 | 1500 | Fig. 1b |
| 661 | 5...1 | 250 | Fig. 1a |
| | 6...1 | 1500 | Fig. 1b |
| 662 | 5...1 | 250 | Fig. 1a |
| | 66111 to 67011 | 1500 | Fig. 1b |
| | 68311 to 69211 | 750 | Fig. 1b |
| 663 | 5...1 | 200 | Fig. 1a |
| 664 | 5...1 | 100 | Fig. 1a |

PTC THERMISTORS IN BULK



Fig. 1a

| DIMENSIONS OF BULK TYPE PTC'S (in mm) | |
|---------------------------------------|------------|
| D | See table |
| d | 0.6 ± 10 % |
| T | 4.0 max. |
| H2 | 4.0 ± 1.0 |
| H3 | D + 5 max. |
| L1 | 20 min. |
| F | 5.0 |

PTC THERMISTORS ON TAPE ON REEL



Fig. 1b

| TAPE AND REEL ACCORDING TO IEC 60286-2 dimensions in millimeters | | | |
|--|--|------------------|----------------|
| SYMBOL | PARAMETER | DIMENSIONS | TOLERANCE |
| D | Body diameter | See table | max. |
| d | Lead diameter | 0.6 | ± 10 % |
| P | Pitch of components | Diameter < 12 mm | ± 1.0 |
| | | Diameter ≥ 12 mm | ± 2.0 |
| P ₀ | Feedhole pitch | 12.7 | ± 0.3 |
| F | Leadcenter to leadcenter distance (between component and tape) | 5.0 | + 0.6 - 0.1 |
| H0 | Lead wire clinch height | 16.0 | ± 0.5 |
| H2 | Component bottom to seating plane | 4.0 | ± 1.0 |
| H3 | Component top to seating plane | D + 5 | max. |
| T | Total thickness | 4.0 | max. |



TYPICAL RESISTANCE/TEMPERATURE CHARACTERISTIC



TYPICAL RESISTANCE/TEMPERATURE CHARACTERISTIC



TYPICAL RESISTANCE/TEMPERATURE CHARACTERISTIC



TYPICAL RESISTANCE/TEMPERATURE CHARACTERISTIC





Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Material Category Policy

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А