Low Noise, Precision 16 V CMOS, Rail-to-Rail Operational Amplifiers

Data Sheet

AD8661/AD8662/AD8664

FEATURES

Low offset voltage: 100 µV maximum at V_S = 5 V
Low input bias current: 1 pA maximum
Single-supply operation: 5 V to 16 V
Low noise: 10 nV/√Hz
Wide bandwidth: 4 MHz
Unity-gain stable
Small package options
- **3 mm × 3 mm 8-lead LFCSP**
- **8-lead MSOP and narrow SOIC**
- **14-lead TSSOP and narrow SOIC**

APPLICATIONS

Sensors
Medical equipment
Consumer audio
Photodiode amplification
ADC drivers

PIN CONFIGURATIONS



Figure 1. AD8661, 8-Lead SOIC (R-8)



Figure 2. AD8661, 8-Lead LFCSP (CP-8-13)



Figure 3. AD8662, 8-Lead SOIC (R-8)



Figure 4. AD8662, 8-Lead MSOP (RM-8)



Figure 5. AD8664, 14-Lead SOIC (R-14)



Figure 6. AD8664, 14-Lead TSSOP (RU-14)

GENERAL DESCRIPTION

The AD8661/AD8662/AD8664[1] are rail-to-rail output, single-supply amplifiers that use the Analog Devices, Inc., patented DigiTrim® trimming technique to achieve low offset voltage. The AD8661/AD8662/AD8664 series features extended operating ranges, with supply voltages up to 16 V. It also features low input bias current, wide signal bandwidth, and low input voltage and current noise.

The combination of low offset, very low input bias current, and a wide supply range makes these amplifiers useful in a wide variety of applications usually associated with higher priced JFET amplifiers. Systems using high impedance sensors, such as photodiodes, benefit from the combination of low input bias current, low noise, low offset, and wide bandwidth. The wide operating voltage range meets the demands of high performance analog-to-digital converters (ADCs) and digital-to-analog converters (DACs). Audio applications and medical monitoring equipment can take advantage of the high input impedance, low voltage, low current noise, and wide bandwidth.

The single AD8661 is available in a narrow 8-lead SOIC package and a very thin, dual lead, 8-lead LFCSP. The AD8661 SOIC package is specified over the extended industrial temperature range of −40°C to +125°C. The AD8661 LFCSP is specified over the industrial temperature range of −40°C to +85°C. The AD8662 is available in a narrow 8-lead SOIC package and an 8-lead MSOP, both specified over the extended industrial temperature range of −40°C to +125°C. The AD8664 is available in a narrow 14-lead SOIC package and a 14-lead TSSOP, both with an extended industrial temperature range of −40°C to +125°C.

[1] Protected by U.S. Patents 6,194,962 and 6,696,894.

Rev. E **Document Feedback**
Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices. Trademarks and registered trademarks are the property of their respective owners.

One Technology Way, P.O. Box 9106, Norwood, MA 02062-9106, U.S.A.
Tel: 781.329.4700 **©2005–2016 Analog Devices, Inc. All rights reserved.**
Technical Support **www.analog.com**

TABLE OF CONTENTS

Features ... 1
Applications ... 1
Pin Configurations ... 1
General Description ... 1
Revision History ... 2
Specifications ... 3
AD8661/AD8662/AD8664 Electrical Characteristics—SOIC, MSOP, and TSSOP ... 3
AD8661/AD8662/AD8664 Electrical Characteristics—SOIC, MSOP, and TSSOP ... 4
AD8661 Electrical Characteristics—LFCSP Only ... 5
AD8661 Electrical Characteristics—LFCSP Only ... 6
Absolute Maximum Ratings ... 7
Thermal Resistance ... 7
Typical Performance Characteristics ... 8
Outline Dimensions ... 13
Ordering Guide ... 15

REVISION HISTORY

7/2016—Rev. D to Rev. E

Changed CP-8-2 to CP-8-13 ... Throughout
Changes to Figure 1 and Figure 2 ... 1
Added Patent Note, Note 1 ... 1
Updated Outline Dimensions ... 13
Changes to Ordering Guide ... 15

7/2006—Rev. C to Rev. D

Added AD8664 ... Universal
Added 14-Lead SOIC_N and 14-Lead TSSOP ... Universal
Changes to Features ... 1
Changes to Table 1 ... 3
Changes to Table 2 ... 4
Changes to Table 3 ... 5
Changes to Table 4 ... 6
Changes to Table 5 and Table 6 ... 7
Changes to Figure 29 ... 11
Updated Outline Dimensions ... 13
Changes to Ordering Guide ... 15

5/2006—Rev. B to Rev. C

Changes to Ordering Guide ... 13

3/2006—Rev. A to Rev. B

Added AD8662 ... Universal
Added MSOP ... Universal
Changes to Table 1 ... 3
Changes to Table 2 ... 4
Changes to Table 3 ... 5
Changes to Table 4 ... 6
Changes to Table 5 ... 7
Updated Outline Dimensions ... 13
Changes to Ordering Guide ... 13

1/2006—Rev. 0 to Rev. A

Added LFCSP_VD ... Universal
Changes to Table 1 ... 3
Changes to Table 2 ... 4
Changes to Ordering Guide ... 13

9/2005—Revision 0: Initial Version

SPECIFICATIONS

AD8661/AD8662/AD8664 ELECTRICAL CHARACTERISTICS—SOIC, MSOP, AND TSSOP

V_S = 5.0 V, V_{CM} = V_S/2, T_A = 25°C, unless otherwise noted.

Table 1.

Parameter	Symbol	Test Conditions/Comments	Min	Typ	Max	Unit
INPUT CHARACTERISTICS						
Offset Voltage	V_{OS}	$V_{CM} = V_S/2$		30	100	µV
AD8661		−40°C < T_A < +85°C			1000	µV
AD8661		−40°C < T_A < +125°C			1400	µV
AD8662		−40°C < T_A < +125°C			1000	µV
AD8664		−40°C < T_A < +125°C			1200	µV
Input Bias Current	I_B			0.3	1	pA
		−40°C < T_A < +85°C			50	pA
		−40°C < T_A < +125°C			300	pA
Input Offset Current	I_{OS}			0.2	0.5	pA
		−40°C < T_A < +85°C			20	pA
		−40°C < T_A < +125°C			75	pA
Input Voltage Range			−0.1		+3.0	V
Common-Mode Rejection Ratio	CMRR	V_{CM} = −0.1 V to +3.0 V	85	100		dB
		−40°C < T_A < +125°C	80	100		dB
Large Signal Voltage Gain	A_{VO}	R_L = 2 kΩ, V_O = 0.5 V to 4.5 V	100	220		V/mV
Offset Voltage Drift	TCV_{OS}					
AD8661		−40°C < T_A < +125°C		3	10	µV/°C
AD8662, AD8664		−40°C < T_A < +125°C		2	9	µV/°C
OUTPUT CHARACTERISTICS						
Output Voltage High	V_{OH}	I_L = 1 mA	4.85	4.93		V
		−40°C < T_A < +125°C	4.80			V
Output Voltage Low	V_{OL}	I_L = 1 mA		50	100	mV
		−40°C < T_A < +125°C			110	mV
Short-Circuit Current	I_{SC}			±19		mA
Closed-Loop Output Impedance	Z_{OUT}	f = 1 MHz, A_V = 1		50		Ω
POWER SUPPLY						
Supply Current per Amplifier	I_{SY}	$V_O = V_S/2$		1.15	1.40	mA
		−40°C < T_A < +125°C			2.0	mA
DYNAMIC PERFORMANCE						
Slew Rate	SR	R_L = 2 kΩ		3.5		V/µs
Gain Bandwidth Product	GBP			4		MHz
Phase Margin	Φ_O			65		Degrees
NOISE PERFORMANCE						
Peak-to-Peak Noise	e_n p-p	f = 0.1 Hz to 10 Hz		2.5		µV p-p
Voltage Noise Density	e_n	f = 1 kHz		12		nV/√Hz
		f = 10 kHz		10		nV/√Hz
Current Noise Density	i_n	f = 1 kHz		0.1		pA/√Hz

AD8661/AD8662/AD8664 ELECTRICAL CHARACTERISTICS—SOIC, MSOP, AND TSSOP

V_S = 16.0 V, V_{CM} = V_S/2, T_A = 25°C, unless otherwise noted.

Table 2.

Parameter	Symbol	Test Conditions/Comments	Min	Typ	Max	Unit
INPUT CHARACTERISTICS						
Offset Voltage	V_{OS}	$V_{CM} = V_S/2$		50	160	µV
AD8661		−40°C < T_A < +85°C			1000	µV
AD8661		−40°C < T_A < +125°C			1400	µV
AD8662		−40°C < T_A < +125°C			1000	µV
AD8664		−40°C < T_A < +125°C			1200	µV
Input Bias Current	I_B			0.3	1	pA
		−40°C < T_A < +85°C			50	pA
		−40°C < T_A < +125°C			300	pA
Input Offset Current	I_{OS}			0.2	0.5	pA
		−40°C < T_A < +85°C			20	pA
		−40°C < T_A < +125°C			75	pA
Input Voltage Range			−0.1		+14.0	V
Common-Mode Rejection Ratio	CMRR	V_{CM} = −0.1 V to +14.0 V	90	110		dB
		−40°C < T_A < +125°C	90	110		dB
Large Signal Voltage Gain	A_{VO}	R_L = 2 kΩ, V_O = 0.5 V to 15.5 V	200	360		V/mV
Offset Voltage Drift	TCV_{OS}					
AD8661		−40°C < T_A < +125°C		3	10	µV/°C
AD8662, AD8664		−40°C < T_A < +125°C		2	9	µV/°C
OUTPUT CHARACTERISTICS						
Output Voltage High	V_{OH}	I_L = 1 mA	15.93	15.97		V
		I_L = 10 mA	15.60	15.70		V
		−40°C < T_A < +125°C	15.50			V
Output Voltage Low	V_{OL}	I_L = 1 mA		24	50	mV
		I_L = 10 mA		190	300	mV
		−40°C < T_A < +125°C			350	mV
Short-Circuit Current	I_{SC}			±140		mA
Closed-Loop Output Impedance	Z_{OUT}	f = 1 MHz, A_V = 1		45		Ω
POWER SUPPLY						
Power Supply Rejection Ratio	PSRR	V_S = 5 V to 16 V	95	110		dB
		−40°C < T_A < +125°C	95	115		dB
Supply Current per Amplifier	I_{SY}	$V_O = V_S/2$		1.25	1.55	mA
		−40°C < T_A < +125°C			2.1	mA
DYNAMIC PERFORMANCE						
Slew Rate	SR	R_L = 2 kΩ		3.5		V/µs
Gain Bandwidth Product	GBP			4		MHz
Phase Margin	Φ_O			65		Degrees
NOISE PERFORMANCE						
Peak-to-Peak Noise	e_n p-p	f = 0.1 Hz to 10 Hz		2.5		µV p-p
Voltage Noise Density	e_n	f = 1 kHz		12		nV/√Hz
		f = 10 kHz		10		nV/√Hz
Current Noise Density	i_n	f = 1 kHz		0.1		pA/√Hz

AD8661 ELECTRICAL CHARACTERISTICS—LFCSP ONLY

V_S = 5.0 V, V_{CM} = V_S/2, T_A = 25°C, unless otherwise noted.

Table 3.

Parameter	Symbol	Test Conditions/Comments	Min	Typ	Max	Unit
INPUT CHARACTERISTICS						
Offset Voltage	V_{OS}	$V_{CM} = V_S/2$		50	300	µV
		−40°C < T_A < +85°C			2000	µV
Input Bias Current	I_B			0.3	1	pA
		−40°C < T_A < +85°C			50	pA
Input Offset Current	I_{OS}			0.2	0.5	pA
		−40°C < T_A < +85°C			20	pA
Input Voltage Range			−0.1		+3.0	V
Common-Mode Rejection Ratio	CMRR	V_{CM} = −0.1 V to +3.0 V	85	100		dB
		−40°C < T_A < +85°C	80	100		dB
Large Signal Voltage Gain	A_{VO}	R_L = 2 kΩ, V_O = 0.5 V to 4.5 V	100	240		V/mV
Offset Voltage Drift	TCV_{OS}	−40°C < T_A < +85°C		4	17	µV/°C
OUTPUT CHARACTERISTICS						
Output Voltage High	V_{OH}	I_L = 1 mA	4.85	4.93		V
		−40°C < T_A < +85°C	4.80			V
Output Voltage Low	V_{OL}	I_L = 1 mA		50	100	mV
		−40°C < T_A < +85°C			120	mV
Short-Circuit Current	I_{SC}			±19		mA
Closed-Loop Output Impedance	Z_{OUT}	f = 1 MHz, A_V = 1		65		Ω
POWER SUPPLY						
Supply Current per Amplifier	I_{SY}	$V_O = V_S/2$		1.15	1.40	mA
		−40°C < T_A < +85°C			1.8	mA
DYNAMIC PERFORMANCE						
Slew Rate	SR	R_L = 2 kΩ		3.5		V/µs
Gain Bandwidth Product	GBP			4		MHz
Phase Margin	Φ_O			65		Degrees
NOISE PERFORMANCE						
Peak-to-Peak Noise	e_n p-p	f = 0.1 Hz to 10 Hz		2.5		µV p-p
Voltage Noise Density	e_n	f = 1 kHz		12		nV/√Hz
		f = 10 kHz		10		nV/√Hz
Current Noise Density	i_n	f = 1 kHz		0.1		pA/√Hz

AD8661 ELECTRICAL CHARACTERISTICS—LFCSP ONLY

V_S = 16.0 V, V_{CM} = V_S/2, T_A = 25°C, unless otherwise noted.

Table 4.

Parameter	Symbol	Test Conditions/Comments	Min	Typ	Max	Unit
INPUT CHARACTERISTICS						
Offset Voltage	V_{OS}	$V_{CM} = V_S/2$		50	300	µV
		−40°C < T_A < +85°C			2000	µV
Input Bias Current	I_B			0.3	1	pA
		−40°C < T_A < +85°C			50	pA
Input Offset Current	I_{OS}			0.2	0.5	pA
		−40°C < T_A < +85°C			20	pA
Input Voltage Range			−0.1		+14.0	V
Common-Mode Rejection Ratio	CMRR	V_{CM} = −0.1 V to +14.0 V	90	110		dB
		−40°C < T_A < +85°C	90	110		dB
Large Signal Voltage Gain	A_{VO}	R_L = 2 kΩ, V_O = 0.5 V to 15.5 V	200	420		V/mV
Offset Voltage Drift	TCV_{OS}	−40°C < T_A < +85°C		4	17	µV/°C
OUTPUT CHARACTERISTICS						
Output Voltage High	V_{OH}	I_L = 1 mA	15.95	15.97		V
		I_L = 10 mA	15.60	15.70		V
		−40°C < T_A < +85°C	15.50			V
Output Voltage Low	V_{OL}	I_L = 1 mA		24	50	mV
		I_L = 10 mA		210	350	mV
		−40°C < T_A < +85°C			400	mV
Short-Circuit Current	I_{SC}			±140		mA
Closed-Loop Output Impedance	Z_{OUT}	f = 1 MHz, A_V = 1		45		Ω
POWER SUPPLY						
Power Supply Rejection Ratio	PSRR	V_S = 5 V to 16 V	95	110		dB
		−40°C < T_A < +85°C	95	115		dB
Supply Current per Amplifier	I_{SY}	$V_O = V_S/2$		1.25	1.55	mA
		−40°C < T_A < +85°C			1.9	mA
DYNAMIC PERFORMANCE						
Slew Rate	SR	R_L = 2 kΩ		3.5		V/µs
Gain Bandwidth Product	GBP			4		MHz
Phase Margin	Φ_O			65		Degrees
NOISE PERFORMANCE						
Peak-to-Peak Noise	e_n p-p	f = 0.1 Hz to 10 Hz		2.5		µV p-p
Voltage Noise Density	e_n	f = 1 kHz		12		nV/√Hz
		f = 10 kHz		10		nV/√Hz
Current Noise Density	i_n	f = 1 kHz		0.1		pA/√Hz

ABSOLUTE MAXIMUM RATINGS

Table 5.

Parameter	Rating
Supply Voltage	18 V
Input Voltage	−0.1 V to V_S
Differential Input Voltage	18 V
Output Short-Circuit Duration to GND	Indefinite
Storage Temperature Range	−60°C to +150°C
Operating Temperature Range	
R-8, RM-8, R-14, and RU-14	−40°C to +125°C
CP-8-13	−40°C to +85°C
Junction Temperature Range	−65°C to +150°C
Lead Temperature, Soldering (60 sec)	300°C

Stresses at or above those listed under Absolute Maximum Ratings may cause permanent damage to the product. This is a stress rating only; functional operation of the product at these or any other conditions above those indicated in the operational section of this specification is not implied. Operation beyond the maximum operating conditions for extended periods may affect product reliability.

THERMAL RESISTANCE

θ_{JA} is specified for the worst-case conditions, that is, a device soldered in a circuit board for surface-mount packages.

Table 6. Thermal Resistance

Package Type	θ_{JA}	θ_{JC}	Unit
8-Lead SOIC	121	43	°C/W
8-Lead LFCSP	75[1]	18[1]	°C/W
8-Lead MSOP	142	44	°C/W
14-Lead SOIC	88.2	56.3	°C/W
14-Lead TSSOP	114	23.3	°C/W

[1] Exposed pad soldered to application board.

ESD CAUTION

ESD (electrostatic discharge) sensitive device. Charged devices and circuit boards can discharge without detection. Although this product features patented or proprietary protection circuitry, damage may occur on devices subjected to high energy ESD. Therefore, proper ESD precautions should be taken to avoid performance degradation or loss of functionality.

TYPICAL PERFORMANCE CHARACTERISTICS



Figure 7. Input Offset Voltage Distribution



Figure 10. Input Bias Current vs. Temperature



Figure 8. Offset Voltage Drift Distribution



Figure 11. Output Swing Saturation Voltage vs. Load Current



Figure 9. Input Offset Voltage vs. Common-Mode Voltage



Figure 12. Output Swing Saturation Voltage vs. Temperature, I_L = 1 mA



Figure 13. Output Swing Saturation Voltage vs. Temperature, I_L = 10 mA



Figure 14. Open-Loop Gain and Phase Shift vs. Frequency



Figure 15. Closed-Loop Output Impedance vs. Frequency



Figure 16. CMRR vs. Frequency



Figure 17. PSRR vs. Frequency



Figure 18. Small Signal Overshoot vs. Load Capacitance



Figure 19. Supply Current vs. Temperature



Figure 20. Supply Current vs. Supply Voltage (Dual-Supply Configuration), $T_A = 25°C$



Figure 21. 0.1 Hz to 10 Hz Input Voltage Noise



Figure 22. Small Signal Transient Response



Figure 23. Large Signal Transient Response



Figure 24. Positive Overload Recovery



Figure 25. Negative Overload Recovery



Figure 26. Voltage Noise Density vs. Frequency



Figure 27. Input Offset Voltage Distribution



Figure 28. Offset Voltage Drift Distribution



Figure 29. Input Offset Voltage vs. Common-Mode Voltage



Figure 30. Output Swing Saturation Voltage vs. Load Current



Figure 31. Closed-Loop Output Impedance vs. Frequency



Figure 33. No Phase Reversal



Figure 32. Large Signal Transient Response

OUTLINE DIMENSIONS



COMPLIANT TO JEDEC STANDARDS MS-012-AA

CONTROLLING DIMENSIONS ARE IN MILLIMETERS; INCH DIMENSIONS (IN PARENTHESES) ARE ROUNDED-OFF MILLIMETER EQUIVALENTS FOR REFERENCE ONLY AND ARE NOT APPROPRIATE FOR USE IN DESIGN.

060506-A

Figure 34. 8-Lead Small Outline Package [SOIC_N]
Narrow Body
(R-8)
Dimensions shown in millimeters and (inches)



COMPLIANT TO JEDEC STANDARDS MO-229-WEED-4

05-11-2016-A

Figure 35. 8-Lead Lead Frame Chip Scale Package [LFCSP]
3 mm × 3 mm Body and 0.75 mm Package Height
(CP-8-13)
Dimensions shown in millimeters



COMPLIANT TO JEDEC STANDARDS MO-187-AA

Figure 36. 8-Lead Mini Small Outline Package [MSOP]
(RM-8)
Dimensions shown in millimeters



COMPLIANT TO JEDEC STANDARDS MS-012-AB
CONTROLLING DIMENSIONS ARE IN MILLIMETERS; INCH DIMENSIONS (IN PARENTHESES) ARE ROUNDED-OFF MILLIMETER EQUIVALENTS FOR REFERENCE ONLY AND ARE NOT APPROPRIATE FOR USE IN DESIGN.

060606-A

Figure 37. 14-Lead Standard Small Outline Package [SOIC_N]
Narrow Body
(R-14)
Dimensions shown in millimeters and (inches)



COMPLIANT TO JEDEC STANDARDS MO-153-AB-1

Figure 38. 14-Lead Thin Shrink Small Outline Package [TSSOP]
(RU-14)
Dimensions shown in millimeters

ORDERING GUIDE

Model[1]	Temperature Range	Package Description	Package Option	Branding
AD8661ARZ	−40°C to +125°C	8-Lead Small Outline Package [SOIC_N]	R-8	
AD8661ARZ-REEL	−40°C to +125°C	8-Lead Small Outline Package [SOIC_N]	R-8	
AD8661ARZ-REEL7	−40°C to +125°C	8-Lead Small Outline Package [SOIC_N]	R-8	
AD8661ACPZ-R2	−40°C to +85°C	8-Lead Lead Frame Chip Scale Package [LFCSP]	CP-8-13	A0M
AD8661ACPZ-REEL7	−40°C to +85°C	8-Lead Lead Frame Chip Scale Package [LFCSP]	CP-8-13	A0M
AD8662ARZ	−40°C to +125°C	8-Lead Small Outline Package [SOIC_N]	R-8	
AD8662ARZ-REEL	−40°C to +125°C	8-Lead Small Outline Package [SOIC_N]	R-8	
AD8662ARZ-REEL7	−40°C to +125°C	8-Lead Small Outline Package [SOIC_N]	R-8	
AD8662ARMZ	−40°C to +125°C	8-Lead Mini Small Outline Package [MSOP]	RM-8	A10
AD8662ARMZ-REEL	−40°C to +125°C	8-Lead Mini Small Outline Package [MSOP]	RM-8	A10
AD8664ARZ	−40°C to +125°C	14-Lead Standard Small Outline Package [SOIC_N]	R-14	
AD8664ARZ-REEL	−40°C to +125°C	14-Lead Standard Small Outline Package [SOIC_N]	R-14	
AD8664ARZ-REEL7	−40°C to +125°C	14-Lead Standard Small Outline Package [SOIC_N]	R-14	
AD8664ARUZ	−40°C to +125°C	14-Lead Thin Shrink Small Outline Package [TSSOP]	RU-14	
AD8664ARUZ-REEL	−40°C to +125°C	14-Lead Thin Shrink Small Outline Package [TSSOP]	RU-14	

[1] Z = RoHS Compliant Part.

NOTES

©2005–2016 Analog Devices, Inc. All rights reserved. Trademarks and registered trademarks are the property of their respective owners.
D05200-0-7/16(E)

OCEAN CHIPS
Океан Электроники
Поставка электронных компонентов

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения **«JONHON»**, а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов **«FORSTAR»**.

AVIC JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).

FORSTAR®

Телефон: 8 (812) 309-75-97 (многоканальный)
Факс: 8 (812) 320-03-32
Электронная почта: ocean@oceanchips.ru
Web: http://oceanchips.ru/
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А