Type CPF Series

Key Features

Thin film precision resistors with TC's to 15ppm and tolerances to 0.05%.

Wide range of case sizes from 0201 to 2512

Suitable for all applications where close accuracy and stability are essential

Terminal finish – electroplated 100% matte Sn

Applications

Communications

Industrial Controls

Instrumentation

Medical

The CPF series is a high stability precision chip resistor range offering various power dissipations relating to a wide range of chip sizes. The CPF series offers TCR's down to 15ppm/°C and resistance tolerances to 0.1%. Standard values are within the IEC 63 E96 and E24 value grids. The CPF has accurate and uniform physical dimensions to facilitate placement

Electrical Characteristics

Chip Size		0201			
Rated Power @70°C		0.03125W			
Resistance Range Ω	Min.	49R9	49R9	49R9	49R9
	Max	4K99	33K	4K99	33K
Tolerance		0.5		1	
Code Letter		D		F	
Selection series		E24 & E96			
Temp. Coefficient (ppm/°C)		25	50	25	50
Code Letter		E	C	E	C
Operating Voltage (Max)		15V			
Max. Overload Voltage		30V			
Operating Temp. Range		-55 ~ +155°C			
Insulation Resistance dry min.		>1000MΩ			
Stability		0.5%			

Dimensions in millimetres unless otherwise specified

Dimensions Shown for reference purposes only. Specifications subject to change

For Email, phone or live chat, go to: www.te.com/help

Chip Size		0402											
Rated Power @70°C		0.063W											
Resistance	Min.	49R9			49R9	10R		49R9	4R7		49R9	4R7	
Range Ω	Max	20K			69K8	255K		69K8	511K		69K8	511K	
Tolerance (%)		0.05			0.1			0.5			1		
Code Letter		A			B			D			F		
Selection series		E24 & E96											
T.C.R. (ppm/°C)		15	25	50	15	25	50	15	25	50	15	25	50
Code Letter		D	E	C	D	E	C	D	E	C	D	E	C
Max Operating Volt.		25V											
Max. Overload Volt.		50V											
Op. Temp. Range		-55 ~ +155°C											
Insulation Resistance		>1000MΩ											
Stability		0.5%											

Chip Size		0603											
Rated Power @70°C		0.063W											
Resistance	Min.	4R7			4R7	4R7		4R7	1R0		4R7	1R0	
Range Ω	Max	332K			511K	1M0		511K	1M0		511K	1M0	
Tolerance (%)		0.05			0.1			0.5			1		
Code Letter		A			B			D			F		
Selection series		E24 & E96											
T.C.R. (ppm/°C)		15	25	50	15	25	50	15	25	50	15	25	50
Code Letter		D	E	C	D	E	C	D	E	C	D	E	C
Max Operating Volt.		50V											
Max. Overload Volt.		100V											
Op. Temp. Range		-55 ~ +155°C											
Insulation Resistance		>1000MΩ											
Stability		0.5%											

Chip Size		0805											
Rated Power @70°C		0.1W											
Resistance	Min.	4R7			4R7	4R7		4R7	1R0		4R7	1R0	
Range Ω	Max	1M0			1M0	2M0		1M0	2M0		1M0	2M0	
Tolerance (%)		0.05			0.1			0.5			1		
Code Letter		A			B			D			F		
Selection series		E24 & E96											
T.C.R. (ppm/°C)		15	25	50	15	25	50	15	25	50	15	25	50
Code Letter		D	E	C	D	E	C	D	E	C	D	E	C
Max Operating Volt.		100V											
Max. Overload Volt.		200V											
Op. Temp. Range		-55 ~ +155°C											
Insulation Resistance		>1000MΩ											
Stability		0.5%											

Chip Size		1206											
Rated Power @70°C		0.125W											
Resistance Range Ω	Min.	4R7			4R7	4R7		4R7	1R0		4R7	1R0	
	Max	1M0			1M0	2M49		1M0	2M49		1M0	2M49	
Tolerance (%)		0.05			0.1			0.5			1		
Code Letter		A			B			D			F		
Selection series		E24 & E96											
T.C.R. (ppm/°C)		15	25	50	15	25	50	15	25	50	15	25	50
Code Letter		D	E	C	D	E	C	D	E	C	D	E	C
Max Operating Volt.		150V											
Max. Overload Volt.		300V											
Op. Temp. Range		-55 ~ +155°C											
Insulation Resistance		>1000MΩ											
Stability		0.5%											

Chip Size		1210											
Rated Power @70°C		0.25W											
Resistance Range Ω	Min.	4R7			4R7	4R7		4R7	1R0		4R7	1R0	
	Max	1M0			1M0	2M49		1M0	2M49		1M0	2M49	
Tolerance (%)		0.05			0.1			0.5			1		
Code Letter		A			B			D			F		
Selection series		E24 & E96											
T.C.R. (ppm/°C)		15	25	50	15	25	50	15	25	50	15	25	50
Code Letter		D	E	C	D	E	C	D	E	C	D	E	C
Max Operating Volt.		150V											
Max. Overload Volt.		300V											
Op. Temp. Range		-55 ~ +155°C											
Insulation Resistance		>1000MΩ											
Stability		0.5%											

Chip Size		2010											
Rated Power @70°C		0.25W											
Resistance Range Ω	Min.	4R7			4R7	4R7		4R7	1R0		4R7	1R0	
	Max	1M0			1M0	3M0		1M0	3M0		1M0	3M0	
Tolerance (%)		0.05			0.1			0.5			1		
Code Letter		A			B			D			F		
Selection series		E24 & E96											
T.C.R. (ppm/°C)		15	25	50	15	25	50	15	25	50	15	25	50
Code Letter		D	E	C	D	E	C	D	E	C	D	E	C
Max Operating Volt.		150V											
Max. Overload Volt.		300V											
Op. Temp. Range		-55 ~ +155°C											
Insulation Resistance		>1000MΩ											
Stability		0.5%											

Chip Size		2512											
Rated Power @70°C		0.5W											
Resistance	Min.	4R7			4R7	4R7		4R7		1R0	4R7		1R0
Range Ω	Max	1M0			1M0	3M0		1M0		3M0	1M0		3M0
Tolerance (%)		0.05			0.1			0.5			1		
Code Letter		A			B			D			F		
Selection series		E24 & E96											
T.C.R. (ppm/°C)		15	25	50	15	25	50	15	25	50	15	25	50
Code Letter		D	E	C	D	E	C	D	E	C	D	E	C
Max Operating Volt.		150V											
Max. Overload Volt.		300V											
Op. Temp. Range		-55 ~ +155°C											
Insulation Resistance		>1000MΩ											
Stability		0.5%											

Environmental Characteristics

Item	Requirement		Test Method
	Tol. ≤0.05%	TOL. >0.05%	
Temperature Coefficient of Resistance (TCR)	As per TCRs specified in Electrical Characteristics tables		MIL-STD-202 Method 304 +25/-55/+25/+125/+25°C
Short Time Overload	ΔR±0.05%	ΔR±0.2%	JIS-C-5201-1 5.5 RCWV*2.5 or Max. overload voltage whichever is lower for 5 seconds
Insulation Resistance	>9999 MΩ		MIL-STD-202 Method 302 Apply 100VDC for 1 minute
Endurance	ΔR±0.05%	ΔR±0.2%	MIL-STD-202 Method 108A 70±2°C, RCWV for 1000 hrs with 1.5 hrs "ON" and 0.5 hrs "OFF"
	>7kΩ ΔR±0.5%		
Damp Heat with Load	ΔR±0.05%	ΔR±0.3%	MIL-STD-202 Method 103B 40±2°C, 90~95% R.H. RCWV for 1000 hrs with 1.5 hrs "ON" and 0.5 hrs "OFF"
Bending Strength	ΔR±0.05%	ΔR±0.1%	JIS-C-5201-1 6.1.4 Bending amplitude 3 mm for 10 seconds
Solderability	95% min. coverage		MIL-STD-202 Method 208H 245±5°C for 3 seconds
Resistance to Soldering Heat	ΔR±0.05%	ΔR±0.1%	MIL-STD-202 Method 210E 260±5°C for 10 seconds
Dielectric Withstand Voltage	By Type		MIL-STD-202 Method 301 Max. overload voltage for 1 minute
Thermal Shock	ΔR±0.05%	ΔR±0.2%	MIL-STD-202 Method 107G -55°C ~150°C, 100 cycles
Low Temperature Operation	ΔR±0.05%	ΔR±0.2%	JIS-C-5201-1 7.1 1 hour, -65°C, followed by 45 minutes of RCWV
High Temperature Exposure	ΔR±0.5%		MIL-STD-202 Method 107G At +155°C for 1000 hours

RCWV(Rated continuous working voltage)= √(P*R) or Max. Operating voltage whichever is lower

Storage Temperature: 25±3°C; Humidity < 80%RH

Derating Curve



Construction and dimensions



①	Alumina Substrate	④	Edge Electrode (NiCr)	⑦	Resistor Layer (NiCr)
②	Bottom Electrode (Ag)	⑤	Barrier Layer (Ni)	⑧	Overcoat (Epoxy)
③	Top Electrode (Ag)	⑥	External Electrode (Sn)	⑨	Marking

Size	L (mm)	W (mm)	T (mm)	D1 (mm)	D2 (mm)	Weight (g) (1000 Pcs.)
0201	0.58±0.05	0.29±0.05	0.23±0.05	0.12±0.05	0.15±0.05	0.14
0402	1.00±0.05	0.50±0.05	0.30±0.05	0.20±0.10	0.20±0.10	0.54
0603	1.55±0.10	0.80±0.10	0.45±0.10	0.30±0.20	0.30±0.20	1.83
0805	2.00±0.15	1.25±0.15	0.55±0.10	0.30±0.20	0.40±0.20	4.71
1206	3.05±0.15	1.55±0.15	0.55±0.10	0.42±0.20	0.35±0.25	9.02
1210	3.10±0.15	2.40±0.15	0.55±0.10	0.40±0.20	0.55±0.25	10
2010	4.90±0.15	2.40±0.15	0.55±0.10	0.60±0.30	0.50±0.25	23.61
2512	6.30±0.15	3.10±0.15	0.55±0.10	0.60±0.30	0.50±0.25	38.06



Recommended Land Pattern			
Size	A	B	C
0201	0.25	0.30	0.40±0.2
0402	0.50	0.50	0.60±0.2
0603	0.80	1.00	0.90±0.2
0805	1.00	1.00	1.35±0.2
1206	2.00	1.15	1.70±0.2
1210	2.00	1.15	2.50±0.2
2010	3.60	1.40	2.50±0.2
2512	4.90	1.60	3.10±0.2

Marking

Case sizes 0805 to 2512 IEC 4 Digit Marking:

Resistance	100R (100Ω)	2K2 (2.2kΩ)	10K (10kΩ)	499K (499kΩ)	100K (100kΩ)
Code	1000	2201	1002	4992	1003

Case Size 0603 E24 3 digit marking – Example 101 = 100R 102=1K0

E24	10	11	12	13	15	16	18	20	22	24	27	30
	33	36	39	43	47	51	56	62	68	75	82	91

Case size 0603 E96 3 digit marking – Examples 14C = 13K7 68B = 4K99 68X = 49R9

Code	E96	Code	E96	Code	E96	Code	E96
01	100	25	178	49	316	73	562
02	102	26	182	50	324	74	576
03	105	27	187	51	332	75	590
04	107	28	191	52	340	76	604
05	110	29	196	53	348	77	619
06	113	30	200	54	357	78	634
07	115	31	205	55	365	79	649
08	118	32	210	56	374	80	665
09	121	33	215	57	383	81	681
10	124	34	221	58	392	82	698
11	127	35	226	59	402	83	715
12	130	36	232	60	412	84	732
13	133	37	237	61	422	85	750
14	137	38	243	62	432	86	768
15	140	39	249	63	442	87	787
16	143	40	255	64	453	88	806
17	147	41	261	65	464	89	825
18	150	42	267	66	475	90	845
19	154	43	274	67	487	91	866
20	158	44	280	68	499	92	887
21	162	45	287	69	511	93	909
22	165	46	294	70	523	94	931
23	169	47	301	71	536	95	953
24	174	48	309	72	549	96	976

Code	A	B	C	D	E	F	G	H	X	Y	Z
Multiplier	10^0	10^1	10^2	10^3	10^4	10^5	10^6	10^7	10^{-1}	10^{-2}	10^{-3}

NB For case size 0603 values other than E24 and E96 resistors will be supplied unmarked.

All resistors smaller than 0603 supplied unmarked.

Packaging

Packing Quantity and Reel Specification



Size	ØA ±1.0	ØB ±1.0	ØC ±0.7	W ±1.0	T ±1.0	Paper Tape	Embossed Plastic Tape
0201	178.0	60.0	13.5	9.5	11.5	1000 / 10000	N/A
0402							
0603						1000 / 5000	
0805							
1206							
1210							
2010				13.5	15.5	N/A	4000
2512							

Paper tape Specification



Size	A ±0.05	B ±0.05	W ±0.10	E ±0.05	F ±0.05	P_o	P_1	P_2 ±0.05	ØDo	T
0201	0.40	0.70	8.00	1.75	3.5	4.00 ±0.10	2.00 ±0.05	2.00	1.55 ±0.03	0.42 ±0.02
0402	0.70	1.16							1.55 ±0.05	0.40 ±0.03
0603	1.10	1.90					4.00 ±0.10			0.60 ±0.03
0805	1.60	2.37								0.75 ±0.05
1206	2.00	3.55								
1210	2.75	3.40				4.00 ±0.05			1.60 ±0.10	

Peel force of top cover tape

The peel speed shall be about 300mm/min±5%

The peel force of top cover tape shall be between 8gf to 60gf



Embossed Plastic Tape Specifications



Type	A	B	W	E	F	P_0	P_1	P_2	ØD0	T
2010	2.85±0.10	5.45±0.10	12.0±0.10	1.75±0.10	5.5±0.05	4.00±0.05	4.00±0.10	2.00±0.05	1.50+0.10	1.00±0.20
2512	3.40±0.10	6.65±0.10	12.0±0.10	1.75±0.10	5.5±0.05	4.00±0.05	4.00±0.10	2.00±0.05	1.50+0.10	1.00±0.20

Peel force of top cover tape

The peel speed shall be about 300mm/min±5%

The peel force of top cover tape shall be between 20gf to 80g



Reflow Solder Profile



Time of Reflow soldering at maximum temperature point 260°C = 10s

Wave Solder Profile



Time of Wave soldering at maximum temperature point 260°C = 10s

Time of Soldering Iron at maximum temperature point 410°C = 5s

How To Order

CPF	0603	B	100R	E	1
Common Part	**Package Size**	**Tolerance**	**Value**	**TCR**	**Packaging**
CPF - precision thin film chip resistor	0201 1206 0402 1210 0603 2010 0805 2512	B - ±0.1% D - ±0.5% F - ±1%	100R - 100Ω 1K0 - 1000Ω 10K – 10,000Ω	D – 15PPM E - 25PPM C - 50PPM	1 – 1K REEL Blank – standard reel 0201 0402 - 10K 0603 0805 1206 1210 – 5K 2010 2512 - 4K

OCEAN CHIPS
Океан Электроники
Поставка электронных компонентов

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «**JONHON**», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «**FORSTAR**».

AVIC JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).

FORSTAR®

Телефон: 8 (812) 309-75-97 (многоканальный)
Факс: 8 (812) 320-03-32
Электронная почта: ocean@oceanchips.ru
Web: http://oceanchips.ru/
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А